Table of Contents

2	Notes
3	KEA MCU
4	OpenSDA
5	Power Supply/CAN/LIN
6	I/O Headers
7	Headers Multiple Functions

Revisions

Rev	Description	Date	Approved
X1	Original Release	DEC-17-2014	O. Romero
X2	Second Release	JAN-30-2015	O. Romero
A	Production Release	FEB-03-2015	O. Romero
B	2nd Production Release *J3-9 Connected to 5V instead of PSV_SDA_PSW *J3-3 Connect to VDD instead of 3V3 *Added J107 *Replaced XTAL *Placed C48 and C47 after D9 and D13 *Replace C48 with 10 uF cap. *Placed D14 *Changed net name PS-9V to Vin *Relocate FTM2 channels *Relocate signals on J202 to J212 *Place R11 and DNP R94 *Changed CAN and LIN header with right angle headers *Place R105 by default and leave R104 DNP *J11 pin 2 connected to VBAT *Replaced R80 with two 2K resistors in parallel. *Removed L3 *Removed C34 *Placed SW4 button, R118, R116 and C46 *Placed J14 *Button resistors changed to pulldown. *Changed 3.3 voltage regulator *Changed Q1 transistor *Replaced D9, D13 and D6 *Replaced C35 and C38	JUL-06-2015	J.Romero J.Sanchez

FREEDOM+ KEA

Automotive Processing Product Line
6501 William Cannon Drive West
Austin, TX 78735-8598

This document contains information proprietary for NXP Semiconductors and shall now be used for engineering design, procurement or manufacture in whole or in part without the express written permission of NXP Semiconductors.

ICAP Classification: FCP: FIUO: X PUBI:

Designer: Osvaldo Romero	Drawing Title: FRDM+KEA	
Drawn by: Osvaldo Romero	Page Title: TITLE PAGE	
Approved: J.Romero - J.Sanchez	Size C / Document Number SCH-28698 PDF: SPF-28698	Rev B
	Date: Monday, July 06, 2015	Sheet 1 of 7

1. Unless Otherwise Specified:
   All resistors are in ohms, 1% and 5 %
   All capacitors are in uF, 10% , 20 % and 5%
   All voltages are DC
   All polarized capacitors are aluminum electrolytic

2. Interrupted lines coded with the same letter or letter combinations are electrically connected.

3. Device type number is for reference only. The number varies with the manufacturer.

4. Special signal usage:
   _B Denotes - Active-Low Signal
   <> or [] Denotes - Vectored Signals

5. Interpret diagram in accordance with American National Standards Institute specifications, current revision, with the exception of logic block symbology.



ICAP Classification:	FCP: __	FIUO: X	PUBI: __
Drawing Title: FRDM+KEA			
Page Title: NOTES			
Size C	Document Number SCH-28698 PDF: SPF-28698		Rev B
Date: Monday, July 06, 2015		Sheet 2 of 7	









Populated with KEA128

Populated with KEA64

Populated with KEA32

ICAP Classification:	FCP: FMD: X PUBI:
Drawing Title:	FRDM+KEA
Page Title:	KEA MCU
Size: A	Document Number: SCH-28898 PDF: SPF-28898
Custom	Rev: B
Date: Monday, July 06, 2015	Sheet 3 of 7

OpenSDA Interface











ICAP Classification:	FCP: ___	FIUO: X	PUBI: ___
Drawing Title: FRDM+KEA			
Page Title: Power Supply/SWD/Reset			
Size C	Document Number SCH-28698 PDF: SPF-28698		Rev B
Date: Monday, July 06, 2015	Sheet 5 of 7		











ICAP Classification:	FCP: ___	FIUO: X	PUBI: ___
Drawing Title: FRDM+KEA			
Page Title: I/O Headers			
Size C	Document Number SCH-28698 PDF: SPF-28698		Rev B
Date: Monday, July 06, 2015	Sheet 6 of 7		



J1 MULTIPLE FUNCTIONALITIES



J6 MULTIPLE FUNCTIONALITIES

ICAP Classification: FCP: ___ FIUO: X PUBI: ___

Drawing Title: **FRDM+KEA**

Page Title: **Headers Multiple Functions**

Size	Document Number	Rev
C	SCH-28698 PDF: SPF-28698	B

Date: Monday, July 06, 2015 Sheet 7 of 7