(1,1)




```
battbuffer.good = FALSE
battstatus[0] = 0
                                                    sprintf(battstatus, sd_data_layout1,
                utctime, timerint_count, PRIPOWEROK, DIPSW, SDC0.DAYCLOCK, SDC0.sdpos, SDC0.sdnext, SDC0.timekeep,
  SDC0.harvest.energy, SDC0.harvest.usage, SDC0.harvest.prev_energy, SDC0.harvest.prev_usage, SDC0.harvest.e_total, S
SDC0.harvest.count, SDC0.harvest.charger, SDC0.harvest.c_total, SDC0.harvest.prev_charger)
                                                    sprintf(battstatus + strlen(battstatus), sd_data_layout2,
                                commint_count, buttonint_count, highint_count, lowint_count, worker_count, CHARGERL, DIVERSION,
                R.systemvoltage, R.ccvoltage, R.inputvoltage, R.primarypower[B1], R.primarypower[B2], R.currentin, R.current, C.c
                                                    cell[B1].cconline, cell[B1].online, cell[B2].cconline,
                                                cell[B2].online, cell[B1].id, cell[B2].id, cell[B3].id, cell[B4].id,
R.thermo_batt, (LONG) (hist[CCS.boc].cef * 100))
MBMC.thermo_batt = R.thermo_batt
MBMC.cef_boc = (LONG) (hist[CCS.boc].cef * 100)
MBMC.PRIPOWEROK = PRIPOWEROK
MBMC.DIPSW = DIPSW
MBMC.UTC = utctime
MBMC.pick = CCS.pick
MBMC.boi = CCS.boi
```

MBMC.boi = CCS.boi
MBMC.boc = CCS.boc
MBMC.alert = CCS.alert
MBMC.bn = CCS.bn
MBMC.CHARGER_B = CHARGERL
MBMC.DIVERSION_B = DIVERSION
MBMC.systemvoltage = R.systemvoltage
MBMC.ccvoltage = R.ccvoltage
MBMC.inputvoltage = R.inputvoltage
MBMC.primarypower_B1 = R.primarypower[B1]
MBMC.primarypower_B2 = R.primarypower[B2]
MBMC.currentin = R.currentin
MBMC.current = R.current
MBMC.currentload = C.currentload
MBMC.harvest = SDC0.harvest
MBMC.ports.PORTB=LATB
MBMC.ports.PORTD=LATD
MBMC.ports.PORTE=LATE
MBMC.ports.PORTJ=LATJ




(2, 1)
start
igned char j, k
igned int z
C_read()
rit(HL)
STEM_STABLE && !SDD0.dumping)
no
no
usy && !SDD0.dumping)
timekeep, SDC0.time,
st.e_total, SDC0.harvest.u_total,
VERSION,
current, C.currentload,


(battstatus, ",###")
n = strlen(battstatus)
no
th > SDBUFFERSIZE)
yes
].bn = CCS.boc
++].alm_num = 12
lag = TRUE
boc, " mkbstring1 ")
no
battbuffer.good = TRUE
e_crit()
end