FILENAME: 10000022

PROPRIETARY NOTICE
THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO VARIAN. IT MUST NOT BE REPRODUCED, OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED IN WRITING BY VARIAN.

| REVISIONS | | | |
|---|---|---|---|
| ZONE | REV | DESCRIPTION | APPROVAL/DATE |
| | 1 | REL PER ECO 16595 | DE 5/11/95 |
| | 2 | CHG PER ECO 18688 WES 6/10/96 | A.H. HAHNL 7/8/96 |
| 2B | 3 | ECO 19677 REMOVE CONN FROM PS1-RTN ES 9/6/96 | WRH 9/25/96 |
| | 4 | CHG PER ECO 20028, GJK 10/31/96 | WRH 10/31/96 |

A1
TERMINAL SUPPRESSION POWER SUPPLY BOARD
ASSY E15001930
SCHEM E13001930

TB1 TB2 TB3 TB4

BLK/WHT 110V
BLK 0V
BRN/WHT 120V
BRN 115V

DS1 HV ON

6kV 5MA T1

CR1 CR2 CR3 CR4

R1 100, 10W
R2 100, 10W

C1 .1 μf 3kV

BLEEDER R3 20M 3.6W 1%

CONTROL GRID
ANODE
Q2

R29 470,2W
R27 .2, 5W
R28 .2, 5 W
TP1 TP2

R9–R14
R15 1K, 1%, 10W
C2 .25μf 3kV
R16–R21 408Ω 300 Ω
CR12

J2 J3 E1

BLU GRN/YEL BRN
AC
F1 3 AMP
LN LD

FL1 10K1 CORCOM LINE FILTER
RV1 V130 RV2 V130 RV3 V130

P4 8 PIN PANDUIT

T1 T2 K1

9 PIN WINCHESTER J1 HV ON
+D −C STATUS B A

FERRITE BEAD
18 BLU
S1 C2 NO2
P6KE18CA
K1

J4 AC POWER/STATUS

5 PIN PANDUIT J3 DIGITAL I/O
OVERLOAD

J2 16 PIN PANDUIT ANALOG PROGRAMMING AND MONITOR

HV ON STATUS
HV ON COMMAND
V MON I MON V PROG I PROG

FERRITE BEAD
18 AWG BLUE TYP
P3 P2 P5 P6

+5 P3.5 P3.4 P3.3 GND
CH2 CH3 DAC0 DAC1

J3 5 PIN PANDUIT DIGITAL I/O
J2 16 PIN PANDUIT ANALOG I/O

B1 FAN P1 J1

FL2 10K1 CORCOM LINE FILTER
RV4 V130

TO REAR PANEL
DOWN LINK U1 (BLUE) U2 (GRAY)
UP LINK U3 (BLUE) U4 (GRAY)

A08
POWER SUPPLY CONTROLLER
ASSY E15002350
SCHEM E13002350
ADDRESS 8

J1 8 PIN PANDUIT POWER
+5 DGND +15 AGND −15

P7

J1 8 PIN PANDUIT POWER
+15 → 4
GND → 5
−15 → 6

P1

E3

18 WHT
18 RED
18 ORG
18 RED
18 BLU
18 WHT
BLK
NC GRN NC
NC 18 ORG NC

XENTEK XT18–15
PS1
A B RTN C
T1

18 GRN/YEL

FRONT PANEL
E3

3A27

| PN SUFFIX & QUANTITY | UI | DESCRIPTION VENDOR & PART NUMBER | PART NUMBER | DWG SIZE | FIND NO. | REV CHG |
|---|---|---|---|---|---|---|

PARTS LIST

WORKMANSHIP PER VARIAN WORKMANSHIP STANDARDS

UNSPECIFIED TOL
.XXX ±
.XX ±
FRAC ±
ANG ±

DO NOT SCALE THIS DRAWING
RADIUS OR CHAMFER ALL SHARP EDGES .015 MAX
ALL MACH. SURFACES 63 RMS
CONCENTRICITY .005 TIR
PERPENDICULARITY WITHIN TOLERANCE ZONE

| NEXT ASSY | USED ON |
|---|---|
| | E500 |
| | E220 |
| APPLICATION | FINISH |

| APPROVALS | DATE |
|---|---|
| DRAWN VAUGHAN J.C. | 4-18-95 |
| CHECKED C.P. | 3/3/95 |
| ELEC ENGR | |
| MECH ENGR A.H. HAHNL | 3/3/95 |
| PROJ ENGR | |
| MFG ENGR | |
| QUAL ENGR | |

varian
ION IMPLANT SYSTEMS, GLOUCESTER, MA

SCHEMATIC
MACHENCL–TERM SUPP
POWER SUPPLY

SIZE D E10000022 REV 4

SCALE NONE SHEET 1 OF 1