FILENAME: E13002350-SH1

REVISIONS			
ZONE	REV	DESCRIPTION	APPROVAL/DATE
	1	GENERATED BY ENG INPUT	
	2	CHANGED R49–R51, WERE 100 OHMS	
SH2	3	CHG'D PER ECO 20242 CF 11-21-96 REMOVE JP2 ON E15002357	CLF 11-21-96
SH2	A	CHG'D PER ECO 21825 BW 12-2-97 ADD MODIFICATION TABLE FOR E15002373	BFW 12-2-97
	B	CHG'D PER ECO 22798 CF 8-11-98 U13, U15 WAS LT1013; C16, C26, C42 WAS 33V, 2.5%	CLF 8-11-98
	C	ECO 27017 REPLACE E61000004	
	D	ECO 27019 ORIG E15002374 SH. 2	
B3 C4	E	REVISED PER ECO #30991 ECO ORIGINATOR/DRAFTMAN S. GREEN 02/05/03 SH1–ADDED NOTE 5 REFERENCE SH2–ORIG E15002375	D.OLSON 02-10-03

WATCHDOG

DOWN LINK

UP LINK

DC POWER

ANALOG I/O

DECOUPLING CHART		
U5	C3	.1UF
U6	C49	.1UF
U13	C33,C45	.1UF
U15	C43,C44	.1UF

REF DES	DEVICE	+15V PWR	−15V GND	+5V PWR	5 GND
U5	LM556			14	7
U13	LT1013	8	4		
U15	LT1013	8	4		
U16	75454			8	4

HIGHEST REF DES		
C56	L3	TP2
D35	Q1	U16
J3	RN2	VR3
JP3	R51	X1

REF DES NOT USED		
R5	R6	R10
R11	R46–R48	
R35	R37	
RN1	D32	

NOTES:
1. UNLESS OTHERWISE SPECIFIED:
   ALL RESISTANCE VALUES ARE IN OHMS
   ALL CAPACITANCE VALUES ARE IN MICROFARADS
2. C51 IS USED FOR ACCEL P/S AND EXTRACTION P.S. ONLY
3. SHEET 1 OF THE SCHEMATIC REFERS TO THE BASIC CIRCUITRY AND SHEET 2 COVER'S THE DIFFERENT CONFIGURATIONS.
4. * – DENOTES THAT THESE COMPONENTS MAY CHANGE ON OTHER CONFIGURATIONS OF THIS CIRCUIT. SEE SHEET 2 FOR TABLES WITH CONFIGURATIONS.
5. ELECTRICAL TIE POINT OF GND 5 AND GND 15 AT U10–8 AND U10–7.

PN SUFFIX & QUANTITY	UI	DESCRIPTION VENDOR & PART NUMBER	PART NUMBER	DWG SIZE	FIND NO.	REV CHG

PARTS LIST

WORKMANSHIP PER VSEA WORKMANSHIP STANDARDS

DRAWING STANDARDS ACCORDING TO VSEA DRAWING PROCEDURES

PROPRIETARY NOTICE
THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION PROPRIETARY TO VSEA. IT MUST NOT BE REPRODUCED OR DISCLOSED TO OTHERS OR USED IN ANY OTHER WAY, IN WHOLE OR PART EXCEPT AS AUTHORIZED IN WRITING BY VSEA.

ALL DIM ARE IN INCHES
UNSPECIFIED TOL ARE:
.XXX ± .005
.XX ± .01
FRAC ± 1/32
ANG ± 0° 30'

THIRD ANGLE PROJECTION

DO NOT SCALE THIS DRAWING

RADIUS OR CHAMFER ALL SHARP EDGES .015 MAX
ALL MACH. SURFACES 63 RMS
CONCENTRICITY .005 TIR
PERPENDICULARITY WITHIN TOLERANCE ZONE.

FINISH

APPROVALS	DATE
DRAWN C. FAHNESTOCK	6-14-95
CHECKED M. BANUSIEWICZ	6-20-95
ELEC ENGR S. GREEN	6-20-95
MECH ENGR	
PROJ ENGR	
MFG ENGR	
QUAL ENGR	

varian semiconductor equipment — Gloucester, MA

SCHEMATIC
POWER SUPPLY
CONTROLLER

SIZE E | E13002350 | REV E

SCALE NONE | SHEET 1 OF 2

1 RASTER