

## Contents

<b>1</b>	<b>Installation</b>	<b>3</b>
1.1	Requests and Complaints . . . . .	3
1.2	Installation on Home Computers . . . . .	3
<b>2</b>	<b>Problem Files</b>	<b>5</b>
2.1	Problem XML Specification . . . . .	5
2.2	Topics . . . . .	7
2.3	Types . . . . .	8
2.4	Usage . . . . .	9
<b>3</b>	<b>The <i>Edit</i> Tool</b>	<b>10</b>
3.1	Creating a New Problem . . . . .	10
3.2	Creating a New Version . . . . .	10
3.3	Validating a Problem File . . . . .	11
3.4	Editing Topics and Types . . . . .	11
<b>4</b>	<b>The <i>Build</i> Tool</b>	<b>12</b>
4.1	Building Specific Problems . . . . .	12
4.2	Building All Problems of a Type . . . . .	12
<b>5</b>	<b>Assignment Files</b>	<b>14</b>
5.1	Assignment XML Specification . . . . .	14
5.2	Building . . . . .	15
5.3	Finalizing . . . . .	15
<b>6</b>	<b>Features Being Implemented</b>	<b>16</b>
<b>7</b>	<b>ℒ<sub>T</sub>E<sub>X</sub> Style</b>	<b>17</b>
7.1	22-Specific Macros . . . . .	18

---

7.2	$\text{\LaTeX}$ Tips . . . . .	18
7.3	Adding to This List . . . . .	19

# 1 Installation

To use L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub>, you must be using some version of Python 2, and must have `pdflatex` installed on your system. The following Python packages are also required:

- `argparse`
- `xml`

The environment variable `LATEXML_CONFIG` must be set to the location of a valid configuration XML file in order to run L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub>. If you are a CS22 TA (in the `cs022ta` group) using a department machine, this should be done for you – talk to an HTA if an error appears referring to `LATEXML_CONFIG`.

If you are on your home computer, the next few sections will help you set up your configuration file correctly. Note that L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub> doesn't currently port well to Windows unless you are using Cygwin or another Unix-like environment – Nick will try to figure out how to do this soon!

## 1.1 Requests and Complaints

Please tell Nick the moment something doesn't work, or something is harder than it should be. This is meant to simplify your life significantly: if there is a particular tool you think might help you write things more efficiently, Nick would love to at least hear about it (or tell you why it's impossible, that's fun too). If something is confusing or buggy, also say so – I can't fix something if I don't know it's broken!

Also feel free, if you are good with Python, to submit a pull request in git.

## 1.2 Installation on Home Computers

First, open a terminal (Linux or Mac) or Cygwin (Windows - currently do not know another option, sorry!). Create a new folder where L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub> will be installed (`mkdir ~/latexml`) and switch into it (`cd ~/latexml`). Download L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub> using git by running

```
git clone https://www.github.com/nschank/latexml
```

Open your `bashrc` file (`~/.bashrc`) and add the line:

```
export LATEXML_CONFIG="/home/login/latexml/config/config.xml"
```

We also recommend adding aliases to the tools by adding the lines

```
alias 22build="python /home/login/latexml/build.py"
```

```
alias 22edit="python /home/login/latexml/edit.py"
```

Now open the config.xml file in `~/latexml/config`. Change the `include` tag to contain the path

```
/home/login/latexml/include/simple22.sty
```

This is the location of the header file inserted into the top of built documents. The other tags should not be changed; if you ever need to build an assignment xml file locally, you may need to change the `problemroot` to a folder of your preference, but that seems unlikely.

You should now run the tests (`python tests.py`) to make sure that everything is running smoothly.

## 2 Problem Files

To write a problem using L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub>, you must first understand the basics of the XML encoding being used.

### 2.1 Problem XML Specification

Here is a sample problem, for the sake of explanation:

```
<problem>
  <usedin year="2015">Homework 5</usedin>
  <usedin year="2014" private="true">Midterm 1</usedin>
  <version id="2">
    <author>cjk</author>
    <year>2016</year>
    <topics>number_theory graph_theory</topics>
    <types>proof induction</types>
    <param name="modulus">3</param>
    <dependency>tikz</dependency>
    <body>
      The modulus is \modulus.
    </body>
    <solution>
      TODO
    </solution>
    <rubric>
      TODO
    </rubric>
  </version>
  <version id="1">
    ...
  </version>
</problem>
```

**A problem XML file must have the extension ‘.xml’ or it will not be incorporated into PDF builds.**

**A Problem XML file MUST have root tag problem, which is made up of one or more child versions.** Loosely speaking, two ‘versions’ should be part of the same ‘problem’ if having the solution to one would make writing the other’s solution trivial. For example: adding a part to, theming, or changing the numbers in a previous year’s problem would call for a new version of

the problem. If several different problems are combined into one, that is generally a new problem (rather than a version of any of them).

**Each version MUST have exactly one year** (in a `<year>` tag), which may be “Unknown”. This is the year that the version was written.

**Each version MUST have at least one author, at least one topic, and at least one type.** Each of these tags accepts a whitespace separated list of items; thus,

```
<authors>cjk nschank    kl47</authors>
```

would be parsed as three authors: cjk, nschank, and kl47. Additional instances of a tag will append to the list, so e.g. multiple `<author>` tags within a version are allowed.

Each of these fields accepts both the singular and plural of their tagname, purely for convenience. Thus...

**Authors** `<author>` or `<authors>`

**Topic** `<topic>` or `<topics>`

**Type** `<type>` or `<types>`

Note that, while either tagname is accepted, the beginning and ending tags must match.

See the next section for an explanation of acceptable values for topic and type.

**Each version MUST have a body, a solution, and a rubric.** Each of these fields should be filled with arbitrary L<sup>A</sup>T<sub>E</sub>X; whatever you would have put between `\begin{document}` and `\end{document}` goes here. It is expected that, if a solution or rubric is not complete, the four letters “TODO” (case insensitive) should appear somewhere within their text. This allows the L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub> tools to keep track of any problems that need attention.

As an important note, the characters `&`, `<`, and `>` are special characters within XML. In order for the problem to be parsed, you MUST escape them with the XML sequences `&amp;`, `&lt;`, and `&gt;`; respectively. They will be unescaped before being parsed as L<sup>A</sup>T<sub>E</sub>X, so should be treated identically to their corresponding characters (e.g. tables will contain many instances of “`&amp;`”).

**Each version MUST have an id attribute, unique within the problem, set to a positive integer, such that the newest version has the highest ID.**

A version MAY have zero or more `param` or, equivalently, `parameter` tags, which MUST have a `name` attribute. This is equivalent to temporarily creating a command `\name` which produces the value given in the tag’s field. In the provided example, the command “`\modulus`” will evaluate to 3. This field is intended for use within problems that can be easily changed without needing to create a new version. As an example, the name of a person or object within a problem should be refactored into a parameter, so that the problem can be changed easily.

A version MAY have zero or more **dependency** (also allowed: **dep**, **deps**, **dependencies**) tags, each of which should be a whitespace-separated list of packages which are required in order to build the problem. **tikz** is the most commonly included by far. These dependencies will be dynamically imported when building an assignment including this problem.

**usedin** tags should never be created or edited by hand.

## 2.2 Topics

A **topic** is a unit of the class which a question is attempting to focus on. A problem-version may have multiple topics (we encourage it!), and the topics should be kept specific but not overly so. Any unrecognized topic within a topic list is considered a fatal error.

Allowed topics are:

- basic<sup>1</sup>
- big\_o
- bijections
- circuits
- counting
- equivalence\_relations
- graph\_theory
- logic
- mod
- number\_theory
- pigeonhole
- probability
- relations
- set\_theory
- todo<sup>2</sup>

If ever confused about what topic(s) a problem covers, consider that the topics field is meant to be organizational. Keep two questions in mind:

---

<sup>1</sup>The ‘basic’ topic should be included on anything that could go on the first homework, before we have really introduced any definitions. As an example, *Prove that  $\sqrt{2}$  is irrational* would be in the basic topic.

<sup>2</sup>If the topics field of a version should be looked at later (e.g. you are unsure about one and want to return to it), *always* include todo as a topic.

1. If Carly were making the final exam, and wanted to include a question on this topic, would she want to see this problem? If so, include the topic!
2. Does the question mention or incorporate a topic, even if the question doesn't seem to be "about" that topic? For instance, does this graph theory question define a relation? Is this probability question asking about circuits? Always include *both* topics – we like to include questions that bring together multiple units, so that students can find connections and recall old definitions.

## 2.3 Types

A **type** is a characteristic of the question itself, and is equivalent to a 'tag' in many other contexts. (The name 'type' is used to differentiate from an XML tag.) Like topics, questions can (and usually do) have multiple types. Any unknown type is a fatal error.

The acceptable types (and their meanings):

**computation** Any part of the question requires numerical computation *with little justification*, or asks for an explicit instance of something.

*Examples:* Encrypt this using RSA; determine the size of this set; provide a coloring of this graph; use Chinese Remainder Theorem; show these logical statements are equivalent using set algebra.

*Non-example:* Convert these logical expressions to English (see **notation**); counting questions (these usually require justification)

**core** This question is an extremely common question that is definitely simple to Google, but also very important to the class. Some subset of these questions are proven in class every year.

*Examples:* Prove the infinitude of primes; prove that  $\text{mod}$  is an equivalence relation; prove that there are an equal number of odd- and even-cardinality subsets of any set.

**contradiction** Any part of the question explicitly asks for a proof by contradiction, or it is the only feasible way to solve the problem.

**contrapositive** Any part of the question is a proof by contrapositive.

**direct** Any part of the question explicitly asks for a direct proof, or it is the only feasible way to solve the problem.

**element\_method** Any part of the question asks for a proof that two sets are equal. (It does not need to say 'element method' explicitly)

**induction** Any part of the question is a proof by induction.



**large** This question has multiple ( $> 3$ ) *small* parts *that build upon each other*, generally while getting progressively harder. If you think your question is hard or long, but it does not satisfy the previous sentence, you should fix that.

As a general note, the first part of a ‘large’ problem should be very easy (often just a computation question meant to ease the student in). See a later section on writing good problems.

**needs\_work** If you come across a problem that you think needs to be looked at again or rewritten, add the ‘needs\_work’ type so that someone can come look at it.

**notation** This question is meant to help the student practice notation.

*Example:* Put this into set-builder notation.

**piece** This question is very short, and could probably be incorporated into another problem. This type is a bit subtle: in general, a ‘piece’ is a question that has one or two parts (usually short proofs) that are not all that interesting by themselves. They are called ‘pieces’ because, when trying to come up with interesting problems, we can use several of them as inspiration to build a ‘large’ problem with many small parts.

*Example:* “Given a set of 52 distinct integers, show that there must be 2 whose sum or difference is divisible by 100.” Easy and not very interesting, but could be used very well as a lead-in to a question about a more general property of divisibility and pigeonhole.

**proof** Any part of the question asks for a non-trivial proof.

**repetitive** A question which asks you to do the same thing to several different examples.

*Example:* For each of the following relations, state whether they are injective, surjective, or both; turn the following logical expressions into circuits.

**todo** If the types field of a version should be looked at later (e.g. you are unsure about one and want to return to it), *always* include todo as a type.

## 2.4 Usage

Look at the next section for a summary of tools to help you create and edit problem files. The section following that looks at how to build problem files into PDFs.

## 3 The *Edit* Tool

### 3.1 Creating a New Problem

If you are building a new problem from scratch, you should first make sure that no question like it already exists. You can check this by opening the all-problem PDF (ask the HTAs where this is) and searching for some keywords about your problem.

Then, you should make a new XML file in the root `problems/` directory, wherever makes the most sense to you.<sup>3</sup> There is a simple tool for constructing the skeleton of a new problem XML. On a command line, run:

```
22edit new filename.xml
```

This command builds a new problem with one version, the current year, your login as the sole author, and other required fields ready to be filled in.

The optional `-i` flag allows you to select the topics and types of the new file with a convenient interactive command-line interface.

### 3.2 Creating a New Version

If you are adding a new version to an existing problem, the edit tool will let you add a new version with minimal effort. Run:

```
22edit branch a_problem.xml [-c|-e|-i]
```

The final flag is optional, and defaults to `-e`.

`-e` means the new version will be emp<sub>y</sub>; the version number will be correctly incremented, the year will be set to the current year, and the sole author will be your login, but all other fields will be empty or “TODO”.

`-i` is the same as `-e`, except it uses the same interactive interface as `22edit new` to let you choose topics and types.

`-c` copies the previous version’s contents (topics, types, parameters, dependencies, body, solution, and rubric), and updates the version number, author, and year in the same way that `-e` does.

---

<sup>3</sup>Replace this once there’s some kind of organization convention!

### 3.3 Validating a Problem File

To make you feel reassured that your problem XML looks like it's up to the specifications, you can run

```
22edit validate a_problem.xml
```

Validation is actually stricter (but more verbose) than the build tools: it looks closely at things like L<sup>A</sup>T<sub>E</sub>X style, probable errors, and possible misspellings of topics which the build tool would simply reject without much explanation. It also prints all likely exceptions simultaneously, rather than halting at the first sign of a problem. You should always run `validate`, even if your problem builds successfully.

Note that `validate` cannot help you if your XML is invalid (since the third-party parser will fail), and will not verify that your L<sup>A</sup>T<sub>E</sub>X will correctly compile.

**Note:** The current version does not have some of the features mentioned above (it will have these features within a few days), and is approximately equivalent to the build tool validator.

### 3.4 Editing Topics and Types

You can start the interactive topic and type editor on a problem using

```
22edit edit a_problem.xml
```

Optionally, the flag `--remove-todo` automatically removes the todo topic and type, when fixing such problems.

## 4 The *Build* Tool

### 4.1 Building Specific Problems

You can build any problem(s) into a PDF in one step by running the following command:

```
22build problems output[.pdf] problem1.xml [problem2.xml ...]  
[-s] [-m] [-r] [--title ‘TITLE’]
```

If making only a single problem, you can use the shortcut:

```
22build single name.xml [-s] [-m] [-r] [--title ‘TITLE’]
```

which simply names the output *name.pdf* (i.e. the same name as the problem file, except with .pdf instead of .xml).

The build script is overwrite-safe and tolerant of multiple people building the same pdf simultaneously. In particular, it will build a randomly named temporary file and check for overwriting afterwards, allowing you to specify another name or to overwrite if necessary. The generated .tex file is removed, as are the logs and auxiliary files – if you need these for some reason, let Nick know and he’ll add an option to keep them. Exception: the .tex file is not removed if there were L<sup>A</sup>T<sub>E</sub>X errors, so that you can find where the error occurred.

The most recent version (by highest ID) of each problem will be built in order, with repetition if requested. The header on top is temporary and will be removed in a later version of the builder. To change the title of the output, use the `--title` flag (which takes one argument, so may need quotes).

The `-s`, `-m`, and `-r` flags control whether solutions, metadata (like filename and topics), and rubrics are printed, respectively. All are optional, and they can be used together arbitrarily.

An invalid problem XML will be skipped and a warning will be printed, but the build will continue.

### 4.2 Building All Problems of a Type

The builder script can search all of the problems within the root problem directory<sup>4</sup> individually, building those that meet a set of criteria. You should run

```
22build all output[.pdf] [CRITERIA]  
[-s] [-m] [-r] [--title ‘TITLE’]
```

---

<sup>4</sup>This is set for you in the department machines, within `/course/cs022/problems`; on your local machine, you can set it within the config file by changing the path set as the `problemroot`.

If no criteria are given, the above command builds every problem in the problem root directory, with the four optional flags acting just as in the previous section.

Alternatively, you can specify a different directory to search using the `from` option:

```
22build from problems/ output[.pdf] [CRITERIA]
           [-s] [-m] [-r] [--title ‘‘TITLE’’]
```

This would search everything within the `problems/` directory.

The criteria for inclusion can be specified with any or all of the following flags, where a problem will be included only if it satisfies all specified flags.

**--allowed-topics** After this flag, include one or more topic names, separated by spaces. A problem will be included only if its topics are a subset of this list. **Common use case:** List all topics that the students have learned so far, and you will never include problems that they are not qualified to answer.

**--grep** After this flag, include one or more search terms separated by whitespace. A problem will be included only if each search term is present in either the body, solution, or rubric. The search is case insensitive, but note that it is searching the raw L<sup>A</sup>T<sub>E</sub>X so is sensitive to formatting and whitespace.

**--not-used-in** If present, only includes problems that were not used in any of the years given. Use ‘none’ to only include problems that have been used in at least one homework.

**--required-topics** After this flag, include one or more topic names, separated by spaces. A problem will be included only if it has at least one required topic. Note that it does not need to possess *all* required topics. **Common use case:** List the topics that the homework should focus on to get a good set of tentative problems for a homework.

**--required-types** After this flag, include one or more topic names, separated by spaces. A problem will be included only if it has at least one required type. Note that it does not need to possess *all* required types. **Common use cases:** Finding (for instance) an inductive proof on a particular topic; listing all ‘pieces’ related to a topic, to get inspiration; finding things that need work.

**--todo** If present, only includes problems that have “TODO” in their solution or rubric. Meant to make it easier to find problems still being worked on.

**--used-in** If present, only includes problems that were used in any of the years given. Use ‘none’ to include problems that have never been used.

**--written** If present, only includes problems that were written in any of the years given.

## 5 Assignment Files

We don't release problems by themselves - we release assignments! L<sup>A</sup>T<sub>E</sub>X<sub>ML</sub> uses a different specification to specify assignments and the problems within them, which simplify the process of building the same set of problems repeatedly.

Assignments are designed in such a way that they may be *finalized*. Finalization is meant to signify that an assignment has been released – or, more accurately, that an assignment's solutions have been released. When finalized, the assignment updates all of its contained problems with a **usedin** tag, allowing later years to know how long it has been since a problem was used. It also reifies the version attribute of all problems, so that if a problem is later given a new version, the old homework will not be changed.

### 5.1 Assignment XML Specification

```
<assignment>
  <name>Homework 4</name>
  <year>2016</year>
  <due>Tuesday, January 85, 2016</due>
  <problem>problems/problem1.xml</problem>
  <problem>problems/problem2.xml</problem>
  <problem version="4">problems/problem1.xml</problem>
</assignment>
```

**Note:** The assignment XML specification is still in progress, in the hopes of providing more flexibility in the near future. Thus, any document files not kept in the 22 course folder are not guaranteed to be forward-compatible - Nick will fix any document files kept in the correct location.

All assignments **MUST** have been given a name (equivalently, a *title*) in a **name** (equiv. **title**) tag. The name is used as the header of the built document, in a very large font.

All assignments **MUST** have the year that the assignment was made. This year should be accurate—when an assignment is finalized, this is the year the problem will be marked as **usedin**.

All assignments **MUST** have a due date, which will be used in the header and the introduction of the document exactly as written.

All assignments **MUST** have at least one **problem**, and an unlimited number (with repeats allowed). These problems will be added in the same order as they are in the XML file, with repetition intact. The ***version*** attribute can be used to mark which version of the problem is desired. If none is provided, the most recent is automatically used.

The text of a problem tag should be the filepath of an existing, validated problem XML file. (If it is invalid or does not exist, the assignment build will fail.)

## 5.2 Building

You can build an assignment XML with the build tool as follows:

```
22build doc assign.xml output[.pdf]  
          [-s] [-m] [-r]
```

The `-s`, `-m`, and `-r` flags control whether solutions, metadata (like filename and topics), and rubrics are printed, respectively. All are optional, and they can be used together arbitrarily.

## 5.3 Finalizing

Finalizing an assignment is simple, and has no options:

```
22edit finalize assign.xml
```

## 6 Features Being Implemented

- Move to 'templates' that documents can be built into
- Implement the validator with stylistic checking
- Enforce line-length limits
- Remove blurbs from `single` or `problems`
- Possibly figure out a way to avoid the stupid `&amp;` and `&lt;` things.



## 7 L<sup>A</sup>T<sub>E</sub>X Style

In order to keep the formatting of L<sup>A</sup>T<sub>E</sub>X consistent between problems, we have a few special macros and stylistic choices you are *required* to use.

1. You should **ALWAYS** use the environments `22itemize` and `22enumerate` rather than `itemize` and `enumerate` respectively. Specifically, these environments change the spacing between items, and use a consistent lettering scheme.
2. When providing a hint or a note, you **MUST** use the commands `hint` and `note`, as in

```
\hint{Think about the pigeonhole principle.}
```

This allows us to change how all hints and notes look without seeking them out individually.

3. The newline commands (e.g. `\\`) should **NEVER** be used to make paragraphs or for spacing. To make a new paragraph, leave a blank line between two blocks of text, as in:

```
\begin{document}
  First paragraph.

  Second paragraph.
\end{document}
```

4. All parts to a question should end with a period (or question/exclamation mark). You'd be surprised how often people forget this!
5. **NEVER** use the double-dollar-sign notation (e.g. `$$x$$`); in fact, don't do it in real life either. It is error-prone and difficult to identify using i.e. regexes. Use `\[x\]` instead. (Single dollar signs are still the preferred notation for inline math.)
6. **ALWAYS** use `\pmod` to write things in mod notation.  
**Example:** `3\equiv 4\pmod 5` compiles to  $3 \equiv 4 \pmod{5}$ .  
**Wrong:** `3\equiv 4\mod 5` compiles to  $3 \equiv 4 \mod 5$ , has weird spacing and we wish to maintain consistency.  
**Very Wrong:** `3=4 mod 5` compiles to  $3 = 4mod5$  and will lead to spontaneous crying among the staff.
7. Keep lines under 80 characters to remain editor friendly. The validator will enforce this soon!

## 7.1 22-Specific Macros

Here is a small table of other convenience macros that are available to you. We **highly recommend** them, as they cut down on (1) useless clutter, and (2) minor typos.

Symbol	Command
$\mathbb{N}$	<code>\N</code>
$\mathbb{Z}$	<code>\Z</code>
$\mathbb{R}$	<code>\R</code>
$\mathbb{Q}$	<code>\Q</code>
$E[X]$	<code>\E[X]</code>
$V(X)$	<code>\V(X)</code>
$\{x \mid x \in X\}$	<code>\setbuilder{x}{x\in X}</code>
$\mathcal{P}$	<code>\Pow</code>
$\Pr[ ]$	<code>\Pr[ ]</code>

Note that the `setbuilder` command does not deal with multiple line equations.

## 7.2 L<sup>A</sup>T<sub>E</sub>X Tips

Here are some tips to writing L<sup>A</sup>T<sub>E</sub>X more effectively.

- The commands `\left` and `\right` can be used with delimiters like `{}`, `()`, and `[]` to make them grow with their contents. So, for instance, `[\binom{n}{r}]` looks like

$$[\binom{n}{r}]$$

while `\left[\binom{n}{r}\right]` looks like

$$\left[\binom{n}{r}\right]$$

The matching command `\middle` can be used with the pipe character `|` to produce effective set builder notation (and that's exactly how `\setbuilder` does it!)

- Trying to write implies statements or iff statements? You are looking for `\Rightarrow` ( $\Rightarrow$ ) and `\Leftrightarrow` ( $\Leftrightarrow$ ).
- Be careful with XML special characters `&`, `<`, and `>`! See the section on special characters to avoid confusing XML parse errors. (Thankfully, XML color coding should make these errors relatively easy to spot.)

### 7.3 Adding to This List

Contact Nick and offer more tips or stylistic decisions, if you think they are important! We are very willing to add useful commands into our built-in macros.