SMALL DATA MACHINE LEARNING: FUNDAMENTAL CHALLENGES AND TARGETED SOLUTIONS

Ilya Emelyanov* 1820262250@bit.edu.cn
Dmitrii Dobrydin 1820262226@bit.edu.cn
Muhammad Hamza email@bit.edu.cn

Beijing Institute of Technology, Beijing, China

November 13, 2026

ABSTRACT

Machine learning on small tabular datasets ($n < 1000$) presents unique mathematical bottlenecks, including severe overfitting, vulnerability to outliers, and the breakdown of standard hyperparameter tuning due to validation signal depletion. Instead of proposing a universal framework, this paper conceptualizes these fundamental challenges and presents two targeted, pre-tuned algorithmic baselines as case studies. For robust classification, we evaluate SmallGBM, which utilizes size-adaptive leaf aggregation and stochastic split selection to mitigate outlier sensitivity without hyperparameter tuning. For nonlinear regression, we analyze SmallMLP, an adaptive neural network that employs empirically validated capacity scaling rules based on dataset constraints (n, d, K) alongside locally weighted conformal prediction for calibrated uncertainty quantification. Through rigorous zero-tuning benchmarks across strictly disjoint hold-out datasets, we establish the exact performance boundaries of these methods, demonstrating scaling curves that identify where standard models like XGBoost and AutoML frameworks become optimal. By explicitly documenting both empirical successes and negative results, this work provides a grounded, empirically robust foundation for future research in extreme low-sample learning regimes.

1 Introduction: The Small Data Paradigm

For the past two decades, the trajectory of machine learning has been overwhelmingly defined by the "big data" paradigm. Success stories in computer vision [**?**, **?**], natural language processing [**?**, **?**], and tabular prediction [**?**] are predicated on the availability of massive datasets where highly parameterized models can approximate arbitrarily complex functions. However, a vast array of critical scientific and industrial problems do not operate in this regime. In clinical medicine [**?**, **?**], materials science [**?**, **?**], and high-energy physics [**?**, **?**], data acquisition is inherently bottlenecked by physical or financial constraints, yielding datasets with fewer than 1000 samples. In these high-stakes domains, algorithms must adapt to strict data limits rather than relying on scale.

To address tabular data, a substantial body of literature has established gradient-boosted decision trees as the prevailing state-of-the-art. Implementations such as XGBoost [**?**], LightGBM [**?**], and CatBoost [**?**] consistently outperform alternative methods on medium-to-large tabular datasets [**?**, **?**]. These frameworks utilize second-order Taylor approximations for leaf weight estimation. While robust alternatives (e.g., Huber loss, mean absolute error) exist within these libraries, their default mean-based ERM estimators remain highly sensitive to heavy-tailed noise and outliers [**?**, **?**]. Crucially, selecting the appropriate robust loss function and configuring its thresholds—alongside coordinating depth and regularization—strictly depends on hyperparameter tuning via validation splits [**?**, **?**]. On scarce data, this validation process inevitably breaks down.

Parallel literature has extensively explored deep learning adaptations for tabular data. Recent advances include specialized attention mechanisms (e.g., TabNet [**?**], SAINT [**?**]), differentiable trees (NODE [**?**]), and heavily regularized multi-layer perceptrons [**?**, **?**]. While these models offer smooth function approximation, they require extensive

neural architecture search, exacerbating the depletion of training data in low-sample regimes. Additionally, standard architectures lack native uncertainty quantification (UQ). While Bayesian Neural Networks [**?**], Deep Ensembles [**?**], and Gaussian Processes [**?**] provide principled UQ, they frequently suffer from kernel degeneracy and Type-II maximum likelihood overfitting when dimensionality approaches the sample size ($d \approx n$).

Recently, in-context meta-learning models have been proposed to bypass validation tuning entirely. Most notably, Prior-Data Fitted Networks (TabPFN) [**?**, **?**] achieve strong zero-shot performance by performing approximate Bayesian inference via a Transformer pre-trained on synthetic causal models. However, TabPFN is structurally constrained by the quadratic $\mathcal{O}(n^2)$ computational complexity of its attention mechanism and imposes strict hard limits on feature dimensionality (typically $d \leq 100$) and class count. Concurrently, to address UQ without unverifiable parametric assumptions, conformal prediction [**?**, **?**] and its locally adaptive weighted variants [**?**, **?**] have emerged as rigorous methods for finite-sample coverage. In summary, while existing literature optimizes models for scale or synthetic priors, it lacks tuning-free, robust estimation for continuous regression and unconstrained classification in strict low-sample regimes.

This structural gap is rooted in the inherent limitations of standard model selection. When minimizing empirical risk on small data ($n < 1000$), extracting a validation set to constrain the hypothesis class dangerously depletes the scarce training signal [**?**, **?**]. The resulting selection bias and validation set overfitting dominate the optimization process [**?**], meaning the configuration that minimizes validation loss frequently exploits random sample fluctuations rather than identifying a true generalizable signal.

The aim of this paper is to formalize these fundamental bottlenecks of small tabular data and to present targeted, pre-tuned algorithmic baselines. In order to do this, we introduce two case studies: SmallGBM, which utilizes size-adaptive leaf aggregation and stochastic split selection for robust classification; and SmallMLP, an adaptive neural network that employs empirically validated capacity scaling rules based on dataset constraints (n, d, K) alongside weighted conformal prediction for calibrated uncertainty. Through rigorous zero-tuning benchmarks, we establish the strict performance boundaries of these methods, providing a grounded, empirically robust foundation for extreme low-sample learning.

2 Fundamental Bottlenecks and Mathematical Principles

To rigorously approach learning on $n < 1000$, we must separate incidental engineering issues from fundamental mathematical bottlenecks. Standard algorithms fail in this regime due to the *Trilemma of Small Data Learning*: the inability to simultaneously achieve low variance, low bias, and calibrated uncertainty without depleting the training set for validation tuning. In this section, we formalize these bottlenecks and define the mathematical principles used by our targeted solutions.

2.1 Vulnerability to Outliers and Robust Estimation

Modern gradient boosting implementations (e.g., XGBoost, LightGBM) utilize a second-order Taylor approximation of the loss. For a leaf node with instance set I, the optimal weight is given by:

$$w^* = -\frac{\sum_{i \in I} g_i}{\sum_{i \in I} h_i + \lambda} \tag{1}$$

While more stable than a simple empirical mean, this estimator remains non-robust. Under severe label noise, the numerator $\sum_{i \in I} g_i$ exhibits an unbounded influence function, allowing a single extreme outlier to shift the leaf weight arbitrarily far, yielding an asymptotic breakdown point of zero.

To overcome this, robust statistics must be integrated directly into the estimators. SmallGBM replaces this mean-based approach with a sample median of the pseudo-residuals r_i for small leaves ($|I| \leq 30$):

$$\hat{w}_{\text{leaf}} = \text{median}_{i \in I}(r_i) \tag{2}$$

This leverages a local 50% breakdown point to strictly bound the influence function against isolated noise spikes, before transitioning to an inverse-distance weighted mean based on feature-space proximity for larger leaves ($|I| > 30$) to recover statistical efficiency. Furthermore, to stabilize noisy splits without allowing outliers to inflate variance estimates, SmallGBM applies empirical Bayes shrinkage toward the parent node weight $\hat{w}_{\text{parent}}$ using the Median Absolute Deviation (MAD):

$$\hat{\sigma}_{\text{leaf}} = 1.4826 \cdot \text{median}_{i \in I} \left| r_i - \text{median}_{j \in I}(r_j) \right|, \quad \hat{w}_{\text{final}} = (1 - \gamma)\hat{w}_{\text{leaf}} + \gamma \hat{w}_{\text{parent}} \tag{3}$$

where $\gamma = (\hat{\sigma}^2_{\text{leaf}}/|I|)/(\sigma^2_{\text{prior}} + \hat{\sigma}^2_{\text{leaf}}/|I|)$ adaptively shrinks high-dispersion leaves toward the parent estimate.

2.2 The Hyperparameter Trap and Adaptive Complexity

Standard model selection relies on validation splits. In the low-sample regime, partitioning data is mathematically destructive. Furthermore, hyperparameter tuning over a grid Λ requires evaluating empirical risk on a held-out validation set of size n_{val}. The maximum deviation between the validation error $\hat{R}_{\text{val}}(\lambda)$ and the true risk $R(\lambda)$ scales as:

$$\sup_{\lambda \in \Lambda} \left| \hat{R}_{\text{val}}(\lambda) - R(\lambda) \right| = \mathcal{O}\left(\sqrt{\frac{\log |\Lambda|}{n_{\text{val}}}} \right) \tag{4}$$

When n_{val} is small, this selection bias and validation set overfitting dominate the optimization process, meaning the selected configuration frequently exploits validation noise rather than identifying a true generalizable signal.

To bypass this trap, architecture and regularization must be derived directly from data geometry. For multiclass classification ($K \geq 2$), SmallMLP eliminates neural architecture search by scaling the width of the first hidden layer deterministically:

$$w_1 = \max\left(2K,\ \min\left(\left\lfloor \alpha \sqrt{nK\sqrt{d}} \right\rfloor,\ 4n\right)\right) \tag{5}$$

where α is a structural scaling constant derived during meta-training (see Section 3.4), with subsequent layers decaying geometrically according to:

$$w_l = \max\left(K,\ \lfloor w_1 \cdot \beta^{l-1} \rfloor\right) \tag{6}$$

For continuous regression ($K = 1$), where output capacity does not scale with class cardinality, this formulation simplifies to a deterministic width bound $w_1 = \min(2n, 128)$. Similarly, dropout probability across both regimes is governed by a clamped dimensional ratio:

$$p_{\text{drop}} = \min\left(\max\left(3 \cdot \frac{d}{n},\ 0.1\right),\ 0.5\right) \tag{7}$$

This enforces strict capacity bottlenecks that prevent noise memorization without requiring a validation sweep.

2.3 Distribution-Free Uncertainty Quantification

In high-stakes domains, point predictions are insufficient. While Gaussian Processes provide principled uncertainty, they suffer from metric degeneracy and Type-II marginal likelihood overfitting when $d \approx n$. To guarantee validity without unverifiable parametric assumptions, distribution-free frameworks such as conformal prediction are required, guaranteeing finite-sample marginal coverage:

$$\mathbb{P}\left(Y_{n+1} \in C(X_{n+1})\right) \geq 1 - \alpha \tag{8}$$

To avoid the validation depletion paradox, locally weighted conformal prediction is applied over the penultimate embedding space $h(x)$ using a deterministic median heuristic for the kernel bandwidth:

$$h_{\text{cal}} = \text{median}\left(\|h(x_i) - h(x_j)\|\right) \tag{9}$$

computed over the pairwise distances of the calibration set. While pairwise distances can concentrate in high dimensions, the strict capacity bottlenecks of the network preserve sufficient metric structure. Crucially, although this framework structurally requires a single calibration split, it resolves the Trilemma: we entirely avoid iterative, high-dimensional validation sweeps (which induce severe selection bias and overfitting via Equation (4)), utilizing a single, non-tuned split strictly to guarantee valid finite-sample marginal coverage.

3 Real-World Applications and Experimental Methodology

Having established the mathematical bottlenecks, we now outline the experimental methodology designed to test these limits in practice.

3.1 Real-World Benchmark Domains

We selected hold-out benchmark datasets that natively exhibit the pathologies of small tabular data. We classify these into three primary constraint domains:

- **Clinical Medicine ($d \approx n$ Regime):** High-dimensional, low-sample datasets (e.g., *Hepatitis*: $n = 155, d = 19$; *Breast Cancer*: $n = 569, d = 30$). This regime induces ill-conditioned covariance matrices and critically tests algorithms lacking intrinsic dimensional regularization.
- **Physical and Engineering Sciences (Heteroscedastic Noise):** Experimental physical datasets (e.g., *Yacht Hydrodynamics*: $n = 308, d = 6$; *Energy Efficiency*: $n = 768, d = 8$) typically exhibit input-dependent noise variance $\sigma^2(x)$, requiring locally adaptive conformal intervals rather than homoscedastic uncertainty.
- **Physical Sensors and Remote Sensing (Heavy-Tailed Outliers):** Sensor data (e.g., *Ionosphere*: $n = 351, d = 34$; *Parkinson's*: $n = 195, d = 22$) frequently contains measurement outliers. These datasets strictly demand robust statistics to prevent models from isolating individual noise spikes.

3.2 Standard Baselines and AutoML Frameworks

To establish strict performance boundaries across classification, regression, and uncertainty quantification, we compare our targeted solutions against prevailing baselines across six algorithmic families:

- **Standard GBDTs (XGBoost / LightGBM):** The de facto tabular baselines [**?**, **?**]. Due to the lack of validation data, these are evaluated using their default hyperparameters, leaving their second-order leaf estimators vulnerable to heavy-tailed outliers and overfitting on $n < 1000$.
- **Random Forests (RF):** Bagging ensembles that mitigate variance via bootstrap aggregation and feature subsampling without heavy tuning. However, their piecewise-constant orthogonal splits induce structural bias on smooth continuous regression tasks, cannot extrapolate beyond the training bounding box, and lack distribution-free interval calibration.
- **Standard MLPs:** Unconstrained multilayer perceptrons trained with standard empirical risk minimization (MSE or cross-entropy). Without validation-guided neural architecture search over depth, width, and dropout, fixed-capacity MLPs either memorize noise or underfit, while producing uncalibrated confidence scores.
- **Gaussian Processes (GPs):** Non-parametric Bayesian models offering principled uncertainty quantification [**?**]. While computationally tractable at $n < 1000$, GPs suffer from Euclidean kernel degeneracy when $d \approx n$ and frequently overfit kernel length-scales during Type-II Maximum Likelihood optimization on small samples.
- **In-Context Foundation Models (TabPFN):** A tuning-free Transformer pre-trained on synthetic structural causal models to perform single-pass approximate Bayesian inference [**?**]. While it yields well-calibrated posterior predictive probabilities on in-domain classification tasks ($d \leq 100, K \leq 10$), its calibration remains strictly prior-dependent—lacking distribution-free, finite-sample coverage guarantees under real-world prior mismatch—and its standard architecture does not natively support continuous regression.
- **AutoML Frameworks (AutoGluon / GluonML):** State-of-the-art automated systems that construct multi-layer stack ensembles across diverse model families [**?**]. While dominant on medium-to-large datasets, their reliance on internal out-of-fold validation splits depletes the training signal and induces selection bias on extreme low-sample tasks.

Table 1 synthesizes how each baseline family interacts with the mathematical bottlenecks of Section 2 compared to SmallGBM and SmallMLP.

Table 1: Mapping Algorithmic Families to Small-Data Mathematical Bottlenecks

Algorithm	**Outlier Sensitivity**	**Tuning / Split Burden**	**Uncertainty Validity**	**Primary Regime / Limitation**
XGBoost / LightGBM	High (unbounded g_i)	High ($\lvert\Lambda\rvert \gg 10^2$)	None (point)	Overfits without validation tuning
Random Forest	Moderate (bagging)	Low	Empirical variance	Structural bias on smooth regression
Standard MLP	High (under MSE)	Extreme (arch search)	Uncalibrated	Severe validation overfitting
Gaussian Process	High (Gaussian noise)	Moderate (Type-II ML)	Parametric / Fragile	Fails at $d \approx n$ (kernel degeneracy)
TabPFN	Moderate (prior-bound)	None (in-context)	Approx. Bayesian (prior-dependent)	Classification only ($d \leq 100, K \leq 10$)
AutoGluon (AutoML)	Moderate (stacking)	Out-of-fold stacking	Empirical / None	Signal depletion on $n < 500$
SmallGBM	**Low (median + MAD)**	**None (tuning-free)**	None (point)	**Robust classification** ($n < 1000$)
SmallMLP	**Moderate** ($\lambda = 1/n$)	**Single cal. split** (h_{cal})	**Finite-sample** ($1 - \alpha$)	**Nonlinear Regr., Multiclass & UQ** ($n < 500$)

3.3 Zero-Tuning Implementations: SmallGBM and SmallMLP

We evaluate two algorithmic implementations designed to operate strictly without validation tuning. **SmallGBM** applies the robust median leaf estimation and highly stochastic split selection (evaluating only five random thresholds per feature) to prevent outlier isolation. Its core logic is implemented in a native C backend with 256-bin histograms,

yielding a $2\times$–$3\times$ computational speedup over pure Python implementations. **SmallMLP** implements the deterministic capacity scaling laws ($\alpha = 6.0, \beta = 0.7$), inverse weight decay ($\lambda = 1/n$), and clamped dropout. For regression, it utilizes the tuning-free weighted conformal prediction framework outlined in Section 2.3 to generate calibrated uncertainty intervals.

3.4 Meta-Training Protocol and the Avoidance of Data Leakage

To ensure a mathematically rigorous evaluation and strictly prevent data leakage, we separate the derivation of algorithmic constants from the final benchmark. All heuristic hyperparameters for SmallGBM and SmallMLP—such as the leaf size threshold $|I| \leq 30$ and the structural constant $\alpha = 6.0$—were derived empirically on a disjoint *Meta-Training Set*. This set comprises a diverse collection of small tabular datasets sourced from the *scikit-learn* library and the UCI Machine Learning Repository, **strictly disjoint** from the evaluation benchmarks. The models were subsequently frozen. All comparative evaluations against baselines are conducted on the independent *Hold-Out Benchmark Set* in a strict zero-tuning regime.

4 Empirical Pathologies and Performance Boundaries in the Low-Sample Regime

4.1 The Validation Breakdown and Scaling Boundaries

4.2 Surviving Data Pathologies

4.3 Component Ablations and Meta-Validation

4.3.1 The α and β Capacity Surface on the Meta-Training Set

As established in Section 2.2, continuous regression ($K = 1$) utilizes the deterministic $w_1 = \min(2n, 128)$ width bound, whereas the capacity scaling constants α and β in Equations (5) and (6) specifically govern multiclass representation capacity ($K \geq 2$). To verify that this scaling rule does not rely on fragile hyperparameter tuning or test-set leakage, we evaluate the joint sensitivity of $\alpha \in [2.0, 10.0]$ and $\beta \in [0.5, 0.9]$ across the classification tasks of the disjoint Meta-Training Set.




Figure 1: Empirical capacity surface across the disjoint Meta-Training Set plotted on a standardized accuracy scale ($[0.76, 0.84]$). Total mean accuracy fluctuates by less than 0.97% across the entire 45-point grid ($[0.7970, 0.8067]$), visually confirming a flat stability plateau. The red bounding box denotes the selected structural prior ($\alpha = 6.0, \beta = 0.7$).

As illustrated in Figure 1, when viewed on a non-distorted accuracy scale, the performance surface forms a remarkably uniform stability plateau: across a five-fold increase in α and the full spectrum of β, mean meta-training accuracy varies within a narrow band of 0.97% (from 0.7970 to 0.8067). The minor cell-to-cell fluctuations ($\pm 0.2\%$) reflect stochastic weight initialization variance inherent to $n < 500$ rather than structural sensitivity. This confirms that the asymptotic scaling factor $\sqrt{nK\sqrt{d}}$ captures the intrinsic geometry of the low-sample regime, rendering the network largely invariant to local constant perturbations.

To lock in a single operating point prior to hold-out evaluation, we apply two structural boundary conditions. First, we reject boundary configurations with minimal decay ($\beta = 0.9$, such as $(\alpha = 5.0, \beta = 0.9)$ at 0.8067), as they fail to compress the second hidden layer and inflate parameter count. Second, while aggressive compression ($\beta \leq 0.6$, such as $(\alpha = 6.0, \beta = 0.5)$ at 0.8064) yields marginally higher point averages on specific random seeds, slashing penultimate layer width by $\geq 40\%$ risks representation collapse and metric distortion in the embedding space $h(x)$ required for locally weighted conformal calibration (Equation (9)). Consequently, we freeze the central operating point $\alpha = 6.0, \beta = 0.7$ (0.8040 accuracy, within 0.27% noise tolerance of the grid maximum) as a conservative structural prior that balances parameter compression (30% decay) with metric preservation for uncertainty quantification.

4.4 True Negative Results and Structural Limitations