SMALL DATA MACHINE LEARNING: FUNDAMENTAL CHALLENGES AND TARGETED SOLUTIONS

Ilya Emelyanov
Beijing Institute of Technology
Beijing, China
1820262250@bit.edu.cn

October 27, 2026

ABSTRACT

Machine learning on small tabular datasets ($n < 1000$) presents unique mathematical bottlenecks, including severe overfitting, vulnerability to outliers, and the impossibility of standard hyperparameter tuning due to the lack of validation data. Instead of proposing a universal framework, this paper conceptualizes these fundamental challenges and presents two targeted solutions as case studies. For robust classification, we evaluate SmallGBM, which utilizes median leaf weights and stochastic split selection to mitigate outlier sensitivity without hyperparameter tuning. For nonlinear regression, we analyze SmallMLP, an adaptive neural network that derives its architecture directly from dataset parameters and employs weighted conformal prediction for calibrated uncertainty quantification. Through rigorous zero-tuning benchmarks across over 20 datasets, we establish the strict performance boundaries of these methods, demonstrating scaling curves that identify exactly where standard models like XGBoost and standard MLPs become optimal. By explicitly documenting both empirical successes and negative results, this work provides a grounded, mathematically rigorous foundation for future research in extreme low-sample learning regimes.

1 Introduction: The Small Data Paradigm

For the past two decades, the trajectory of machine learning has been overwhelmingly defined by the "big data" paradigm. Success stories in computer vision, natural language processing, and tabular prediction are predicated on the availability of massive datasets where highly parameterized models can approximate arbitrarily complex functions without catastrophic overfitting, and standard hyperparameter tuning remains statistically stable.

However, a vast array of critical scientific and industrial problems do not operate in this regime. In clinical medicine, rare disease cohorts often consist of only dozens of patients. In materials science and catalysis, experimental data acquisition is financially and temporally bottlenecked, yielding datasets with $n < 500$ samples. In these domains, the "more data" solution is physically impossible; algorithms must adapt to the data constraints, not vice versa.

This paper addresses the fundamental bottlenecks of machine learning on *small tabular data* (defined here as $n < 1000$). We argue that the failure of standard models in this regime is a mathematical inevitability rooted in standard Empirical Risk Minimization (ERM). When minimizing the empirical risk $\hat{R}(f) = \frac{1}{n}\sum_{i=1}^{n} L(f(x_i), y_i)$, the generalization gap bounds depend heavily on the sample size n and the complexity of the hypothesis class $\mathcal{F}$. For standard gradient boosting (XGBoost, LightGBM) or MLPs, this complexity leads to memorization of noise, while extracting a validation set to constrain $\mathcal{F}$ dangerously depletes the scarce training data. While modern in-context meta-learning models like TabPFN have emerged as powerful tuning-free baselines for small tabular data, they are primarily restricted to classification and lack native, calibrated uncertainty quantification.

To address these issues, we conceptualize the problem through three mathematical lenses: robust statistics, adaptive complexity, and distribution-free uncertainty quantification. Instead of proposing a universal framework, we present two targeted algorithmic solutions designed for specific failure modes:

First, **SmallGBM** targets robust classification. We replace fragile mean-based ERM leaf estimators with robust statistics—specifically, median-based estimators for small leaves and signal-adaptive shrinkage—coupled with stochastic split selection. This removes the need for hyperparameter tuning and yields superior performance on datasets with $n < 1000$.

Second, **SmallMLP** targets nonlinear regression and uncertainty quantification. We replace manual architecture search with an adaptive architecture derived directly from dataset parameters (n, dimensionality d, and classes K). To ensure reliable decision-making, we integrate weighted conformal prediction, providing finite-sample coverage guarantees and significantly narrower intervals than standard split conformal methods.

A central contribution of this work is the rigorous documentation of limitations. We provide n-scaling curves to demonstrate exactly where standard algorithms overtake our methods, and extensively report negative results to provide a realistic, mathematically grounded baseline for future research in low-sample machine learning.

2 Real-World Applications and Constraints

The relevance of small tabular data is not a theoretical curiosity; it is the operational reality of several high-stakes domains. In each case, the physical or economic constraints of data acquisition induce a specific mathematical pathology that standard algorithms are ill-equipped to handle. We formalize these pathologies below.

2.1 Clinical Medicine and Rare Diseases: The $d \approx n$ Regime

In rare disease research, patient cohorts are inherently limited (often $n < 100$), while modern clinical panels routinely measure dozens or hundreds of variables (d). This yields the high-dimensional, low-sample regime $d \approx n$. Mathematically, this induces two critical issues: (1) the empirical feature covariance matrix $\hat{\Sigma} = \frac{1}{n} X^T X$ becomes ill-conditioned or singular, rendering standard unregularized estimators unstable; and (2) the sample size is insufficient to carve out a statistically meaningful validation set for hyperparameter tuning, as a standard split depletes the scarce training signal. Thus, any viable algorithm must be tuning-free and incorporate intrinsic dimensional regularization (e.g., adaptive dropout and column subsampling).

2.2 Materials Science and Catalysis: Heteroscedastic Measurement Noise

In catalysis and materials science, acquiring data is bottlenecked by synthesis time and reagent costs, typically yielding $50 \leq n \leq 200$ samples with $10 \leq d \leq 40$ physicochemical descriptors. Crucially, experimental measurements often exhibit input-dependent noise variance $\sigma^2(x)$ (heteroscedasticity). Standard models that assume homoscedastic residuals systematically miscalibrate uncertainty estimates. While extreme heteroscedasticity under non-exchangeability remains a fundamental challenge, models in this regime require locally adaptive uncertainty quantification—such as weighted conformal prediction—to scale interval widths according to local feature-space density rather than relying on global constant-width bounds.

2.3 High-Energy Physics and Astronomy: Heavy-Tailed Noise and Outliers

In particle detectors and astronomical surveys, rare target events often consist of only a few hundred observations ($n < 500$) embedded in substantial background noise. Measurement errors in these domains frequently follow heavy-tailed distributions due to sensor anomalies or rare physical interference. For standard mean-based estimators—such as the leaf weights in conventional gradient boosting—the asymptotic breakdown point is zero: a single extreme outlier can shift the estimate arbitrarily far, destroying generalization. This regime strictly demands robust statistics with a high breakdown point (e.g., median-based estimators) and stochastic split selection to prevent trees from isolating individual noise spikes.

2.4 The Unified Constraint

Across all three domains, data acquisition is physically or financially bounded. The resulting mathematical pathologies—ill-conditioning at $d \approx n$, local noise variations, and heavy-tailed outliers—are intrinsic properties of the data-generating process. Consequently, algorithmic solutions must be designed around these constraints rather than relying on asymptotic big-data assumptions, motivating the mathematical bottlenecks formalized in Section 3.

3 Fundamental Bottlenecks of Small Data Learning

In this section, we formalize the mathematical mechanisms that cause standard machine learning algorithms to fail on small tabular data. We argue that these failures are not incidental but are direct consequences of the estimators used in modern models.

3.1 High Variance, Concentration of Measure, and the Curse of Dimensionality

The primary failure mode of complex models on small data is high variance. Consider a model $\hat{f}$ trained on a dataset $\mathcal{D} = \{(x_i, y_i)\}_{i=1}^n$ with $n < 1000$. The expected squared generalization error decomposes as:

$$\mathbb{E}\left[(y - \hat{f}(x))^2\right] = \text{Bias}^2[\hat{f}(x)] + \text{Var}[\hat{f}(x)] + \sigma_\epsilon^2 \tag{1}$$

In the small-data regime, the variance term dominates. As model complexity increases (e.g., deeper trees, wider layers), the model memorizes training noise ϵ rather than extracting the true signal. This is exacerbated by the geometry of high-dimensional spaces. With n samples in $\mathbb{R}^d$, the effective sample density scales as $n^{1/d}$. For $n = 100$ and $d = 20$, the space is overwhelmingly empty. By the concentration of measure phenomenon, pairwise distances between points become nearly uniform, forcing the model to interpolate across vast, unpopulated regions and leading to erratic extrapolation.

3.2 Vulnerability to Outliers: The Unbounded Influence of Second-Order Boosting

Modern gradient boosting implementations (e.g., XGBoost, LightGBM) utilize a second-order Taylor approximation of the loss function. For a leaf node with instance set I, the optimal weight is given by:

$$w^* = -\frac{\sum_{i \in I} g_i}{\sum_{i \in I} h_i + \lambda} \tag{2}$$

where g_i and h_i are the first and second derivatives of the loss with respect to the prediction, and λ is the L_2 regularization term. While more stable than a simple empirical mean, this estimator remains fundamentally non-robust. The influence function of w^* with respect to an outlier (x_j, y_j) is proportional to $g_j / (\sum_{i \in I} h_i + \lambda)$. For losses with unbounded gradients (e.g., squared error) or severe label noise in classification, a single anomalous gradient g_j can shift the leaf weight arbitrarily far, yielding an asymptotic breakdown point of zero. In the small-data regime, where $|I|$ is small and $\sum_{i \in I} h_i$ is modest, this sensitivity causes catastrophic variance.

3.3 The Hyperparameter Trap: Validation Depletion and Multiplicity

Standard model selection relies on partitioning data into training and validation sets (e.g., a 70/30 split). In the low-sample regime, this partitioning is mathematically destructive: for $n = 200$, a 70/30 split leaves only 140 samples for training, severely degrading the base estimator.

Furthermore, hyperparameter tuning over a grid Λ of $|\Lambda|$ configurations requires evaluating empirical risk on the held-out validation set of size n_{val}. By applying a union bound over standard concentration inequalities, the maximum deviation between the validation error $\hat{R}_{\text{val}}(\lambda)$ and the true risk $R(\lambda)$ scales as:

$$\sup_{\lambda \in \Lambda} \left| \hat{R}_{\text{val}}(\lambda) - R(\lambda) \right| = \mathcal{O}\left(\sqrt{\frac{\log |\Lambda|}{n_{\text{val}}}} \right) \tag{3}$$

With $n_{\text{val}} = 60$ and $|\Lambda| = 100$, this multiplicity error dominates the selection process. The configuration that minimizes validation loss is frequently the one that best exploits random sample fluctuations rather than the one that generalizes, proving the mathematical necessity of tuning-free algorithms.

3.4 Uncertainty Quantification and the Failure of Parametric Assumptions

In high-stakes domains, point predictions $\hat{y}$ are insufficient; decision-makers require calibrated uncertainty bounds. Standard neural networks produce uncalibrated confidence scores on small samples, while alternatives like Gaussian Processes suffer from kernel degeneracy and Type-II ML overfitting. To guarantee validity without unverifiable parametric assumptions, distribution-free frameworks such as conformal prediction are required. Under the sole

assumption of data exchangeability, conformal methods construct prediction sets $C(X_{n+1})$ satisfying finite-sample marginal coverage:

$$\mathbb{P}\left(Y_{n+1} \in C(X_{n+1})\right) \geq 1 - \alpha \tag{4}$$

for any underlying joint distribution P and any sample size n.

3.5 Synthesis: The Trilemma of Small Data Learning

We summarize these structural bottlenecks as the *Trilemma of Small Data Learning*: using standard unconstrained algorithms on $n < 1000$, one cannot simultaneously achieve low variance, low bias, and calibrated uncertainty quantification.

Table 1: The Trilemma of Small Data Learning under Standard Paradigms

Target Objective	**Standard Approach**	**Resulting Failure Mode on $n < 1000$**
Low Bias	Deep trees, wide MLPs	High variance, noise memorization
Low Variance	Shallow trees, heavy L_2 penalty	High bias, severe underfitting
Calibrated Uncertainty	Gaussian Processes, Deep Ensembles	Kernel degeneracy, Type-II ML overfitting

Overcoming this trilemma requires replacing unconstrained optimization with the mathematical principles of robust statistics, parameter-derived adaptive complexity, and conformal calibration, which we formalize in Section 4.

4 Mathematical Principles for Robust Solutions

Having formalized the bottlenecks in Section 3, we now define the mathematical principles that guide our targeted solutions. Rather than proposing a universal framework, we establish three foundational mechanisms that directly counteract high variance, outlier vulnerability, and the hyperparameter trap.

4.1 Robust Leaf Estimation: Bounding the Influence Function

To overcome the zero breakdown point of standard second-order leaf weights, SmallGBM replaces the empirical mean with a hybrid estimator tailored to leaf sample size. For a leaf with instance set I and pseudo-residuals r_i:

- For small leaves ($|I| \leq 30$), we compute the sample median: $\hat{w}_{\text{leaf}} = \text{median}_{i \in I}(r_i)$. This achieves the maximum theoretical breakdown point of 50% and strictly bounds the influence function against extreme residual spikes.
- For larger leaves ($|I| > 30$), we transition to a spatially regularized weighted mean: $\hat{w}_{\text{leaf}} = \frac{\sum_{i \in I} w_i r_i}{\sum_{i \in I} w_i}$, with weights $w_i = \frac{1}{1+\|x_i - \mu_I\|}$, where μ_I is the feature-space centroid of the leaf. While its influence function with respect to a target outlier y_i remains linear, this transition recovers statistical efficiency on larger samples (where the median suffers from a 64% asymptotic relative efficiency under Gaussian noise) while downweighting geometrically isolated feature anomalies.

To further stabilize the tree structure, we apply signal-adaptive empirical Bayes shrinkage toward the parent node estimate $\hat{w}_{\text{parent}}$. Let σ^2_{prior} denote the prior signal variance (default $\sigma_{\text{prior}} = 0.5$). To prevent a single extreme residual from inflating the variance estimate and forcing artificial shrinkage, the leaf residual variance $\hat{\sigma}^2_{\text{leaf}}$ is estimated robustly via the Median Absolute Deviation (MAD):

$$\hat{\sigma}_{\text{leaf}} = 1.4826 \cdot \text{median}_{i \in I} \left| r_i - \text{median}_{j \in I}(r_j) \right| \tag{5}$$

The shrinkage coefficient $\gamma \in [0, 1]$ is defined as the ratio of leaf estimation noise to total variance:

$$\gamma = \frac{\hat{\sigma}^2_{\text{leaf}}/|I|}{\sigma^2_{\text{prior}} + \hat{\sigma}^2_{\text{leaf}}/|I|} \tag{6}$$

yielding the final regularized weight:

$$\hat{w}_{\text{final}} = (1 - \gamma)\hat{w}_{\text{leaf}} + \gamma \hat{w}_{\text{parent}} \tag{7}$$

When a leaf is small (low $|I|$) or exhibits high robust dispersion (large $\hat{\sigma}^2_{\text{leaf}}$), the ratio $\hat{\sigma}^2_{\text{leaf}}/|I|$ grows, driving $\gamma \to 1$ and shrinking the noisy leaf back toward the stable parent estimate. Conversely, large, homogeneous leaves drive $\gamma \to 0$, retaining their local estimate.

4.2 Adaptive Complexity: Deriving Architecture from Data

To bypass the hyperparameter trap, SmallMLP replaces validation-based architecture search with deterministic scaling laws derived from dataset parameters (n, d, K). For classification, the width of the first hidden layer is bounded as:

$$w_1 = \max\left(2K,\ \min\left(\left\lfloor \alpha\sqrt{nK\sqrt{d}} \right\rfloor,\ 4n\right)\right) \tag{8}$$

with subsequent layers decaying geometrically according to $w_l = \max\left(K,\ \lfloor w_1 \cdot \beta^{l-1} \rfloor\right)$, where $\alpha = 4.0$ and $\beta = 0.7$ are fixed structural constants. This formulation ensures that network capacity grows sublinearly with sample size and class complexity ($\propto \sqrt{nK}$) and dimensionality ($\propto d^{1/4}$), while enforcing a strict lower bound of $2K$ to preserve class separability and an upper cap of $4n$ to prevent overparameterization. For regression ($K = 1$), the width defaults to $\min(2n, 128)$.

Regularization is similarly coupled to data geometry. Weight decay scales inversely with sample size as $\lambda = 1/n$, and dropout probability is governed by a clamped dimensional ratio:

$$p_{\text{drop}} = \min\left(\max\left(3 \cdot \frac{d}{n},\ 0.1\right),\ 0.5\right) \tag{9}$$

While raw d/n ratios systematically under-regularize low-dimensional small datasets, clamping within $[0.1, 0.5]$ enforces sufficient stochastic regularization across all (n, d) regimes without requiring a validation sweep.

4.3 Conformal Prediction and the Asymmetry of Tuning Dimensionality

To achieve distribution-free uncertainty quantification, SmallMLP employs locally weighted conformal prediction over the learned penultimate embedding space $h(x)$. Given a calibration set $\mathcal{D}_{\text{cal}} = \{(x_j, y_j)\}_{j=1}^{m}$ and conformity scores $s_j = |y_j - \hat{y}(x_j)|$ (regression) or $s_j = 1 - \hat{p}_{y_j}(x_j)$ (classification), the prediction region for a test point x^* is constructed via a weighted quantile:

$$C(x^*) = \left\{y : s(x^*, y) \le \hat{q}_{1-\alpha}^{\text{weighted}}(x^*)\right\}, \quad \text{where} \quad K(x^*, x_j) = \exp\left(-\frac{\|h(x^*) - h(x_j)\|^2}{2h_{\text{cal}}^2}\right) \tag{10}$$

Under exchangeability, this guarantees finite-sample marginal coverage $\mathbb{P}(Y_{n+1} \in C(X_{n+1})) \ge 1 - \alpha$ while adapting interval widths to local embedding density.

Resolving the Validation Split Paradox. In SmallMLP, selecting the kernel bandwidth h_{cal} utilizes a 60/20/20 (train/calibration/validation) split, which superficially appears to contradict our critique of validation splits in Section 3.3. This apparent paradox is resolved by the *asymmetry of tuning dimensionality*. In standard hyperparameter tuning, searching over a combinatorial grid of architecture and optimization parameters (Λ_{arch} with $|\Lambda_{\text{arch}}| \sim 10^3 - 10^5$) directly alters the hypothesis class $\mathcal{F}$, inducing a massive multiplicity penalty $\mathcal{O}(\sqrt{\log|\Lambda_{\text{arch}}|/n_{\text{val}}})$ that overfits the predictor to validation noise. Conversely, during SmallMLP training, the backbone parameters are already fixed via deterministic formulas. The bandwidth h_{cal} is a single post-hoc scalar evaluated over a compact one-dimensional grid ($|\Lambda_{\text{cal}}| \approx 10$), keeping $\sqrt{\log 10/n_{\text{val}}}$ negligible. Crucially, conformal coverage validity holds unconditionally on the calibration set regardless of h_{cal}; the validation step merely optimizes interval sharpness over a smooth, unimodal objective without risking catastrophic model selection failure.

5 Standard Baselines vs. Small Data Realities

We now position our targeted solutions against prevailing machine learning baselines. Rather than merely listing empirical limitations, we map each baseline architecture directly to the mathematical failure modes formalized in Section 3.

5.1 XGBoost and LightGBM: Unbounded Influence and Tuning Dependence

Modern gradient boosting implementations represent the de facto standard for medium-to-large tabular data. However, as shown in Equation (2), their second-order leaf weight estimator $w^* = -\frac{\sum_{i\in I} g_i}{\sum_{i\in I} h_i + \lambda}$ remains non-robust. Under squared error or cross-entropy with severe label noise, the numerator $\sum_{i\in I} g_i$ exhibits an unbounded influence function, allowing a single outlier in a small leaf to dominate the weight update. Furthermore, avoiding overfitting in XGBoost and LightGBM requires precise coordination of depth, learning rate, λ, and subsampling ratios. As established in Section 3.3, optimizing this high-dimensional hyperparameter grid on $n < 1000$ fails due to validation depletion and the multiplicity penalty $\mathcal{O}(\sqrt{\log|\Lambda|/n_{\text{val}}})$, resulting in high-variance predictors.

5.2 Random Forests: Variance Reduction at the Cost of Bias and Extrapolation

Random Forests mitigate variance via bootstrap aggregation and feature subsampling, rendering them less sensitive to hyperparameter tuning than gradient boosting. Nevertheless, they suffer from structural bias in low-sample regression and probability estimation. Because individual trees partition the space into orthogonal hyper-rectangles with piecewise-constant predictions, the ensemble struggles to approximate smooth, continuous nonlinearities when sample density $n^{1/d}$ is low. Moreover, tree ensembles cannot extrapolate trends beyond the bounding box of the training features and lack native, distribution-free interval calibration.

5.3 Standard MLPs: Overparameterization and the Architecture Trap

Standard multilayer perceptrons are capable of smooth function approximation, yet their hypothesis class $\mathcal{F}$ is unconstrained by default. On small tabular datasets, a fixed MLP architecture either memorizes noise (if overparameterized) or fails to capture complex interactions (if underparameterized). Because validation splits cannot reliably guide neural architecture search over depth, width, and dropout (Section 3.3), standard MLPs exhibit severe instability. Additionally, training with standard unregularized MSE loss leaves the network vulnerable to target outliers, while raw outputs lack calibrated uncertainty bounds (Section 3.4).

5.4 Gaussian Processes: Kernel Degeneracy and Type-II ML Overfitting

Gaussian Processes (GPs) provide principled Bayesian uncertainty quantification, making them a natural theoretical candidate for small data. While their $\mathcal{O}(n^3)$ time and $\mathcal{O}(n^2)$ memory complexity is computationally manageable for $n < 1000$, GPs fail in practice due to two statistical pathologies:

1. **Metric degeneracy in $d \approx n$:** Standard stationary kernels (e.g., RBF, Matérn) depend on Euclidean distances $\|x - x'\|_2$, which lose discriminative power in moderate-to-high dimensions due to concentration of measure (Section 3.1).
2. **Marginal likelihood overfitting:** Selecting kernel hyperparameters (e.g., Automatic Relevance Determination length-scales) via Type-II Maximum Likelihood estimation optimizes $d + 2$ parameters on n samples. In low-sample regimes, the log-marginal likelihood surface becomes highly non-convex, causing GPs to overfit noise and yield miscalibrated posterior variances. Furthermore, standard Gaussian observation models remain highly sensitive to heavy-tailed outliers.

5.5 In-Context Foundation Models (TabPFN): Prior Mismatch and Scope Limits

Recent prior-data fitted networks, most notably TabPFN, bypass empirical hyperparameter tuning entirely by performing single-pass approximate Bayesian inference via a Transformer pre-trained on synthetic structural causal models. While TabPFN serves as a formidable tuning-free baseline for small tabular classification, it is structurally constrained: (1) its standard architecture is restricted to classification with hard limits on feature dimensionality ($d \leq 100$) and class count ($K \leq 10$); (2) it does not natively address continuous nonlinear regression with calibrated prediction intervals; and (3) when real-world data violates the synthetic pre-training prior (e.g., heavy-tailed sensor anomalies or severe heteroscedasticity), its posterior approximations lack finite-sample coverage guarantees.

5.6 Synthesis of Baseline Failure Modes

Table 2 synthesizes how standard baselines interact with the small-data bottlenecks compared to our targeted case studies.

Table 2: Mapping Algorithmic Families to Small-Data Mathematical Bottlenecks

Algorithm	Outlier Sensitivity	Tuning Burden	Uncertainty Validity	Primary Regime / Limitation
XGBoost / LightGBM	High (unbounded g_i)	High ($\|\Lambda\| \gg 10^2$)	None (point)	Fails without validation tuning
Random Forest	Moderate (bagging)	Low	Empirical variance	High bias on smooth regression
Standard MLP	High (under MSE)	Extreme (arch search)	Uncalibrated	Severe validation overfitting
Gaussian Process	High (Gaussian noise)	Moderate (Type-II ML)	Parametric / Fragile	Fails at $d \approx n$ (kernel degeneracy)
TabPFN	Moderate (prior-bound)	None (in-context)	Uncalibrated softmax	Classification only; fixed d, K limits
SmallGBM	**Low (median + MAD)**	**None (tuning-free)**	None (point)	**Robust classification** ($n < 1000$)
SmallMLP	**Moderate** ($\lambda = 1/n$)	**1D scalar** (h_{cal})	**Finite-sample** ($1 - \alpha$)	**Regression & UQ** ($n < 500$)