NSF/IUCRC CAC PROJECT

INTEGRATED VISUALIZING, MONITORING, AND MANAGING HPC SYSTEMS

Jie Li

Doctoral Student, TTU

11/06/2020

Advisors:

Mr. Jon Hass, SW Architect, Dell Inc.

Dr. Alan Sill, Managing Director, HPCC, TTU

Dr. Yong Chen, Associate Professor, CS Dept, TTU

Dr. Tommy Dang, Assistant Professor, CS Dept, TTU

JOB - STEP - TASK

Created with **sbatch**

Created with **srun**

Requested via **--ntasks**
or **--ntasks-per-node**

Job

Step1	Step2	Step3
Task	Task	Task
Task	Task	Task
Task	Task	Task
...	...	...

...

CPUs are requested via **--cpus-per-task**

- $JOBID
  - Statistics relevant to the job allocation itself, utilization statistics for job allocations will be reported as zero.
- $JOBID.batch
  - Jobs submitted with sbatch have one implicit step: the Bash script itself. It accounts for the resources needed by the batch script.
- $JOBID.extern
  - accounts for all resources usage by that job outside of slurm.
- $JOBID.0, $JOBID.1, etc.
  - All jobsteps are accounted for resource usage separately by Slurm.

RedRaider
Cluster

MongoDB

Influx

sacct

RedRaider
Login Node

Job data strings

Call *sacct* remotely

Demo

QUESTIONS?/COMMENTS?