

## Exercise Solutions

### Section 3 Lesson 1. Application Initialization

---

#### Exercise 1: Application Initialization

Use your IDE to do this exercise.

##### Step 1. Examine the *index.php* file contents

- a) Open the file *index.php* in the Magento root directory in your IDE.
- b) Step through it up until `Mage::run()` is called.

##### Step 2. Change the store view via *.htaccess*

---

**Note:** This configuration should not be done in the *.htaccess* file for production installations, because that file is overwritten during upgrades. The configuration should take place in the web server configuration; for example, the Apache `<VirtualHost>` directive.

---

- a) Find the store view codes for the Magento instance you are working on. Refer to the exercise solutions for Section 2, Lesson 6, Exercise 2 for instructions on how to locate a store view code.
- b) Open the file *.htaccess* in the Magento root directory.
- c) Add the following code to declare an environment variable named `MAGE_RUN_CODE`.

---

**Note:** Replace `german` with a store view code from your installation, but don't use the store code `default` for this exercise.

---

```
SetEnv MAGE_RUN_CODE german
```

- d) Start a fresh session and load the Magento home page. There are several ways to start a fresh session depending on your browser:
  - Open a private browsing tab
  - Clear all cookies for your development website.
- e) Load the Magento home page.
- f) Notice that the specified store view is loaded.