	Request							
ID	Request the User API with valid required parameters	Status code	Response (match the model)	Status check	Response headers	Performance	Result	Comments
1	GET/store/inventory	-		Doesn't have negative responses (in Swagger)	-	-	Pass	
2	POST/store/order	400		The 'Bad input' message should be displayed when user uses invalid {orderId} or {petId} *enter symbols to int fields	Has following headers: - Content-Type: application/json - Accept: application/json	Response received within a reasonable time	Pass	
3	GET/store/order/{orderId}	400	{ "code": 400, "type": "unknown", "message": "Invalid ID supplied" }	The 'Invalid Id Supplied' message is displayed when user uses invalid (OrderId) *e.g. OrderId=Iwe	Has following headers: - Accept: application/json	Response received within a reasonable time	Fail	Postman response: { "code": 404, "type": "unknown", "message": "java.lang. NumberFormatException: For input string: \"df\"" }
4	GET/store/order/{orderId}	404		The 'Order not found' message is displayed when user uses a valid but non-existent {OrderId}	Has following headers: - Accept: application/json	Response received within a reasonable time	Pass	
5	Delete/store/order/{orderId}	400		The 'Invalid ID supplied' message should be displayed when user uses an invalid 'OrderId' *OrderID=qwe	Has following headers: - Content-Type: application/json - Accept: application/json	Response received within a reasonable time	Fail	Postman response: { "code": 404, "type": "unknown", "message": "java.lang. NumberFormatException: For input string: \"qwe\\"" }
6	Delete/store/order/{orderId}	404		The 'Order not found' message is displayed when used valid but non-existent {OrderId} *{OrderId = 7979797979}	Has following headers: - Content-Type: application/json - Accept: application/json	Response received within a reasonable time	Pass	