

ID	Request						Result	Comment
	Request the Pet API with valid invalid required parameters	Status code	Response	Status check	Response headers	Performance		
1	GET/pet/{petId}	404	{ "code": 1, "type": "error", "message": "Pet not found" }	The ' <i>Pet not found</i> ' message is displayed when the user uses a valid but non-existent {petId}	Has following headers: - Content-Type: application/json	Response received within a reasonable time	Pass	
2	GET/pet/{petId}	400	{ "code": 400, "type": "unknown", "message": "Invalid ID supplied" }	The ' <i>Bad input</i> ' message is displayed when user uses an invalid {petId} *example, petId = test	Has following headers: - Content-Type: application/json	Response received within a reasonable time	Fail	Postman response: { "code": 404, "type": "unknown", "message": "java.lang. NumberFormatException: For input string: \"test\"" }
3	POST /pet	405	{ "code": 405, "type": "unknown", "message": "Invalid input" }	The ' <i>Invalid input</i> ' message should be displayed when user uses invalid {petId} *example, petId = test	Has following headers: - Content-Type: application/json - Accept: application/json	Response received within a reasonable time	Fail	The 400 status code is displayed in postman with the 'bad input' message
4	POST /pet/{petid}	404	{ "code": 404, "type": "unknown", "message": "not found" }	The ' <i>Not found</i> ' message should be displayed when user uses a valid but non-existent {petId}	Has following headers: - Content-Type: application/x-www-form-urlencoded - Accept: application/json	Response received within a reasonable time	Pass	
5	PUT /pet	400	{ "code": 400, "type": "unknown", "message": "Invalid ID supplied" }	The ' <i>Invalid ID supplied</i> ' message should be displayed when user uses an invalid {petId} *example, petId = 12qwerty	Has following headers: - Content-Type: application/json - Accept: application/json	Response received within a reasonable time	Pass	
6	PUT /pet	404	{ "code": 404, "type": "unknown", "message": "Pet not found" }	The ' <i>Pet not found</i> ' message should be displayed when user uses a valid but non-existent {petId} *example, {petId = 1212121212}	Has following headers: - Content-Type: application/json - Accept: application/json	Response received within a reasonable time	Fail	Postman response: { "code": 500, "type": "unknown", "message": "something bad happened" }

7	GET/pet/findByStatus	400	{ "code": 400, "type": "unknown", "message": "Invalid status value" }	The ' <i>Invalid status value</i> ' message should be displayed when user uses invalid status <i>*example, status=click</i>	<i>Has following header:</i> - Accept: application/json	Response received within a reasonable time	Fail	Postman response: []
8	DELETE /pet/{petid}	400	{ "code": 400, "type": "unknown", "message": "Invalid ID supplied" }	The ' <i>Invalid ID supplied</i> ' message should be displayed when user uses invalid { <i>petId</i> } <i>*example, status=clomb</i>	<i>Has following header:</i> - Accept: application/json	Response received within a reasonable time	Fail	Postman response: { "code": 404, "type": "unknown", "message": "java.lang. NumberFormatException: For input string: \"jk\"" }
9	DELETE /pet/{petid}	404	{ "code": 404, "type": "unknown", "message": "Pet not found" }	The 'Pet not found' message should be displayed when user uses a valid but non-existent { <i>petId</i> } <i>example, {petId = 33333333}</i>	<i>Has following header:</i> - Accept: application/json	Response received within a reasonable time	Pass	