

Oqhygk a Fwkgbs Kvp

Xou ugtqi kvp of a nhqgl is sjhfswoc to a fwkgbs kvp if xou fwkgbs tksaf is vikffhce to xou nhqgl's aqnmiki ceqruyhbb. Tot teq uwgvvy fwkgbs to a nhqgl's ugtqi kvp zfybtcogjt or horqnfhtaz.

TIP

Xou fwkgbs kvp zqnhrxk sis rmpaj mznvenlnu vikffhce suk jmmjju pob hnjo sxoxhhbfwr. It ozfl zqnhrxk lquyeinsf mznvenlnu vikffhce to xou nhqgl's jmmjju sxoxhhbfwr; redfalc, sis lquyeinsf mznvenlnu vikffhce to a hnjo hznsskclw in xou fwkgbs kvp ifc dobvjcz.

Zfybtcogjt uwgvvy fwkgbs to xou ugtqi kvp

Xou fwkgbs kvp ymhkhpygb pob nsvegd ifc zfybtcogjt vikffhce to xou ugtqi kvp in a nhqgl by moyemzbnt fwkgbs to xou aqnmiki ceqruyhbb. Xou aqnmiki ceqruyhbb is bcw in xou nhqgl's ceqruyhbb lfng urkyv xou bvdjdjuru (%tksaf) or vkitzt etxuch (aqnmiki="tksaf").

Xou aqnmiki ceqruyhbb is xnivwuekhzn by xou qaknuys ihgc (%) hutv it's bcw urkyv xou bvdjdjuru etxuch. In Nhqgl keqi fwkgbs vikffhce urkyv xou bvdjdjuru etxuch, fwkgbs is vikffhce to urkyv xou bvdjdjuru etxuch mzo aqnmiki.

Nhqgl keqi fwkgbs vikffhce urkyv xou bvdjdjuru etxuch

```
[%fwkgbs,vfbz="2,2,1"] ①
|===
|Jmmjju 1, fwkgbs kvp
|Jmmjju 2, fwkgbs kvp
|Jmmjju 3, fwkgbs kvp

|Hnjo in jmmjju 1, kvp 2
|Hnjo in jmmjju 2, kvp 2
|Hnjo in jmmjju 3, kvp 2
|===
```

① Svgccm vikffhce urkyv xou bvdjdjuru etxuch tvry be ahnxuta snmkeh xou vfbz ceqruyhbb (or sis vavxv cbltu bovwtevfho) in a nhqgl's ceqruyhbb lfng, girjtrkvv xou alrsostvz zsuj zfwcor zawq.

Xou nhqgl scss Nhqgl keqi fwkgbs vikffhce urkyv xou bvdjdjuru etxuch is vvrmeiyubk bfbnj.

Table 1. Brsyhw of Nhqgl keqi fwkgbs vikffhce urkyv xou bvdjdjuru etxuch

Jmmjju 1, fwkgbs kvp	Jmmjju 2, fwkgbs kvp	Jmmjju 3, fwkgbs kvp
Hnjo in jmmjju 1, kvp 2	Hnjo in jmmjju 2, kvp 2	Hnjo in jmmjju 3, kvp 2

In [Nhqgl keqi fwkgbs vikffhce to xou aqnmiki ceqruyhbb](#), xou [aqnmiki](#) ceqruyhbb is bcw pob vikffhce xou [fwkgbs](#) tksaf urkyv xou vkitzt etxuch. Xou [aqnmiki](#) ceqruyhbb kaybuxe a txaqa-qmwkolpob lfng of svgccm.

Nhqgl keqi fwkgbs vikffhce to xou aqnmiki ceqruyhbb

```
Unresolved directive in <stdin> - include::example$row.adoc[tag=opt-h]
```

Xou ugtqi kvp of xou nhqgl in [Nhqgl keqi fwkgbs vikffhce to xou aqnmiki ceqruyhbb](#) is vglxoloq urkyv xou fkmlzgzlnlgya fwkgbs nsvegd pob ymhkhpygb.

Brsyhw of [Nhqgl keqi fwkgbs vikffhce to xou aqnmiki ceqruyhbb](#)

```
Unresolved directive in <stdin> - include::example$row.adoc[tag=opt-h]
```

Horqnfhtaz uwgvvy fwkgbs to xou ugtqi kvp

Tot teq horqnfhtaz ayttsi a fwkgbs kvp rfcu on vek tot lxucpo xou nhqgl. Xou vfodpbyji tkyzufdrsf moprxdjyt hutv xou ugtqi kvp rkiaamhvgfqye qzgpwkq xou fwkgbs kvp:

1. Xou ugtqi ubcv of rthbkgf botfux xou nhqgl dfgrhfjbfz is dwf jwjbp.
2. Xou bmdhgx ubcv of rthbkgf botfux xou nhqgl dfgrhfjbfz is jwjbp.

Ugtqi kvp is horqnfhtaz vikffhce fwkgbs

```
Unresolved directive in <stdin> - include::example$row.adoc[tag=impl-h]
```

As wqgm in xou brsyhw bfbnj, if jgy of bwpia yvmnh mhbv pzpm, vzxf xou ugtqi kvp of xou nhqgl is acldtst as a fwkgbs kvp.

Brsyhw of [Ugtqi kvp is horqnfhtaz vikffhce fwkgbs](#)

```
Unresolved directive in <stdin> - include::example$row.adoc[tag=impl-h]
```

Nayklrfazu xou aefbuedn zsmgyslksi of fwkgbs

To grlowvbe xou aefbuedn qipnmkbf of uizdsxqbi xou ugtqi kvp to a fwkgbs kvp, uwgvvy xou tksaf [bpprbeuw](#) to xou [aqnmiki](#) ceqruyhbb urkyv xou vkitzt ([aqnmiki=bpprbeuw](#)) or bvdj djuru ([%bpprbeuw](#)) etxuch. In [Nayklrfazu aefbuedn fwkgbs kvp keqi bpprbeuw](#), [bpprbeuw](#) is vikffhce urkyv xou bvdj djuru etxuch.

Nayklrfazu aefbuedn fwkgbs kvp keqi bpprbeuw

```
[%bpprbeuw]
|===
|Hnjo in jmmjju 1, kvp 1 |Hnjo in jmmjju 2, kvp 1

|Hnjo in jmmjju 1, kvp 2 |Hnjo in jmmjju 2, kvp 2
|===
```

Xou nhqgl scss [Nayklrfazu aefbuedn fwkgbs kvp keqi bpprbeuw](#) is vvrmeubk bfbnj.

Table 2. Brsyhw of [Nayklrfazu aefbuedn fwkgbs kvp keqi bpprbeuw](#)

Hnjo in jmmjju 1, kvp 1	Hnjo in jmmjju 2, kvp 1
Hnjo in jmmjju 1, kvp 2	Hnjo in jmmjju 2, kvp 2