

# **Dynamic visualization of high-dimensional functions via low-dimension projections and sectioning across 2D and 3D display devices**


A thesis submitted for the degree of

Doctor of Philosophy

by

Nicholas S Spyrison

B.Sc. Statistics, Iowa State University



Department of Econometrics and Business Statistics

Monash University

Australia

---

January 2019

# Contents

<b>Acknowledgements</b>	<b>v</b>
<b>Declaration</b>	<b>vii</b>
<b>Preface</b>	<b>ix</b>
<b>Abstract</b>	<b>xi</b>
<b>1 Introduction</b>	<b>1</b>
<b>2 Literature review</b>	<b>3</b>
2.1 Touring . . . . .	3
2.2 Virtual reality . . . . .	7
<b>3 Tour methodology</b>	<b>9</b>
3.1 Spinnifex . . . . .	9
<b>4 Display dimensionality</b>	<b>11</b>
4.1 My work . . . . .	11
<b>5 Human-computer interaction of 3d projections</b>	<b>13</b>
5.1 Tour in 3D . . . . .	13
<b>A Additional stuff</b>	<b>15</b>
<b>Bibliography</b>	<b>17</b>



# Acknowledgements

I would like to thank ...



# Declaration

I hereby declare that this thesis contains no material which has been accepted for the award of any other degree or diploma in any university or equivalent institution, and that, to the best of my knowledge and belief, this thesis contains no material previously published or written by another person, except where due reference is made in the text of the thesis.

Nicholas S Spyrison





# Preface

The material in Chapter 1 has been submitted to the journal *Journal of Impossible Results* for possible publication.

The contribution in Chapter ?? of this thesis was presented in the International Symposium on Nonsense held in Dublin, Ireland, in July 2015.



# **Abstract**

This thesis is about ...



# **Chapter 1**

## **Introduction**

This is where you introduce the main ideas of your thesis, and an overview of the context and background.

In a PhD, Chapter 2 would normally contain a literature review. Typically, Chapters 3–5 would contain your own contributions. Think of each of these as potential papers to be submitted to journals. Finally, Chapter 6 provides some concluding remarks, discussion, ideas for future research, and so on. Appendixes can contain additional material that don't fit into any chapters, but that you want to put on record. For example, additional tables, output, etc.



## Chapter 2

# Literature review

### 2.1 Touring

#### 2.1.1 Overview

In univariate datasets histograms, or smoothed density curves are employed to visualize data. In bivariate data scatterplots and contour plots (2-d density) can be employed. In three dimensions the two most common techniques are: 2-d scatter plot with the 3rd variable as an aesthetic (such as, color, size, height, *etc.*) or rendering the data in a 3-d volume using some perceptive cues giving information describing the seeming depth of the image <sup>1</sup>. When there are 4 variables: 3 variables as spatial-dimensions and a 4th as aesthetic, or a scatterplot matrix consisting of 4 histograms, and 6 unique combinations of bivariate scatterplots.

Let  $p$  be the number of numeric variables; how do we visualize data for even modest values of  $p$  (say 6 or 12)? It's far too common that visualizing in data-space is dropped altogether in favor of modeling parameter-space, model-space, or worse, long tables of statistics without visuals(Wickham, Cook, and Hofmann, 2015). Yet, we all know of the risks and possible mis-leadingness of relying too heavily on parameters alone(Anscombe,

---

<sup>1</sup>Graphs of data depicting 3 dimension are typically printed on paper, or rendered on a 2-d monitor, they are intrinsically 2-d images. They are sometimes referred to as 2.5-d, or more frequently erroneously referred to as 3-d, more on this later.

1973; Matejka and Fitzmaurice, 2017). So why do we get aware from visualizing in data-space? Scalability, in a word, we are not familiar with methods that allow us to concisely depict and digest  $p \geq 5$  or so dimensions. This is where touring comes in; using the wide range of touring techniques we are able to preserve the visualization of data-space, and the intrinsic understanding of structure and the data, beyond looking at statistic values alone.

Touring is a linear dimensionality reduction technique that orthogonally projects  $p$ -space down to  $d$ -space. Many of these projections are interpolated while varying the rotation of  $p$ -space and viewed in order to the effect of watching an animation of the lower dimensional embedding changing as  $p$ -space is manipulated. Shadow puppets offer a useful analogy to aid in conceptualizing touring. Imagine a fixed light source facing a wall. When a hand or puppet is introduced the 3-dimensional object projects a 2-dimensional shadow onto the wall. This is a physical representation of a simple projection, that from  $p = 3$  down to  $d = 2$ . If the object rotates then the shadow correspondingly changes. Observers watching only the shadow are functionally watching a 2-dimensional tour as the 3-dimensional object is manipulated.

### 2.1.2 History

In 1974 Friedman and Tukey purposed Projection Pursuit(Friedman and Tukey, 1974) (sometimes referred to as PP) while working at Bell Labs. Projection Pursuit involves identifying “interesting” projection, remove a single component of the data, and then iterate in this newly embedded subspace. Within each subspace the projection seeks for a local extrema via gradient descent (historically referred to as hill climbing algorithms), hence the nomenclature pursuit.

Touring was first introduced by Asimov in 1985 with his purposed Grand Tour(Asimov, 1985) at Stanford University. In which, Asimov suggested three types of Grand Tours: torus, at-random, and random-walk. The specifics of which will be discussed below in the Typology section.



... Note that the the above methods have no input from the user aside from the starting basis. the remainder touring development has largely been around user interaction and application.

Below is a non-exhaustive list of software implementing touring in some degree, ordered by descending year:

- Spinifex(**spinifex**) – 2018 for Linux, Unix, and Windows.
- Tourr(Wickham et al., [2011](#)) – 2011 for Linux, Unix, and Windows. R package.
- CyrstalVision(Wegman, [2003](#)) – 2003 for Windows
- GGobi(Swayne et al., [2003](#)) – 2003 for Linux and Windows
- VRGobi(Nelson, Cook, and Cruz-Neira, [1998](#)) – 1998 for use with the C2 in stereoscopic 3d spaces
- ExplorN(Carr, Wegman, and Luo, [1996](#)) – 1996 for SGI Unix
- XGobi(Swayne, Cook, and Buja, [1991](#)) – 1991 for Linux, Unix, and Windows (via emulation)
- XLispStat(Tierney, [1990](#)) – 1991 for Unix, and Windows
- Prim-9(Asimov, [1985](#); FisherKeller, Friedman, and Tukey, [1974](#)) – 1985 on internal os

additionally there have been a number of graphical user interfaces (gui) that have been produced including[Huang, Cook, and Wickham ([2012](#));]

### **2.1.3 Typology**

#### **Movement**

A fundamental aspect of touring is the path of rotation. Of which there are four primary distinctions(Buja et al., [2005](#)): random choice, precomputed choice, data driven, and manual control.

- Random choice such as Asimov’s grand tour(Asimov, [1985](#)).
  - torus
  - at-random

- random-walk
- Precomputed choice, *e.g.* the little tour(McDonald, 1982).
  - little tour
- Data driven - a guided tour performing (stochastic) gradient descent on some objective function(Hurley and Buja, 1990).
  - holes
  - cmass
- Manual control, a constrained rotation on selected manipulation variable and magnitude(Cook and Buja, 1997).

... \* torus: where a  $p$ -dimensional torus,  $T^p$  is created from a Cartesian product of  $p$  unit circles with  $T^p \in \mathbb{R}^p$ . Unfortunately uniformity of the parameters do not correlate to uniform points on the surface of the torus. If step distance between frames is fixed, disproportionate time is spent between subspaces. If step distance is change to account for uniform points on the torus then the continuity of the tour is lost.

\* at-random: where each 2-frame is chosen at random without replacement. This affords an assured uniform distribution of subspaces, but is far to discontinuous for observation. It also leaves no parameters to control. \* random-walk: combines the continuity of the torus method and the uniformity of the at-random method while leaving room for a control parameter.

## Geoms

Scatterplots offer a simple, general case for viewing lower-dimension embeddings of higher-dimensions. Such visualization offer  $p$ -dim down to  $d$ -dim, typically two in the case of a standard monitor. Yet, no intrinsic value stops touring being used in other graphics or geoms (geometrics). For instance using parallel coordinate plots (PCP)(Ocagne, 1885), Andrews plots (Andrews, 1972), Chernoff faces (Chernoff, 1973), anaglyphs (Rollmann, 1853), star glyphs (Siegel et al., 1972), scatterplot matrix (Chambers et al., 1983), and even pictures all offer perfectly valid graphs in  $p$ -dimensions.

This works well when the number of dimensions being toured is small (in the neighborhood of 5-10), yet the number of view, or 2-frames and we can produce from  $p$ -space suffers from the so called blessing/curse of dimensionality. In which the plethora of degrees of freedom either offer many (non-unique) solutions to a problem or something that becomes ever increasing unlikely, *ie.* a bivariate square needs .

### **2.1.4 Linear vs non-linear dimensionality reduction**

## **2.2 Virtual reality**



## **Chapter 3**

# **Tour methodology**

### **3.1 Spinnifex**

#### **3.1.1 Tourr**

#### **3.1.2 Plottly**



## **Chapter 4**

# **Display dimensionality**

### **4.1 My work**

#### **4.1.1 XGobbi vs the C2**





## **Chapter 5**

# **Human-computer interaction of 3d projections**

### **5.1 Tour in 3D**

#### **5.1.1 ImAxes / IATK**



## **Appendix A**

### **Additional stuff**

You might put some computer output here, or maybe additional tables.

Note that line 5 must appear before your first appendix. But other appendices can just start like any other chapter.



# Bibliography

- Andrews, DF (1972). Plots of High-Dimensional Data. *Biometrics* **28**(1), 125–136. (Visited on 12/19/2018).
- Anscombe, FJ (1973). Graphs in Statistical Analysis. *The American Statistician* **27**(1), 17–21. (Visited on 12/19/2018).
- Asimov, D (1985). The grand tour: a tool for viewing multidimensional data. *SIAM journal on scientific and statistical computing* **6**(1), 128–143.
- Buja, A, D Cook, D Asimov, and C Hurley (2005). “Computational Methods for High-Dimensional Rotations in Data Visualization”. en. In: *Handbook of Statistics*. Vol. 24. Elsevier, pp.391–413. [http : / / linkinghub . elsevier . com / retrieve / pii / S0169716104240147](http://linkinghub.elsevier.com/retrieve/pii/S0169716104240147) (visited on 04/15/2018).
- Carr, D, E Wegman, and Q Luo (1996). ExplorN: Design considerations past and present. **129**.
- Chambers, J, W Cleveland, B Kleiner, and P Tukey (1983). Graphical Methods for Data Analysis. eng.
- Chernoff, H (1973). The Use of Faces to Represent Points in K-Dimensional Space Graphically. *Journal of the American Statistical Association* **68**(342), 361–368. (Visited on 01/05/2019).
- Cook, D and A Buja (1997). Manual Controls for High-Dimensional Data Projections. *Journal of Computational and Graphical Statistics* **6**(4), 464–480. (Visited on 04/15/2018).
- FisherKeller, MA, JH Friedman, and JW Tukey (1974). PRIM-9: An Interactive Multidimensional Data Display and Analysis System.
- Friedman, J and J Tukey (1974). A Projection Pursuit Algorithm for Exploratory Data Analysis. en. *IEEE Transactions on Computers* **C-23**(9), 881–890. (Visited on 06/22/2018).

- Huang, B, D Cook, and H Wickham (2012). tourrGui: A gWidgets GUI for the tour to explore high-dimensional data using low-dimensional projections. *Journal of Statistical Software* **49**(6), 1–12.
- Hurley, C and A Buja (1990). Analyzing High-Dimensional Data with Motion Graphics. *SIAM Journal on Scientific and Statistical Computing* **11**(6), 1193–1211. (Visited on 11/27/2018).
- Matejka, J and G Fitzmaurice (2017). Same Stats, Different Graphs: Generating Datasets with Varied Appearance and Identical Statistics through Simulated Annealing. en. In: *Proceedings of the 2017 CHI Conference on Human Factors in Computing Systems - CHI '17*. Denver, Colorado, USA: ACM Press, pp.1290–1294. <http://dl.acm.org/citation.cfm?doid=3025453.3025912> (visited on 12/19/2018).
- McDonald, JA (1982). INTERACTIVE GRAPHICS FOR DATA ANALYSIS.
- Nelson, L, D Cook, and C Cruz-Neira (1998). XGobi vs the C2: Results of an Experiment Comparing Data Visualization in a 3-D Immersive Virtual Reality Environment with a 2-D Workstation Display. en. *Computational Statistics* **14**(1), 39–52.
- Ocagne, Md (1885). *Coordonnées parallèles et axiales. Méthode de transformation géométrique et procédé nouveau de calcul graphique déduits de la considération des coordonnées parallèles, par Maurice d'Ocagne, ...* French. OCLC: 458953092. Paris: Gauthier-Villars.
- Rollmann, W (1853). Zwei neue stereoskopische Methoden. *Annalen der Physik* **166**, 186–187. (Visited on 01/05/2019).
- Siegel, JH, EJ Farrell, RM Goldwyn, and HP Friedman (1972). The surgical implications of physiologic patterns in myocardial infarction shock. English. *Surgery* **72**(1), 126–141. (Visited on 01/05/2019).
- Swayne, DF, D Cook, and A Buja (1991). *Xgobi: Interactive Dynamic Graphics In The X Window System With A Link To S*.
- Swayne, DF, DT Lang, A Buja, and D Cook (2003). GGobi: evolving from XGobi into an extensible framework for interactive data visualization. *Computational Statistics & Data Analysis*. Data Visualization **43**(4), 423–444. (Visited on 12/19/2018).
- Tierney, L (1990). *LISP-STAT: An Object Oriented Environment for Statistical Computing and Dynamic Graphics*. eng. Wiley Series in Probability and Statistics. New York, NY, USA: Wiley-Interscience.
-

- Wegman, EJ (2003). Visual data mining. en. *Statistics in Medicine* **22**(9), 1383–1397. (Visited on 12/19/2018).
- Wickham, H, D Cook, and H Hofmann (2015). Visualizing statistical models: Removing the blindfold: Visualizing Statistical Models. en. *Statistical Analysis and Data Mining: The ASA Data Science Journal* **8**(4), 203–225. (Visited on 03/16/2018).
- Wickham, H, D Cook, H Hofmann, and A Buja (2011). **tourr** : An R Package for Exploring Multivariate Data with Projections. en. *Journal of Statistical Software* **40**(2). (Visited on 11/23/2018).