

ECS 174: Intro to Computer Vision, Spring 2020

Problem Set 3

Instructor: Yong Jae Lee (yongjaelee@ucdavis.edu)
Instructor: Krishna Kumar Singh (krsingh@ucdavis.edu)
TA: Haotian Liu (lhtliu@ucdavis.edu)
TA: Utkarsh Ojha (uojha@ucdavis.edu)
TA: Yuheng Li (yhnli@ucdavis.edu)

Due: Monday, June 1st, 11:59 PM


Instructions

1. Answer sheets must be submitted on Canvas. Hard copies will not be accepted.
2. Please submit your answer sheet containing the written answers in a file named: `FirstName_LastName_PS3.pdf`.
3. Please submit your code and input/output images in a zip file named: `FirstName_LastName_PS3.zip`. Please do not create subdirectories within the main directory.
4. **You may complete the assignment individually or with a partner (i.e., maximum group of 2 people). If you worked with a partner, provide the name of your partner. We will be using MOSS to check instances of plagiarism/cheating.**
5. For the implementation questions, make sure your code is documented, is bug-free, and works out of the box. Please be sure to submit all main and helper functions. Be sure to not include absolute paths. Points will be deducted if your code does not run out of the box.
6. If plots are required, you must include them in your answer sheet (pdf) and your code must display them when run. Points will be deducted for not following this protocol.

1 Short answer problems [10 points]

1. What exactly does the value recorded in a single dimension of a SIFT keypoint descriptor signify?
2. When performing interest point detection with the Laplacian of Gaussian, how would results differ if we were to (a) take any positions that are local maxima in scale-space, or (b) take any positions whose filter response exceeds a threshold? Specifically, what is the impact on repeatability or distinctiveness of the resulting interest points?

2 Programming: Video search with bag of visual words [90 points]



For this problem, you will implement a video search method to retrieve relevant frames from a video based on the features in a query region selected from some frame. We are providing the image data and some starter code for this assignment.

Provided data

You can access pre-computed SIFT features here:

<https://drive.google.com/file/d/10yk7tvDfmge9fEVm2XbwAmaIRL9R7clK/view?usp=sharing>

The associated images are stored here:

<https://ucdavis.box.com/s/ylxih5tgwja1azx78jkc0d5awcxla71m>

Please note the data takes about **6 GB**. Each .mat file in the provided SIFT data corresponds to a single image, and contains the following variables, where n is the number of detected SIFT features in that image:

descriptors	$n \times 128$	double	// SIFT vectors as rows
imname	1×57	char	// name of image file that goes with this data
numfeats	1×1	double	// number of detected features
orients	$n \times 1$	double	// orientations of the patches
positions	$n \times 2$	double	// positions of the patch centers
scales	$n \times 1$	double	// scales of the patches

Provided code

The following are the provided code files. You are not required to use any of these functions, but you will probably find them helpful. You can access the code here:


<https://ucdavis.box.com/s/cll544a6gq4zaqgf6emn9uf3cq5gwy51>

- `loadDataExample.m`: Run this first and make sure you understand the data format. It is a script that shows a loop of data files, and how to access each SIFT descriptor. It also shows how to use some of the other functions below.
- `displaySIFTPatches.m`: given SIFT descriptor info, it draws the patches on top of an image
- `getPatchFromSIFTParameters.m`: given SIFT descriptor info, it extracts the image patch itself and returns as a single image
- `selectRegion.m`: given an image and list of feature positions, it allows a user to draw a polygon showing a region of interest, and then returns the indices within the list of positions that fell within the polygon.
- `dist2.m`: a fast implementation of computing pairwise distances between two matrices for which each row is a data point
- `kmeansML.m`: a faster k-means implementation that takes the data points as columns

What to implement and discuss in the write-up

Write one script for each of the following (along with any helper functions you find useful), and in your pdf writeup report on the results, explain, and show images where appropriate. **Your code must access the frames and the SIFT features from subfolders called 'frames' and 'sift', respectively, in your main working directory.**

1. **Raw descriptor matching [20 pts]**: Allow a user to select a region of interest (see provided `selectRegion.m`) in one frame, and then match descriptors in that region to descriptors in the second image based on Euclidean distance in SIFT space. Display the selected region of interest in the first image (a polygon), and the matched features in the second image, something like the below example. Use the two images and associated features in the provided file `twoFrameData.mat` (in the zip file) to demonstrate. Note, no visual vocabulary should be used for this one. Name your script `raw_descriptor_matches.m`



2. **Visualizing the vocabulary [25 pts]**: Build a visual vocabulary. Display example image patches associated with two of the visual words. Choose two words that are distinct to illustrate what the

different words are capturing, and display enough patch examples so the word content is evident (25 patches per word displayed). See provided helper function `getPatchFromSIFTParameters.m`. Explain what you see. Name your script `visualize_vocabulary.m`. Please submit your visual words in a file called `kMeans.mat`. This file should contain a matrix of size $k \times 128$ called `kMeans`.

3. **Full frame queries [25 pts]:** After testing your code for bag-of-words visual search, choose 3 different frames from the entire video dataset to serve as queries. Display each query frame and its $M=5$ most similar frames (in rank order) based on the normalized scalar product between their bag of words histograms. Explain the results. Name your script `full_frame_queries.m`
4. **Region queries [20 pts]:** Select your favorite query regions from 3 frames of your choice (which may be different than those used above) to demonstrate the retrieved frames when only a portion of the SIFT descriptors are used to form a bag of words. *Try to include example(s) where the same object is found in the most similar M frames but amidst different objects or backgrounds, and also include a failure case.* Display each query region (marked in the frame as a polygon) and its $M=5$ most similar frames. Explain the results, including possible reasons for the failure cases. Name your script `region_queries.m`

Tips: overview of framework requirements

The basic framework will require these components:

- **Compute nearest raw SIFT descriptors.** Use the Euclidean distance between SIFT descriptors to determine which are nearest among two images' descriptors. That is, "match" features from one image to the other, without quantizing to visual words.
- **Form a visual vocabulary.** Cluster a large, representative random sample of SIFT descriptors from some portion of the frames using k-means. Let the k centers be the visual words. The value of k is a free parameter; for this data something like $k=1500$ should work, but feel free to play with this parameter [see Matlab's `kmeans` function, or provided `kmeansML.m` code]. *Note:* you may run out of memory if you use all the provided SIFT descriptors to build the vocabulary.
- **Map a raw SIFT descriptor to its visual word.** The raw descriptor is assigned to the nearest visual word. [see provided `dist2.m` code for fast distance computations]
- **Map an image's features into its bag-of-words histogram.** The histogram for image I_j is a k -dimensional vector: $F(I_j) = [freq_{1,j}, freq_{2,j}, \dots, freq_{k,j}]$, where each entry $freq_{i,j}$ counts the number of occurrences of the i -th visual word in that image, and k is the number of total words in the vocabulary. In other words, a single image's list of n SIFT descriptors yields a k -dimensional bag of words histogram. [Matlab's `histc` is a useful function]
- **Compute similarity scores.** Compare two bag-of-words histograms using the normalized

scalar product.

- **Sort the similarity scores** between a query histogram and the histograms associated with the rest of the images in the video. Pull up the images associated with the M most similar examples. [see Matlab's `sort` function]
- **Form a query from a region within a frame.** Select a polygonal region interactively with the mouse, and compute a bag of words histogram from only the SIFT descriptors that fall within that region. [see provided `selectRegion.m` code]
- There may be some frames (e.g., all black) in which no features are detected and hence no descriptors are available. If so, you will need to ignore those frames (e.g., using an if statement).

3 OPTIONAL: Extra credit (10 points)

- **Stop list and tf-idf.** Implement a stop list to ignore very common words, and apply tf-idf weighting to the bags of words. Discuss and create an experiment to illustrate the impact on your results.