Product Environmental Footprint

FK-MCP 1,5/ 8-STF-3,81 (1851290)



Product overview

PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Sn, contact connection type: Socket, number of potentials: 8, number of rows: 1, number of positions: 8, number of connections: 8, product range: FK-MCP 1,5/..-STF, pitch: 3.81 mm, connection method: Push-in spring connection, conductor/PCB connection direction: 0 °, pin layout: Linear pinning, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

Constituent materials

Composition of used materials for production:

Material	Share of mass (if possible)
Plastics	41,12%
Metal	54,79%
Packaging	4,09%

In case of negative numbers, additional semi-finished products are created besides the product.



Substance assessment

Products of this range are designed in conformity with the material restrictions according to Directive 2011/65/EU (RoHS 2), including Delegated Directive 2015/863/EU. In addition, the products comply with the requirements of Annex XIV and Annex XVII under Regulation (EC) No. 1907/2006 (REACH Regulation).

Details of ROHS and REACH standard followed by Phoenix Contact
Website: Product Compliance | Phoenix Contact

Life cycle stages - Overview

Manufacturing

Our production sites are certified according to the environmental management system of DIN EN ISO 14001:2015. The focus is on resource-saving processes. In addition, the company uses 100% green electricity for manufacturing.

Use

The use phase is excluded from the system boundary and determined not to be applicable.

Distribution to Customer

The information on transport distances and means was provided by our logistics department. As a result of the logistics data, an average distance of 800 Km to the customers is assumed.
The weight and volume of the packaging have been optimized, based on the European Union ‘s packaging directive.

End of life

The product end of life factors is considered during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse.

Framework / Calculation rules

System approach

Life cycle assessment has been performed on the following life cycle phases: Upstream and Manufacturing (M), Distribution (D) and End of life (EoL). Please note that the values given above are only valid within the context specified and cannot be used directly to draw up the environmental assessment of an installation.

Modelling hypothesis and method:

The preparation and calculation were carried out in accordance with the current standards DIN EN ISO 14040 and DIN EN ISO 14044. Eco database and primary data were used to determine the emission factors.

Data quality level:

Emission factors from general eco databases as well as emission factors submitted by our suppliers were used to calculate the product environmental footprint. The quality level of the calculated environmental indicators indicates how granular the results are for Phoenix Contact. The average level for the quality level of the product is calculated based on the mass balance and quality level of each component.

Data quality level	Description
0	No data available
1 - 30	Indicators based on average values for industries
31 - 59	Indicators based on eco-database values
60 - 69	Indicators based on individually for this product modelled information
70 - 79	Indicators based on supplier values
80 - 100	Indicators based on primary supplier values including a third-party certification

Results

Environmental indicators:	Unit	Total	Upstream + Manufacturing	Distribution	Use	End of Life
Acidification	mol H+ Eq	n/c	n/c	n/c	n/a	n/c
Climate Change Global Warming Potential	kg CO2 Eq	6,086E-02	6,019E-02	5,867E-04	n/a	8,750E-05
Climate Change Biogenic	kg CO2 Eq	n/c	n/c	n/c	n/a	n/c
Climate Change Fossil	kg CO2 Eq	6,019E-02	6,019E-02	n/c	n/a	n/c
Climate Change Land Use And Land Use Change	kg CO2 Eq	n/c	n/c	n/c	n/a	n/c
Ecotoxicity Freshwater	CTUe	n/c	n/c	n/c	n/a	n/c
Energy Resources Non Renewable	MJ	n/c	n/c	n/c	n/a	n/c
Eutrophication Freshwater	kg PO4 Eq	n/c	n/c	n/c	n/a	n/c
Eutrophication Marine	kg N Eq	n/c	n/c	n/c	n/a	n/c
Eutrophication Terrestrial	mol N Eq	n/c	n/c	n/c	n/a	n/c
Human Toxicity Carcinogenic	CTUh	n/c	n/c	n/c	n/a	n/c
Human Toxicity Non Carcinogenic	CTUh	n/c	n/c	n/c	n/a	n/c
Ionising Radiation Human Health	kBq U235 Eq	n/c	n/c	n/c	n/a	n/c
Land Use	dimensionless	n/c	n/c	n/c	n/a	n/c
Material Resources Metals Minerals	kg Sb Eq	n/c	n/c	n/c	n/a	n/c
Ozone Depletion	kg CFC-11 Eq	n/c	n/c	n/c	n/a	n/c
Particulate Matter Formation	Disease incidence	n/c	n/c	n/c	n/a	n/c
Photochemical Ozone Formation Human Health	kg NMVOC Eq	n/c	n/c	n/c	n/a	n/c
Water Use	m3 world eq. deprived	n/c	n/c	n/c	n/a	n/c

Data Quality level: climate change	64



Glossary

Climate Change / Global Warming (GW)	The global warming of the planet is the result of the increase in the greenhouse effect due to the sunlight reflected by the earth's surface being absorbed by certain gases known as „greenhouse- effect „gases. The effect is quantified in gram equivalent of CO2.
n/a (not applicable)	n/a means not applicable. If we do not have emission factors for environmental indicators, process emissions are not quantifiable, or lifecycle phase excluded from the system boundary the results table indicates n/a.
n/c (not calculated)	n/c means not calculated. If environmental indicators could not be calculated, e.g., due to non-existing emission values or missing information, n/c was used.

Definitions and information on the other environmental indicators can be found on the page of the European Platform on Life Cycle Assessment: https://eplca.jrc.ec.europa.eu/LCDN/EF_archive.xhtml

Verifier accreditation not required	More information www.phoenixcontact.com
Date of issue 27.09.2024	Creator Phoenix Contact GmbH & Co.KG

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 52 35/3-1 20 00