BECKHOFF

Apr 27 2026 15:13:03

EL/ED3xxx | EtherCAT Terminals, analog input

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
0...10 V Standard signal	**EL3061** 12 bit	**EL3062** 12 bit	**EL3064** 12 bit	**EL3068** 12 bit
	EL3161 16 bit	**EL3162** 16 bit	**EL3164** 16 bit	
0...±10 V Standard signal	**EL3001** single-ended, 12 bit	**EL3002** single-ended, 12 bit	**EL3004** single-ended, 12 bit	**EL3008** single-ended, 12 bit
	EL3101 differential input, 16 bit	**EL3102** differential input, 16 bit	**EL3104** differential input, 16 bit	
		EL3602 differential input, 24 bit		
		EL3702 differential input, 16 bit, oversampling		
0...±75 mV		**EL3602-0010** differential input, 24 bit		
0...±150 mV		**EL3702-0015** differential input, 16 bit, oversampling		
0...±200 mV		**EL3602-0002** differential input, 24 bit		
0...30 V		**EL3062-0030** 12 bit		
0...±30 V		**ELM3002-0000** 24 bit, 20 ksps, push-in	**ELM3004-0000** 24 bit, 10 ksps, push-in	
±1200 V...±60 V **±5 V...60 mV**		**ELM3002-0205** 24 bit, 50 ksps, galv. isolated, 4 mm, 2 x ±1200...60 mV		
		ELM3002-0305 New 24 bit, 50 ksps, galv. isolated, 4 mm, 2 x ±5 V...60 mV		

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
		ELM3002-0405 New 24 bit, 50 ksps, galv. isolated, 4 mm, 1 x ±1200 V...60 mV, 1 x 5 V...60 mV		
0...20 mA Standard signal	**EL3041** single-ended, 12 bit	**EL3042** single-ended, 12 bit	**EL3044** single-ended, 12 bit	**EL3048** single-ended, 12 bit
	EL3141 single-ended, 16 bit	**EL3142** single-ended, 16 bit	**EL3144** single-ended, 16 bit	
		EL3142-0010 single-ended, ±10 mA, 16 bit	**EL3184** single-ended, 16 bit, HART	
	EL3011 differential input, 12 bit	**EL3012** differential input, 12 bit	**EL3014** differential input, 12 bit	
	EL3111 differential input, 16 bit	**EL3112** differential input, 16 bit	**EL3114** differential input, 16 bit	
		EL3612 differential input, 24 bit		
		EL3742 differential input, 16 bit, oversampling		
		EL3182 single-ended, 16 bit, HART		
4...20 mA Standard signal	**EL3051** single-ended, 12 bit	**EL3052** single-ended, 12 bit	**EL3054** single-ended, 12 bit	**EL3058** single-ended, 12 bit
	EL3151 single-ended, 16 bit	**EL3152** single-ended, 16 bit	**EL3154** single-ended, 16 bit	
	EL3021 differential input, 12 bit	**EL3022** differential input, 12 bit	**EL3024** differential input, 12 bit	
	EL3121 differential input, 16 bit	**EL3122** differential input, 16 bit	**EL3124** differential input, 16 bit	
	EL3621-0020 differential input, 24 bit		**EL3124-0090** 16 bit, TwinSAFE SC	
0...±20 mA		**EL3112-0011** differential input, 16 bit		
		ELM3102-0000 24 bit, 20 ksps, NAMUR NE43, push-in	**ELM3104-0000** 24 bit, 10 ksps, NAMUR NE43, push-in	

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
			ELM3104-0020 24 bit, 10 ksps, NAMUR NE43, push-in, factory calibrated	
0...±10 V/±20 mA Standard signal		**EL3072** Preferred type 16 bit, NAMUR NE43	**EL3074** Preferred type 16 Bit, NAMUR NE43	**EL3078** Preferred type 16 bit, NAMUR NE43
		EL3172 Preferred type 16 bit, NAMUR NE43	**EL3174** Preferred type 16 bit, NAMUR NE43	
		EL3172-0020 New 16 bit, NAMUR NE43, factory calibrated	**EL3174-0002** 16 bit, electrically isolated, NAMUR NE43	
			EL3174-0090 16 bit, NAMUR NE43, TwinSAFE SC	**ELM3146-0000** 24 bit, 1 ksps, push-in
		ELM3142-0000 24 bit, 1 ksps, push-in	**ELM3144-0000** 24 bit, 1 ksps, push-in	**ELM3148-0000** 24 bit, 1 ksps, push-in
0...±3 V/0...±20 mA			**EL3174-0032** 16 bit, electrically isolated, NAMUR NE43, ±3 V	
±3 V/±5 V				**EL3008-0003** ±3 V, 16 bit, cascaded channels
				EL3008-0005 New ±5 V, 16 bit, cascaded channels
0...±60 V			**EL3174-0042** 16 bit, electrically isolated, NAMUR NE43	
0...±60 V/0...±20 mA		**ELM3102-0100** 24 bit, 20 ksps, push-in, galv. isolated		
Multi-function	**EL3751** 24 bit, 10 ksps	**ELM3702-0000** 24 bit, 10 ksps, push-in	**ELM3704-0000** 24 bit, 10 ksps, push-in	
	EL3751-0004 24 bit, 10 ksps, resistance or temperature measurement	**ELM3702-0101** 24 bit, 10 ksps, galvanically isolated, LEMO	**ELM3704-0001** 24 bit, 10 ksps, LEMO	
	EL3751-0024 24 bit, 10 ksps, factory calibrated		**ELM3704-0020** 24 bit, 10 ksps, push-in, factory calibrated	

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
Temperature measurement resistance thermometer RTD	**EL3201** 16 bit	**EL3202** 16 bit	**EL3204** 2-wire, 16 bit	**EL3208** 16 bit
	EL3201-0010 16 bit, high-precision	**EL3202-0010** 16 bit, high-precision	**EL3204-0162** 2-wire, 16 bit, 2 x RTD, 2 x ±10 V	**EL3208-0010** Pt1000, Ni1000, NTC 1.8... 100 k, potentiom. 1, 5, 10 kΩ
			EL3204-0200 16 bit, universal input for RTD	
			EL3214 3-wire, 16 bit	**EL3218** 3-wire, 16 bit
			EL3214-0090 16 bit, TwinSAFE SC	
			ELM3244-0000 24 bit, high-precision, 1 ksps, push-in	**ELM3246-0000** 24 bit, high-precision, 1 ksps, push-in
Temperature measurement thermocouple, mV	**EL3311** 16 bit	**EL3312** 16 bit	**EL3314** 16 bit	**EL3318** 16 bit
			EL3314-0002 24 bit, electrically isolated	
			EL3314-0010 24 bit	
			EL3314-0090 16 bit, TwinSAFE SC	
			EL3314-0092 24 bit, galvanically isolated, TwinSAFE SC	
			ELM3344-0000 24 bit, 1 ksps, push-in	**ELM3348-0000** 24 bit, 1 ksps, push-in
			ELM3344-0003 24 bit, 1 ksps, push-in, Mini-TC universal	**ELM3348-0003** 24 bit, 1 ksps, push-in, Mini-TC universal
			ELM3704-1001 24 bit, 10 ksps, push-in, TC adjustment	
Measurement bridge strain gauge	**EL3351** strain gauge, 16 bit	**ELM3502-0000** 24 bit, 20 ksps, push-in	**ELM3504-0000** 24 bit, 10 ksps, push-in	
	EL3356 self-calibration	**ELM3542-0000** 24 bit, 1 ksps, push-in	**ELM3544-0000** 24 bit, 1 ksps, push-in	

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
	EL3356-0010 24 bit, 10 ksps			
	EL3356-0090 TwinSAFE SC			
Measurement technology	**EL3681** digital multimeter terminal, voltage/current, 18 bit	**EL3692** resistance measurement, 100 mΩ...10 MΩ		**EL3255** potentiometer measurement, 5-channel
Acceleration measurement Position, vibration, Condition Monitoring, IEPE		**EL3632** 16 bit, 50 ksps		
		ELM3602-0000 24 bit, 50 ksps, push-in	**ELM3604-0000** 24 bit, 20 ksps, push-in	
		ELM3602-0002 24 bit, 50 ksps, BNC	**ELM3604-0002** 24 bit, 20 ksps, BNC	
Pressure measuring	**EM3701** differential pressure, ±100 hPa	**EM3702** relative pressure, 7500 hPa		
		EM3712 relative pressure, ±1000 hPa		
Power measurement ≤ 500 V		**EL3403** 500 V AC, 1 A		
		EL3423 480 V AC/DC, 1 A, economy		
		EL3443 Preferred type 480 V AC/DC, 1 A, extended functionalities		**EL3446** Preferred type 1 A, distributed power measurement
		EL3443-0010 480 V AC/DC, 5 A, extended functionalities		**EL3446-0011** New 100 mA, distributed power measurement
		EL3443-0011 480 V AC/DC, 100 mA, extended functionalities		**EL3475** distributed power measurement, RJ45
		EL3443-0013 480 V AC/DC, 333 mV, extended functionalities		**EL3475-0200** distributed power measurement, RJ45, extended functionalities

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
		EL3443-0020 480 V AC/DC, 1 A, extended functionalities, factory calibrated	**EL3444** 10 A, distributed power measurement, galv. isolated	
Power measurement > 500 V		**EL3453** 690 V AC, 5 A, extended functionalities		
		EL3453-0020 690 V AC, 5 A, extended functionalities, factory calibrated		
		EL3453-0100 130 V AC, 5 A, extended functionalities		
Mains monitor ±480 V		**EL3483** 480 V AC/DC, mains monitor		
		EL3483-0060 480 V AC/DC, mains monitor with voltage measurement		
Power monitoring ≤ 500 V		**EL3773** 500 V, 1 A AC/DC, 10 ksps		
Power monitoring > 500 V		**EL3783** 690 V AC, 5 A AC, 20 ksps		
		EL3783-0100 130 V AC, 5 A AC, 20 ksps		
Ex i, 0/4...20 mA Standard signal	**ELX3181** 4...20 mA, single-ended, 16 bit, HART	**ELX3152** 0/4...20 mA, single-ended, 16 bit	**ELX3184** 4...20 mA, single-ended, 16 bit, HART	**ELX3158** 4...20 mA, single-ended, 16 bit
		ELX3152-0090 0/4...20 mA, single-ended, 16 bit, TwinSAFE SC		
Ex i, temperature measurement resistance thermometer RTD		**ELX3202** RTD, 2-, 3- and 4-wire, 16 bit	**ELX3204** RTD, 2-wire, 16 bit	
		ELX3202-0090 RTD, 2-, 3- and 4-wire, 16 bit, TwinSAFE SC	**ELX3204-0090** RTD, 2-wire, 16 bit, TwinSAFE SC	
Ex i, temperature measurement thermocouple, mV		**ELX3312** thermocouple/mV measurement, 2-wire, 16 bit	**ELX3314** thermocouple/mV measurement, 2-wire, 16 bit	

EL3xxx | Analog input

	1-channel	2-/3-channel	4-channel	5-/6-/8-/12-channel
Signal				
		ELX3312-0090 thermocouple/mV measurement, 2-wire, 16 bit, TwinSAFE SC	**ELX3314-0090** thermocouple/mV measurement, 2-wire, 16 bit, TwinSAFE SC	
Ex i, measurement technology	**ELX3351** strain gauge, 24 bit	**ELX3252** potentiometer measurement, 16 bit		
	ELX3351-0090 strain gauge, 24 bit, TwinSAFE SC	**ELX3632** New IEPE, 16 bit		

Details for a pluggable wiring level (where present) can be seen in the housing data and ordering information on the product page.