

Network Topology Report

Topology topo-sample-001 - 2026-09-19T18:22:41 - seed 192.168.10.1 - 10 devices / 9 links in 14.2s

Types: router: 1, switch: 2, server: 3, host: 3, unknown: 1 - **SNMP-accessible:** 6 - **Subnets:** 192.168.10.0/24

Device Inventory

IP	MAC	Type	Vendor	Hostname
192.168.10.1	00:1D:D8:4A:2C:10	router	Cisco-Linksys	gw01.office.local
192.168.10.2	00:23:04:BB:19:44	switch	Cisco	sw01.office.local
192.168.10.2	00:23:04:BB:19:44	switch	Cisco	sw02.office.local
192.168.10.10	00:50:56:C0:00:08	server	VMware	filesrv01.office.local
192.168.10.11	00:50:56:C0:00:09	server	VMware	db01.office.local
192.168.10.21	B8:27:EB:11:22:33	host	Raspberry Pi	-
192.168.10.34	F0:18:98:7A:1B:02	host	Apple	anna-laptop
192.168.10.35	3C:D9:2B:55:41:0E	host	HP	ben-workstation
192.168.10.36	84:16:F9:CC:2D:71	unknown	TP-Link	-
192.168.10.40	00:11:32:0A:9F:3E	server	Synology	nas01.office.local

Methodology & Authorization Note

Discovery used an ICMP ping sweep with ARP-cache correlation; SNMP queries (read-only GET of sysDescr/sysName) enriched devices where community strings were provided. Traceroute reveals only the forward path; asymmetric routing is not captured. Network discovery generates traffic - run only on networks you are authorized to scan.