

WireGuard Tunnel Provisioning Report

Session a3fdc69a67 - 2026-09-21T02:44:48 - interface wg0 - port 51820/udp

Server: 10.0.0.1/24 - public key fingerprint a4d18420527d6bfa

Peers

Name	Tunnel IP	Allowed IPs	Fingerprint	PSK
laptop	10.0.0.2	0.0.0.0/0	31f750e3b53ddcb6	yes
phone	10.0.0.3	0.0.0.0/0	fbcb104c2bd5e6a20	yes
branch	10.0.0.4	192.168.20.0/24	9d49d4ae3dbc977f	no

Server Config

```
[Interface]
Address = 10.0.0.1/24
ListenPort = 51820
PrivateKey = cJz5R4mM0sMuPgVfZaze3d13D5DVLURL0XrNVHTm23o=

[Peer]
# laptop
PublicKey = 55GeP0ihgmunpDpr/Q6dQWad3Alpnq7EiLtSkq+D2w8=
PresharedKey = XjfVu6TfKMqMPkswH7pybBhsoiBck90vzhMAgnMNU7U=
AllowedIPs = 10.0.0.2

[Peer]
# phone
PublicKey = xVIolf7Z2hG5Ium0wxuKKVgiFuU4ziZmI+XzRkeoRXA=
PresharedKey = reJkmdQfMU78RrDRzQz1BG+cF/GdxtjiAcDYogLCY8=
AllowedIPs = 10.0.0.3

[Peer]
# branch
PublicKey = 3J/P788qI0AX7a3q1JQd6tjKg1i/t3rYq8ZFxvKxVFM=
AllowedIPs = 10.0.0.4
```

Security Notes

Private keys are never included in reports. Distribute peer configs over a secure channel; anyone with a config can join the tunnel. Preshared keys add a post-quantum resistance layer. Verify handshakes with 'wg show' after deployment.