



Magnetic grippers - Basic - #24 mm - 34 N

Article number	TPGC024078
Product key	HGR-SQ-024-FL-R-M-F
Switching	<ul style="list-style-type: none"> • Pneumatic: 2 compressed air connections or: • 1 vacuum connection: see 'Gripper connection for vacuum control' (Document tab)
Delivery time (if not in stock)	4-6 weeks
Advised working load	11 N (under ideal conditions - with safety factor 3 acc. EN13155)
Max. tear off force	34 N (under ideal conditions - Graph: see Document tab - Factors influencing lifting capacity: see lifting magnets)
Min. advised sheet thickness	1 mm
Interface/connection dim's	Threaded hole M5 (4x)
Connections	Pneumatic: M5 (2x)
Material housing	<ul style="list-style-type: none"> • Aluminium • AISI316L (SS 1.4404) (screw cap)
Surface treatment/finishing	Anodized
Colour	Red
Min./max. ambient temperature	0 to 70 °C
Switching pressure	<ul style="list-style-type: none"> • 4 bar (recommended), 6 bar (max.) • Vacuum pressure -0.3 bar (switch on)
Air consumption	0.013 l/cycle (1x up, 1x down)
Magnetic system	2 Permanent magnet poles
Magnet quality	Neodymium GSN-52, Br 14,800 gauss (at 20°C), Tmax. 80°C
Depth	24 mm
Width	24 mm
Height	63 mm
Weight	0,10 kg