### Ivan Trepakov

NSU Sys.Pro

#### Evaluate expression

```
succ (2 - pred 1)
drop 2 (take 4 "Haskell") > map succ "cat"
sum (map fromEnum (enumFrom False))
map (\x -> x * 2) [1,3..10] ++ [100,1000]
```

#### Guess type signature

```
max "Haskell"
map fst
map (take 2)
```

### Guess type signature

```
(++) [True]
zip [0..]
map filter
```

#### Guess type signature

```
alph = 'a' : alph
foo = zipWith (:)
f = f f
y g = g (y g)
```

# Guess type signature

```
z \times y = zip \times (concat y)
concatMap f x = concat (map f x)
f = 0 : 1 : zipWith (+) f (tail f)
```

#### Guess the function(s)

```
_ :: a -> a
_ :: a -> b
_ :: a -> [a] -> [a]
_ :: [a] -> Maybe (a, [a])
```

#### Guess the function(s)

# Guess the function(s)

#### Evaluate expression

```
(2^) . (3+) $ 4

map ($2) [(*2), (^3), (1+)]

(++ "!") . reverse $ "abc"
```

#### Guess type signature

```
flip const
const undefined
foldr (:) []
((filter even .) .)
```

#### Guess type signature

```
filter (const True)
foldl' (flip (:)) []
map (,)
```

# How many distinguishable total functions?

```
- :: a -> a
- :: (a, a) -> (a, a)
- :: a -> a -> Bool
- :: Eq a => a -> a -> Bool
```

#### How many distinguishable *total* functions?

# How many distinguishable total functions?

```
_ :: a -> Maybe a
```

# Q&A