

## Copy #1 of Data Structures Array Lab Quiz-2

Question Prompt: 1

Total Points: 2

**What will be the output of the given code : `int array[ 5 ] = {1, 2, 3, 4, 5} printf ("%ld", array);`**

- ☐ 1 2 3 4 5
  - ☐ 1
  - ☒ Address of array[0]
  - ☐ Compilation error
- 

Question Prompt: 2

Total Points: 1

**An array is**

- ☐ Sequential memory allocation
  - ☐ Fixed size memory
  - ☐ Can hold multiple values with same reference name
  - ☒ All the above
- 

Question Prompt: 3

Total Points: 1

**The disadvantage of an array is :**

- ☐ All elements are accessed by single name
  - ☒ Size is fixed
  - ☐ Using index values to access elements is complex
  - ☐ Consumes lot of memory
- 

Question Prompt: 4

Total Points: 1

**We can declare the array size as negative.**

- ☐ True
  - ☒ False
- 

Question Prompt: 5

Total Points: 2

**What does the following declaration mean? `int (*ptr)[10];`**

- ☐ ptr is array of pointers to 10 integers
  - ☒ ptr is a pointer to an array of 10 integers
  - ☐ ptr is an array of 10 integers
  - ☐ ptr is a pointer to array
- 

Question Prompt: 6

Total Points: 1

**In C, if you pass an array as an argument to a function, what actually gets passed?**

- ☐ Value of elements in array
  - ☐ First element of the array
  - ☒ Base address of the array
  - ☐ Address of the last element of array
- 

Question Prompt: 7

Total Points: 3

**What will be the output of :** `int main() { int a[5] = {5, 1, 15, 20, 25}; int i, j, m; i = ++a[1]; j = a[1]++; m = a[i++]; printf("%d, %d, %d", i, j, m); return 0; }`

- ☐ 2, 1, 5
  - ☐ 1, 2, 5
  - ☒ 3, 2, 15
  - ☐ 2, 3, 20
-