



# **Installing the data broker in Azure**

## **Cloud Manager**

Ben Cammett  
September 01, 2021

This PDF was generated from [https://docs.netapp.com/us-en/occm/task\\_sync\\_installing\\_azure.html](https://docs.netapp.com/us-en/occm/task_sync_installing_azure.html) on September 14, 2021. Always check docs.netapp.com for the latest.

# Table of Contents

- Installing the data broker in Azure ..... 1
  - Supported Azure regions ..... 1
  - Networking requirements ..... 1
  - Authentication method ..... 1
  - Installing the data broker ..... 1
  - Details about the data broker VM. .... 3

# Installing the data broker in Azure

When you create a new data broker, choose the Azure Data Broker option to deploy the data broker software on a new virtual machine in a VNet. Cloud Sync guides you through the installation process, but the requirements and steps are repeated on this page to help you prepare for installation.

You also have the option to install the data broker on an existing Linux host in the cloud or on your premises. [Learn more.](#)

## Supported Azure regions

All regions are supported except for the China, US Gov, and US DoD regions.

## Networking requirements

- The data broker needs an outbound internet connection so it can poll the Cloud Sync service for tasks over port 443.

When Cloud Sync deploys the data broker in Azure, it creates a security group that enables the required outbound communication.

If you need to limit outbound connectivity, see [the list of endpoints that the data broker contacts](#).

- NetApp recommends configuring the source, target, and data broker to use a Network Time Protocol (NTP) service. The time difference between the three components should not exceed 5 minutes.

## Authentication method

When you deploy the data broker, you'll need to choose an authentication method: a password or an SSH public-private key pair.

For help with creating a key pair, refer to [Azure Documentation: Create and use an SSH public-private key pair for Linux VMs in Azure](#).

## Installing the data broker


You can install a data broker in Azure when you create a sync relationship.

### Steps


1. Click **Create New Sync**.
2. On the **Define Sync Relationship** page, choose a source and target and click **Continue**.

Complete the pages until you reach the **Data Broker** page.


3. On the **Data Broker** page, click **Create Data Broker** and then select **Microsoft Azure**.

If you already have a data broker, you'll need to click the  icon first.


**Select a Provider**




Microsoft Azure



Amazon Web Services



Google Cloud Platform



On-Prem Data Broker

4. Enter a name for the data broker and click **Continue**.
5. If you're prompted, log in to your Microsoft account. If you're not prompted, click **Log in to Azure**.

The form is owned and hosted by Microsoft. Your credentials are not provided to NetApp.

6. Choose a location for the data broker and enter basic details about the virtual machine.

**Location**

**Virtual Machine**

Subscription

OCCM Dev ▼

Azure Region

West US 2 ▼

VNet

Vnet1 ▼

Subnet

Subnet1 ▼

VM Name ?

netappdatabroker

User Name ?

databroker

Authentication Method:

☒ Password
 ☐ Public Key

Enter Password ?

.....

Resource Group:

☒ Generate a new group
 ☐ Use an existing group

7. Specify a proxy configuration, if a proxy is required for internet access in the VNet.
8. Click **Continue** and keep the page open until the deployment is complete.

The process can take up to 7 minutes.

9. In Cloud Sync, click **Continue** once the data broker is available.
10. Complete the pages in the wizard to create the new sync relationship.

## Result

You have deployed a data broker in Azure and created a new sync relationship. You can use this data broker with additional sync relationships.

### Getting a message about needing admin consent?

If Microsoft notifies you that admin approval is required because Cloud Sync needs permission to access resources in your organization on your behalf, then you have two options:

1. Ask your AD admin to provide you with the following permission:

In Azure, go to **Admin Centers > Azure AD > Users and Groups > User Settings** and enable **Users can consent to apps accessing company data on their behalf**.

2. Ask your AD admin to consent on your behalf to **CloudSync-AzureDataBrokerCreator** using the following URL (this is the admin consent endpoint):

`https://login.microsoftonline.com/{FILL HERE YOUR TENANT ID}/v2.0/adminconsent?client_id=8ee4ca3a-bafa-4831-97cc-5a38923cab85&redirect_uri=https://cloudsync.netapp.com&scope=https://management.azure.com/user_impersonationhttps://graph.microsoft.com/User.Read`

As shown in the URL, our app URL is `https://cloudsync.netapp.com` and the application client ID is `8ee4ca3a-bafa-4831-97cc-5a38923cab85`.

## Details about the data broker VM

Cloud Sync creates a data broker in Azure using the following configuration.

### VM type

Standard DS4 v2

### vCPUs

8

### RAM

28 GB

### Operating system

CentOS 7.7

### Disk size and type

64 GB Premium SSD

## Copyright Information

Copyright © 2021 NetApp, Inc. All rights reserved. Printed in the U.S. No part of this document covered by copyright may be reproduced in any form or by any means-graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system-without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

## Trademark Information

NETAPP, the NETAPP logo, and the marks listed at <http://www.netapp.com/TM> are trademarks of NetApp, Inc. Other company and product names may be trademarks of their respective owners.