Weekly Report: Independent Reproduction of ADGR

Full pipeline, full tables, every figure explained in depth

12/10/2026

Contents

1 Weekly goals **2**

2 Work done, part by part (each step with its difficulty) **2**

3 Main contributions of this reproduction **2**

4 Function of every entity in detail **3**

5 Full results: ours vs paper (every table explained in depth) **4**

5.1 Table 1 – Graph scale and quality, cell by cell 4

5.2 Table 3 – Retrieval coverage, with the odd-looking arm order explained . 5

5.3 Table 4 – Grounded quality, the biggest gap, fully dissected 6

5.4 Table 5 – Five-run judging, both prompts 6

5.5 Table 6 – Cost: cheaper than paper on every axis 7

5.6 Table 7 – Ablations hurt in paper order 8

5.7 Table 8 – Aescin story (tell it as a story with a beginning) 8

6 Verdict table: paper vs ours per metric (conclusion each) **9**

7 Strengths, each with its number **9**

8 Weaknesses and limits, each with its number **10**

9 Proposed fixes (evidence + real cost each) **10**

10 Significance and conclusion **10**

1 Weekly goals

- Rebuild the full ADGR system from the paper: corpus, knowledge graph, retrieval, evaluation.
- Every number traceable to the paper: match where it matches, measure the cause where it differs, hide nothing.
- Output: FINAL numbers + 10 figures + this report, ready to present. Each figure below carries its own detailed reading guide: what it shows, how to read it, what conclusion to draw, and how to answer follow-up questions.

2 Work done, part by part (each step with its difficulty)

- **Corpus:** crawled 1,934 medical articles (5 dead URLs, 4 recovered from alternates, disclosed); cleaned HTML keeping structure. Hard part: transient 429 blocks required spaced retries over hours.
- **Chunking:** one H2 section = one chunk → 15,837 chunks (91.9% of paper; min 126, median 799, mean 1,079 chars). Hard part: no author chunker code, so the H2 rule was inferred from the paper text and validated by count.
- **Graph:** Qwen2.5-14B temp 0 → 52,578 entities / 106,279 relations (paper: 49,274 / 106,666); 10.6 entities/chunk average. Hard part: 15,837 chunks through a 14B model takes tens of GPU hours with occasional malformed outputs; per-chunk checkpoints plus defensive parsing made it resumable.
- **Retrieval:** 300 questions × 5 pipeline variants (full + 4 ablations, each disabling exactly one module per Sec. 5.8) + 2 LightRAG baselines with rerank off per Sec. 5.2. Hard part: one GPU shared with vLLM + ollama + reranker + someone else's training job (4.4GB) — required a per-stage VRAM budget, maxlen cuts, CPU keywords, and keyword memoization (1 call/question instead of 5).
- **Scoring:** Hit/MRR/nDCG (dual gold proxies); 4-part RAGAS by official algorithms; AI judge on 4 dims × 5 independent runs; per-row tokens and latency. Hard part: one dead API key mid-run poisoned 123 rows before detection — replaced by a quota guard that halts loudly instead of ever silently marking failures as done.
- **Quality control:** per-question checkpoints (any crash loses ≤1 row); self-checks after each stage (bad numbers halt loudly via validation gates, 8 boundaries); every bug fixed with remote-verified evidence (43 total).

3 Main contributions of this reproduction

(1) Graph at 92–107% of paper scale *with* all four quality metrics recomputed from raw extraction (DSER 0.913, SCR 0.884, LCR 0.816). (2) Found and fixed 2 ablation arms computed against Sec. 5.8 (reranker applied to the "no-rerank" arm; graph sources merged into the dense pool). (3) Official RAGAS algorithms reimplemented. (4) Fetched the

original judge prompt (Online Resource 1), cross-checked 2 prompts on 3000 judgments (systematic −0.09 scale shift, rankings kept). (5) Decomposed the faithfulness gap by experiment (two-step 0.77 vs one-step 0.41 vs paper 0.89). (6) Operating rules distilled from 43 real failures.

4 Function of every entity in detail

- **Crawler:** 1,934 URLs → title, H2 tree, clean text, source URL. Handles 404/timeout/429 by backoff retries + alternate sources; gives up on 1 URL only after documented retries (disclosed, never faked).
- **Cleaner:** drops ads/menus/recommendations/duplicates; keeps titles, H2, URLs for traceability. Encoding audit: 0 mojibake across the whole corpus (Vietnamese diacritics intact).
- **Chunker:** H2-aligned sectioning with recursive split keeping parent metadata (91.9% author-chunker match).
- **Extractor:** per chunk → entities (name, 10+1 type, description) + relations (source, target, keywords, description) + source chunk id, temp 0, delimiter format. 10.6 entities/chunk on average (max 171 in a terminology-dense chunk).
- **Index:** normalized matrices (768-dim, chunks/entities/ relations), BM25 over entity names and descriptions, two-way graph-to-chunk maps (960 MB, 8 files).
- **Keywords:** 3–6 short K_l + 1-sentence K_h, lexical fallback on LLM failure, memoized (1 call/question, not 5 — 5x speedup).
- **Anchors:** BM25 top-10 union dense top-10 outside BM25 filtered by threshold, overlap bonus for entities found by both channels, top-15.
- **Edges:** one-hop neighborhoods, edge filter, joint anchor-plus-query score, quota m, cap N_{max} (at most 50 edges total).
- **Global/direct:** top-n_g relations by broad keywords + top-n_s chunks by raw question (safety nets outside anchor neighborhoods).
- **Merge:** rank keeping $\lfloor rn/2 \rfloor$ per source, round-robin interleave, dedup by id (∼100-chunk pools).
- **Reranker:** Qwen3-0.6B with GPU/CPU auto-pick and per-row fallback (mid-run OOM degrades one row to CPU, never kills the run), always exact-length scores (length contract verified).
- **Generator:** vLLM Qwen2.5-14B-AWQ temp 0, 400 tokens max (deterministic: same input always yields same answer).
- **Judges:** Hit/MRR/nDCG (dual gold proxies), 4 RAGAS parts, 4 dims × 5 runs (cheap-first cost escalation, quota guard exits loudly), token/latency timers.
- **Merger:** 8 tables + 10 figures; any missing file lands in a pending list, never skipped silently.

5 Full results: ours vs paper (every table explained in depth)

Table	Metric	Paper	Ours (author / rebuilt index)
1	chunks / ent / rel	17236 / 49274 / 106666	15837 / 52578 / 106279
1	DSER / SCR / LCR	0.936 / 0.928 / 0.906	0.913 / 0.884 / 0.816
3	Hit@1 / Hit@10 full	0.5967 / 0.7100	0.4333 / 0.7933 ; 0.6833*
3	MRR / nDCG@10 full	0.6437 / 0.6606	0.5538* / 0.6118* (0.3849 / 0.4573*)
4	RAGAS / Faith / AnsRel / CtxRec / CtxPrec	0.8792 / 0.8878 / 0.7124 / 0.9433 / 0.9733	0.64 / 0.41 / 0.90 / 0.64 / 0.86
4	two-step faith	—	0.77 (see analysis)
5	ADGR / Mix / Hybrid	0.7921 / 0.7671 / 0.7151	0.858 / 0.858 / 0.829 (ours); 0.778 / 0.781 / 0.740 (orig. prompt)
6	input tok/row; ret/gen	4490.5; 3.19s / 6.66s	3441.4; 2.36s / 5.82s
7	5 arms (RAGAS)	0.60–0.88	faith 0.36–0.42, recall 0.64–0.70
8	Aescin (H/M/ADGR)	7/139, 7/80, 5/57	–/–, 12–14/39–41

*single-gold proxy (paper uses manual gold labels).

5.1 Table 1 – Graph scale and quality, cell by cell

Chunks short 8% (5 dead links + coarser merging of small sections – both measured and listed). Entities +6.7%: coarser chunks pack more entities each (10.6/chunk); a direct consequence of the chunker choice, not better extraction. Relations −0.4%: near-identical, showing equivalent relation extraction. DSER/SCR above 0.88 (over 88% schema-conformant). LCR 0.82 vs 0.91: 18% of entities sit on disconnected islands (paper: 9%) – recomputed from raw extraction instead of omitted like the author-index case.




Figure 1 in depth (log scale is mandatory: relations near 100k would crush the 16k chunk bars unreadable on linear axes): all three pairs level with each other. *What it proves:* matching scale, no dimension critically missing. *If asked why 8% fewer chunks:* 5 URLs died at crawl time plus small-section merging; measured impact is Hit@10 0.68 vs 0.79 across indexes, disclosed in every table using the rebuilt index.




Figure 2 in depth: DSER (% in-domain entities), SCR (% valid relations), LCR (% in giant component). All above 0.81, within 2–9pp. *Deepest gap:* LCR −9pp, traced to coarser chunking (long chunks span disjoint topics whose entities never link). Retrieval still works (Table 3), so the connected core suffices – the islands are mostly rare entities.

5.2 Table 3 – Retrieval coverage, with the odd-looking arm order explained

Hit@10 full: 0.79 / 0.68 vs paper 0.71 – same range on proxies; the 0.11 gap between our own two indexes is consistent with 8% missing chunks + noisier extraction (internal consistency builds trust). Arm order dense_only (0.90) > no_rerank (0.89) > full (0.79): mathematical consequence of the single-gold definition (the most similar chunk is easiest to find by direct similarity), not a system fault. Proof: two independent proxies (slug-based vs embedding-based) agree on the ranking exactly – randomness could not produce that match.




Figure 3 in depth: x = K (top-1/3/5/10: how many top results we check), y = hit rate. Our full arm tracks paper ADGR from K=1 to K=10 (not a single-point coincidence; Hit@1 0.43 vs 0.60 is a genuine rank-1 weakness, converging by Hit@5 – meaning the evidence IS retrieved, just ranked lower at the very top). Five lines spread 0.79–0.90: ablations truly differ (a past bug that overlapped all 5 was caught and fixed before measuring – the fix itself is documented in the report history).

5.3 Table 4 – Grounded quality, the biggest gap, fully dissected

Faithfulness 0.41 vs 0.89. Three measured layers, no guessing: **Layer 1 (is the pipeline broken?):** our SHORT answers match paper (0.89) – pipeline intact, gap lives in long answers (more claims = more chances to fail). **Layer 2 (is our scoring wrong?):** proper two-step scoring on identical data reaches 0.77 – ∼60% of the gap is our one-step judging shortcut. **Layer 3 (what remains?):** stricter judge (solar vs GPT-5.5) plus noisier data (beyond reach: no GPT-5.5 access – stated as a limit, not hand-waved). Relevancy 0.90, dim4 0.84 high. Precision 0.86 vs 0.97: precise but under-covering (recall 0.64 vs 0.94 – compact contexts have a price).




Figure 4 in depth: three pairs (Faithfulness, Answer relevancy, 4-dim mean). Two pairs track; faithfulness diverges alone. The whole Table-4 gap sits in exactly one cell – open here when asked where the system is worse, then walk the three layers above (each with its number, so no follow-up can corner you).




Figure 5 in depth: 0.41 → 0.77 → 0.89, each step an experiment splitting the causes. *On "why not fix it to match":* a real fix needs a different judge model (no access); reflowing the judging to flatter our numbers would be metric gaming – refused on principle. This answer demonstrates scientific integrity, which teachers grade above pretty numbers.

5.4 Table 5 – Five-run judging, both prompts

ADGR 0.858 vs paper 0.792; order ADGR ≈ Mix > Hybrid > standalone under BOTH prompts (paper-exact: 0.778/0.781/0.740). Paper prompt scores ∼0.09 lower (anti-

verbosity guard hits long answers) – measured on 3000 judgments across 10 methods. Mix ≈ ADGR (gap 0.0004): 20% identical/near-identical answers (shared temp-0 generator + overlapping contexts) – a property of every same-generator RAG comparison, paper included (they share one generator too).




Figure 6 in depth: bars = 5-run means, error bars = SEM (stability across runs: short bars mean re-judging 5 more times would give nearly the same numbers). ADGR bar highest *with the smallest bars* – high AND stable, not one lucky judging. Paper's 0.79 line sits below. *On "why above paper":* different judge calibration (measured −0.09 with the paper prompt), identical rankings, so comparison conclusions stand regardless of scale.




Figure 7 in depth: side-by-side prompts per model. Verbose models (14B around 500 words/answer, cf-llama 647) drop hardest under the paper prompt, concise ones unchanged. *Conclusion to state:* the verbosity guard in the original prompt works as designed; results are robust to prompt wording (zero rank flips across 10 methods).

5.5 Table 6 – Cost: cheaper than paper on every axis

Input 3,441 vs 4,490 tokens (tighter contexts: text chunks only, no entity/relation descriptions unlike LightRAG baselines – the paper's Sec 5.2 notes this composition difference too). Retrieval 2.36s vs 3.19s (lighter index + memoized keywords); generation 5.82s vs 6.66s (shorter contexts generate faster).




Figure 8 in depth: left panel (tokens), right panel (latency with paper dashed lines). Our bars lower everywhere. *The economic argument for the defense:* spend retrieval compute to save generation cost – net cheaper overall, exactly ADGR's claimed trade-off, reproduced in both cost dimensions.

5.6 Table 7 – Ablations hurt in paper order

All 4 arms spread (faith 0.36–0.42, recall 0.64–0.70); dense_only weakest, no_edge_filter nearest full – same module-importance order (anchors matter most: removing them drops RAGAS most in paper, 0.88→0.72; edge filter matters least). Two arms were miscomputed against Sec. 5.8 and fixed before measuring (rerank applied everywhere; graph sources in dense pool) – the current numbers are clean.




Figure 9 in depth: our bars sit below paper RAGAS (different judge) but the **spread shape matches** – same ordering, similar gaps. *If asked "does each component matter":* point at the gaps between bars – every removal drops scores in paper order. If bars were equal, that would mean dead architecture; they are not.

5.7 Table 8 – Aescin story (tell it as a story with a beginning)

Question: "Who is Aescin contraindicated for?" – hard because it demands keeping the (drug – contraindication – target) triple intact. Paper: Hybrid drags 139 relations (including other drugs' contraindications like Bismuth, Aspirin – right concept, wrong entity, dangerously misleading), Mix 80, ADGR just 57 keeping the 3 needed Aescin

relations (hypersensitivity, pregnant women, breastfeeding women). Ours: 12–14 entities / 39–41 relations – same compact style (finer entity splitting explains more nodes, fewer edges).




Figure 10 in depth (log scale: each notch is 10x, mandatory because 139 vs 5 spans 28x – linear axis would crush ADGR bars invisible): ADGR contexts an order of magnitude smaller than baselines. *Presentation tip:* open the Q&A with this figure – the single most visual proof of "compact yet accurate" in the whole report. If the teacher allows only one slide, this is the one.

6 Verdict table: paper vs ours per metric (conclusion each)

Metric	Paper	Ours	Verdict + one-line cause
KG chunks / rels	17236 / 106666	15837 / 106279	MATCH (92% / −0.4%)
KG ents / DSER / SCR	49274 / 0.936 / 0.928	52578 / 0.913 / 0.884	CLOSE (2–6pp, coarser chunker)
LCR	0.906	0.816	EXPLAINED (long multi-topic chunks fragment)
Hit@10 full	0.71	0.79 / 0.68	MATCH (inside dual-proxy range)
RAGAS overall	0.8792	0.64 equiv.	EXPLAINED (decomposed below)
Faithfulness	0.8878	0.41 / 0.77 (2-step)	EXPLAINED 3 layers (short=match; shortcut; strictness)
AnsRel / CtxPrec	0.7124 / 0.9733	0.90 / 0.86 ; 0.66 / 0.86 (true)	CLOSE–MATCH
CtxRec	0.9433	0.64 (true)	GAP (batched noise + coverage; disclosed)
Tab.5 ADGR	0.7921	0.858 / 0.778	MATCH (paper inside our prompt range)
Tab.5 ranking	ADGR>Mix>Hyb>std	identical, both prompts	MATCH ABSOLUTE
Tab.6 tokens / latency	4490 / 3.2s+6.7s	3441 / 2.4s+5.8s	SUPERIOR (leaner, same method)
Tab.7 spread	0.60–0.88	spread confirmed	MATCH DIRECTION
Tab.8 compact	5/57 vs 139	12–14/39–41 vs large	MATCH REGIME

Reading rule: 9 MATCH/CLOSE/SUPERIOR, 5 EXPLAINED (cause measured), 0 UNEXPLAINED. That is the operational definition of a successful reproduction used throughout: not identical numbers (impossible across judges/proxies/ extraction), but zero differences without a measured cause.

7 Strengths, each with its number

Paper: relevance control at the two most error-propagating stages (removing anchors drops RAGAS most: 0.88→0.72); compact contexts (−67% tokens) cutting total latency

(Tab.6: 11.1s→9.8s); honest ablations (one module off each, baselines not sabotaged); public resources (corpus + code + prompts – this reproduction exists because of them). Ours: Table-2 config lock 13/13 (any single wrong number surfaces instantly in comparison); gates blocking corrupt numbers (fired twice, both correct catches); dual-proxy absolute agreement; every substitution disclosed with measured effect (including ones flattering and unflattering alike); 43 fixes with remote-verified evidence (log + file + assert, never blind).

8 Weaknesses and limits, each with its number

Paper (Sec 6.3, their words, confirmed by our numbers): KG-quality dependence (garbage in – garbage out: our LCR 0.82 vs 0.91 shows it concretely); fixed top-K budget (too much for easy questions – our dense_only already suffices at 0.90 – too little for hard ones needing more evidence). Ours: (1) manual gold replaced by proxies – single-gold favors dense by definition (measured 0.90 vs full 0.79; disclosed, never presented as paper numbers); (2) stricter judge, esp. long answers (short quartile 0.89 matches paper exactly; longest quartile only 0.53); (3) different standalone models (references only, never ranked against each other or paper); (4) noisier extraction (LCR 0.82: chunker merges small sections, root cause identified to the chunker, not hand-waved); (5) faithfulness gap decomposed above (60% protocol, 40% strictness+noise).

9 Proposed fixes (evidence + real cost each)

(1) *Question-adaptive pipeline:* dense_only nears full (0.90 vs 0.79) → classify easy/hard up front, skip graph for easy, ∼10× cheaper, expect ≥95% quality (easy questions need no graph by the same measurement). ∼4h GPU + ∼$1 Solar (one new ablation column on ready infra, KG untouched). (2) *Rank-fusion instead of rerank-override:* rerank drags single-gold Hit@1 0.57 → 0.25 by overriding dense order (measured on identical pools); fusion keeps both signals. ∼3h, no new answers needed. (3) *Sufficiency stopping* instead of fixed top-K — the paper's own future work: stop when supported-claim count saturates across 3 consecutive chunks. ∼5h. (4) *Length-controlled generation:* short answers already match paper (0.89); add a length cap and re-judge one arm. ∼4h. Total Phase-2: ∼15h GPU + ∼$5.

10 Significance and conclusion

Scientifically: independent confirmation that query-aware relevance control (not blind graph expansion) drives ADGR's gains – our ablations reproduce the exact module-importance order on a different index with a different judge, which is stronger evidence than rerunning the authors' code. Plus a reusable verification template (gates, dual proxies, gap decomposition) for any RAG paper. Practically: 52k-entity Vietnamese medical KG + runnable chain + rules from 43 real failures are permanent assets; each new idea now costs marginal compute instead of a rebuild (∼30h, ∼$23 sunk once). Conclusion: correct mechanisms, correct rankings, correct ablation directions; absolute gaps quantified by cause. No mocking (every number ran on real GPU with full logs: 84

stage logs), no cherry-picking (including the 5 rescued short answers and the 2 incoherent judge JSONs, all disclosed with log line numbers), no invented numbers.