

# Exam Questions CKA

Certified Kubernetes Administrator (CKA) Program

<https://www.2passeasy.com/dumps/CKA/>



### NEW QUESTION 1

Score: 4%



Task

Create a persistent volume with name app-data , of capacity 1Gi and access mode ReadOnlyMany. The type of volume is hostPath and its location is /srv/app-data .

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:

```
#vi pv.yaml apiVersion: v1
kind: PersistentVolume metadata:
name: app-config spec:
capacity: storage: 1Gi accessModes:
- ReadOnlyMany hostPath:
path: /srv/app-config
#
kubectl create -f pv.yaml
```

### NEW QUESTION 2

A Kubernetes worker node, named wk8s-node-0 is in state NotReady. Investigate why this is the case, and perform any appropriate steps to bring the node to a Ready state, ensuring that any changes are made permanent.

You can ssh to the failed node using:

```
[student@node-1] $ | ssh Wk8s-node-0
```

You can assume elevated privileges on the node with the following command:

```
[student@wk8s-node-0] $ | sudo -i
```

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

solution

F:\Work\Data Entry Work\Data Entry\20200827\CKA\20 C.JPG

Readme Web Terminal THE LINUX FOUNDATION

```
root@node-1:~# kubectl config use-context wk8s
Switched to context "wk8s".
root@node-1:~# k get nodes
NAME             STATUS    ROLES    AGE   VERSION
wk8s-master-0    Ready     master   77d   v1.18.2
wk8s-node-0      NotReady  <none>    77d   v1.18.2
wk8s-node-1      Ready     <none>    77d   v1.18.2
root@node-1:~# ssh wk8s-node-0
█
```

F:\Work\Data Entry Work\Data Entry\20200827\CKA\20 D.JPG

Readme Web Terminal THE LINUX FOUNDATION

```
wk8s-node-0      NotReady  <none>    77d   v1.18.2
wk8s-node-1      Ready     <none>    77d   v1.18.2
root@node-1:~# ssh wk8s-node-0
Welcome to Ubuntu 16.04.6 LTS (GNU/Linux 4.4.0-1109-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

 * Are you ready for Kubernetes 1.19? It's nearly here! Try RC3 with
   sudo snap install microk8s --channel=1.19/candidate --classic

   https://microk8s.io/ has docs and details.

4 packages can be updated.
1 update is a security update.


New release '18.04.5 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

student@wk8s-node-0:~$ sudo -i
root@wk8s-node-0:~# systemctl restart kubelet
root@wk8s-node-0:~# systemctl enable kubelet
█
```

F:\Work\Data Entry Work\Data Entry\20200827\CKA\20 E.JPG

Readme

Web Terminal



```

https://microk8s.io/ has docs and details.

4 packages can be updated.
1 update is a security update.

New release '18.04.5 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

student@wk8s-node-0:~$ sudo -i
root@wk8s-node-0:~# systemctl restart kubelet
root@wk8s-node-0:~# systemctl enable kubelet
Created symlink from /etc/systemd/system/multi-user.target.wants/kubelet.service to /lib/sy
stemd/system/kubelet.service.
root@wk8s-node-0:~# exit
logout
student@wk8s-node-0:~$ exit
logout
Connection to 10.250.5.34 closed.
root@node-1:~# k get nodes
NAME             STATUS    ROLES    AGE   VERSION
wk8s-master-0    Ready     master   77d   v1.18.2
wk8s-node-0      Ready     <none>    77d   v1.18.2
wk8s-node-1      Ready     <none>    77d   v1.18.2
root@node-1:~#

```

### NEW QUESTION 3

List the nginx pod with custom columns POD\_NAME and POD\_STATUS

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

kubect1 get po -o=custom-columns="POD\_NAME:.metadata.name, POD\_STATUS:.status.containerStatuses[].state"

### NEW QUESTION 4

List all the pods showing name and namespace with a json path expression

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

kubect1 get pods -o=jsonpath="{.items[\*]}['metadata.name', 'metadata.namespace']}"

### NEW QUESTION 5

Get IP address of the pod – “nginx-dev”

- A. Mastered
- B. Not Mastered

**Answer:** A

#### Explanation:

Kubect1 get po -o wide Using JsonPath  
kubect1 get pods -o=jsonpath='{range items[\*]}{.metadata.name}{\t}{.status.podIP}{\n}{end}'

### NEW QUESTION 6

Create an nginx pod and list the pod with different levels of verbosity

- A. Mastered

B. Not Mastered

**Answer:** A

**Explanation:**

```
// create a pod
kubectl run nginx --image=nginx --restart=Never --port=80
// List the pod with different verbosity kubectl get po nginx --v=7
kubectl get po nginx --v=8 kubectl get po nginx --v=9
```

**NEW QUESTION 7**

Get list of all the pods showing name and namespace with a jsonpath expression.

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

```
kubectl get pods -o=jsonpath="{.items[*]['metadata.name']
, 'metadata.namespace']}"
```

**NEW QUESTION 8**

Create a deployment as follows:

- > Name: nginx-random
- > Exposed via a service nginx-random
- > Ensure that the service & pod are accessible via their respective DNS records
- > The container(s) within any pod(s) running as a part of this deployment should use the nginx Image

Next, use the utility nslookup to look up the DNS records of the service & pod and write the output to /opt/KUNW00601/service.dns and /opt/KUNW00601/pod.dns respectively.


- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:

F:\Work\Data Entry Work\Data Entry\20200827\CKA\17 C.JPG




The screenshot shows a web terminal interface with a dark background. At the top, there is a blue header bar with a 'Readme' button and a 'Web Terminal' button. The terminal content shows the following commands and output:


```
root@node-1:~#
root@node-1:~# k create deploy nginx-random --image=nginx
deployment.apps/nginx-random created
root@node-1:~# k expose deploy nginx-random --name=nginx-random --port=80 --target-port=80
service/nginx-random exposed
root@node-1:~# vim dns.yaml
```

F:\Work\Data Entry Work\Data Entry\20200827\CKA\17 D.JPG





F:\Work\Data Entry Work\Data Entry\20200827\CKA\17 E.JPG



### NEW QUESTION 9

Create a busybox pod that runs the command “env” and save the output to “envpod” file

- A. Mastered  
B. Not Mastered

**Answer: A**

**Explanation:**

```
kubectl run busybox --image=busybox --restart=Never --rm -it -- env > envpod.yaml
```

### NEW QUESTION 10

Score: 4%



Task

Create a pod named kucc8 with a single app container for each of the following images running inside (there may be between 1 and 4 images specified): nginx + redis + memcached .

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:  
 kubectl run kucc8 --image=nginx --dry-run -o yaml > kucc8.yaml  
 # vi kucc8.yaml apiVersion: v1 kind: Pod metadata:  
 creationTimestamp: null name: kucc8  
 spec: containers:  
 - image: nginx name: nginx  
 - image: redis name: redis  
 - image: memcached  
 name: memcached  
 - image: consul name: consul  
 #  
 kubectl create -f kucc8.yaml  
 #12.07

#### NEW QUESTION 10

Create a nginx pod with label env=test in engineering namespace

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

kubectl run nginx --image=nginx --restart=Never --labels=env=test --namespace=engineering --dry-run -o yaml > nginx-pod.yaml  
 kubectl run nginx --image=nginx --restart=Never --labels=env=test --namespace=engineering --dry-run -o yaml | kubectl create -n engineering -f -  
 YAML File: apiVersion: v1 kind: Pod metadata: name: nginx  
 namespace: engineering labels:  
 env: test spec: containers:  
 - name: nginx image: nginx  
 imagePullPolicy: IfNotPresent restartPolicy: Never  
 kubectl create -f nginx-pod.yaml

#### NEW QUESTION 14

Score:7%



Task

Create a new PersistentVolumeClaim

- Name: pv-volume
- Class: csi-hostpath-sc
- Capacity: 10Mi

Create a new Pod which mounts the PersistentVolumeClaim as a volume:

- Name: web-server
- Image: nginx

- Mount path: /usr/share/nginx/html

Configure the new Pod to have ReadWriteOnce access on the volume.

Finally, using kubectl edit or kubectl patch expand the PersistentVolumeClaim to a capacity of 70Mi and record that change.

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

Solution:

```
vi pvc.yaml storageclass pvc apiVersion: v1
```

```
kind: PersistentVolumeClaim metadata:
```

```
name: pv-volume spec: accessModes:
```

```
- ReadWriteOnce volumeMode: Filesystem resources:
```

```
requests: storage: 10Mi
```

```
storageClassName: csi-hostpath-sc
```

```
# vi pod-pvc.yaml apiVersion: v1 kind: Pod metadata:
```

```
name: web-server spec:
```

```
containers:
```

```
- name: web-server image: nginx volumeMounts:
```

```
- mountPath: "/usr/share/nginx/html"
```

```
name: my-volume volumes:
```

```
- name: my-volume persistentVolumeClaim: claimName: pv-volume
```

```
# craete
```

```
kubectl create -f pod-pvc.yaml
```

```
#edit
```

```
kubectl edit pvc pv-volume --record
```

**NEW QUESTION 16**

Configure the kubelet systemd- managed service, on the node labelled with name=wk8s-node-1, to launch a pod containing a single container of Image httpd named webtool automatically. Any spec files required should be placed in the /etc/kubernetes/manifests directory on the node.

You can ssh to the appropriate node using:

```
[student@node-1] $ ssh wk8s-node-1
```

You can assume elevated privileges on the node with the following command:

```
[student@wk8s-node-1] $ | sudo -i
```

- A. Mastered
- B. Not Mastered

**Answer:** A

**Explanation:**

solution

F:\Work\Data Entry Work\Data Entry\20200827\CKA\21 C.JPG



Readme
Web Terminal

THE LINUX FOUNDATION

```

root@node-1:~#
root@node-1:~# kubectl config use-context wk8s
Switched to context "wk8s".
root@node-1:~# ssh wk8s-node-1
Welcome to Ubuntu 16.04.6 LTS (GNU/Linux 4.4.0-1109-aws x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/advantage

 * Are you ready for Kubernetes 1.19? It's nearly here! Try RC3 with
   sudo snap install microk8s --channel=1.19/candidate --classic

   https://microk8s.io/ has docs and details.

4 packages can be updated.
1 update is a security update.

New release '18.04.5 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

student@wk8s-node-1:~$ sudo -i
root@wk8s-node-1:~# vim /var/lib/kubelet/config.yaml

```

F:\Work\Data Entry Work\Data Entry\20200827\CKA\21 D.JPG

Readme
Web Terminal

THE LINUX FOUNDATION

```

    clientCAFile: /etc/kubernetes/pki/ca.crt
authorization:
  mode: Webhook
  webhook:
    cacheAuthorizedTTL: 0s
    cacheUnauthorizedTTL: 0s
clusterDNS:
- 10.96.0.10
clusterDomain: cluster.local
cpuManagerReconcilePeriod: 0s
evictionPressureTransitionPeriod: 0s
fileCheckFrequency: 0s
healthzBindAddress: 127.0.0.1
healthzPort: 10248
httpCheckFrequency: 0s
imageMinimumGCAge: 0s
kind: KubeletConfiguration
nodeStatusReportFrequency: 0s
nodeStatusUpdateFrequency: 0s
rotateCertificates: true
runtimeRequestTimeout: 0s
staticPodPath: /etc/kubernetes/manifests
streamingConnectionIdleTimeout: 0s
syncFrequency: 0s
:WG

```

F:\Work\Data Entry Work\Data Entry\20200827\CKA\21 E.JPG

F:\Work\Data Entry Work\Data Entry\20200827\CKA\21 F.JPG

F:\Work\Data Entry Work\Data Entry\20200827\CKA\21 G.JPG

Readme

Web Terminal

THE LINUX FOUNDATION

```
https://microk8s.io/ has docs and details.

4 packages can be updated.
1 update is a security update.

New release '18.04.5 LTS' available.
Run 'do-release-upgrade' to upgrade to it.

student@wk8s-node-1:~$ sudo -i
root@wk8s-node-1:~# vim /var/lib/kubelet/config.yaml
root@wk8s-node-1:~# cd /etc/kubernetes/manifests
root@wk8s-node-1:/etc/kubernetes/manifests#
root@wk8s-node-1:/etc/kubernetes/manifests# vim pod.yaml
root@wk8s-node-1:/etc/kubernetes/manifests# systemctl restart kubelet
root@wk8s-node-1:/etc/kubernetes/manifests# systemctl enable kubelet
root@wk8s-node-1:/etc/kubernetes/manifests# exit
logout
student@wk8s-node-1:~$ exit
logout
Connection to 10.250.5.39 closed.
root@node-1:~# k get po
NAME                READY   STATUS    RESTARTS   AGE
webtool-wk8s-node-1  1/1     Running   0           11s
root@node-1:~#
```

#### NEW QUESTION 17

.....

## THANKS FOR TRYING THE DEMO OF OUR PRODUCT

Visit Our Site to Purchase the Full Set of Actual CKA Exam Questions With Answers.

We Also Provide Practice Exam Software That Simulates Real Exam Environment And Has Many Self-Assessment Features. Order the CKA Product From:

<https://www.2passeasy.com/dumps/CKA/>

## Money Back Guarantee

### CKA Practice Exam Features:

- \* CKA Questions and Answers Updated Frequently
- \* CKA Practice Questions Verified by Expert Senior Certified Staff
- \* CKA Most Realistic Questions that Guarantee you a Pass on Your FirstTry
- \* CKA Practice Test Questions in Multiple Choice Formats and Updatesfor 1 Year