

Lecture 10c: Reasoning About Correctness

Spontaneous Right Action

1

So far in the course

- ◆ Important basic data structures
 - Arrays, Lists, Sequences, Trees, Priority Queues, Heaps, Dictionaries, Hash Tables, and Binary Search Trees
 - Search Trees
- ◆ Important algorithms
 - Sorting (insertion, heap, PQ, merge, Quick, bucket, radix)
 - Searching (Dictionary: binary search, hash table, BST)
 - Selection (Quick, deterministic) **not covered this time**
- ◆ Design strategies
 - Exhaustive Search, Divide-and-Conquer, Prune-and-Search, and randomization
- ◆ Solution to recurrences
- ◆ Amortized analysis (**average behavior over a large number of times running the algorithm**)

2

Reasoning About Loops

- ◆ Make sure the loop has a goal and it is progressing toward that goal each time through the loop
 - Make sure the loop invariant holds every time at the start and end of the loop body
- ◆ Make sure the loop terminates
 - Make sure the loop is making progress toward the terminating condition
- ◆ Check boundary conditions
 - E.g., check size 0, 1, n

3

What is the loop invariant?

- ◆ An assertion that is necessarily true immediately before and immediately after each iteration of a loop
- ◆ Could be false part way through the loop, but must be re-established before the end of the loop body
- ◆ **The invariant at termination of the loop should imply the goal of the loop has been achieved!!!!**

4

Binary Search Algorithm (What's wrong)

```
Algorithm BinarySearch(S, k):
  Input: key k and Sequence S storing n items, sorted by item.key()
  Output: the value associated with key k or NO_SUCH_KEY
  low ← 0
  high ← S.size() - 1
  while low < high do
    mid ← (low + high)/2
    if k = key(S.elemAtRank(mid)) then
      return value(S.elemAtRank(mid))
    if k < key(S.elemAtRank(mid)) then
      high ← mid - 1
    else
      low ← mid + 1
  return NO_SUCH_KEY
```

5

Error in binary search

- ◆ Does not handle the case when low equals high (boundary condition)
 - When the segment is size 1, the key may not be found because we do not enter the loop

6

Binary Search Algorithm (Corrected)

Algorithm `BinarySearch(S, k)`:
Input: key k and Sequence S storing n items, sorted by `item.key()`
Output: the value associated with key k or `NO_SUCH_KEY`

```

low ← 0
high ← S.size() - 1
while low ≤ high do
    mid ← (low + high)/2
    if k = key(S.elemAtRank(mid)) then
        return value(S.elemAtRank(mid))
    if k < key(S.elemAtRank(mid)) then
        high ← mid - 1
    else
        low ← mid + 1
return NO_SUCH_KEY

```

7

Introducing Errors through Copy-Paste

- ◆ We wish to have only one key comparison during each iteration of the loop
- ◆ So we copy from above version then modify as described
 - Move the check for equality after the loop
 - Now we do not exit the loop early however we do half the key comparisons during each iteration

8

Binary Search Algorithm (what's wrong? Look at red)

Algorithm `BinarySearch(S, k)`:
Input: An ordered Sequence S storing n items, accessed by keys()
Output: An element of S with key k .

```

low ← 0
high ← S.size() - 1
while low ≤ high do
    mid ← (low + high)/2
    if k < key(S.elemAtRank(mid)) then // one key comparison per iteration
        high ← mid - 1
    else
        low ← mid + 1
if k = key(S.elemAtRank(mid)) then // done once outside the loop now
    return value(S.elemAtRank(mid))
else
    return NO_SUCH_KEY

```

9

Errors

- ◆ Does not handle a Sequence with 0 elements
 - `mid` is not initialized since loop is not entered and, further, it cannot be initialized to handle an empty Sequence
- ◆ Does not handle a Sequence with 1 element that matches k
 - The else eliminates `mid` when it hasn't yet been eliminated, so delete the `+ 1` from the else branch

10

Binary Search Algorithm (better, but what else is wrong?)

Algorithm `BinarySearch(S, k)`:
Input: An ordered Sequence S storing n items, accessed by keys()
Output: An element of S with key k .

```

low ← 0
high ← S.size() - 1
while low ≤ high do
    mid ← (low + high)/2
    if k < key(S.elemAtRank(mid)) then // one key comparison per iteration
        high ← mid - 1
    else
        low ← mid // eliminate + 1 because mid has not been eliminated yet
if S.size() > 0 ∧ k = key(S.elemAtRank(mid)) then // handles empty S
    return value(S.elemAtRank(mid))
else
    return NO_SUCH_KEY

```

11

Error: loop does not terminate

- ◆ Does not handle a Sequence with 1 item (or a segment with 1 item) when its key matches k
 - The loop does not terminate
 - Modify the loop condition from `≤` to `<` so the loop terminates when `high = low` since `low` does not change when the key of the item equals k
- ◆ The rank `mid` may not contain the item with the key after fixing the loop's terminating condition
 - Either `low` or `high` will contain the key if it is in the Sequence
 - Fixing this eliminates the need to initialize `mid` before the loop since `mid` will only be used inside the loop now

12

Binary Search Algorithm (red shows corrections)

```

Algorithm BinarySearch(S, k):
  Input: An ordered Sequence S storing n items, accessed by keys()
  Output: An element of S with key k.
  low ← 0
  high ← S.size() - 1
  while low < high do
    mid ← (low + high + 1)/2 // needs to be < to terminate
    if k < key(S.elemAtRank(mid)) then // one key comparison per iteration
      high ← mid - 1
    else
      low ← mid // + 1 because mid has not been eliminated yet
  if S.size() > 0 ∧ k = key(S.elemAtRank(high)) then // handles empty S
    return value(S.elemAtRank(high)) // high or low contain matching key
  else
    return NO_SUCH_KEY

```

13

Binary Search Algorithm (change < to ≤ in the loop)

```

Algorithm BinarySearch(S, k):
  Input: An ordered Sequence S storing n items, accessed by keys()
  Output: An element of S with key k.
  low ← 0
  high ← S.size() - 1
  while low < high do
    mid ← (low + high + 1)/2 // needs to be < to terminate
    if k ≤ key(S.elemAtRank(mid)) then // change to ≤ instead of <
      high ← mid // changed due to change of condition
    else
      low ← mid + 1 // changed due to change of condition
  if S.size() > 0 ∧ k = key(S.elemAtRank(high)) then // handles empty S
    return value(S.elemAtRank(high)) // high or low contain matching key
  else
    return NO_SUCH_KEY

```

14

Errors

- ◆ The loop does not always terminate
 - mid needs to be the floor of the expression otherwise mid and high do not/cannot change which causes non-termination

15

15

Binary Search Algorithm (loop now terminates)

```

Algorithm BinarySearch(S, k):
  Input: An ordered Sequence S storing n items, accessed by keys()
  Output: An element of S with key k.
  low ← 0
  high ← S.size() - 1
  while low < high do
    mid ← (low + high)/2 // needs to be the floor to terminate
    if k ≤ key(S.elemAtRank(mid)) then // changed to ≤ instead of <
      high ← mid // removed - 1 (since mid is not eliminated)
    else
      low ← mid + 1 // changed
  if S.size() > 0 ∧ k = key(S.elemAtRank(low)) then // handles empty S
    return value(S.elemAtRank(low)) // high or low contain matching key
  else
    return NO_SUCH_KEY

```

16

Why a third version?

- ◆ Depends on the purpose
- ◆ The third version is an improvement in the binary search used by the Lookup Table

17

17

Errors (none)

- ◆ Handles a Sequence with 0 elements
- ◆ Handles a Sequence with 1 element that matches the key k
- ◆ We do not want the ceiling((high+low)/2) this time
- ◆ The loop terminates
 - mid is initialized correctly with the floor of the expression (does not add 1)
- ◆ Handles a Sequence with 2 elements (or a segment with 2 elements) with one matching the key k
 - Two cases: first and second element
- ◆ Finds the key when it is in the Sequence by using rank low although could have left it as high

18

18

The loop invariant of the loop in function BinarySearch

if the key k is in the Sequence S , then
 $S.\text{elemAtRank}(\text{low}) \leq k \leq S.\text{elemAtRank}(\text{high})$

- Informally, if key k is in the Sequence S , then k is the key of an item in S at a rank between low and high

19

Is it worth exiting early from the loop?

20

Binary Search Algorithm (Two comparisons per iteration)

Algorithm BinarySearch(S, k):
Input: An ordered Sequence S storing n items, accessed by keys()
Output: An element of S with key k .
 $\text{low} \leftarrow 0$
 $\text{high} \leftarrow S.\text{size}() - 1$
while $\text{low} \leq \text{high}$ **do**
 $\text{mid} \leftarrow (\text{low} + \text{high})/2$
 if $k = \text{key}(S.\text{elemAtRank}(\text{mid}))$ **then** *(exit early from the loop)*
 return $\text{value}(S.\text{elemAtRank}(\text{mid}))$
 else if $k < \text{key}(S.\text{elemAtRank}(\text{mid}))$ **then**
 $\text{high} \leftarrow \text{mid} - 1$
 else
 $\text{low} \leftarrow \text{mid} + 1$
return **NO_SUCH_KEY**

21

Binary Search Algorithm (One comparison per iteration)

Algorithm BinarySearch(S, k):
Input: An ordered Sequence S storing n items, sorted by keys()
Output: An item of S with key k and rank between low & high .
 $\text{low} \leftarrow 0$
 $\text{high} \leftarrow S.\text{size}() - 1$
while $\text{low} < \text{high}$ **do**
 $\text{mid} \leftarrow (\text{low} + \text{high} + 1)/2$
 if $k < \text{key}(S.\text{elemAtRank}(\text{mid}))$ **then** *(always does log n comparisons)*
 $\text{high} \leftarrow \text{mid} - 1$
 else
 $\text{low} \leftarrow \text{mid}$ *// + 1 does not yet eliminate mid*
if $S.\text{size}() > 0 \wedge k = \text{key}(S.\text{elemAtRank}(\text{low}))$ **then**
 return $\text{value}(S.\text{elemAtRank}(\text{low}))$
else
 return **NO_SUCH_KEY**

22

Homework

- Both algorithms make $O(\log n)$ key comparisons
- Which algorithm makes fewer actual key comparisons when the key is not in S ?
- Which makes fewer comparisons, **on average**, when the key is in S , assuming all keys are equally likely to be searched?

23

What's Wrong with this In Place Version of Partition

Algorithm inPlacePartition(S, lo, hi):
Input: Sequence S and ranks lo and hi , $0 \leq lo \leq hi < S.\text{size}()$
Output: the pivot is now stored at its sorted rank
 $p \leftarrow$ a random integer between lo and hi
 $S.\text{swapElements}(S.\text{atRank}(lo), S.\text{atRank}(p))$
 $\text{pivot} \leftarrow S.\text{elemAtRank}(lo)$
 $j \leftarrow lo + 1$
 $k \leftarrow hi$
while $j \leq k$ **do**
 while $k > j \wedge S.\text{elemAtRank}(k) \geq \text{pivot}$ **do**
 $k \leftarrow k - 1$
 while $j < k \wedge S.\text{elemAtRank}(j) \leq \text{pivot}$ **do**
 $j \leftarrow j + 1$
 if $j < k$ **then**
 $S.\text{swapElements}(S.\text{atRank}(j), S.\text{atRank}(k))$
 $S.\text{swapElements}(S.\text{atRank}(lo), S.\text{atRank}(k))$ *{move pivot to sorted rank}*
return k

24

24

Error

- ◆ Does not terminate!
- ◆ Some swaps could incorrectly or unnecessarily move elements/items

25

Corrected In Place Version of Partition

Algorithm *inPlacePartition*(*S*, *lo*, *hi*)

Input Sequence *S* and ranks *lo* and *hi*, $0 \leq lo \leq hi < S.size()$
Output the pivot is now stored at its sorted rank

```
p ← a random integer between lo and hi
S.swapElements(S.atRank(lo), S.atRank(p))
pivot ← S.elemAtRank(lo)
j ← lo + 1
k ← hi
while j ≤ k do
  while k ≥ j ∧ S.elemAtRank(k) ≥ pivot do
    k ← k - 1
  while j ≤ k ∧ S.elemAtRank(j) ≤ pivot do
    j ← j + 1
  if j < k then
    S.swapElements(S.atRank(j), S.atRank(k))
S.swapElements(S.atRank(lo), S.atRank(k)) {move pivot to sorted rank}
return k
```

26