



CS544 EA

Applications

Spring MVC: Flash Attributes

Flash Attributes

- Flash attributes are a way for a request to store attributes intended for use in the next (single) request
 - Stored in the **session** for a very **short time**
 - Removed right away after first use
- Commonly used in combination with redirect
 - POST/REDIRECT/GET when the 'get' needs data
 - Also when there are validation errors on the POST

Specifying Flash Attributes

```
@Controller
public class CarController {

    @PostMapping(value="/cars")
    public String add(Car car, RedirectAttributes redirectAttrs) {
        carDao.add(car);
        String msg = "Added " + car.getMake() + " " + car.getModel();
        redirectAttrs.addFlashAttribute("message", msg);
        return "redirect:/cars";
    }
}
```

RedirectAttributes
additional parameter

This URL will receive them

Make sure you use the
.addFlashAttribute() method
not the .addAttribute() method!

Receiving Flash Attributes

@Controller

public class CarController {

The URL that receives

May be called from Flash
or just normally called

@GetMapping(value="/cars")

public String getAll(ModelMap model) {

If there are Flash attributes
they are stored in the Model

if (model.containsKey("message")) {

System.out.println("Message: " + model.get("message"));

} **else** {

System.out.println("No Message");

}

model.addAttribute("cars", carDao.getAll());

return "carList";

}

}

Using a Flash Attribute

```
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c" %>
<%@ page language="java" contentType="text/html; charset=UTF-8"
pageEncoding="UTF-8"%>
<!DOCTYPE html>
<html>
<head>
  <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
  <title>Cars currently in the shop</title>
</head>
<body>
  <h1>Cars currently in the shop</h1>
  <table>
    <c:forEach var="car" items="${cars}">
      <tr>
        <td>${car.make}</td>
        <td>${car.model}</td>
        <td>${car.year}</td>
        <td>${car.color}</td>
        <td><a href="cars/${car.id}">edit</a></td>
      </tr>
    </c:forEach>
  </table>

  <c:if test="${not empty message}">
    <p>Message: <strong>${message}</strong></p>
  </c:if>

  <a href="addCar.html"> Add a Car</a>
</body>
</html>
```

If Flash attribute passed in
it will be available during
View rendering