



CS544 EA

Applications

Concurrency: Pessimistic Locking

Pessimistic Locking



- For certain operations optimistic concurrency might not be enough
 - Stricter isolation might be required to prevent the unrepeatable reads problem
 - Hibernate can **request explicit database level locks** to provide increased isolation
 - These locks will be released on commit

SELECT FOR UPDATE
on DBs that support it

```
Customer cust = (Customer)em.find(Customer.class, 1);  
em.lock(cust, LockModeType.UPGRADE);
```

```
Customer cust = em.find(Customer.class, 1, LockModeType.UPGRADE);
```

LockModeType

Lock Mode	Description	Throws PersistenceException on objects without version
None	Nothing	
OPTIMISTIC	Performs a version column check	
OPTIMISTIC_FORCE_INCREMENT	Ensures an increment on the version column before the transactions commits	
PESSIMISTIC_FORCE_INCREMENT	Forces and increment on the version column right away and tries to get a write lock	
PESSIMISTIC_READ	Tries to get a read lock in the DB	
PESSIMISTIC_WRITE	Tries to get a write lock in the DB	
READ	Synonym of OPTIMISTIC	
WRITE	Synonym of OPTIMISTIC_FORCE_INCREMENT	

Newer apps should use
OPTIMISTIC versions
Not READ / Write