





```
logo
PQ362741.1
                                      624
LC507900.1
                                      624
LC507896.1
                                      616
             . . . . . . . . . . . . . . . . . . .
KT265714.1
             T C A . . . . . . . . . . . . . . . .
                                      635
KT265715.1
                <mark>A</mark> . . . . . . . . . . . . . . . .
                                      635
MT159541.1
             TCAATAAGCGGA . . . . . .
                                      644
             TCAATAAGCGGAG....
JF705215.1
                                      645
MW369639.1
             TCAATAAGCGGAG....
                                      645
             TCAATAAGCGGAG....
KF176606.1
                                      645
MW186478.1
             TCAATAAGCGGAG....
                                      645
KF176581.1
            TCAATAAGCGGAG....
                                      645
JF701784.1
                                      591
MK442087.1
                                      577
MG837526.1
             TCAATAAGCGGAG....
                                      645
             TCAATAAGCGGAG....
                                      644
MG837524.1
MG837525.1
             TCAATAAGCGGAG....
                                      645
            TCAATAAGCGGAG....
DQ102438.1
                                      646
KF372657.1
                                      600
MT522873.1
                                      581
             TCAATAAGCGGAG....
KY965395.1
                                      642
            TCACTAAACGGAGAAGAA
MD-R1
                                      662
                 13.9 (C); Accessible sidechain area (Å^2)
                 23.0 (I); 23.5 (V); 25.2 (G)
                 28.7 (F); 29.0 (L); 30.5 (M); 31.5 (A)
                 41.7 (W); 44.2 (S); 46.0 (T); 46.7 (H)
            X
                 53.7 (P)
                 59.1 (Y); 60.9 (D); 62.2 (N)
                72.3 (E); 74.0 (Q)
```

93.8 (R) 110.3 (K)