Cardinality Estimation Using Neural Networks

CASCON '15

Henry Liu University of Waterloo, Waterloo, Canada

Mingbin Xu York University, Toronto, Canada

Ziting Yu University of Waterloo, Waterloo, Canada

Vincent Corvinelli IBM Canada Ltd., Markham, Canada

Calisto Zuzarte IBM Canada Ltd., Markham, Canada

Join-Orders Matter

```
SELECT * FROM a, b WHERE 5 < a.x < 9 AND 20 < b.y < 2000 AND a.z = b.z

nested-loop join
```

```
for outer_record in outer_table:
    for inner_record in inner_table:
        print(outer_record + inner record)
```

Option 1: a as outer table, b as inner table Option 2: b as outer table, a as inner table

Terminologies in paper title:

Cardinality Estimation Using Neural Networks

Cardinality = # of total records * selectivity

name	age
J	3
Α	5
Р	3
Χ	4
С	5
I	4

```
Eg:
```

Select name from tb1 where age>3

of total records: 6

Selectivity: 0.67

(4/6)

Cardinality:4

Cardinality = # of total records * selectivity


How to estimate selectivity?

–a naïve approach: assume uniform distribution


–a better approach: histogram

Cardinality = # of total records * selectivity

assume uniform distribution



Cardinality = # of total records * selectivity



Multi-Column Selectivity Estimation

- Assume columns are independent
 - estimate the selectivity of each column and obtains the product of them
- Correlation between columns

Multi-Column Selectivity Estimation

Assume

- half of the population is order than 45
- half of the population has salary more than 45K
- Under the independent-column assumption
 - -set=0.5*0.5=0.25
 - however, the actual selectivity may be farless than that

Problem Formulation

- Input
 - k fields, 2k boundaries
- Output
 - selectivity

```
SELECT * FROM population
WHERE 0 < age < 45 AND 45000 < salary < max_salary</pre>
```

Questions

- If columns are independent, can we do more better estimation of selectivity?
- If columns are dependent, can we improve the estimation of selectivity more?