

PART	OD / PILOT	ID	LENGTH	MATERIAL / NOTE
M0 fixed collar	18 body x7 + 11.8 pilot x2	8.05	9.00	303 SS; radial M3
M0 inner shim	12.00	8.10	1.00	301/304 SS
M1 outer spacer	21.80	18.20	16.00	6061-T6
M1 inner spacer	17.80	8.05	16.00	6061-T6
M1 lower spacer	17.80	8.05	12.00	6061-T6
M1 upper collar	16.00	8.05	9.00	303 SS; radial M3
M2 outer spacer	27.80	22.00 +0.05/0	11.00	6061-T6
M2 rear shim	18.00	12.05	0.50	301/304 SS
M2 center spacer	17.80 +0/-0.05	12.05	11.00	6061-T6
M2 front spacer	18.00	12.05	4.00	6061-T6

COMMON TURNING AND INSPECTION NOTES

- 1. Unless individually toleranced: diameters +/-0.05; lengths +/-0.03; face parallelism <=0.02.
- 2. Bearing-abutment faces Ra <=1.6; remove burrs without rolling an edge onto the face.
- 3. M2 unilateral diameters preserve the validated 2.10 nominal radial clearance.
- 4. ID12.05 parts require measured flyer tube OD <=12.02; otherwise ream as a matched set.
- 5. DIN 472 retaining rings are catalog hardware and are not included in this custom packet.