


FRONT



ARM FLATS @ 64.75 FROM A

FEATURE	FROM DATUM A	NORMAL	CONTROL
D10 clamp seat	0.00..18.50	axis	OD9.991-10.000 h6; round, no pulley flats; ID6.000-6.030
ID transition	18.50..21.50	axis	coaxial ID6-to-ID9 cone; polish
Arm flat 1	64.75 +/-0.05	-Y	depth 0.30 +/-0.03; axial L5.00 +/-0.10
Arm flat 2	64.75 +/-0.05	+X	90 deg +/-0.5 deg from arm flat 1
Shaft	L79.00 +/-0.05	axis	main OD11.980-12.000; main ID9.000-9.050

1. 6061-T6 machined hollow bar; total indicated runout ≤ 0.05 over the bearing span. The shoulder at 18.50 is the stock-pulley axial datum.
2. The full 18.50 mm pulley through-bore must remain OD10 h6 and round. NBK also permits h7, but Rev D selects h6; record three-axis micrometer readings before clamp assembly.
3. The ID6 neck leaves 2.00 mm nominal and 1.980 mm minimum radial wall at drawing limits. Blend coaxially to the controlled ID9 over 3.00 mm; the wire centerline stays straight and has no forced bend.
4. Round and polish the rear ID6 and front ID9 mouths to R0.5 minimum and $R_a \leq 0.4$ micrometre; polish the transition, then clean all chips and abrasive.
5. Use only stock NBK P30-3GT-BLP-6C-10 with its supplied M2 split-clamp bolt at the manufacturer torque. No M3 pulley flats or set screws are permitted.