

STEP PART	QTY	MATERIAL	CONTROLLED FUNCTION
flyer_peek_guide_bell	1	Natural unfilled PEEK	One-piece ID0.60 polished bore, R3.25 root elbow and integral exit bell
stator_short_leadin_cap_front	1	Natural unfilled PEEK	Front 24-sector cap with open short lead-ins; paired M2 retention
stator_short_leadin_cap_rear	1	Natural unfilled PEEK	Rear 24-sector cap with open short lead-ins; paired M2 retention
active_sector_peek_guide_front	1	Natural unfilled PEEK	M0-following front capture shoe with open bowls and keyed pads
active_sector_peek_guide_rear	1	Natural unfilled PEEK	M0-following rear capture shoe with open bowls and keyed pads

RFQ AND RELEASE BLOCKERS

- 1. The paired STEP is the exact shape authority. Do not close, bridge, or simplify any polished open wire channel.
- 2. Quote only natural unfilled PEEK. State exact resin grade, filler declaration, lot certificate, machining process, achievable finish, and dimensional inspection method.
- 3. Wire-contact surfaces require supplier DFM review, burr-free polish, and later abrasion, dielectric, varnish and 60 N hot coupons. This packet is not production authorization.
- 4. No price or supplier is selected. Return a marked-up drawing and quote before any order state may advance.

STEP PART	QTY	MATERIAL	CONTROLLED FUNCTION
active_sector_aluminum_yoke	1	Certified 6061-T6 only	One-solid keyed M0 carriage yoke; four M4 tower stacks and four M3 guide stacks

RFQ AND RELEASE BLOCKERS

- 1. Preserve all keyed datums and M3/M4 hole positions from the yoke STEP. No decorative substitutions are allowed.
- 2. Supplier must confirm certified 6061-T6 and return heat treatment, machining tolerance, concentricity, runout, balance and surface-treatment proposal. No alloy or temper substitution is pre-authorized; prices remain TBD.
- 3. The selected flyer pulley is the separate stock NBK P30-3GT-BLP-6C-10 and is not a custom machined part in this packet.
- 4. All M3 and M4 yoke fasteners are ordered separately. Motor-side BNW witnesses remain outside this packet and have purchase quantity zero.

STEP PART	QTY	GEOMETRY	SOLVED CONTROL
balance_b777_rear_1	1	Rear annular stack	Solved axial length 1.537534 mm
balance_b777_rear_2	1	Rear annular stack	Solved axial length 0.600000 mm
balance_b777_rear_3	1	Rear annular stack	Solved axial length 0.630832 mm
balance_b777_rear_4	1	Rear annular stack	Solved axial length 1.568040 mm
balance_b777_front_left	1	OD6 / ID2.2 annulus	Common thickness 1.502168 mm
balance_b777_front_right	1	OD6 / ID2.2 annulus	Common thickness 1.502168 mm

MATERIAL, WEIGHING AND RELEASE BLOCKERS

- 1. Quote ASTM-B777 tungsten heavy alloy but state grade, certified density, chemistry, lot and achievable dimensional tolerance. No grade substitution is pre-authorized.
- 2. Machine each serialized trim to its own STEP. Deburr without rounding bearing faces or changing the annular bore. Weigh each finished trim and record actual mass and serial number.
- 3. Four rear trims use separate printed retainers, M3x6 countersunk screws and 94459A130 inserts. Two front trims use M2x8 screws, washers and standard M2 inserts.
- 4. The six solved dimensions are nominal digital balance values. Final installed G2.5 balance, retention pull tests and hot 300 RPM endurance remain mandatory before use.