


Layer	Name	Material	Thickness	Constant	Gerber	Board Layer Stack
	Top Overlay				GTO	<div></div>
	Top Solder	Solder Resist	0.010mm	3.5	GTS	
1	Top Layer		0.035mm		GTL	
	Dielectric1	FR-4 (7628)	0.099mm	4.2		<div></div>
2	MidLayer1		0.018mm		G1	
	Core		1.265mm	4.2		
3	MidLayer2		0.018mm		G2	<div></div>
	Dielectric 4	FR-4 (7628)	0.099mm	4.2		
4	Bottom Layer		0.035mm		GBL	
	Bottom Solder	Solder Resist	0.010mm	3.5	GBS	<div></div>
	Bottom Overlay				GBO	

Total board thickness: 1.589mm



Symbol	Count	Hole Size	Hole Length	Plated	Hole Type	Drill Layer Pair	Via/Pad	Pad Shape
	253	0.200mm (7.87mil)	-	PTH	Round	Top Layer - Bottom Layer	Via	Rounded
	2	0.600mm (23.62mil)	1.600mm (62.99mil)	PTH	Slot	Top Layer - Bottom Layer	Pad	Rounded
	2	0.600mm (23.62mil)	2.100mm (82.68mil)	PTH	Slot	Top Layer - Bottom Layer	Pad	Rounded
	18	1.000mm (39.37mil)	-	PTH	Round	Top Layer - Bottom Layer	Pad	(Mixed)
	4	1.200mm (47.24mil)	-	PTH	Round	Top Layer - Bottom Layer	Pad	Rounded
	279 Total							

Slot definitions : Routed Path Length = Calculated from tool start centre position to tool end centre position.
Hole Length = Routed Path Length + Tool Size = Slot length as defined in the PCB layout

