

# Running Probabilistic Programs Backward

Neil Toronto    Jay McCarthy

PLT @ Brigham Young University  
ntoronto@racket-lang.org    jay@cs.byu.edu

## Abstract

Problem: doesn't exist: Turing-equivalent, probabilistic programming language with a semantics and implementation that supports any kind of probability measure and—critically—can do probabilistic conditioning

Why problem:

Solution:

Why solution:

**Categories and Subject Descriptors** XXX-CR-number  
[XXX-subcategory]: XXX-third-level

**General Terms** XXX, XXX

**Keywords** XXX, XXX

## 1. Introduction

XXX: motivate conditional probability

XXX: densities fail:

1. infinite or variable-length data
2. discontinuities in random variables
3. nonlinear conditions

XXX: measures instead of densities, preimage measure

Purely functional languages do not allow effects, including randomness. (Of course, to be Turing-equivalent, “pure” languages usually allow divergence, which is an applicative effect.) Programmers must write probabilistic programs as functions from a random source to outputs. Monads and other categorical classes such as idioms and arrows can make doing so easier. The strength of this approach lies in how it factors each probabilistic program into an effectful part and a pure part.

It seems this approach should make interpreting probabilistic programs in measure theory easy. For a probabilistic program  $f : X \Rightarrow Y$ , the probability measure over output sets  $B \subseteq Y$  should be defined by preimages of  $B$  under  $f$  and the probability measure over  $X$ . Unfortunately, it is difficult to make a compositional semantics from this simple-sounding idea, for the following reasons.

- “Preimage under  $f$ ” is a senseless phrase unless  $f$  has an observable domain of definition. Lambdas do not. Hash tables do, but their domains are finite.
- Probability measures can be defined only for *measurable* subsets of  $X$  and of  $Y$ . Thus,  $f$  is constrained: preimages of measurable subsets of  $Y$  must be measurable subsets of  $X$ . Proving the conditions under which this is true is difficult, especially when  $f$  may diverge.
- Probability measures cannot be defined for function types without imposing difficult restrictions.

Implementing a language based on such a semantics is complicated by these facts:

- Contemporary mathematics is unlike any implementation's host language.
- It requires running programs backward, efficiently, on possibly infinite sets of outputs.

XXX: rewrite the following

In this paper, we

1. Define the *bottom arrow*, type  $X \rightsquigarrow_{\perp} Y$ , as a compilation target for first-order functions that may raise errors.
2. Derive the *mapping arrow* from the bottom arrow, type  $X \rightsquigarrow_{\text{map}} Y$ . Prove that its instances return extensional functions, or mappings, that compute the same values as corresponding bottom arrow computations.
3. Derive the *preimage arrow* from the mapping arrow, type  $X \rightsquigarrow_{\text{pre}} Y$ . Prove that its instances compute preimages under corresponding mapping (or bottom) arrow instances.
4. Define an arrow transformer via a natural transformation  $\eta$  to thread random stores and avoid divergence.
5. Define a computable approximation of the transformed preimage arrow and report on its implementation.

Most of our correctness theorems can be described in terms of the following commutative diagram:

$$\begin{array}{ccccc}
 X \rightsquigarrow_{\perp} Y & \xrightarrow{\text{lift}_{\text{map}}} & X \rightsquigarrow_{\text{map}} Y & \xrightarrow{\text{lift}_{\text{pre}}} & X \rightsquigarrow_{\text{pre}} Y \\
 \eta_{\perp*} \downarrow & & \downarrow \eta_{\text{map}*} & & \downarrow \eta_{\text{pre}*} \\
 X \rightsquigarrow_{\perp*} Y & \xrightarrow{\text{lift}_{\text{map}*}} & X \rightsquigarrow_{\text{map}*} Y & \xrightarrow{\text{lift}_{\text{pre}*}} & X \rightsquigarrow_{\text{pre}*} Y
 \end{array} \quad (1)$$

We prove that all the functions between arrow types in (1) are homomorphisms, which implies that  $X \rightsquigarrow_{\text{pre}} Y$  and  $X \rightsquigarrow_{\text{pre}*} Y$  instances compute preimages correctly.

XXX: something about how we know the approximations are correct

## 2. Operational Metalanguage

From here on, significant terms are introduced in **bold**, and significant terms we invent are introduced in ***bold italics***.

We write all of the programs in this paper in  $\lambda_{\text{ZFC}}$  [2], an untyped, call-by-value lambda calculus designed for deriving implementable programs from contemporary mathematics.

Contemporary mathematics is generally done in **ZFC**: **Zermelo-Fraenkel** set theory extended with the axiom of **Choice** (equivalently unique **Cardinality**). ZFC has only first-order functions and no general recursion, which makes implementing a language defined by a transformation into contemporary mathematics quite difficult. The problem is exacerbated if implementing the language requires approximation. Targeting  $\lambda_{\text{ZFC}}$  instead allows creating a precise mathematical specification and deriving an approximating implementation without changing languages.

In  $\lambda_{\text{ZFC}}$ , essentially every set is a value, as well as every lambda and every set of lambdas. All operations, including operations on infinite sets, are assumed to complete instantly if they terminate.<sup>1</sup>

Almost everything definable in contemporary mathematics can be formally defined by a finite  $\lambda_{\text{ZFC}}$  program, except objects that most mathematicians would agree are nonconstructive. More precisely, any object that *must* be defined by a statement of existence and uniqueness without giving a bounding set is not definable by a *finite*  $\lambda_{\text{ZFC}}$  program.

Because  $\lambda_{\text{ZFC}}$  includes an inner model of ZFC, essentially every contemporary theorem applies to  $\lambda_{\text{ZFC}}$ 's set values without alteration. Further, proofs about  $\lambda_{\text{ZFC}}$ 's set values apply to contemporary mathematical objects.<sup>2</sup>

In  $\lambda_{\text{ZFC}}$ , algebraic data structures are encoded as sets; e.g. a ***primitive ordered pair*** of  $x$  and  $y$  is  $\{\{x\}, \{x, y\}\}$ . Only the *existence* of encodings into sets is important, as it means data structures inherit a defining characteristic of sets: strictness. More precisely, the lengths of paths to data structure leaves is unbounded, but each path must be finite. Less precisely, data may be “infinitely wide” (such as  $\mathbb{R}$ ) but not “infinitely tall” (such as infinite trees and lists).

We assume data structures, including pairs, are encoded as *primitive* ordered pairs with the first element a unique tag, so that they can be distinguished by checking tags. Accessors such as **fst** and **snd** are trivial to define.

$\lambda_{\text{ZFC}}$  is untyped so its users can define an auxiliary type system that best suits their application area. For this work, we use an informal, manually checked, polymorphic type system characterized by these rules:

- A free lowercase type variable is universally quantified.
- A free uppercase type variable is a set.
- A set denotes a member of that set.
- $x \Rightarrow y$  denotes a partial function.
- $\langle x, y \rangle$  denotes a pair of values with types  $x$  and  $y$ .
- **Set**  $x$  denotes a set with members of type  $x$ .

The type **Set**  $X$  denotes the same values as the powerset  $\mathcal{P} X$ , or *subsets* of  $X$ . Similarly, the type  $\langle X, Y \rangle$  denotes the same values as the product set  $X \times Y$ .

<sup>1</sup>An example of a nonterminating  $\lambda_{\text{ZFC}}$  function is one that attempts to decide whether other  $\lambda_{\text{ZFC}}$  programs halt.

<sup>2</sup>Assuming the existence of an inaccessible cardinal.

We write  $\lambda_{\text{ZFC}}$  programs in heavily sugared  $\lambda$ -calculus syntax, with an if expression and these additional primitives:

$$\begin{array}{ll} \text{true} : \text{Bool} & (\in) : x \Rightarrow \text{Set } x \Rightarrow \text{Bool} \\ \text{false} : \text{Bool} & \mathcal{P} : \text{Set } x \Rightarrow \text{Set } (\text{Set } x) \\ \emptyset : \text{Set } x & \bigcup : \text{Set } (\text{Set } x) \Rightarrow \text{Set } x \\ \omega : \text{Ord} & \text{image} : (x \Rightarrow y) \Rightarrow \text{Set } x \Rightarrow \text{Set } y \\ \text{take} : \text{Set } x \Rightarrow x & |\cdot| : \text{Set } x \Rightarrow \text{Ord} \end{array} \quad (2)$$

Shortly,  $\emptyset$  is the empty set,  $\omega$  is the cardinality of the natural numbers, **take**  $\{x\}$  reduces to  $x$  and diverges for non-singleton sets,  $x \in A$  decides membership,  $\mathcal{P} A$  reduces to the set of subsets of  $A$ ,  $\bigcup A$  reduces to the union of the sets in  $A$ , **image**  $f A$  applies  $f$  to each member of  $A$  and reduces to the set of results, and  $|A|$  reduces to the cardinality of  $A$ .

We assume literal set notation such as  $\{0, 1, 2\}$  is already defined in terms of the set primitives.

We import contemporary theorems as lemmas.

### 2.1 Internal and External Equality

Set theory extends first-order logic with an axiom that defines equality to be extensional, and with axioms that ensure the existence of sets in the domain of discourse.  $\lambda_{\text{ZFC}}$  is defined the same way as any other operational  $\lambda$ -calculus: by (conservatively) extending the domain of discourse with expressions and defining a reduction relation.

While  $\lambda_{\text{ZFC}}$  does not have an equality primitive, set theory's extensional equality can be recovered internally using  $(\in)$ . *Internal* extensional equality is defined by

$$x = y := x \in \{y\} \quad (3)$$

which means

$$(\equiv) := \lambda x. \lambda y. x \in \{y\} \quad (4)$$

Thus,  $1 = 1$  reduces to  $1 \in \{1\}$ , which reduces to **true**.<sup>3</sup> Because of the particular way  $\lambda_{\text{ZFC}}$ 's lambda terms are defined, for two lambda terms  $f$  and  $g$ ,  $f = g$  reduces to **true** when  $f$  and  $g$  are structurally identical modulo renaming. For example,  $(\lambda x. x) = (\lambda y. y)$  reduces to **true**, but  $(\lambda x. 2) = (\lambda x. 1 + 1)$  reduces to **false**.

We understand any  $\lambda_{\text{ZFC}}$  term  $e$  used as a truth statement as shorthand for “ $e$  reduces to **true**.” Therefore, while the terms  $(\lambda x. x) 1$  and  $1$  are (externally, extensionally) unequal, we can say that  $(\lambda x. x) 1 = 1$ .

Any truth statement  $e$  implies that  $e$  converges. In particular, the truth statement  $e_1 = e_2$  implies that both  $e_1$  and  $e_2$  converge. However, we often want to say that  $e_1$  and  $e_2$  are equivalent when they both diverge. In these cases, we use a slightly weaker equivalence.

**Definition 2.1** (observational equivalence). *Two  $\lambda_{\text{ZFC}}$  terms  $e_1$  and  $e_2$  are **observationally equivalent**, written  $e_1 \equiv e_2$ , when  $e_1 = e_2$  or both  $e_1$  and  $e_2$  diverge.*

It could be helpful to introduce even coarser notions of equivalence, such as applicative or logical bisimilarity. However, we do not want internal equality and external equivalence to differ too much. We therefore introduce type-specific notions of equivalence as needed.

### 2.2 Additional Functions and Forms

We assume a desugaring pass over  $\lambda_{\text{ZFC}}$  expressions, which automatically curries (including for the two-argument primitives  $(\in)$  and **image**), and interprets special binding forms

<sup>3</sup>Technically,  $\lambda_{\text{ZFC}}$  has a big-step semantics, and the derivation tree for  $1 = 1$  contains the derivation tree for  $1 \in \{1\}$ .

such as indexed unions  $\bigcup_{x \in e_A} e$ , destructuring binds as in  $\text{swap } \langle x, y \rangle := \langle y, x \rangle$ , and comprehensions like  $\{x \in A \mid x \in B\}$ . (We may be rather informal with the latter two binding forms when the meaning is clear.) We assume we have logical operators, bounded quantifiers (unbounded quantifiers are not  $\lambda_{\text{ZFC}}$ -definable), and typical set operations.

A less typical set operation we use is disjoint union:

$$\begin{aligned} (\uplus) : \text{Set } x &\Rightarrow \text{Set } x \Rightarrow \text{Set } x \\ A \uplus B &:= \text{if } (A \cap B = \emptyset) (A \cup B) (\text{take } \emptyset) \end{aligned} \quad (5)$$

$A \uplus B$  diverges when  $A$  and  $B$  overlap.

In set theory, functions are encoded as sets of input-output pairs. The increment function for the natural numbers, for example, is  $\{\langle 0, 1 \rangle, \langle 1, 2 \rangle, \langle 2, 3 \rangle, \dots\}$ . To distinguish these huge tables from lambdas, we call them **mappings**, and use the word **function** to mean a lambda or mapping.

Syntax for defining unnamed mappings is defined by

$$\lambda x_a \in e_A. e_b := \text{mapping } (\lambda x_a. e_b) e_A \quad (6)$$

$$\begin{aligned} \text{mapping} : (X \Rightarrow Y) &\Rightarrow \text{Set } X \Rightarrow (X \rightarrow Y) \\ \text{mapping } f \ A &:= \text{image } (\lambda a. \langle a, f \ a \rangle) \ A \end{aligned} \quad (7)$$

For convenience, as with lambdas, we use adjacency (e.g.  $(f \ x)$ ) to apply mappings.

Figure 1 defines a few common operations on mappings: **domain**, **range**, **preimage**, **restrict**, **pairing**, **composition**, and **disjoint union**. The latter three are particularly important in the preimage arrow's derivation, and **preimage** is critical in measure theory's account of probability. For symmetry with partial functions  $x \Rightarrow y$ , they are defined on  $X \rightarrow Y$ , where  $X \rightarrow Y$  is the set of all partial mappings from any domain set  $X$  to any codomain set  $Y$ .

The set  $X \rightarrow Y$  contains all the *total* mappings from  $X$  to  $Y$ . We use total mappings as possibly infinite vectors, with application for indexing. Projections are produced by

$$\begin{aligned} \pi : J &\Rightarrow (J \rightarrow X) \Rightarrow X \\ \pi \ j \ f &:= f \ j \end{aligned} \quad (8)$$

which will be useful when  $f$  is unnamed.

Pairs  $\langle A, f \rangle : \langle \text{Set } x, x \Rightarrow y \rangle$  are like functions with an observable domain and range; we call them **lazy mappings**. We do not use them in this paper, but we define a similar function-like type in Section 5 for computing preimages.

### 3. Arrows and First-Order Semantics

XXX: really short arrow intro (XXX: cite Hughes, Lindley et al)

#### 3.1 Alternative Arrow Definitions

For every arrow  $a$  in this paper, we do not give a typical minimal definition. Instead of  $\text{first}_a$ , we define  $(\&\&\&_a)$ —typically called **fanout**, but its use will be clearer if we call it **pairing**—which applies two functions to an input and returns the pair of their outputs. Though  $\text{first}_a$  may be defined in terms of  $(\&\&\&_a)$  and vice-versa [1], we give  $(\&\&\&_a)$  definitions in this paper because the applicable contemporary theorems are in terms of pairing functions.

One way to strengthen an arrow  $a$  is to define an additional combinator  $\text{left}_a$ , which can be used to choose an arrow computation based on the result of another. Again, we define a different combinator,  $\text{ifte}_a$ , to make it easier to apply contemporary theorems.

In a nonstrict  $\lambda$ -calculus, simply defining a choice combinator allows writing recursive functions using nothing but

arrow combinators and lifted, pure functions. However, any strict  $\lambda$ -calculus (such as  $\lambda_{\text{ZFC}}$ ) requires an extra combinator to defer computations in conditional branches.

For example, suppose we define the **function arrow** with choice, by defining

$$\begin{aligned} \text{arr } f &:= f \\ (f_1 \ggg f_2) \ a &:= f_2 (f_1 \ a) \\ (f_1 \ \&\&\& \ f_2) \ a &:= \langle f_1 \ a, f_2 \ a \rangle \\ \text{ifte } f_1 \ f_2 \ f_3 \ a &:= \text{if } (f_1 \ a) (f_2 \ a) (f_3 \ a) \end{aligned} \quad (9)$$

and try to define the following recursive function:

$$\text{halt-on-true} := \text{ifte } (\text{arr id}) (\text{arr id}) \text{halt-on-true} \quad (10)$$

The defining expression diverges in a strict  $\lambda$ -calculus. In a nonstrict  $\lambda$ -calculus, it diverges only when applied to **false**.

Using  $\text{lazy } f \ a := f \ 0 \ a$ , which receives thunks and returns arrow computations, we can write **halt-on-true** as

$$\text{halt-on-true} := \text{ifte } (\text{arr id}) (\text{arr id}) (\text{lazy } \lambda 0. \text{halt-on-true}) \quad (11)$$

which diverges only when applied to **false** in any  $\lambda$ -calculus.

**Definition 3.1** (arrow with choice). *A binary type constructor  $(\rightsquigarrow_a)$  and the combinators*

$$\begin{aligned} \text{arr}_a : (x \Rightarrow y) &\Rightarrow (x \rightsquigarrow_a y) \\ (\ggg)_a : (x \rightsquigarrow_a y) \Rightarrow (y \rightsquigarrow_a z) &\Rightarrow (x \rightsquigarrow_a z) \\ (\&\&\&)_a : (x \rightsquigarrow_a y) \Rightarrow (x \rightsquigarrow_a z) &\Rightarrow (x \rightsquigarrow_a \langle y, z \rangle) \end{aligned} \quad (12)$$

*define an **arrow** if certain monoid, homomorphism, and structural laws hold. The additional combinators*

$$\begin{aligned} \text{ifte}_a : (x \rightsquigarrow_a \text{Bool}) \Rightarrow (x \rightsquigarrow_a y) &\Rightarrow (x \rightsquigarrow_a y) \Rightarrow (x \rightsquigarrow_a y) \\ \text{lazy}_a : (1 \Rightarrow (x \rightsquigarrow_a y)) &\Rightarrow (x \rightsquigarrow_a y) \end{aligned} \quad (13)$$

*define an **arrow with choice** if certain additional homomorphism and structural laws hold.*

From here on, as all of our arrows are arrows with choice, we simply call them arrows.

The necessary homomorphism laws ensure that  $\text{arr}_a$  distributes over function arrow combinators. These laws can be put in terms of more general homomorphism properties that deal with distributing an arrow-to-arrow lift, which we use extensively to prove correctness.

**Definition 3.2** (arrow homomorphism). *A function  $\text{lift}_b : (x \rightsquigarrow_a y) \Rightarrow (x \rightsquigarrow_b y)$  is an **arrow homomorphism** from arrow  $a$  to arrow  $b$  if the following distributive laws hold for appropriately typed  $f, f_1, f_2$  and  $f_3$ :*

$$\text{lift}_b (\text{arr}_a f) \equiv \text{arr}_b f \quad (14)$$

$$\text{lift}_b (f_1 \ggg_a f_2) \equiv (\text{lift}_b f_1) \ggg_b (\text{lift}_b f_2) \quad (15)$$

$$\text{lift}_b (f_1 \ \&\&\&_a f_2) \equiv (\text{lift}_b f_1) \ \&\&\&_b (\text{lift}_b f_2) \quad (16)$$

$$\text{lift}_b (\text{ifte}_a f_1 f_2 f_3) \equiv \text{ifte}_b (\text{lift}_b f_1) (\text{lift}_b f_2) (\text{lift}_b f_3) \quad (17)$$

$$\text{lift}_b (\text{lazy}_a f) \equiv \text{lazy}_b \lambda 0. \text{lift}_b (f \ 0) \quad (18)$$

The homomorphism laws state that  $\text{arr}_a$  must be a homomorphism from the function arrow to arrow  $a$ .

The monoid and structural arrow laws play little role in our semantics or its correctness. For the arrows we define, then, we elide the proofs of these arrow laws, and concentrate on homomorphisms.

XXX: actually, need to prove some of them, to prove that the natural transformation for the applicative store-passing arrow transformer is a homomorphism

$\text{domain} : (X \multimap Y) \Rightarrow \text{Set } X$	$\langle \cdot, \cdot \rangle_{\text{map}} : (X \multimap Y_1) \Rightarrow (X \multimap Y_2) \Rightarrow (X \multimap Y_1 \times Y_2)$
$\text{domain} := \text{image fst}$	$\langle g_1, g_2 \rangle_{\text{map}} := \text{let } A := (\text{domain } g_1) \cap (\text{domain } g_2) \\ \text{in } \lambda a \in A. \langle g_1 a, g_2 a \rangle$
$\text{range} : (X \multimap Y) \Rightarrow \text{Set } Y$	$(\circ_{\text{map}}) : (Y \multimap Z) \Rightarrow (X \multimap Y) \Rightarrow (X \multimap Z)$
$\text{range} := \text{image snd}$	$g_2 \circ_{\text{map}} g_1 := \text{let } A := \text{preimage } g_1 (\text{domain } g_2) \\ \text{in } \lambda a \in A. g_2 (g_1 a)$
$\text{preimage} : (X \multimap Y) \Rightarrow \text{Set } Y \Rightarrow \text{Set } X$	$(\uplus_{\text{map}}) : (X \multimap Y) \Rightarrow (X \multimap Y) \Rightarrow (X \multimap Y)$
$\text{preimage } f B := \{a \in \text{domain } f \mid f a \in B\}$	$g_1 \uplus_{\text{map}} g_2 := \text{let } A := (\text{domain } g_1) \uplus (\text{domain } g_2) \\ \text{in } \lambda a \in A. \text{if } (a \in \text{domain } g_1) (g_1 a) (g_2 a)$
$\text{restrict} : (X \multimap Y) \Rightarrow \text{Set } X \Rightarrow (X \multimap Y)$	
$\text{restrict } f A := \lambda a \in (A \cap \text{domain } f). f a$	

Figure 1: Operations on mappings.

### 3.2 First-Order Let-Calculus Semantics

XXX: Figure 2...

XXX: Stack machine...

XXX: Roughly, first-order application  $(x e)$  runs arrow computation  $x$  with a fresh stack with  $e$  at the head. The binding form  $(\text{let } e_0 e_b)$  pushes  $e_0$  onto the stack. Variables are referenced using  $(\text{env } n)$  with  $(\text{env } 0)$  referring to the head.

## 4. The Bottom and Mapping Arrows

We are certain that the preimage arrow correctly computes preimages under some function  $f$  because we ultimately *derive* it from a simpler arrow used to construct  $f$ .

One obvious candidate for the simpler arrow is the function arrow, defined in (9). However, we will need to explicitly handle divergence, so we need a slightly more complicated arrow for which running computations may raise an error.

Figure 3 defines the **bottom arrow**. Its computations are of type  $x \rightsquigarrow_{\perp} y ::= x \Rightarrow y_{\perp}$ , where the inhabitants of  $y_{\perp}$  are the error value  $\perp$  as well as the inhabitants of  $y$ . The type  $\text{Bool}_{\perp}$ , for example, denotes the members of  $\text{Bool} \cup \{\perp\}$ .

**Theorem 4.1.**  $\text{arr}_{\perp}$ ,  $(\&\&\&_{\perp})$ ,  $(\ggg_{\perp})$ ,  $\text{ifte}_{\perp}$  and  $\text{lazy}_{\perp}$  define an arrow.

*Proof.* The bottom arrow is the Maybe monad's Kleisli arrow with  $\text{Nothing} = \perp$ .  $\square$

### 4.1 Deriving the Mapping Arrow

Contemporary theorems about functions are about mappings, not lambdas. As in intermediate step toward the preimage arrow, then, we need an arrow whose computations produce mappings or are mappings themselves.

It is tempting to try to define the mapping arrow's type constructor as  $X \rightsquigarrow_{\text{map}} Y ::= X \multimap Y$ , and define  $f_1 \ggg_{\text{map}} f_2 := f_2 \circ_{\text{map}} f_1$  and  $(\&\&\&_{\text{map}}) := \langle \cdot, \cdot \rangle_{\text{map}}$ . Unfortunately, we run into a problem defining  $\text{arr}_{\text{map}} : (X \Rightarrow Y) \Rightarrow (X \multimap Y)$ : to define a mapping, we need a domain, but lambdas' domains are unobservable.

To parameterize mapping arrow computations on a domain, we define the **mapping arrow** computation type as

$$X \rightsquigarrow_{\text{map}} Y ::= \text{Set } X \Rightarrow (X \multimap Y) \quad (19)$$

Notice that  $\perp$  is absent in  $\text{Set } X \Rightarrow (X \multimap Y)$ . This will make it easier to disregard diverging inputs when computing preimages further on. (XXX: section)

A computation  $g : X \rightsquigarrow_{\text{map}} Y$  must meet the following **restriction law**. For all  $A \subseteq X$  for which  $g A$  converges, and for all  $A' \subseteq A$ ,

$$g A' = \text{restrict } (g A) A' \quad (20)$$

Roughly,  $g$  must act as if it returns restricted mappings.

To make the correspondence between bottom arrow and mapping arrow computations as clear as possible, we start by defining a function  $\text{lift}_{\text{map}} : (X \rightsquigarrow_{\perp} Y) \Rightarrow (X \rightsquigarrow_{\text{map}} Y)$  to lift bottom arrow computations. It must restrict its argument  $f$ 's domain to a subset of  $X$  for which  $f$  does not return  $\perp$ . It is helpful to have a standalone function  $\text{domain}_{\perp}$  that computes such domains, so we define that first, and then define  $\text{lift}_{\text{map}}$  in terms of it:

$$\begin{aligned} \text{domain}_{\perp} : (X \rightsquigarrow_{\perp} Y) \Rightarrow \text{Set } X \Rightarrow \text{Set } X \\ \text{domain}_{\perp} f A := \{a \in A \mid f a \neq \perp\} \end{aligned} \quad (21)$$

$$\begin{aligned} \text{lift}_{\text{map}} : (X \rightsquigarrow_{\perp} Y) \Rightarrow (X \rightsquigarrow_{\text{map}} Y) \\ \text{lift}_{\text{map}} f A := \text{mapping } f (\text{domain}_{\perp} f A) \end{aligned} \quad (22)$$

The clearest way to ensure that mapping arrow computations mean what we think they mean is to derive each combinator in a way that makes  $\text{lift}_{\text{map}}$  distribute over bottom arrow computations; i.e. it must be an arrow homomorphism (Definition 3.2). If  $\text{lift}_{\text{map}}$  is a homomorphism, then  $\llbracket e \rrbracket_{\text{map}} \equiv \text{lift}_{\text{map}} \llbracket e \rrbracket_{\perp}$  for any let-calculus expression  $e$ , because  $\text{lift}_{\text{map}}$  distributes through its expansion.

To meet the homomorphism laws, we need equivalence to be more extensional for mapping computations.

**Definition 4.2** (mapping arrow equivalence). *Two mapping arrow computations  $g_1 : X \rightsquigarrow_{\text{map}} Y$  and  $g_2 : X \rightsquigarrow_{\text{map}} Y$  are equivalent, or  $g_1 \equiv g_2$ , when  $g_1 A \equiv g_2 A$  for all  $A \subseteq X$ .*

Clearly  $\text{arr}_b := \text{lift}_b \circ \text{arr}_a$  meets the first homomorphism identity (14), so we define  $\text{arr}_{\text{map}}$  as a composition. The following subsections derive  $(\&\&\&_{\text{map}})$ ,  $(\ggg_{\text{map}})$ ,  $\text{ifte}_{\text{map}}$  and  $\text{lazy}_{\text{map}}$  from their corresponding bottom arrow combinators, in a way that ensures  $\text{lift}_{\text{map}}$  is an arrow homomorphism. Figure 4 contains the resulting definitions.

$$\begin{array}{ll}
[x := e; \dots ; e_{body}]_a &::= x := [e]_a; \dots ; [e_{body}]_a & [v]_a &::= \text{arr}_a \lambda \_. v \\
[x \ e]_a &::= [(e, \langle \rangle)]_a \ggg_a x & [\langle e_1, e_2 \rangle]_a &::= [e_1]_a \&\&a [e_2]_a \\
[\text{let } e \text{ } e_{body}]_a &::= ([e]_a \&\&a (\text{arr}_a \text{id})) \ggg_a [e_{body}]_a & [\text{fst } e]_a &::= [e]_a \ggg_a (\text{arr}_a \text{fst}) \\
[\text{env } 0]_a &::= \text{arr}_a \text{fst} & [\text{snd } e]_a &::= [e]_a \ggg_a (\text{arr}_a \text{snd}) \\
[\text{env } (n + 1)]_a &::= \text{arr}_a \text{snd} \ggg_a [\text{env } n]_a & [\text{if } e_c \ e_t \ e_f]_a &::= \text{ifte}_a [e_c]_a (\text{lazy}_a \lambda 0. [e_t]_a) (\text{lazy}_a \lambda 0. [e_f]_a)
\end{array}$$

$$\begin{array}{l}
x \rightsquigarrow_{\perp} y ::= x \Rightarrow y_{\perp} \\
\text{arr}_{\perp} : (x \Rightarrow y) \Rightarrow (x \rightsquigarrow_{\perp} y) \\
\text{arr}_{\perp} f := f \\
(\ggg_{\perp}) : (x \rightsquigarrow_{\perp} y) \Rightarrow (y \rightsquigarrow_{\perp} z) \Rightarrow (x \rightsquigarrow_{\perp} z) \\
(f_1 \ggg_{\perp} f_2) a := \text{if } (f_1 a = \perp) \perp (f_2 (f_1 a)) \\
(\lll_{\perp}) : (x \rightsquigarrow_{\perp} y_1) \Rightarrow (x \rightsquigarrow_{\perp} y_2) \Rightarrow (x \rightsquigarrow_{\perp} \langle y_1, y_2 \rangle) \\
(f_1 \lll_{\perp} f_2) a := \text{if } (f_1 a = \perp \text{ or } f_2 a = \perp) \perp \langle f_1 a, f_2 a \rangle \\
\text{ifte}_{\perp} : (x \rightsquigarrow_{\perp} \text{Bool}) \Rightarrow (x \rightsquigarrow_{\perp} y) \Rightarrow (x \rightsquigarrow_{\perp} y) \Rightarrow (x \rightsquigarrow_{\perp} y) \\
\text{ifte}_{\perp} f_1 f_2 f_3 a := \text{case } f_1 a \\
\qquad \text{true} \Rightarrow f_2 a \\
\qquad \text{false} \Rightarrow f_3 a \\
\qquad \text{else} \Rightarrow \perp \\
\text{lazy}_{\perp} : (1 \Rightarrow (x \rightsquigarrow_{\perp} y)) \Rightarrow (x \rightsquigarrow_{\perp} y) \\
\text{lazy}_{\perp} f a := f \ 0 \ a
\end{array}$$

$$\begin{aligned}
X_{\text{map}} \rightsquigarrow Y &::= \text{Set } X \Rightarrow (X \multimap Y) \\
\text{arr}_{\text{map}} : (X \Rightarrow Y) &\Rightarrow (X \rightsquigarrow_{\text{map}} Y) \\
\text{arr}_{\text{map}} &:= \text{lift}_{\text{map}} \circ \text{arr}_{\perp} \\
(\ggg_{\text{map}}) : (X \rightsquigarrow_{\text{map}} Y) &\Rightarrow (Y \rightsquigarrow_{\text{map}} Z) \Rightarrow (X \rightsquigarrow_{\text{map}} Z) \\
(g_1 \ggg_{\text{map}} g_2) A &:= \text{let } g'_1 := g_1 A \\
&\quad g'_2 := g_2 (\text{range } g'_1) \\
&\quad \text{in } g'_2 \circ_{\text{map}} g'_1 \\
(\&\&\&_{\text{map}}) : (X \rightsquigarrow_{\text{map}} Y_1) &\Rightarrow (X \rightsquigarrow_{\text{map}} Y_2) \Rightarrow (X \rightsquigarrow_{\text{map}} \langle Y_1, Y_2 \rangle) \\
(g_1 \&\&\&_{\text{map}} g_2) A &:= \langle g_1 A, g_2 A \rangle_{\text{map}} \\
\text{ifte}_{\text{map}} : (X \rightsquigarrow_{\text{map}} \text{Bool}) &\Rightarrow (X \rightsquigarrow_{\text{map}} Y) \Rightarrow (X \rightsquigarrow_{\text{map}} Y) \\
\text{ifte}_{\text{map}} g_1 g_2 g_3 A &:= \text{let } g'_1 := g_1 A \\
&\quad g'_2 := g_2 (\text{preimage } g'_1 \{\text{true}\}) \\
&\quad g'_3 := g_3 (\text{preimage } g'_1 \{\text{false}\}) \\
&\quad \text{in } g'_2 \uplus_{\text{map}} g'_3 \\
\text{lazy}_{\text{map}} : (1 \Rightarrow (X \rightsquigarrow_{\text{map}} Y)) &\Rightarrow (X \rightsquigarrow_{\text{map}} Y) \\
\text{lazy}_{\text{map}} g A &:= \text{if } (A = \emptyset) \emptyset (g \ 0 \ A)
\end{aligned}$$


---


$$\begin{aligned}
\text{lift}_{\text{map}} : (X \rightsquigarrow_{\perp} Y) &\Rightarrow (X \rightsquigarrow_{\text{map}} Y) \\
\text{lift}_{\text{map}} f A &:= \{ \langle a, b \rangle \in \text{mapping } f \ A \mid b \neq \perp \}
\end{aligned}$$

## 4.2 Case: Pairing

$$\begin{aligned}
& \text{lift}_{\text{map}} (f_1 \text{ } \text{or}_{\perp} \text{ } f_2) A \\
& \equiv \text{lift}_{\text{map}} (\lambda a. \text{if } (f_1 a = \perp \text{ or } f_2 a = \perp) \perp \langle f_1 a, f_2 a \rangle) A \\
& \equiv \text{let } f := \lambda a. \text{if } (f_1 a = \perp \text{ or } f_2 a = \perp) \perp \langle f_1 a, f_2 a \rangle \\
& \quad \text{in mapping } f (\text{domain}_{\perp} f A)
\end{aligned} \tag{23}$$

$$\begin{aligned}
& \text{lift}_{\text{map}} \ (f_1 \ \&\&\&\_ \ f_2) \ A \\
& \equiv \text{let } A_1 := (\text{domain}_{\perp} \ f_1 \ A) \\
& \quad A_2 := (\text{domain}_{\perp} \ f_2 \ A) \\
& \quad A' := A_1 \cap A_2 \\
& \quad \text{in } \lambda a \in A'. \langle f_1 \ a, f_2 \ a \rangle \\
& \equiv \text{let } g_1 := \text{lift}_{\text{map}} \ f_1 \ A \\
& \quad g_2 := \text{lift}_{\text{map}} \ f_2 \ A \\
& \quad A' := (\text{domain } g_1) \cap (\text{domain } g_2) \\
& \quad \text{in } \lambda a \in A'. \langle g_1 \ a, g_2 \ a \rangle \\
& \equiv \langle \text{lift}_{\text{map}} \ f_1 \ A, \text{lift}_{\text{map}} \ f_2 \ A \rangle_{\text{map}} \tag{24}
\end{aligned}$$

### 4.3 Case: Composition

The derivation of  $(\ggg)_{\text{map}}$  is similar to that of  $(\&\&\&)_{\text{map}}$  but a little more involved.

XXX: include it?

### 4.4 Case: Conditional

Starting with the left side of (17), we expand definitions, and simplify  $f$  by restricting it to a domain for which  $f_1 a \neq \perp$ :

$$\begin{aligned}
& \text{lift}_{\text{map}} (\text{ifte}_{\perp} f_1 f_2 f_3) A \\
& \equiv \text{let } f := \lambda a. \text{case } f_1 a \\
& \quad \text{true} \implies f_2 a \\
& \quad \text{false} \implies f_3 a \\
& \quad \text{else} \implies \perp \\
& \text{in mapping } f (\text{domain}_{\perp} f A) \\
& \equiv \text{let } g_1 := \text{mapping } f A \\
& \quad A_2 := \text{preimage } g_1 \{\text{true}\} \\
& \quad A_3 := \text{preimage } g_1 \{\text{false}\} \\
& \quad f := \lambda a. \text{if } (f_1 a) (f_2 a) (f_3 a) \\
& \text{in mapping } f (\text{domain}_{\perp} f (A_2 \uplus A_3))
\end{aligned} \tag{25}$$

We finish by converting bottom arrow computations to the mapping arrow and rewriting in terms of  $(\uplus)_{\text{map}}$ :

$$\begin{aligned}
& \text{lift}_{\text{map}} (\text{ifte}_{\perp} f_1 f_2 f_3) A \\
& \equiv \text{let } g_1 := \text{lift}_{\text{map}} f_1 A \\
& \quad g_2 := \text{lift}_{\text{map}} f_2 (\text{preimage } g_1 \{\text{true}\}) \\
& \quad g_3 := \text{lift}_{\text{map}} f_3 (\text{preimage } g_1 \{\text{false}\}) \\
& \quad A' := (\text{domain } g_2) \uplus (\text{domain } g_3) \\
& \text{in } \lambda a \in A'. \text{if } (a \in \text{domain } g_2) (g_2 a) (g_3 a) \\
& \equiv \text{let } g_1 := \text{lift}_{\text{map}} f_1 A \\
& \quad g_2 := \text{lift}_{\text{map}} f_2 (\text{preimage } g_1 \{\text{true}\}) \\
& \quad g_3 := \text{lift}_{\text{map}} f_3 (\text{preimage } g_1 \{\text{false}\}) \\
& \text{in } g_2 \uplus_{\text{map}} g_3
\end{aligned} \tag{26}$$

Substituting  $g_1$  for  $\text{lift}_{\text{map}} f_1$ ,  $g_2$  for  $\text{lift}_{\text{map}} f_2$ , and  $g_3$  for  $\text{lift}_{\text{map}} f_3$  gives a definition for  $\text{ifte}_{\text{map}}$  (Figure 4) for which (17) holds.

### 4.5 Case: Laziness

Starting with the left side of (18), we first expand definitions:

$$\begin{aligned}
& \text{lift}_{\text{map}} (\text{lazy}_{\perp} f) A \\
& \equiv \text{let } A' := \text{domain}_{\perp} (\lambda a. f 0 a) A \\
& \text{in mapping } (\lambda a. f 0 a) A'
\end{aligned}$$

$\lambda_{\text{ZFC}}$  does not have an  $\eta$  rule (i.e.  $\lambda x. e x \neq e$  because  $e$  may diverge), but we can use weaker facts. If  $A \neq \emptyset$ , then  $\text{domain}_{\perp} (\lambda a. f 0 a) A \equiv \text{domain}_{\perp} (f 0) A$ . Further, it diverges iff  $f 0$  diverges, and iff  $\text{mapping } (f 0) A'$  diverges. Therefore, if  $A \neq \emptyset$ , we can replace  $\lambda a. f 0 a$  with  $f 0$ . If  $A = \emptyset$ , then  $\text{lift}_{\text{map}} (\text{lazy}_{\perp} f) A = \emptyset$  (the empty mapping), so

$$\begin{aligned}
& \text{lift}_{\text{map}} (\text{lazy}_{\perp} f) A \\
& \equiv \text{if } (A = \emptyset) \emptyset (\text{mapping } (f 0) (\text{domain}_{\perp} (f 0) A)) \\
& \equiv \text{if } (A = \emptyset) \emptyset (\text{lift}_{\text{map}} (f 0) A)
\end{aligned}$$

Substituting  $g 0$  for  $\text{lift}_{\text{map}} (f 0)$  gives a definition for  $\text{lazy}_{\text{map}}$  (Figure 4) for which (18) holds.

### 4.6 Correctness

**Theorem 4.3** (mapping arrow correctness). *lift<sub>map</sub> is an arrow homomorphism.*

*Proof.* By construction.  $\square$

**Corollary 4.4** (semantic correctness). *If  $\llbracket e \rrbracket_{\perp} : X \rightsquigarrow_{\perp} Y$ , then  $\text{lift}_{\text{map}} \llbracket e \rrbracket_{\perp} \equiv \llbracket e \rrbracket_{\text{map}}$  and  $\llbracket e \rrbracket_{\text{map}} : X \rightsquigarrow_{\text{map}} Y$ .*

## 5. Lazy Preimage Mappings

On a computer, we will not often have the luxury of testing each function input to see whether it belongs to a preimage set. Even for finite domains, doing so is often intractable.

If we wish to compute with infinite sets in the language implementation, we will need an abstraction that makes it easy to replace computation on points with computation on sets. Therefore, in the preimage arrow, we will confine computation on points to *lazy preimage mappings*, or just *preimage mappings*. Further on, we will need their ranges to be observable, so we define their type as

$$X \xrightarrow{\text{pre}} Y ::= \langle \text{Set } Y, \text{Set } Y \Rightarrow \text{Set } X \rangle \tag{27}$$

Converting a mapping to a lazy preimage mapping:

$$\begin{aligned}
& \text{pre} : (X \rightarrow Y) \Rightarrow (X \xrightarrow{\text{pre}} Y) \\
& \text{pre } g := \text{let } Y' := \text{range } g \\
& \quad p := \lambda B. \text{preimage } g B \\
& \text{in } \langle Y', p \rangle
\end{aligned} \tag{28}$$

Applying a preimage mapping to any subset of its codomain:

$$\begin{aligned}
& \text{pre-ap} : (X \xrightarrow{\text{pre}} Y) \Rightarrow \text{Set } Y \Rightarrow \text{Set } X \\
& \text{pre-ap } \langle Y', p \rangle B := p (B \cap Y')
\end{aligned} \tag{29}$$

The necessary property here is that using **pre-ap** to compute preimages is the same as computing them from a mapping using **preimage**.

**Lemma 5.1.** *Let  $g \in X \rightarrow Y$ . For all  $B \subseteq Y$  and  $Y'$  such that  $\text{range } g \subseteq Y' \subseteq Y$ ,  $\text{preimage } g (B \cap Y') = \text{preimage } g B$ .*

**Theorem 5.2** (pre-ap computes preimages). *Let  $g \in X \rightarrow Y$ . For all  $B \subseteq Y$ ,  $\text{pre-ap } (\text{pre } g) B = \text{preimage } g B$ .*

*Proof.* Expand definitions and apply Lemma 5.1 with  $Y' = \text{range } g$ .  $\square$

Figure 5 defines more operations on preimage mappings, including pairing, composition, and disjoint union operations corresponding to the mapping operations in Figure 1. The next three theorems establish that **pre** is a homomorphism (though not an arrow homomorphism): it distributes over mapping operations to yield preimage mapping operations. We will use these facts to derive the preimage arrow from the mapping arrow.

First, we need a new notion of equivalence.

**Definition 5.3.** *Two preimage mappings  $h_1 : X \xrightarrow{\text{pre}} Y$  and  $h_2 : X \xrightarrow{\text{pre}} Y$  are equivalent, or  $h_1 \equiv h_2$ , when  $\text{pre-ap } h_1 B = \text{pre-ap } h_2 B$  for all  $B \subseteq Y$ .*

XXX: define equivalence in terms of equivalence, check observational equivalence in the proofs (specifically divergence)

### 5.1 Preimage Mapping Pairing

XXX: moar wurd in this section

**Lemma 5.4** (preimage distributes over  $\langle \cdot, \cdot \rangle_{\text{map}}$  and  $(\times)$ ). *Let  $g_1 \in X \rightarrow Y_1$  and  $g_2 \in X \rightarrow Y_2$ . For all  $B_1 \subseteq Y_1$  and  $B_2 \subseteq Y_2$ ,  $\text{preimage } \langle g_1, g_2 \rangle_{\text{map}} (B_1 \times B_2) = (\text{preimage } g_1 B_1) \cap (\text{preimage } g_2 B_2)$ .*

**Theorem 5.5** (pre distributes over  $\langle \cdot, \cdot \rangle_{\text{map}}$ ). *Let  $g_1 \in X \rightarrow Y_1$  and  $g_2 \in X \rightarrow Y_2$ . Then  $\text{pre } \langle g_1, g_2 \rangle_{\text{map}} \equiv \langle \text{pre } g_1, \text{pre } g_2 \rangle_{\text{pre}}$ .*

$$\begin{array}{ll}
X \xrightarrow{\text{pre}} Y ::= \langle \text{Set } Y, \text{Set } Y \Rightarrow \text{Set } X \rangle & \langle \cdot, \cdot \rangle_{\text{pre}} : (X \xrightarrow{\text{pre}} Y_1) \Rightarrow (X \xrightarrow{\text{pre}} Y_2) \Rightarrow (X \xrightarrow{\text{pre}} Y_1 \times Y_2) \\
\text{pre} : (X \xrightarrow{\text{map}} Y) \Rightarrow (X \xrightarrow{\text{pre}} Y) & \langle \langle Y'_1, p_1 \rangle, \langle Y'_2, p_2 \rangle \rangle_{\text{pre}} := \text{let } Y' := Y'_1 \times Y'_2 \\
\text{pre } g := \langle \text{range } g, \lambda B. \text{preimage } g \ B \rangle & \quad p := \lambda B. \bigcup_{\langle b_1, b_2 \rangle \in B} (p_1 \{b_1\}) \cap (p_2 \{b_2\}) \\
& \quad \text{in } \langle Y', p \rangle \\
\text{pre-ap} : (X \xrightarrow{\text{pre}} Y) \Rightarrow \text{Set } Y \Rightarrow \text{Set } X & (\circ_{\text{pre}}) : (Y \xrightarrow{\text{pre}} Z) \Rightarrow (X \xrightarrow{\text{pre}} Y) \Rightarrow (X \xrightarrow{\text{pre}} Z) \\
\text{pre-ap } \langle Y', p \rangle \ B := p \ (B \cap Y') & \langle Z', p_2 \rangle \circ_{\text{pre}} h_1 := \langle Z', \lambda C. \text{pre-ap } h_1 \ (p_2 \ C) \rangle \\
\text{pre-range} : (X \xrightarrow{\text{pre}} Y) \Rightarrow \text{Set } Y & (\uplus_{\text{pre}}) : (X \xrightarrow{\text{pre}} Y) \Rightarrow (X \xrightarrow{\text{pre}} Y) \Rightarrow (X \xrightarrow{\text{pre}} Y) \\
\text{pre-range} := \text{fst} & h_1 \uplus_{\text{pre}} h_2 := \text{let } Y' := (\text{pre-range } h_1) \cup (\text{pre-range } h_2) \\
& \quad p := \lambda B. (\text{pre-ap } h_1 \ B) \uplus (\text{pre-ap } h_2 \ B) \\
& \quad \text{in } \langle Y', p \rangle
\end{array}$$

Figure 5: Lazy preimage mappings and operations.

*Proof.* Let  $\langle Y'_1, p_1 \rangle := \text{pre } g_1$  and  $\langle Y'_2, p_2 \rangle := \text{pre } g_2$ . Starting from the right side, for all  $B \in Y_1 \times Y_2$ ,

$$\begin{aligned}
& \text{pre-ap } \langle \text{pre } g_1, \text{pre } g_2 \rangle_{\text{pre}} B \\
&= \text{let } Y' := Y'_1 \times Y'_2 \\
& \quad p := \lambda B. \bigcup_{\langle y_1, y_2 \rangle \in B} (p_1 \{y_1\}) \cap (p_2 \{y_2\}) \\
& \quad \text{in } p \ (B \cap Y') \\
&= \bigcup_{\langle y_1, y_2 \rangle \in B \cap (Y'_1 \times Y'_2)} (p_1 \{y_1\}) \cap (p_2 \{y_2\}) \\
&= \bigcup_{\langle y_1, y_2 \rangle \in B \cap (Y'_1 \times Y'_2)} (\text{preimage } g_1 \{y_1\}) \cap (\text{preimage } g_2 \{y_2\}) \\
&= \bigcup_{y \in B \cap (Y'_1 \times Y'_2)} (\text{preimage } \langle g_1, g_2 \rangle_{\text{map}} \{y\}) \\
&= \text{preimage } \langle g_1, g_2 \rangle_{\text{map}} (B \cap (Y'_1 \times Y'_2)) \\
&= \text{preimage } \langle g_1, g_2 \rangle_{\text{map}} B \\
&= \text{pre-ap } (\text{pre } \langle g_1, g_2 \rangle_{\text{map}}) B
\end{aligned}$$

□

## 5.2 Preimage Mapping Composition

XXX: moar wurd in this section

**Lemma 5.6** (preimage distributes over  $(\circ_{\text{map}})$ ). *Let  $g_1 \in X \rightarrow Y$  and  $g_2 \in Y \rightarrow Z$ . For all  $C \subseteq Z$ ,  $\text{preimage } (g_2 \circ_{\text{map}} g_1) \ C = \text{preimage } g_1 \ (\text{preimage } g_2 \ C)$ .*

**Theorem 5.7** (pre distributes over  $(\circ_{\text{map}})$ ). *Let  $g_1 \in X \rightarrow Y$  and  $g_2 \in Y \rightarrow Z$ . Then  $\text{pre } (g_2 \circ_{\text{map}} g_1) \equiv (\text{pre } g_2) \circ_{\text{pre}} (\text{pre } g_1)$ .*

*Proof.* Let  $\langle Z', p_2 \rangle := \text{pre } g_2$ . Starting from the right side, for all  $C \subseteq Z$ ,

$$\begin{aligned}
& \text{pre-ap } ((\text{pre } g_2) \circ_{\text{pre}} (\text{pre } g_1)) \ C \\
&= \text{let } h := \lambda C. \text{pre-ap } (\text{pre } g_1) \ (p_2 \ C) \\
& \quad \text{in } h \ (C \cap Z') \\
&= \text{pre-ap } (\text{pre } g_1) \ (p_2 \ (C \cap Z')) \\
&= \text{pre-ap } (\text{pre } g_1) \ (\text{pre-ap } (\text{pre } g_2) \ C) \\
&= \text{preimage } g_1 \ (\text{preimage } g_2 \ C) \\
&= \text{preimage } (g_2 \circ_{\text{map}} g_1) \ C \\
&= \text{pre-ap } (\text{pre } (g_2 \circ_{\text{map}} g_1)) \ C
\end{aligned}$$

□

## 5.3 Preimage Mapping Disjoint Union

XXX: moar wurd in this section

**Lemma 5.8** (preimage distributes over  $(\uplus_{\text{map}})$ ). *Let  $g_1 \in X \rightarrow Y$  and  $g_2 \in X \rightarrow Y$  be disjoint mappings. For all  $B \subseteq Y$ ,  $\text{preimage } (g_1 \uplus_{\text{map}} g_2) \ B = (\text{preimage } g_1 \ B) \uplus (\text{preimage } g_2 \ B)$ .*

**Theorem 5.9** (pre distributes over  $(\uplus_{\text{map}})$ ). *Let  $g_1 \in X \rightarrow Y$  and  $g_2 \in X \rightarrow Y$  have disjoint domains. Then  $\text{pre } (g_1 \uplus_{\text{map}} g_2) \equiv (\text{pre } g_1) \uplus_{\text{pre}} (\text{pre } g_2)$ .*

*Proof.* Let  $Y'_1 := \text{range } g_1$  and  $Y'_2 := \text{range } g_2$ . Starting from the right side, for all  $B \subseteq Y$ ,

$$\begin{aligned}
& \text{pre-ap } ((\text{pre } g_1) \uplus_{\text{pre}} (\text{pre } g_2)) \ B \\
&= \text{let } Y' := Y'_1 \cup Y'_2 \\
& \quad h := \lambda B. (\text{pre-ap } (\text{pre } g_1) \ B) \uplus (\text{pre-ap } (\text{pre } g_2) \ B) \\
& \quad \text{in } h \ (B \cap Y') \\
&= (\text{pre-ap } (\text{pre } g_1) \ (B \cap (Y'_1 \cup Y'_2))) \uplus \\
& \quad (\text{pre-ap } (\text{pre } g_2) \ (B \cap (Y'_1 \cup Y'_2))) \\
&= (\text{preimage } g_1 \ (B \cap (Y'_1 \cup Y'_2))) \uplus \\
& \quad (\text{preimage } g_2 \ (B \cap (Y'_1 \cup Y'_2))) \\
&= \text{preimage } (g_1 \uplus_{\text{map}} g_2) \ (B \cap (Y'_1 \cup Y'_2)) \\
&= \text{preimage } (g_1 \uplus_{\text{map}} g_2) \ B \\
&= \text{pre-ap } (\text{pre } (g_1 \uplus_{\text{map}} g_2)) \ B
\end{aligned}$$

□

## 6. Deriving the Preimage Arrow

XXX: intro

$$X \xrightarrow{\text{pre}} Y ::= \text{Set } X \Rightarrow (X \xrightarrow{\text{pre}} Y) \quad (30)$$

$$\begin{aligned}
& \text{lift}_{\text{pre}} : (X \xrightarrow{\text{map}} Y) \Rightarrow (X \xrightarrow{\text{pre}} Y) \\
& \text{lift}_{\text{pre}} \ g \ A := \text{pre } (g \ A)
\end{aligned} \quad (31)$$

**Definition 6.1** (Preimage arrow equivalence). *Two preimage arrow computations  $h_1 : X \xrightarrow{\text{pre}} Y$  and  $h_2 : X \xrightarrow{\text{pre}} Y$  are equivalent, or  $h_1 \equiv h_2$ , when  $h_1 \ A \equiv h_2 \ A$  for all  $A \subseteq X$ .*

As with  $\text{arr}_{\text{map}}$ , defining  $\text{arr}_{\text{pre}}$  as a composition meets (14). The following subsections derive  $(\&\&_{\text{pre}})$ ,  $(\ggg_{\text{pre}})$ ,  $\text{ifte}_{\text{pre}}$  and  $\text{lazy}_{\text{pre}}$  from their corresponding mapping arrow combinators,

$$\begin{array}{ll}
X \rightsquigarrow_{\text{pre}} Y ::= \text{Set } X \Rightarrow (X \rightrightarrows_{\text{pre}} Y) & \text{ifte}_{\text{pre}} : (X \rightsquigarrow_{\text{pre}} \text{Bool}) \Rightarrow (X \rightsquigarrow_{\text{pre}} Y) \Rightarrow (X \rightsquigarrow_{\text{pre}} Y) \Rightarrow (X \rightsquigarrow_{\text{pre}} Y) \\
\text{arr}_{\text{pre}} : (X \Rightarrow Y) \Rightarrow (X \rightsquigarrow_{\text{pre}} Y) & \text{ifte}_{\text{pre}} h_1 h_2 h_3 A := \text{let } h'_1 := h_1 A \\
\text{arr}_{\text{pre}} := \text{lift}_{\text{pre}} \circ \text{arr}_{\text{map}} & \quad h'_2 := h_2 (\text{pre-ap } h'_1 \{\text{true}\}) \\
& \quad h'_3 := h_3 (\text{pre-ap } h'_1 \{\text{false}\}) \\
& \quad \text{in } h'_2 \uplus_{\text{pre}} h'_3 \\
(\ggg_{\text{pre}}) : (X \rightsquigarrow_{\text{pre}} Y) \Rightarrow (Y \rightsquigarrow_{\text{pre}} Z) \Rightarrow (X \rightsquigarrow_{\text{pre}} Z) & \text{lazy}_{\text{pre}} : (1 \Rightarrow (X \rightsquigarrow_{\text{pre}} Y)) \Rightarrow (X \rightsquigarrow_{\text{pre}} Y) \\
(h_1 \ggg_{\text{pre}} h_2) A := \text{let } h'_1 := h_1 A & \text{lazy}_{\text{pre}} h A := \text{if } (A = \emptyset) (\text{pre } \emptyset) (h \ 0 \ A) \\
\quad h'_2 := h_2 (\text{pre-range } h'_1) & \\
\quad \text{in } h'_2 \circ_{\text{pre}} h'_1 & \\
(\lll_{\text{pre}}) : (X \rightsquigarrow_{\text{pre}} Y) \Rightarrow (X \rightsquigarrow_{\text{pre}} Z) \Rightarrow (X \rightsquigarrow_{\text{pre}} Y \times Z) & \\
(h_1 \lll_{\text{pre}} h_2) A := \langle h_1 A, h_2 A \rangle_{\text{pre}} & \\
\end{array}$$


---

Figure 6: Preimage arrow definitions.

in a way that ensures  $\text{lift}_{\text{pre}}$  is an arrow homomorphism from the mapping arrow to the preimage arrow. Figure 6 contains the resulting definitions.

### 6.1 Case: Pairing

Starting with the left side of (16), we expand definitions, apply Theorem 5.5, and rewrite in terms of  $\text{lift}_{\text{pre}}$ :

$$\begin{aligned}
& \text{pre-ap } (\text{lift}_{\text{pre}} (g_1 \lll_{\text{map}} g_2) A) B \\
& \equiv \text{pre-ap } (\text{pre } \langle g_1 A, g_2 A \rangle_{\text{map}}) B \\
& \equiv \text{pre-ap } \langle \text{pre } (g_1 A), \text{pre } (g_2 A) \rangle_{\text{pre}} B \\
& \equiv \text{pre-ap } \langle \text{lift}_{\text{pre}} g_1 A, \text{lift}_{\text{pre}} g_2 A \rangle_{\text{pre}} B
\end{aligned}$$

Substituting  $h_1$  for  $\text{lift}_{\text{pre}} g_1$  and  $h_2$  for  $\text{lift}_{\text{pre}} g_2$ , and removing the application of  $\text{pre-ap}$  from both sides of the equivalence gives a definition of  $(\lll_{\text{pre}})$  (Figure 6) for which (16) holds.

### 6.2 Case: Composition

Starting with the left side of (15), we expand definitions, apply Theorem 5.7 and rewrite in terms of  $\text{lift}_{\text{pre}}$ :

$$\begin{aligned}
& \text{pre-ap } (\text{lift}_{\text{pre}} (g_1 \ggg_{\text{map}} g_2) A) C \\
& \equiv \text{let } g'_1 := g_1 A \\
& \quad g'_2 := g_2 (\text{range } g'_1) \\
& \quad \text{in pre-ap } (\text{pre } (g'_2 \circ_{\text{map}} g'_1)) C \\
& \equiv \text{let } g'_1 := g_1 A \\
& \quad g'_2 := g_2 (\text{range } g'_1) \\
& \quad \text{in pre-ap } ((\text{pre } g'_1) \circ_{\text{pre}} (\text{pre } g'_2)) C \\
& \equiv \text{let } h_1 := \text{lift}_{\text{pre}} g_1 A \\
& \quad h_2 := \text{lift}_{\text{pre}} g_2 (\text{pre-range } h_1) \\
& \quad \text{in pre-ap } (h_2 \circ_{\text{pre}} h_1) C
\end{aligned} \tag{32}$$

Substituting  $h_1$  for  $\text{lift}_{\text{pre}} g_1$  and  $h_2$  for  $\text{lift}_{\text{pre}} g_2$ , and removing the application of  $\text{pre-ap}$  from both sides of the equivalence gives a definition of  $(\ggg_{\text{pre}})$  (Figure 6) for which (15) holds.

### 6.3 Case: Conditional

Starting with the left side of (17), we expand terms, apply Theorem 5.9, rewrite in terms of  $\text{lift}_{\text{pre}}$ , and apply Theo-

rem 5.2 in the definitions of  $h_2$  and  $h_3$ :

$$\begin{aligned}
& \text{pre-ap } (\text{lift}_{\text{pre}} (\text{ifte}_{\text{map}} g_1 g_2 g_3) A) B \\
& \equiv \text{let } g'_1 := g_1 A \\
& \quad g'_2 := g_2 (\text{preimage } g'_1 \{\text{true}\}) \\
& \quad g'_3 := g_3 (\text{preimage } g'_1 \{\text{false}\}) \\
& \quad \text{in pre-ap } (\text{pre } (g'_2 \uplus_{\text{map}} g'_3)) B \\
& \equiv \text{let } g'_1 := g_1 A \\
& \quad g'_2 := g_2 (\text{preimage } g'_1 \{\text{true}\}) \\
& \quad g'_3 := g_3 (\text{preimage } g'_1 \{\text{false}\}) \\
& \quad \text{in pre-ap } ((\text{pre } g'_2) \uplus_{\text{pre}} (\text{pre } g'_3)) B \\
& \equiv \text{let } h_1 := \text{lift}_{\text{pre}} g_1 A \\
& \quad h_2 := \text{lift}_{\text{pre}} g_2 (\text{pre-ap } h_1 \{\text{true}\}) \\
& \quad h_3 := \text{lift}_{\text{pre}} g_3 (\text{pre-ap } h_1 \{\text{false}\}) \\
& \quad \text{in pre-ap } (h_2 \uplus_{\text{pre}} h_3) B
\end{aligned}$$

Substituting  $h_1$  for  $\text{lift}_{\text{pre}} g_1$ ,  $h_2$  for  $\text{lift}_{\text{pre}} g_2$  and  $h_3$  for  $\text{lift}_{\text{pre}} g_3$ , and removing the application of  $\text{pre-ap}$  from both sides of the equivalence gives a definition of  $\text{ifte}_{\text{pre}}$  (Figure 6) for which (17) holds.

### 6.4 Case: Laziness

Starting with the left side of (18), expand definitions, distribute  $\text{pre}$  over the branches of  $\text{if}$ , and rewrite in terms of  $\text{lift}_{\text{pre}} (g \ 0)$ :

$$\begin{aligned}
& \text{pre-ap } (\text{lift}_{\text{pre}} (\text{lazy}_{\text{map}} g) A) B \\
& \equiv \text{let } g' := \text{if } (A = \emptyset) \emptyset (g \ 0 \ A) \\
& \quad \text{in pre-ap } (\text{pre } g') B \\
& \equiv \text{let } h := \text{if } (A = \emptyset) (\text{pre } \emptyset) (\text{pre } (g \ 0 \ A)) \\
& \quad \text{in pre-ap } h B \\
& \equiv \text{let } h := \text{if } (A = \emptyset) (\text{pre } \emptyset) (\text{lift}_{\text{pre}} (g \ 0) A) \\
& \quad \text{in pre-ap } h B
\end{aligned}$$

Substituting  $h \ 0$  for  $\text{lift}_{\text{pre}} (g \ 0)$  and removing the application of  $\text{pre-ap}$  from both sides of the equivalence gives a definition for  $\text{lazy}_{\text{pre}}$  (Figure 6) for which (18) holds.

### 6.5 Correctness

**Theorem 6.2** (preimage arrow correctness).  *$\text{lift}_{\text{pre}}$  is an arrow homomorphism.*

*Proof.* By construction.  $\square$

**Corollary 6.3** (semantic correctness). *If  $\llbracket e \rrbracket_{\text{map}} : X \rightsquigarrow_{\text{map}} Y$ , then  $\text{lift}_{\text{pre}} \llbracket e \rrbracket_{\text{map}} \equiv \llbracket e \rrbracket_{\text{pre}}$  and  $\llbracket e \rrbracket_{\text{pre}} : X \rightsquigarrow_{\text{pre}} Y$ .*



In particular,  $\llbracket e \rrbracket_{\text{pre}}$  correctly computes preimages under the interpretation of  $e$  as a function from a random source.

## 7. Preimages Under Partial Functions

Probabilistic functions that may diverge, but converge with probability 1, are common. They come up not only when practitioners want to build data with random size or structure, but in simpler circumstances as well.

Suppose `random` retrieves a number  $r \in [0, 1]$  from a uniform random source  $r$ . The following recursive function, which defines the well-known **geometric distribution** with parameter  $p$ , counts the number of times `random`  $< p$  is false:

$$\text{geometric } p := \text{if } (\text{random} < p) \ 0 \ (1 + \text{geometric } p) \quad (33)$$

For any  $p > 0$ , `geometric`  $p$  may diverge, but the probability of always taking the false branch is  $(1 - p) \times (1 - p) \times (1 - p) \times \dots = 0$ . Divergence with probability 0 simply does not happen in practice.

Suppose we interpret (33) as  $h : R \rightsquigarrow \mathbb{N}$ , a preimage arrow computation from random sources in  $R$  to natural numbers, and that we have a probability measure  $P \in \mathcal{P} R \rightarrow [0, 1]$ . We could compute the probability of any output set  $N \subseteq \mathbb{N}$  using  $P(h R' N)$ , where  $R' \subseteq R$  and  $P R' = 1$ . We have three hurdles to overcome:

1. Ensuring  $h R'$  converges.
2. Ensuring each  $r \in R$  contains enough random numbers.
3. Determining how `random` indexes numbers in  $r$ .

Ensuring  $h R'$  converges is the most difficult, but doing the other two will provide structure that makes it much easier.

### 7.1 Threading and Indexing

We clearly need a new arrow that threads a random source through its computations. To ensure it contains enough random numbers, the source should be infinite.

In a pure  $\lambda$ -calculus, random sources are typically infinite streams, threaded monadically: each computation receives and produces a random source. A new combinator is defined that removes the head of the random source and passes the tail along. This is likely preferred because pseudorandom number generators are almost universally monadic.

A little-used alternative is for the random source to be a tree, threaded applicatively: each computation receives, but does not produce, a random source. Multi-argument combinators split the tree and pass sub-trees to sub-computations.

We have tried both ways with arrows defined using pairing. The resulting definitions are large, making them conceptually difficult and hard to manipulate. Fortunately, assigning each sub-computation a unique index into a tree-shaped random source, and passing it unchanged, is relatively easy.

We need a way to assign unique indexes to expressions.

**Definition 7.1** (binary indexing scheme). *Let  $J$  be an index set,  $j_0 \in J$  a distinguished element, and  $\text{left} : J \Rightarrow J$  and  $\text{right} : J \Rightarrow J$  be total functions. These define a **binary indexing scheme** if*

- Every finite composition next of `left` and `right` is injective.
- For all  $j \in J$ ,  $j = \text{next } j_0$  for some finite composition next.

For example, let  $J$  be the set of lists of  $\{0, 1\}$ ,  $j_0 := \langle \rangle$ , and  $\text{left } j := \langle 0, j \rangle$  and  $\text{right } j := \langle 1, j \rangle$ .

Alternatively, let  $J$  be the set of dyadic rationals in  $(0, 1)$  (i.e. those with power-of-two denominators),  $j_0 := \frac{1}{2}$  and

$$\begin{aligned} \text{left } (p/q) &:= (p - \frac{1}{2})/q \\ \text{right } (p/q) &:= (p + \frac{1}{2})/q \end{aligned} \quad (34)$$

With this alternative, left-to-right evaluation order can be made to correspond with the natural order ( $<$ ) over  $J$ .

In any case,  $J$  is always countable.

### 7.2 Applicative, Associative Store

**XXX: arrow transformer:** an arrow whose combinators are defined entirely in terms of another arrow

**XXX:** computations receive an index and return an arrow from a store of type  $s$  paired with  $x$ , to  $y$ :

$$\text{AStore } s \ (x \rightsquigarrow_a y) ::= J \Rightarrow (\langle s, x \rangle \rightsquigarrow_a y) \quad (35)$$

**XXX:** motivational words for definition of lift:

$$\begin{aligned} \eta_{a^*} : (x \rightsquigarrow_a y) &\Rightarrow \text{AStore } s \ (x \rightsquigarrow_a y) \\ \eta_{a^*} f \ j &:= \text{arr}_a \text{snd} \ggg_a f \end{aligned} \quad (36)$$

Figure 7 defines the `AStore` arrow transformer. As with the other arrows, proving that its lift is a homomorphism allows us to prove that programs interpreted as its computations are correct. Again, to do so, we need to extend equivalence to be more extensional for arrows `AStore`  $s \ (x \rightsquigarrow_a y)$ .

**Definition 7.2** (`AStore` arrow equivalence). *Two `AStore` arrow computations  $k_1$  and  $k_2$  are equivalent, or  $k_1 \equiv k_2$ , when  $k_1 \ j \equiv k_2 \ j$  for all  $j \in J$ .*

**XXX:** need to define equivalence for the bottom arrow for this to make sense

**Theorem 7.3** (`AStore` arrow correctness). *Let  $x \rightsquigarrow_{a^*} y ::= \text{AStore } s \ (x \rightsquigarrow_a y)$ . Then  $\eta_{a^*}$  is an arrow homomorphism.*

*Proof.* Defining  $\text{arr}_{a^*}$  as a composition clearly meets the first homomorphism identity (14).

*Composition.* Starting with the right side of (15), expand definitions and use  $(\text{arr}_a f \ \&\&\&_a f_1) \ggg_a \text{arr}_a \text{snd} \equiv f_1$ :

$$\begin{aligned} (\eta_{a^*} f_1 \ggg_{a^*} \eta_{a^*} f_2) \ j & \\ \equiv (\text{arr}_a \text{fst} \ \&\&\&_a (\text{arr}_a \text{snd} \ggg_a f_1)) \ggg_a \text{arr}_a \text{snd} \ggg_a f_2 & \\ \equiv \text{arr}_a \text{snd} \ggg_a f_1 \ggg_a f_2 & \\ \equiv \eta_{a^*} (f_1 \ggg_a f_2) \ j & \end{aligned}$$

*Pairing.* Starting with the right side of (16), expand definitions and use the arrow law  $\text{arr}_a f \ggg_a (f_1 \ \&\&\&_a f_2) \equiv (\text{arr}_a f \ggg_a f_1) \ \&\&\&_a (\text{arr}_a f \ggg_a f_2)$ :

$$\begin{aligned} (\eta_{a^*} f_1 \ \&\&\&_{a^*} \eta_{a^*} f_2) \ j & \\ \equiv (\text{arr}_a \text{snd} \ggg_a f_1) \ \&\&\&_a (\text{arr}_a \text{snd} \ggg_a f_2) & \\ \equiv \text{arr}_a \text{snd} \ggg_a (f_1 \ \&\&\&_a f_2) & \\ \equiv \eta_{a^*} (f_1 \ \&\&\&_a f_2) \ j & \end{aligned}$$

*Conditional.* Starting with the right side of (17), expand definitions and use the arrow law  $\text{arr}_a f \ggg_a \text{ifte}_a f_1 f_2 f_3 \equiv \text{ifte}_a (\text{arr}_a f \ggg_a f_1) (\text{arr}_a f \ggg_a f_2) (\text{arr}_a f \ggg_a f_3)$ :

$$\begin{aligned} (\text{ifte}_{a^*} (\eta_{a^*} f_1) (\eta_{a^*} f_2) (\eta_{a^*} f_3)) \ j & \\ \equiv \text{ifte}_a (\text{arr}_a \text{snd} \ggg_a f_1) & \\ \quad (\text{arr}_a \text{snd} \ggg_a f_2) & \\ \quad (\text{arr}_a \text{snd} \ggg_a f_3) & \\ \equiv \text{arr}_a \text{snd} \ggg_a (\text{ifte } f_1 f_2 f_3) & \\ \equiv \eta_{a^*} (\text{ifte } f_1 f_2 f_3) \ j & \end{aligned}$$

$$\begin{array}{ll}
x \rightsquigarrow_{a^*} y ::= \text{AStore } s \ (x \rightsquigarrow_a y) ::= J \Rightarrow (\langle s, x \rangle \rightsquigarrow_a y) & \text{ifte}_{a^*} : (x \rightsquigarrow_{a^*} \text{Bool}) \Rightarrow (x \rightsquigarrow_{a^*} y) \Rightarrow (x \rightsquigarrow_{a^*} y) \Rightarrow (x \rightsquigarrow_{a^*} y) \\
\text{arr}_{a^*} : (x \Rightarrow y) \Rightarrow (x \rightsquigarrow_{a^*} y) & \text{ifte}_{a^*} \ k_1 \ k_2 \ k_3 \ j := \text{ifte}_a \ (k_1 \ (\text{left } j)) \\
\text{arr}_{a^*} := \eta_{a^*} \circ \text{arr}_a & \quad (k_2 \ (\text{left } (\text{right } j))) \\
& \quad (k_3 \ (\text{right } (\text{right } j))) \\
(\ggg_{a^*}) : (x \rightsquigarrow_{a^*} y) \Rightarrow (y \rightsquigarrow_{a^*} z) \Rightarrow (x \rightsquigarrow_{a^*} z) & \text{lazy}_{a^*} : (1 \Rightarrow (x \rightsquigarrow_{a^*} y)) \Rightarrow (x \rightsquigarrow_{a^*} y) \\
(k_1 \ggg_{a^*} k_2) \ j := & \text{lazy}_{a^*} \ k \ j := \text{lazy}_a \ \lambda 0. k \ 0 \ j \\
(\text{arr}_a \text{ fst } \&\&\&_a \ k_1 \ (\text{left } j)) \ggg_{a^*} k_2 \ (\text{right } j) & \\
(\&\&\&_{a^*}) : (x \rightsquigarrow_{a^*} y_1) \Rightarrow (x \rightsquigarrow_{a^*} y_2) \Rightarrow (x \rightsquigarrow_{a^*} \langle y_1, y_2 \rangle) & \\
(k_1 \&\&\&_{a^*} k_2) \ j := k_1 \ (\text{left } j) \&\&\&_a k_2 \ (\text{right } j) & \\
\eta_{a^*} : (x \rightsquigarrow_a y) \Rightarrow (x \rightsquigarrow_{a^*} y) & \\
\eta_{a^*} \ f \ j := \text{arr}_a \ \text{snd} \ \ggg_{a^*} \ f &
\end{array}$$

Figure 7: AStore (associative store) arrow transformer definitions.

*Laziness.* Starting with the right side of (18), expand definitions,  $\beta$ -expand within the outer thunk, and use the arrow law  $\text{arr}_a \ f \ \ggg_a \ \text{lazy}_a \ f_1 \equiv \text{lazy}_a \ \lambda 0. \text{arr}_a \ f \ \ggg_a \ f_1 \ 0$ :

$$\begin{aligned}
& (\text{lazy}_{a^*} \ \lambda 0. \eta_{a^*} \ (f \ 0)) \ j \\
& \equiv \text{lazy}_a \ \lambda 0. (\lambda 0. \lambda j. \text{arr}_a \ \text{snd} \ \ggg_a \ f \ 0) \ 0 \ j \\
& \equiv \text{lazy}_a \ \lambda 0. \text{arr}_a \ \text{snd} \ \ggg_a \ f \ 0 \\
& \equiv \text{arr}_a \ \text{snd} \ \ggg_a \ \text{lazy}_a \ f \\
& \equiv \eta_{a^*} \ (\text{lazy}_a \ f) \ j
\end{aligned}$$

XXX: all of these rely on arrow laws that aren't proved for the mapping and preimage arrows  $\square$

**Corollary 7.4** (semantic correctness). *Let  $x \rightsquigarrow_{a^*} y ::= \text{AStore } s \ (x \rightsquigarrow_a y)$ . If  $\llbracket e \rrbracket_a : x \rightsquigarrow_a y$ , then  $\eta_{a^*} \llbracket e \rrbracket_a \equiv \llbracket e \rrbracket_{a^*}$  and  $\llbracket e \rrbracket_{a^*} : x \rightsquigarrow_{a^*} y$ .*

In particular, Corollary 7.4 implies that, if a pure let-calculus expression is interpreted as a computation  $k : \text{AStore } S \ (X \rightsquigarrow_{\text{pre}} Y)$ , then  $k \ j_0$  correctly computes preimages. We still need to know that preimages under functions that access the store are computed correctly, which we will get to after defining stores and combinators that access them.

### 7.3 Probabilistic Programs

**Definition 7.5** (random source). *Let  $R := J \rightarrow [0, 1]$ . A **random source** is a total mapping  $r \in R$ ; equivalently, an infinite vector of random numbers indexed by  $J$ .*

Let  $x \rightsquigarrow_{a^*} y ::= \text{AStore } R \ (x \rightsquigarrow_a y)$ . The following combinator returns the number at its own index in the random source:

$$\begin{aligned}
\text{random}_{a^*} : x \rightsquigarrow_{a^*} [0, 1] \\
\text{random}_{a^*} \ j := \text{arr}_a \ (\text{fst} \ \ggg \ \pi \ j)
\end{aligned} \tag{37}$$

We extend the let-calculus semantic function with

$$\llbracket \text{random} \rrbracket_{a^*} := \text{random}_{a^*} \tag{38}$$

for arrows  $a^*$  for which  $\text{random}_{a^*}$  is defined.

### 7.4 Partial Programs

The most effective and ultimately implementable way we have found to avoid divergence in computing preimages is to use the store to dictate which branch of each conditional, if any, is allowed to be taken.

**Definition 7.6** (branch trace). A **branch trace** is a total mapping (i.e. vector)  $t \in J \rightarrow \text{Bool}_\perp$  such that  $t \ j = \text{true}$  or  $t \ j = \text{false}$  for no more than finitely many  $j \in J$ .

Let  $T \subset J \rightarrow \text{Bool}_\perp$  be the set of all branch traces, and  $x \rightsquigarrow_{a^*} y ::= \text{AStore } T \ (x \rightsquigarrow_a y)$ . The following combinator returns  $t \ j$  using its own index  $j$ :

$$\begin{aligned}
\text{branch}_{a^*} : x \rightsquigarrow_{a^*} \text{Bool} \\
\text{branch}_{a^*} \ j := \text{arr}_a \ (\text{fst} \ \ggg \ \pi \ j)
\end{aligned} \tag{39}$$

Using  $\text{branch}_{a^*}$ , we define an additional if-then-else combinator, which ensures its conditional expression agrees with the branch trace:

$$\begin{aligned}
\text{agrees} : \langle \text{Bool}, \text{Bool} \rangle \Rightarrow \text{Bool}_\perp \\
\text{agrees} \ \langle b_1, b_2 \rangle := \text{if } (b_1 = b_2) \ b_1 \ \perp
\end{aligned} \tag{40}$$

$$\begin{aligned}
\text{ifte}'_{a^*} : (x \rightsquigarrow_{a^*} \text{Bool}) \Rightarrow (x \rightsquigarrow_{a^*} y) \Rightarrow (x \rightsquigarrow_{a^*} y) \Rightarrow (x \rightsquigarrow_{a^*} y) \\
\text{ifte}'_{a^*} \ k_1 \ k_2 \ k_3 := \\
\text{ifte}_{a^*} \ ((k_1 \&\&\&_{a^*} \text{branch}_{a^*}) \ggg_{a^*} \text{arr}_{a^*} \ \text{agrees}) \ k_2 \ k_3
\end{aligned} \tag{41}$$

If the branch trace agrees with the conditional expression, it computes a branch; otherwise, it returns an error.

Every computation defined using the let-calculus semantic function  $\llbracket \cdot \rrbracket_a$ , whose *defining expression* converges, must have its recurrences guarded by an if. Thus, if we stick to well-defined let-calculus programs, we need only replace  $\text{ifte}_{a^*}$  with  $\text{ifte}'_{a^*}$  to ensure *computations* always converge. Therefore, we can define a semantic function  $\llbracket \cdot \rrbracket'_{a^*}$  for let-calculus programs whose computations always converge by overriding only the if rule:

$$\begin{aligned}
\llbracket \text{if } e_c \ e_t \ e_f \rrbracket'_{a^*} &:: \equiv \text{ifte}'_{a^*} \ \llbracket e_c \rrbracket'_{a^*} \\
&\quad (\text{lazy}_a \ \lambda 0. \llbracket e_t \rrbracket'_{a^*}) \\
&\quad (\text{lazy}_a \ \lambda 0. \llbracket e_f \rrbracket'_{a^*}) \\
\llbracket e \rrbracket'_{a^*} &:: \equiv \llbracket e \rrbracket_{a^*}
\end{aligned} \tag{42}$$

### 7.5 Partial, Probabilistic Programs

Let  $S ::= R \times T$  and  $x \rightsquigarrow_{a^*} y ::= \text{AStore } S \ (x \rightsquigarrow_a y)$ , and update the  $\text{random}_{a^*}$  and  $\text{branch}_{a^*}$  combinators to reflect

that the store is now a pair:

$$\begin{aligned} \text{random}_{a^*} &: x \rightsquigarrow_{a^*} [0, 1] \\ \text{random}_{a^*} j &:= \text{arr}_a (\text{fst} \gg \text{fst} \gg \pi j) \end{aligned} \quad (43)$$

$$\begin{aligned} \text{branch}_{a^*} &: x \rightsquigarrow_{a^*} \text{Bool} \\ \text{branch}_{a^*} j &:= \text{arr}_a (\text{fst} \gg \text{snd} \gg \pi j) \end{aligned} \quad (44)$$

The  $\text{ifte}'_{a^*}$  combinator's definition remains the same.

From here on, let  $x \rightsquigarrow_{\perp^*} y ::= \text{AStore } S (x \rightsquigarrow_{\perp} y)$ ; similarly for  $X \rightsquigarrow_{\text{map}^*} Y$  and  $X \rightsquigarrow_{\text{pre}^*} Y$ .

## 7.6 Correctness

**Theorem 7.7** (natural transformation). *Let  $x \rightsquigarrow_{a^*} y ::= \text{AStore } s (x \rightsquigarrow_a y)$  and  $x \rightsquigarrow_{b^*} y ::= \text{AStore } s (x \rightsquigarrow_b y)$ . Let  $\text{lift}_b : (x \rightsquigarrow_a y) \Rightarrow (x \rightsquigarrow_b y)$  be an arrow homomorphism, and*

$$\begin{aligned} \text{lift}_{b^*} &: (x \rightsquigarrow_{a^*} y) \Rightarrow (x \rightsquigarrow_{b^*} y) \\ \text{lift}_{b^*} f j &:= \text{lift}_b (f j) \end{aligned} \quad (45)$$

The following diagram commutes:

$$\begin{array}{ccc} x \rightsquigarrow_a y & \xrightarrow{\text{lift}_b} & x \rightsquigarrow_b y \\ \eta_{a^*} \downarrow & & \downarrow \eta_{b^*} \\ x \rightsquigarrow_{a^*} y & \xrightarrow{\text{lift}_{b^*}} & x \rightsquigarrow_{b^*} y \end{array} \quad (46)$$

i.e. for all  $f : x \rightsquigarrow_a y$ ,  $\eta_{b^*} (\text{lift}_b f) \equiv \text{lift}_{b^*} (\eta_{a^*} f)$ . Further,  $\text{lift}_{b^*}$  is an arrow homomorphism.

*Proof.* Starting from the right side of the equivalence, expand definitions and apply homomorphism identities (15) and (14) for  $\text{lift}_b$ :

$$\begin{aligned} \text{lift}_{b^*} (\eta_{a^*} f) &\equiv \lambda j. \text{lift}_b (\text{arr}_a \text{snd} \gg \gg_a f) \\ &\equiv \lambda j. \text{lift}_b (\text{arr}_a \text{snd}) \gg \gg_b \text{lift}_b f \\ &\equiv \lambda j. \text{arr}_b \text{snd} \gg \gg_b \text{lift}_b f \\ &\equiv \eta_{b^*} (\text{lift}_b f) \end{aligned}$$

Further, because  $\eta_{a^*}$ ,  $\eta_{b^*}$ , and  $\text{lift}_b$  are homomorphisms,  $\text{lift}_{b^*}$  is a homomorphism by composition.

XXX: not sure I'm allowed to invoke converse of composition of homomorphisms without extra conditions  $\square$

**Corollary 7.8** (mapping\* and preimage\* arrow correctness). *The following diagram commutes:*

$$\begin{array}{ccccc} X \rightsquigarrow_{\perp} Y & \xrightarrow{\text{lift}_{\text{map}}} & X \rightsquigarrow_{\text{map}} Y & \xrightarrow{\text{lift}_{\text{pre}}} & X \rightsquigarrow_{\text{pre}} Y \\ \eta_{\perp^*} \downarrow & & \downarrow \eta_{\text{map}^*} & & \downarrow \eta_{\text{pre}^*} \\ X \rightsquigarrow_{\perp^*} Y & \xrightarrow{\text{lift}_{\text{map}^*}} & X \rightsquigarrow_{\text{map}^*} Y & \xrightarrow{\text{lift}_{\text{pre}^*}} & X \rightsquigarrow_{\text{pre}^*} Y \end{array} \quad (47)$$

Further,  $\text{lift}_{\text{map}^*}$  and  $\text{lift}_{\text{pre}^*}$  are arrow homomorphisms.

**Corollary 7.9** (semantic correctness). *If  $\llbracket e \rrbracket_{\perp^*} : X \rightsquigarrow_{\perp^*} Y$ , then  $\text{lift}_{\text{map}^*} \llbracket e \rrbracket_{\perp^*} \equiv \llbracket e \rrbracket_{\text{map}^*}$  and  $\text{lift}_{\text{pre}^*} \llbracket e \rrbracket_{\text{map}^*} \equiv \llbracket e \rrbracket_{\text{pre}^*}$ .*

**Corollary 7.10** (semantic' correctness). *If  $\llbracket e \rrbracket'_{\perp^*} : X \rightsquigarrow_{\perp^*} Y$ , then  $\text{lift}_{\text{map}^*} \llbracket e \rrbracket'_{\perp^*} \equiv \llbracket e \rrbracket'_{\text{map}^*}$  and  $\text{lift}_{\text{pre}^*} \llbracket e \rrbracket'_{\text{map}^*} \equiv \llbracket e \rrbracket'_{\text{pre}^*}$ .*

In particular,  $\llbracket e \rrbracket_{\text{pre}^*}$  and  $\llbracket e \rrbracket'_{\text{pre}^*}$  correctly compute preimages under the interpretation of  $e$  as a function from an implicit random source. We will make stronger statements about  $\llbracket \cdot \rrbracket'_{\text{pre}^*}$  after proving its computations always converge.

**Theorem 7.11** (divergence implies error). *Let  $f := \llbracket e \rrbracket_{\perp^*}$  and  $f' := \llbracket e \rrbracket'_{\perp^*}$  converge, where  $f : x \rightsquigarrow_{\perp^*} y$ . For all  $r \in R$ ,  $t \in T$  and  $a : x$ ,*

1. *If  $f \langle \langle r, t \rangle, a \rangle = b$ , then  $f' \langle \langle r, t' \rangle, a \rangle = b$  for some  $t' \in T$ .*
2. *If  $f \langle \langle r, t \rangle, a \rangle$  diverges,  $f' \langle \langle r, t' \rangle, a \rangle = \perp$  for all  $t' \in T$ .*

*Proof.* Let  $m : J \Rightarrow J$  invertibly map sub-computation indexes in  $f'$  to corresponding sub-computation indexes in  $f$ . (Defining  $m$  formally is tedious and unilluminating. XXX: check this)

*Case 1.* Define  $t' \in J \rightarrow \text{Bool}_{\perp}$  such that  $t' j = z$  if the sub-computation with index  $m j$  in  $f$  is an if condition that returns  $z$ , otherwise  $t' j = \perp$ . Because  $f \langle \langle r, t \rangle, a \rangle$  converges,  $t' j \neq \perp$  for at most finitely many  $j$ , so  $t' \in T$ . Exists  $t'$ .

*Case 2.* Let  $t' \in T$ . There exists an infinite suffix  $J' \subset J$  closed under left and right, such that for all  $j' \in J'$ ,  $t' j' = \perp$ . Because  $f \langle \langle r, t \rangle, a \rangle$  diverges, the indexes of its if conditions are unbounded; there is therefore a condition with index  $j$  such that  $m^{-1} j \in J'$ . It returns  $\perp$ , so  $f' \langle \langle r, t' \rangle, a \rangle = \perp$ .  $\square$

To compare preimages computed by arrow instances produced by  $\llbracket \cdot \rrbracket_{\text{pre}^*}$  and  $\llbracket \cdot \rrbracket'_{\text{pre}^*}$ , we need a set of inputs on which they should obviously always agree.

**Definition 7.12** (halting set). *A computation's halting set is the largest  $A^* \subseteq (R \times T) \times X$  for which*

- *For  $f : X \rightsquigarrow_{\perp^*} Y$ ,  $f j_0 x \neq \perp$  for all  $x \in A^*$ .*
- *For  $g : X \rightsquigarrow_{\text{map}^*} Y$ ,  $\text{domain } (g j_0 A^*) = A^*$ .*
- *For  $h : X \rightsquigarrow_{\text{pre}^*} Y$ ,  $\text{pre-ap } (h j_0 A^*) Y = A^*$ .*

Recall truth statements like  $f j_0 x \neq \perp$  imply convergence.

That  $\text{lift}_{\text{map}^*}$  and  $\text{lift}_{\text{pre}^*}$  are arrow homomorphisms allows transporting halting set definitions and theorems between arrow types.

**Theorem 7.13** (halting set equality). *Let  $f : X \rightsquigarrow_{\perp^*} Y$ , and  $g : X \rightsquigarrow_{\text{map}^*} Y$  and  $h : X \rightsquigarrow_{\text{pre}^*} Y$  such that  $g \equiv \text{lift}_{\text{map}^*} f$  and  $h \equiv \text{lift}_{\text{pre}^*} g$ . Then  $f$ ,  $g$  and  $h$  have the same halting set.*

*Proof.* XXX: do this  $\square$

**Corollary 7.14** (computed halting set). *Let  $\llbracket e \rrbracket_{\perp^*} : X \rightsquigarrow_{\perp^*} Y$  converge. Then  $A^* = \text{pre-ap } (\llbracket e \rrbracket'_{\text{pre}^*} j_0 (S \times X)) Y$ .*

**Corollary 7.15** (semantic correctness (final)). *Let  $\llbracket e \rrbracket_{\perp^*} : X \rightsquigarrow_{\perp^*} Y$  converge, with halting set  $A^*$ . For  $A \subseteq X$  and  $B \subseteq Y$ ,  $\text{pre-ap } (\llbracket e \rrbracket'_{\text{pre}^*} j_0 A) B = \text{preimage } (\llbracket e \rrbracket_{\text{map}^*} j_0 (A \cap A^*)) B$ .*

In other words, preimages computed using  $\llbracket \cdot \rrbracket'_{\text{pre}^*}$  always converge, never include inputs that give rise to errors or divergence, and are correct.

## 8. Measurability

We have not assigned probabilities to any sets yet.

Recall that, for a mapping  $g : X \rightarrow Y$ , the probability of an output set  $B \subseteq Y$  is

$$P (\text{preimage } g B) \quad (48)$$

where  $P \in \mathcal{P} X \rightarrow [0, 1]$  is a probability measure on  $X$ . This was the motivation for defining arrows to compute preimages in the first place. Note again that  $P$  is a *partial* function. We had left domain  $P$ , and which  $B \subseteq Y$  have preimages in domain  $P$ , as technical conditions to be proved later. Now we determine those conditions.

To save space, we assume readers are familiar with either topology or measure theory. (Readers unfamiliar with both

may wish to skip to the next section.) Many concepts in measure theory can be understood by analogy to topology.

The analogue of a topology is a  $\sigma$ -algebra.

**Definition 8.1** ( $\sigma$ -algebra, measurable set). *A collection of sets  $\mathcal{A} \subseteq \mathcal{P} X$  is called a  $\sigma$ -algebra on  $X$  if it contains  $X$  and is closed under complements and countable unions. The sets in  $\mathcal{A}$  are called **measurable sets**.*

$X \setminus X = \emptyset$ , so  $\emptyset \in \mathcal{A}$ . Additionally, it follows from De Morgan's law that  $\mathcal{A}$  is closed under countable intersections.

The analogue of continuity is measurability.

**Definition 8.2** (measurable mapping). *Let  $\mathcal{A}$  and  $\mathcal{B}$  be  $\sigma$ -algebras respectively on  $X$  and  $Y$ . A mapping  $g : X \rightarrow Y$  is  **$\mathcal{A}$ - $\mathcal{B}$ -measurable** if for all  $B \in \mathcal{B}$ ,  $\text{preimage } g B \in \mathcal{A}$ .*

Measurability is usually a weaker condition than continuity. For example, with respect to the  $\sigma$ -algebra generated from  $\mathbb{R}$ 's standard topology, measurable  $\mathbb{R} \rightarrow \mathbb{R}$  functions may have countably many discontinuities. Likewise, real equality and inequality functions are measurable.

Product spaces are defined the same way as in topology.

**Definition 8.3** (finite product  $\sigma$ -algebra). *Let  $\mathcal{A}_1$  and  $\mathcal{A}_2$  be  $\sigma$ -algebras on  $X_1$  and  $X_2$ , and  $X := \langle X_1, X_2 \rangle$ . The **product  $\sigma$ -algebra**  $\mathcal{A}_1 \otimes \mathcal{A}_2$  is the smallest  $\sigma$ -algebra for which mapping  $\text{fst } X$  and mapping  $\text{snd } X$  are measurable.*

**Definition 8.4** (arbitrary product  $\sigma$ -algebra). *Let  $\mathcal{A}$  be a  $\sigma$ -algebra on  $X$ . The **product  $\sigma$ -algebra**  $\mathcal{A}^{\otimes J}$  is the smallest  $\sigma$ -algebra for which, for all  $j \in J$ , mapping  $(\pi j) (J \rightarrow X)$  is measurable.*

## 8.1 Measurable Pure Computations

It is easier to prove measurability of pure computations than to prove measurability of probabilistic ones. Further, we can use the resulting theorems to prove that probabilistic computations are measurable.

A single mapping arrow computation can produce many mappings, which, it seems, could complicate proving measurability. Fortunately, we need only consider the mapping produced when applying a computation to its halting set.

**Definition 8.5** (halting set). *Let  $g : X \xrightarrow{\text{map}} Y$ . Its **halting set** is the largest  $A^* \subseteq X$  for which  $\text{domain } (g A^*) = A^*$ .*

**Definition 8.6** (measurable mapping arrow computation). *Let  $\mathcal{A}$  and  $\mathcal{B}$  be  $\sigma$ -algebras on  $X$  and  $Y$ . A computation  $g : X \xrightarrow{\text{map}} Y$  is  **$\mathcal{A}$ - $\mathcal{B}$ -measurable** if  $g A^*$  is an  $\mathcal{A}$ - $\mathcal{B}$ -measurable mapping, where  $A^*$  is  $g$ 's halting set.*

The definition of halting set implies  $\text{preimage } (g A^*) Y = A^*$ . Because  $Y \in \mathcal{B}$ ,  $A^* \in \mathcal{A}$ .

**Lemma 8.7.** *Let  $g : X \rightarrow Y$  be an  $\mathcal{A}$ - $\mathcal{B}$ -measurable mapping. For any  $A \in \mathcal{A}$ , restrict  $g A$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable.*

**Theorem 8.8.** *Let  $g : X \xrightarrow{\text{map}} Y$  be an  $\mathcal{A}$ - $\mathcal{B}$ -measurable mapping arrow computation. Then for all  $A \in \mathcal{A}$ ,  $g A$  is an  $\mathcal{A}$ - $\mathcal{B}$ -measurable mapping.*

*Proof.* Use the mapping arrow restriction law (20) and Lemma 8.7.  $\square$

Roughly, if the largest mapping that can be produced by a computation is measurable, any mapping it can produce that we care about is measurable.

That all programs interpreted by  $\llbracket \cdot \rrbracket_a$  are measurable will be proved by structural induction. We therefore need a case for each arrow combinator.

### 8.1.1 Case: Composition

Proving compositions are measurable takes the most work. The main complication is that, under measurable mappings, while *preimages* of measurable sets are measurable, *images* of measurable sets may not be. We need the following four extra theorems to get around this.

**Lemma 8.9** (images of preimages). *Let  $g : X \rightarrow Y$  and  $B \subseteq Y$ . Then  $\text{image } g (\text{preimage } g B) \subseteq B$ .*

**Lemma 8.10** (expanded post-composition). *Let  $g_1 : X \rightarrow Y$  and  $g_2 : Y \rightarrow Z$  such that  $\text{range } g_1 \subseteq \text{domain } g_2$ , and let  $g'_2 : Y \rightarrow Z$  such that  $g_2 \subseteq g'_2$ . Then  $g_2 \circ_{\text{map}} g_1 = g'_2 \circ_{\text{map}} g_1$ .*

**Theorem 8.11** (mapping arrow monotonicity). *Let  $g : X \xrightarrow{\text{map}} Y$ . For any  $A \subseteq X$ ,  $\text{domain } (g A) \subseteq A$ . For any  $A' \subseteq A$ ,  $g A' \subseteq g A$ .*

**Theorem 8.12** (halting subsets). *Let  $g : X \xrightarrow{\text{map}} Y$  with halting set  $A^*$ . For any  $A \subseteq A^*$ ,  $\text{domain } (g A) = A$ .*

*Proof.* Use the mapping arrow restriction law (20).  $\square$

Now we can prove measurability.

**Lemma 8.13** (measurability under  $\circ_{\text{map}}$ ). *If  $g_1 : X \rightarrow Y$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable and  $g_2 : Y \rightarrow Z$  is  $\mathcal{B}$ - $\mathcal{C}$ -measurable, then  $g_2 \circ_{\text{map}} g_1$  is  $\mathcal{A}$ - $\mathcal{C}$ -measurable.*

**Theorem 8.14** (measurability under  $(\ggg_{\text{map}})$ ). *If  $g_1 : X \xrightarrow{\text{map}} Y$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable and  $g_2 : Y \xrightarrow{\text{map}} Z$  is  $\mathcal{B}$ - $\mathcal{C}$ -measurable, then  $g_1 \ggg_{\text{map}} g_2$  is  $\mathcal{A}$ - $\mathcal{C}$ -measurable.*

*Proof.* Let  $A^* \in \mathcal{A}$  and  $B^* \in \mathcal{B}$  be respectively  $g_1$ 's and  $g_2$ 's halting sets. The halting set of  $g_1 \ggg_{\text{map}} g_2$  is  $A^{**} := \text{preimage } (g_1 A^*) B^*$ , which is in  $\mathcal{A}$ . By definition,

$$(g_1 \ggg_{\text{map}} g_2) A^{**} = \text{let } \begin{array}{l} g'_1 := g_1 A^{**} \\ g'_2 := g_2 (\text{range } g'_1) \end{array} \text{ in } g'_2 \circ_{\text{map}} g'_1 \quad (49)$$

By Theorem 8.8,  $g'_1$  is an  $\mathcal{A}$ - $\mathcal{B}$ -measurable mapping. Unfortunately,  $g'_2$  may not be  $\mathcal{B}$ - $\mathcal{C}$ -measurable when  $\text{range } g'_1 \notin \mathcal{B}$ .

Let  $g''_2 := g_2 B^*$ , which is a  $\mathcal{B}$ - $\mathcal{C}$ -measurable mapping. By Lemma 8.13,  $g''_2 \circ_{\text{map}} g'_1$  is  $\mathcal{A}$ - $\mathcal{C}$ -measurable. We need only show that  $g'_2 \circ_{\text{map}} g'_1 = g''_2 \circ_{\text{map}} g'_1$ , which by Lemma 8.10 is true if  $\text{range } g'_1 \subseteq \text{domain } g'_2$  and  $g'_2 \subseteq g''_2$ .

By Theorem 8.12,  $A^{**} \subseteq A^*$  implies  $\text{domain } g'_1 = A^{**}$ . By Theorem 8.11 and Lemma 8.9,

$$\begin{aligned} \text{range } g'_1 &= \text{image } (g_1 A^{**}) (\text{preimage } (g_1 A^*) B^*) \\ &= \text{image } (g_1 A^*) (\text{preimage } (g_1 A^*) B^*) \\ &\subseteq B^* \end{aligned}$$

$\text{range } g'_1 \subseteq B^*$  implies (by Theorem 8.12) that  $\text{domain } g'_2 = \text{range } g'_1$ , and (by Theorem 8.11) that  $g'_2 \subseteq g''_2$ .  $\square$

### 8.1.2 Case: Pairing

**Lemma 8.15** (measurability under  $\langle \cdot, \cdot \rangle_{\text{map}}$ ). *If  $g_1 : X \rightarrow Y_1$  is  $\mathcal{A}$ - $\mathcal{B}_1$ -measurable and  $g_2 : X \rightarrow Y_2$  is  $\mathcal{A}$ - $\mathcal{B}_2$ -measurable, then  $\langle g_1, g_2 \rangle_{\text{map}}$  is  $\mathcal{A}$ - $(\mathcal{B}_1 \otimes \mathcal{B}_2)$ -measurable.*

**Theorem 8.16** (measurability under  $(\&\&_{\text{map}})$ ). *If  $g_1 : X \xrightarrow{\text{map}} Y_1$  is  $\mathcal{A}$ - $\mathcal{B}_1$ -measurable and  $g_2 : X \xrightarrow{\text{map}} Y_2$  is  $\mathcal{A}$ - $\mathcal{B}_2$ -measurable, then  $g_1 \&\&_{\text{map}} g_2$  is  $\mathcal{A}$ - $(\mathcal{B}_1 \otimes \mathcal{B}_2)$ -measurable.*

*Proof.* Let  $A_1^*$  and  $A_2^*$  be respectively  $g_1$ 's and  $g_2$ 's halting sets. The halting set of  $g_1 \&\&_{\text{map}} g_2$  is  $A^{**} := A_1^* \cap A_2^*$ , which is in  $\mathcal{A}$ . By definition,  $(g_1 \&\&_{\text{map}} g_2) A^{**} = \langle g_1 A^{**}, g_2 A^{**} \rangle_{\text{map}}$ , which by Lemma 8.15 is  $\mathcal{A}$ - $(\mathcal{B}_1 \otimes \mathcal{B}_2)$ -measurable.  $\square$

### 8.1.3 Case: Conditional

**Lemma 8.17** (measurability under  $\uplus_{\text{map}}$ ). *If  $g_1 : X \rightarrow Y$  and  $g_2 : X \rightarrow Y$  are  $\mathcal{A}$ - $\mathcal{B}$ -measurable and have disjoint domains,  $g_1 \uplus_{\text{map}} g_2$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable.*

**Theorem 8.18** (measurability under  $\text{ifte}_{\text{map}}$ ). *If  $g_1 : X \xrightarrow{\sim}_{\text{map}} \text{Bool}$  is  $\mathcal{A}$ -( $\mathcal{P} \text{ Bool}$ )-measurable, and  $g_2 : X \xrightarrow{\sim}_{\text{map}} Y$  and  $g_3 : X \xrightarrow{\sim}_{\text{map}} Y$  are  $\mathcal{A}$ - $\mathcal{B}$ -measurable, then  $\text{ifte}_{\text{map}} g_1 g_2 g_3$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable.*

*Proof.* Let  $\mathcal{A}_1^*$ ,  $\mathcal{A}_2^*$  and  $\mathcal{A}_3^*$  be respectively  $g_1$ 's,  $g_2$ 's and  $g_3$ 's halting sets. The halting set of  $\text{ifte}_{\text{map}} g_1 g_2 g_3$  is defined by

$$\begin{aligned} \mathcal{A}_2^{**} &:= \mathcal{A}_2^* \cap \text{preimage}(g_1 \mathcal{A}_1^*) \{\text{true}\} \\ \mathcal{A}_3^{**} &:= \mathcal{A}_3^* \cap \text{preimage}(g_1 \mathcal{A}_1^*) \{\text{false}\} \\ \mathcal{A}^{**} &:= \mathcal{A}_2^{**} \uplus \mathcal{A}_3^{**} \end{aligned} \quad (50)$$

Because  $\text{preimage}(g_1 \mathcal{A}_1^*) B \in \mathcal{A}$  for any  $B \subseteq \text{Bool}$ ,  $\mathcal{A}^{**} \in \mathcal{A}$ . By definition,

$$\begin{aligned} \text{ifte}_{\text{map}} g_1 g_2 g_3 \mathcal{A}^{**} &= \text{let } g'_1 := g_1 \mathcal{A}^{**} \\ &\quad g'_2 := g_2 (\text{preimage } g'_1 \{\text{true}\}) \\ &\quad g'_3 := g_3 (\text{preimage } g'_1 \{\text{false}\}) \\ &\quad \text{in } g'_2 \uplus_{\text{map}} g'_3 \end{aligned} \quad (51)$$

By hypothesis,  $g'_1$ ,  $g'_2$  and  $g'_3$  are measurable mappings, and the mapping arrow restriction law (20) implies  $g'_2$  and  $g'_3$  have disjoint domains. Apply Lemma 8.17.  $\square$

### 8.1.4 Case: Laziness

**Lemma 8.19** (measurability of  $\emptyset$ ). *For any  $\sigma$ -algebras  $\mathcal{A}$  and  $\mathcal{B}$ , the empty mapping  $\emptyset$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable.*

**Theorem 8.20** (measurability under  $\text{lazy}_{\text{map}}$ ). *Let  $g : 1 \rightarrow (X \xrightarrow{\sim}_{\text{map}} Y)$ . If  $g \ 0$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable, then  $\text{lazy}_{\text{map}} g$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable.*

*Proof.* The halting set  $\mathcal{A}^{**}$  of  $\text{lazy}_{\text{map}} g$  is the same as that of  $g \ 0$ . By definition,

$$\text{lazy}_{\text{map}} g \mathcal{A}^{**} = \text{if } (\mathcal{A}^{**} = \emptyset) \emptyset (g \ 0 \mathcal{A}^{**}) \quad (52)$$

If  $\mathcal{A}^{**} = \emptyset$ , then  $\text{lazy}_{\text{map}} g \mathcal{A}^{**} = \emptyset$ ; apply Lemma 8.19. If  $\mathcal{A}^{**} \neq \emptyset$ , then  $\text{lazy}_{\text{map}} g = g \ 0$ , which is  $\mathcal{A}$ - $\mathcal{B}$ -measurable.  $\square$

## 8.2 Measurable Probabilistic Computations

We are now prepared to lift the previous theorems to probabilistic computations.

**Definition 8.21** (measurable mapping\* arrow computation). *Let  $\mathcal{A}$  and  $\mathcal{B}$  be  $\sigma$ -algebras on  $(R \times T) \times X$  and  $Y$ . A computation  $g : X \xrightarrow{\sim}_{\text{map}^*} Y$  is  $\mathcal{A}$ - $\mathcal{B}$ -measurable if  $g \ j_0 \mathcal{A}^*$  is an  $\mathcal{A}$ - $\mathcal{B}$ -measurable mapping, where  $\mathcal{A}^*$  is  $g$ 's halting set.*

To make general measurability statements about computations, whether they have flat or product types, it helps to have a notion of a standard  $\sigma$ -algebra.

**Definition 8.22** (standard  $\sigma$ -algebra). *For a set  $X$  used as a type,  $\Sigma X$  denotes its standard  $\sigma$ -algebra, which must be defined under the following constraints:*

$$\Sigma \langle X_1, X_2 \rangle = \Sigma X_1 \otimes \Sigma X_2 \quad (53)$$

$$\Sigma (J \rightarrow X) = (\Sigma X)^{\otimes J} \quad (54)$$

$$|X| \leq \omega \implies \Sigma X = \mathcal{P} X \quad (55)$$

$$X' \in \Sigma X \implies \Sigma X' = \{X' \cap A \mid A \in \Sigma X\} \quad (56)$$

The predicate “is measurable” means “is measurable with respect to standard  $\sigma$ -algebras.”

Examples: by (55),  $\Sigma \text{Bool} = \mathcal{P} \text{Bool}$ . By both (53) and (55),  $\Sigma \langle \text{Bool}, \text{Bool} \rangle = \mathcal{P} (\text{Bool} \times \text{Bool})$ . By (56),  $\Sigma [0, 1]$  is a sub- $\sigma$ -algebra of  $\Sigma \mathbb{R}$ .

**Theorem 8.23.**  *$\text{arr}_{\text{map}^*} \text{fst}$  and  $\text{arr}_{\text{map}^*} \text{snd}$  are measurable.*

*Proof.* Follows from (53) and Definition 8.3.  $\square$

**Theorem 8.24** (AStore measurability transfer). *Every AStore arrow combinator produces measurable mapping\* computations from measurable mapping\* computations.*

*Proof.* AStore's combinators are defined in terms of the base arrow's combinators and  $\text{arr}_{\text{map}^*} \text{fst}$  and  $\text{arr}_{\text{map}^*} \text{snd}$ .  $\square$

**Theorem 8.25.** *For all  $j \in J$ ,  $\text{arr}_{\text{map}^*} (\pi \ j)$  is measurable.*

*Proof.* Follows from (54) and Definition 8.4.  $\square$

**Corollary 8.26.**  *$\text{random}_{\text{map}^*}$  and  $\text{branch}_{\text{map}^*}$  are measurable.*

**Theorem 8.27.**  *$\text{ifte}'_{\text{map}^*}$  is measurable.*

*Proof.*  $\text{branch}_{\text{map}^*}$  is measurable, and  $\text{arr}_{\text{map}^*} \text{agrees}$  is measurable by (55).  $\square$

**Theorem 8.28** (probabilistic programs are measurable). *If  $\llbracket e \rrbracket_{\text{map}^*}$  converges, it is measurable. If  $\llbracket e \rrbracket'_{\text{map}^*}$  converges, it is measurable.*

*Proof.* By structural induction over  $e$  and the above measurability theorems.  $\square$

Of course, Theorem 8.28 remains true when  $\llbracket \cdot \rrbracket_a$  is extended with any rule whose right side is measurable. Examples include arithmetic, equalities and inequalities, and lambda expressions transformed into closures.

## 8.3 Random Store Probabilities

Preimages under probabilistic programs are measurable subsets of  $(R \times T) \times X$ . While it is possible to put probability measures on such domains, doing so would be surprising for end-users. For example, the probabilities of outputs of the geometric function defined in (33) would depend not only on the probability of  $\text{random} < p$ , but also on some arbitrary probability that each branch is taken. It would not define the geometric distribution.

We therefore have to measure *projections* of subsets of  $(R \times T) \times X$ . Unfortunately, projected sets are generally not measurable. Fortunately, ours is a special case: the excluded dimensions are countable.

As previously, we start with measuring the halting set.

**Definition 8.29** (standard probability measure). *For a type  $X$ , a standard probability measure is a probability measure  $P \in \mathcal{P} X \rightarrow [0, 1]$  where  $\text{domain } P = \Sigma X$ .*

**Definition 8.30** (halting probability). *Let  $g : X \xrightarrow{\sim}_{\text{map}^*} Y$  be measurable, with  $\mathcal{A}^*$  its halting set. Let  $P \in \mathcal{P} R \rightarrow [0, 1]$  be a standard probability measure over random stores. The halting probability of  $g$  is  $P (\text{image } \text{fst} \ggg \text{fst } \mathcal{A}^*)$ .*

**Theorem 8.31** (measurable finite projections). *Let  $A \in \Sigma \langle X_1, X_2 \rangle$ . If  $X_2$  is at most countable,  $\text{image } \text{fst } A \in \mathcal{A}_1$ .*

*Proof.* Because  $\Sigma X_2 = \mathcal{P} X_2$ ,  $A$  is a countable union of rectangles of the form  $A_1 \times \{a_2\}$ , where  $A_1 \in \Sigma X_1$  and  $a_2 \in X_2$ . Because  $\text{image } \text{fst}$  distributes over unions,  $\text{image } \text{fst } A$  is a countable union of sets in  $\Sigma X_1$ .  $\square$

**Theorem 8.32.** *Let  $g : X \rightsquigarrow_{\text{map}^*} Y$  be measurable. If  $X$  is at most countable,  $g$ 's halting probability is well-defined.*

*Proof.*  $T$  is countable; apply Theorem 8.31 twice.  $\square$

In particular, for programs interpreted using  $\llbracket \cdot \rrbracket_{\text{map}^*}$ ,  $X = \{\langle \rangle\}$  (the empty list/stack), so their halting probabilities are well-defined.

**Corollary 8.33.** *Let  $g : X \rightsquigarrow_{\text{map}^*} Y$  be measurable and  $A \subseteq A^*$  a measurable set.  $P(\text{image}(\text{fst} \ggg \text{fst}) A)$ , the probability of  $A$ , is well-defined.*

In particular, for any converging  $g := \llbracket e \rrbracket'_{\text{map}^*}$ , preimages  $A$  of measurable subsets  $B$  are measurable, and the random store component of  $A$  has a well-defined probability.

## 9. Implementable Approximation

XXX:  $\text{arr}_{\text{pre}}$  is generally uncomputable, but we don't need that many lifts; Figure 8 has the rest of the non-arithmetic ones we'll need

XXX: figure out a good way to present the following info  
Figure 4:

- $\text{pre}$ : can't implement
- $\text{pre-ap}$ : need  $\cap$
- $\langle \cdot, \cdot \rangle_{\text{pre}}$ : approximate; need  $\times$  and  $\cap$
- $\circ_{\text{pre}}$ : no change
- $\uplus_{\text{pre}}$ : approximate; need join

Figure 6:

- $\text{arr}_{\text{pre}}$  (and  $\text{lift}_{\text{pre}}$ ): can't implement
- $\ggg_{\text{pre}}$ : no change
- $\&\&\&_{\text{pre}}$ : use approximating  $\langle \cdot, \cdot \rangle_{\text{pre}}$
- $\text{ifte}_{\text{pre}}$ : need  $\{\text{true}\}$  and  $\{\text{false}\}$ ; use approximating  $\uplus_{\text{pre}}$
- $\text{lazy}_{\text{pre}}$ : need  $(= \emptyset)$ ,  $(\text{pre } \emptyset)$

Figure 8:

- $\text{id}_{\text{pre}}$ : no change
- $\text{const}_{\text{pre}}$ : need  $\{y\}$ ,  $(= \emptyset)$ ,  $\emptyset$
- $\text{fst}_{\text{pre}}$  and  $\text{snd}_{\text{pre}}$ : need projections,  $i$ ,  $\times$
- $\pi_{\text{pre}}$ : need projections,  $\cap$ , arbitrary products

## 10. Computable Approximation

### References

- [1] J. Hughes. Programming with arrows. In *5th International Summer School on Advanced Functional Programming*, pages 73–129, 2005.
- [2] N. Toronto and J. McCarthy. Computing in Cantor's paradise with  $\lambda$ -ZFC. In *Functional and Logic Programming Symposium (FLOPS)*, pages 290–306, 2012.

$\text{id}_{\text{pre}} : X \rightsquigarrow_{\text{pre}} X$ $\text{id}_{\text{pre}} A := \langle A, \lambda B. B \rangle$ $\text{const}_{\text{pre}} : Y \Rightarrow X \rightsquigarrow_{\text{pre}} Y$ $\text{const}_{\text{pre}} y A := \langle \{y\}, \lambda B. \text{if } (B = \emptyset) \emptyset A \rangle$ $\pi_{\text{pre}} : J \Rightarrow (J \rightarrow X) \rightsquigarrow_{\text{pre}} X$ $\pi_{\text{pre}} j A := \text{let } A_j := \text{proj } j A$ $\quad p := \lambda B. A \cap \prod_{i \in J} \text{if } (j = i) B (\text{proj } i A)$ $\text{in } \langle A_j, p \rangle$	$\text{fst}_{\text{pre}} : \langle X, Y \rangle \rightsquigarrow_{\text{pre}} X$ $\text{fst}_{\text{pre}} A := \text{let } A_1 := \text{image fst } A$ $\quad A_2 := \text{image snd } A$ $\text{in } \langle A_1, \lambda B. A \cap (B \times A_2) \rangle$ $\text{snd}_{\text{pre}} : \langle X, Y \rangle \rightsquigarrow_{\text{pre}} Y$ $\text{snd}_{\text{pre}} A := \text{let } A_1 := \text{image fst } A$ $\quad A_2 := \text{image snd } A$ $\text{in } \langle A_2, \lambda B. A \cap (A_1 \times B) \rangle$
--	---

---

Figure 8: Specific instances of  $\text{arr}_{\text{pre}} f$