

# Embedded Systems Summary

Nicolas Trüssel

July 31, 2016

# 1 Miscellaneous

Dependable means

- Reliable (continue working correctly when it worked correctly before)
- Maintainable (recover from errors)
- Available (probability that it's working)
- Safety
- Security

Efficient in terms of:

- Energy
- Code size
- Memory consumption
- Run time
- Weight
- Cost

## 2 Generic Time Triggered Cyclic Executive Scheduler

Let  $f$  denote the frame length,  $P$  the full period,  $D(k)$  the relative deadline of task  $k$ ,  $C(k)$  its execution time, and  $p(k)$  the period of task  $k$  (how often it occurs). Then the following conditions have to be satisfied:

- $\forall k. f \leq p(k)$  (at most one execution within a frame)
- $P = \text{lcm}_k(p(k))$
- $\forall k. f \geq C(k)$  (processes start and complete within single frame)
- $\forall k. 2f - \text{gcd}(p(k), f) \leq D(k)$  (between release time and deadline of every task there is at least one frame boundary)

### 3 Aperiodic Scheduling

	Equal arrival, non-preemptive	Arbitrary arrival, preemptive
Independent Tasks	EDD	EDF
Dependent Tasks	LDF	EDF*

#### 3.1 Definitions

- $J = \{j_1, j_2, \dots, j_n\}$  is a set of tasks.
- $a_i$  or  $r_i$  is the arrival / release time of task  $i$ .
- $d_i$  is the deadline of task  $i$ .
- $C_i$  is the total computation time of task  $i$ .
- $c_i(t)$  is the the remaining execution time of task  $i$  at time  $t$ .
- $s_i$  is the start time of task  $i$ .
- $f_i$  is the finish time of task  $i$ .
- $L_i = f_i - d_i$  is the lateness of task  $i$ .
- $E_i = \max(0, L_i)$  is the exceeding time or tardyness of task  $i$ .
- $X_i = d_i - a_i - C_i$  is the laxity or slack of task  $i$ .

#### 3.2 EDD

Schedule the tasks in order of non-decreasing deadlines. This minimizes the maximal lateness.

#### 3.3 EDF

Always execute the task with the earliest absolute deadline. Schedulability test:

$$\forall i \in [n]. t + \sum_{k=1}^i c_k(t) \leq d_i$$

#### 3.4 LDF

Among all tasks without successors select the task with the latest deadline. Put it in a stack. Repeat until no more tasks. Now execute tasks as they are on the stack.

#### 3.5 EDF\*

Modify arrival and deadline of each task and use EDF on modified tasks.

$$r_j^* = \max_j \left( r_j, \max_i (r_i^* + C_i | J_i \rightarrow J_j) \right)$$

$$d_i^* = \min_i \left( d_i, \min_j (d_j^* - C_j | J_i \rightarrow J_j) \right)$$

## 4 Periodic Scheduling

Periodic scheduling is always preemptive.

	Deadline = Period	Deadline $\leq$ Period
Static Priority	Rate Monotonic	Deadline Monotonic
Dynamic Priority	EDF	EDF*

### 4.1 Definitions

- $\Gamma = \{\tau_1, \tau_2, \dots, \tau_n\}$  is set of periodic tasks.
- $\tau_{i,j}$  is the  $j$ -th instance of task  $\tau_i$ .
- $a_{i,j}, r_{i,j}, d_{i,j}, s_{i,j}, f_{i,j}$  are the same as for aperiodic tasks.
- $\Phi_i$  is the phase of task  $i$  (release time of the first instance).
- $D_i$  is the relative deadline of task  $i$ .
- $T_i$  is the period of the task (time between 2 releases).

The following hypotheses are assumed

- $r_{i,j} = \Phi_i + (j-1)T_i$
- $C_i$  is constant.
- $d_{i,j} = \Phi_i + (j-1)T_i + D_i$
- The tasks are independent

### 4.2 Rate Monotonic

Always schedule the task that has the shortest period. Sufficient (but not necessary) schedulability test:

$$\sum_{i=1}^n \frac{C_i}{T_i} \leq n \left( 2^{\frac{1}{n}} - 1 \right)$$

### 4.3 Deadline Monotonic

Always schedule the task that has the shortest relative deadline. Sufficient (but not necessary) schedulability test:

$$\sum_{i=1}^n \frac{C_i}{D_i} \leq n \left( 2^{\frac{1}{n}} - 1 \right)$$

### 4.4 Necessary and sufficient schedulability test

We define the interference  $I_i$  for task  $i$  as

$$I_i(t) = \sum_{j=1}^{i-1} \left\lceil \frac{t}{T_j} \right\rceil C_j$$

where the tasks are ordered such that  $m < n \iff D_m < D_n$

#### 4.4.1 Algorithm

```
foreach ( $\tau_i \in \Gamma$ ) {  
     $I = 0$ ;  
    do {  
         $R = I + C_i$ ;  
        if ( $R > D_i$ ) return false; // unschedulable  
         $I = \sum_{j=1}^{i-1} \left\lceil \frac{R}{T_j} \right\rceil C_j$ ;  
    } while ( $I + C_i > R$ );  
}  
return true;
```

#### 4.5 EDF

Always schedule the task with the earliest deadline. Schedulable with EDF iff  $\sum_{i=1}^n \frac{C_i}{T_i} = U \leq 1$ .

## 5 Mixed Task Sets

A simple solution would be to schedule asynchronous tasks/events whenever there is time available. However this might lead to starvation.

### 5.1 Polling Server (RM)

A polling server is an additional periodic task which is used to serve aperiodic requests. An aperiodic task is schedulable if (sufficient but not necessary):

$$\left(1 + \left\lceil \frac{C_a}{C_s} \right\rceil\right) T_s \leq D_a$$

Where  $C_a, C_s, D_a, T_s$  are the total computation time of the aperiodic request, the computation time of one server task, the deadline of the aperiodic request, and the period of the server task. It is assumed that one aperiodic request is served before another task arrives.

### 5.2 Total Bandwidth Server (EDF)

A certain cpu utilization (bandwidth) is reserved for the server. When the  $k$ th aperiodic request arrives it receives the deadline

$$d_k = \max(r_k, d_{k-1}) + \frac{C_k}{U_s}$$

where  $C_k$  is the total execution time of the request and  $U_s$  is the utilization factor of the server. The request is then treated as a normal periodic task.

The schedule is feasible iff  $U_p + U_s \leq 1$ . Where  $U_p$  is the processor utilisation of the periodic tasks.