

University of Cape Town Department of Computer Science

Test

Enter the following details AND shade in the corresponding blocks to the right with your Student Number.		A			
	: NTSLUVOOS LUVO	G			
Course : (SC 2002 S K					
b) Write you spaces pro	calculations where	S			
OFFICIAL USE ONLY: N N N	1	3 4 5 6 7 8			

University of Cape Town

Computer Science CSC2002S

Class Test 1, 22nd August 2016

Marks:

35

Instructions: Answer all questions

Time:

45 minutes

Question 1 - Multiple Choice [6 marks]

Circle the corresponding letter of the correct answer.

- (1) A divide-and-conquer parallel algorithm for calculating the sum of n numbers has a computational span of:
 - A) O(log n)
 - B. O(n)
 - C. O(n/logn)
 - D. O(nlogn)
 - E. ∞
- (2) If you have a parallel computer with 500 processors, what is the **minimum fraction** of your program that must be parallel in order to obtain a speedup of 500?
 - A. 0.01
 - B. 0.5
 - C. 0.9
 - **(**) 1
 - E. A speedup of 500 is not possible in this case.
- (3) If I obtain ideal speedup for a parallelized program on P processes, this means that:
 - A. $T_P < T_\infty$
 - (B) $T_p = T_1/P$
 - C. $T_p < T_1/P$
 - D. $T_p = 1 T_1$
 - E. All of the above

- (4) In Java, an example of a synchronizer is:
 - (A) Thread.join
 - B. a latch
 - C. a barrier
 - D. A blocking queue
 - E. All of the above
- (5) In Java, you can solve the *Dinining Philosophers* concurrency problem using:
 - A. Using the built-in locks in a synchronized block
 - B. Calling wait() and notify() on a condition variable
 - C. Declaring a variable volatile
 - D. Calling join() on a thread.
 - E. None of the above
- (6) In Java, the method Thread.stop is deprecated because:
 - A. It is inherently unsafe
 - B. It is prone to deadlock
 - C) The Java fork-join framework has superseded traditional threads
 - D. The Producer-Consumer problem
 - E. A and B



Question 2: Parallelism [15 Marks]

Examine the following Java code (assume all necessary imports):

```
public class Para extends RecursiveTask<Integer> {
   int lo, hi, x;
   int[] arr;
    static int CUTOFF=5;
   Para(int[] a, int val, int l, int h) {arr=a; x=val; hi=h;lo=l;}
   protected Integer compute() {
       if((hi-lo) < CUTOFF) {
           int count=0;
           for(int i=lo; i < hi; i++)</pre>
               if (arr[i] == x) count++;
           return count;
        } else {
           Para left = new Para(arr,x,lo,(hi+lo)/2);
           Para right = new Para(arr,x,(hi+lo)/2,hi);
           left.fork(); // #1
           right.fork();// #2
           int b= right.join();// #3
           int a= left.join(); // #4
           return a+b;
```

	Ì
a) Does this class implement a map, or a reduction, or neither? Justify your answer. [2]]
	and the second
Reduction - because it doesn't return	
the outfirt size same as the inker	
5, Ze it returns a single number as so	Suren he
b) Explain clearly what this class computes. [2] [2] [3] [4] [4] [5] [6] [6] [7] [6] [7] [6] [7] [6] [7] [7	
equal to some number inthe giving then count Increment	
or else it certs the avorage into half and browne	
	rice
Hovery then it Toined them counting how has	un y
c) The Drive class listed below was written to test the Para class above. Write down the	
exact output when this code is run (assume all necessary imports). [2]]

```
static final ForkJoinPool fjPool = new ForkJoinPool();
    static int work(int[] arr, int key){
           return fjPool.invoke(new Para(arr, key, 0, arr.length));
   public static void main(String[] args) {
           int max =10000000;
           int [] arr = new int[max];
            Random random = new Random();
           for (int i=0;i<max;i++) { arr[i]=random.nextInt(100); }</pre>
           int key=500;
           int output= work(arr, key);
           System.out.println(key+": "+output);
          500 :
d) Would it be a good idea to replace these lines –
           left.fork(); // #1
           right.fork();// #2
           int b= right.join();// #3
           int a= left.join(); // #4
   - with the lines below?
           left.fork();
           int b=right.compute();
           int a=left.join();
           return a+b;
   Justify and explain your answer.
                                                                             [4]
                             +he
                                      FORK
                                                 me thou
              because
                                           Me
                                                       OI'M ( )
                                und
   waits
                              Kini s hes
                                              the
                  and
                                                      ereculion
                                                  His
                                                           is occurring
                                           OF
                                   C411
                   consulte method
                                                           Calling
           He
                                                     50
                          method Same as (alling fork)

which is what is haftening

the I spacks of lines are basically the same
           Compute
 and
               Toin ()
             ines
```

e) Complete the compute () method for the Recursive Action class listed below. This class performs matrix addition on the one-dimensional arrays a and b: the compute function must calculate all the values for the one-dimensional matrix (or array) c, where c[i]=a[i]+b[i]. You can assume that the matrices a, b and c are all of equal length.

Tr [0 (1 00

public class Driver {

```
public class ParaSupp extends RecursiveAction {
    int lo, hi;
    int[] a; int [] b; int[] output;
    static int CUTOFF=500;

ParaSupp(int[] A, int [] B, int [] out, int l, int h)
    {a=A; b=B; output=out; hi=h;lo=l;}

protected void compute() { //complete this method
}

if ((hi - lo) c (u TOFF) {
    int[] c = new int[hi];

    int
```

Question 3: Concurrency [14 Marks]

a) Does the code above follow the Java mon	nitor pattern? Justify your a	answer.	[2]
yes ix It is To	va That	use the	•
diformicity Abtoo	act dasses	*	<u>.</u>
			/
		Construing of the	
b) In Java, AtomicIntegers guarantee visil	bility. Explain the concep	t of visibility in the	
context of concurrency.	Hae con	P. Iran	[2]
As concurrency is			
efficiency and o		of Sinaulation	1
then the meanin			
the it is known cul		Threevel Heart is	execu!
c) In the code above, why is it not necess incrCount()?	ary to synchronize the met	thods getCount() and	[2]
more country.			[2]
been because they	alteady exi	Et is the	
# Alouric Integer is	acido Class	and also	
there cant be race	0 1	those for met	hood c
d) Why is it not desirable to synchronize the would it be a bad idea to do this)?	e methods getCount() and in	ncrCount() (i.e. why	[2]
	The state of the s		
	No. of the state o		
		The state of the s	
		The state of the s	
e) Explain why it is necessary to synchroniz	e the addHist() method.		[2]
it is hecessary	to encount	ergrace	L—"
Problems like vace	conditator		
		· · · · · · · · · · · · · · · · · · ·	
f) Explain clearly the code adjustments n	ecessary to ensure that the	Histogram class is	
deadlock free when shared between threa	ds.		[4]
······································	The state of the s		
		The state of the s	
		"Palitaberry	1

<u> </u>		•		
		<u></u>		
TOTAL CD (C)		E TITE CDACE	TO COMPLET	r votib
DITIONAL SPAC. SWERS SHOULI	E – PLEASE USI D YOU NEED	ADDITIONAL	SPACE. WRIT	THE
RRESPONDING Q	UESTION NUMBE	ER NEXT TO EA	CH ANSWER.	
	•			
<u></u>				
<u> </u>	<u></u>			
1			······································	
	<u></u>			
			. <u></u>	
	<u> </u>			
<u> </u>				
<u> </u>				
			8	
		<u> </u>		
		3858 10	T. 100 T.	
<u> </u>		20.00C3A.70C0A		

.

: