

LEARNING PROBLEM

Bùi Tiến Lên

2023



KHOA CÔNG NGHỆ THÔNG TIN
TRƯỜNG ĐẠI HỌC KHOA HỌC TỰ NHIÊN

Contents



1. Learning Components
2. A Simple Learning Model
3. Feasibility Of Learning
4. Risk and Empirical Risk

Notation



symbol	meaning
$a, b, c, N \dots$	scalar number
$\mathbf{w}, \mathbf{v}, \mathbf{x}, \mathbf{y} \dots$	column vector
$\mathbf{X}, \mathbf{Y} \dots$	matrix
\mathbb{R}	set of real numbers
\mathbb{Z}	set of integer numbers
\mathbb{N}	set of natural numbers
\mathbb{R}^D	set of vectors
$\mathcal{X}, \mathcal{Y}, \dots$	set
\mathcal{A}	algorithm

operator	meaning
\mathbf{w}^\top	transpose
$\mathbf{X}\mathbf{Y}$	matrix multiplication
\mathbf{X}^{-1}	inverse



Learning Components

Credit Approval



- Suppose that a bank receives thousands of credit card applications every day, and it wants to automate the process of evaluating them.
- Applicant information

age	23 years
gender	male
annual salary	\$30000
years in residence	1 year
years in job	1 year
current debt	\$15000
...	...

- Approve credit?

Problem Statement



Formalization

- Input: \mathbf{x} (*customer application*)
- Output: y (*good/bad customer?* or $\{1, -1\}$)
- Data $(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots, (\mathbf{x}_N, y_N)$ (*historical records*)
- Target function: $f : \mathcal{X} \rightarrow \mathcal{Y}$ (*ideal credit approval formula*)
- Best approximate function $g : \mathcal{X} \rightarrow \mathcal{Y}$ (*formula to be used*)



Inductive Bias


Theorem 1 (No Free Lunch Theorems)

An unbiased learner can never generalize.

Concept 1

An inductive bias of a learner is the set of assumptions a learner uses to predict results given inputs it has not yet encountered.

- **Consider:** arbitrarily wiggly functions or random truth tables.



x_1	x_2	x_3	y
0	0	0	0
0	0	1	?
0	1	0	1
0	1	1	1
1	0	0	0
1	0	1	?
1	1	0	1
1	1	1	?

Inductive Bias (cont.)




Inductive Learning Hypothesis

Generalization is possible.

- If a machine performs well on most **training data** AND it is not too complex, it will probably do well on **similar test data**.

Components of Learning





Learning Model



The two components are referred as the **learning model**

- The **hypothesis set** \mathcal{H} is a set of functions that is potentially similar to f

$$\mathcal{H} = \{h_{\theta_1}, h_{\theta_2}, \dots\}$$

- The **learning algorithm** \mathcal{A} is a **search algorithm** which finds $g \in \mathcal{H}$ such that

$$g \overset{\text{best}}{\approx} f$$





What is hypothesis set

Concept 2



Hypothesis set is a set of potential functions, models or solutions

- Hypothesis set can be **finite**. For example
 - $\{guilty, not\ guilty\}$
 - $\{accept, reject\}$
 - $\{happy, sad\}$
 - $\{1, 2, 3, 4, 5, 6\}$



What is hypothesis set (cont.)


- Hypothesis set can be **infinite**. For example, sets of functions $y = \theta_0 + \theta_1 x$ and $y = \theta_0 + \theta_1 x + \theta_2 x^2 + \theta_3 x^3$





Parameter representations

- Each element of hypothesis set often indexed by **parameters** or **weights** (θ or w)
- Two basic representations for parameters: **factored**, and **structured**
 1. Factored: a parameter set consists of a vector of attribute values; values can be boolean, real-valued, or one of a fixed set of symbols.
 2. Structured: a parameter set includes objects, each of which may have attributes of its own as well as relationships to other objects.





A Simple Learning Model

- Hypothesis Set
- Learning Algorithm



A Simple Hypothesis Set

We start with the simple model (**the perceptron model**)

- For input $\mathbf{x} = (x_1, \dots, x_d)$ (*attributes of a customer*)

Approve credit if $\sum_{i=1}^d w_i x_i \geq \text{threshold}$

Deny credit if $\sum_{i=1}^d w_i x_i < \text{threshold}$ (1)

- This linear formula $h \in \mathcal{H}$ can be written as

$$h(\mathbf{x}) = h_{\mathbf{w}, \text{threshold}}(\mathbf{x}) = \text{sign} \left(\left(\sum_{i=1}^d w_i x_i \right) - \text{threshold} \right) \quad (2)$$



A Simple Hypothesis Set (cont.)

- Set $w_0 = -\text{threshold}$

$$h(x) = h_{\mathbf{w}}(x) = \text{sign} \left(\left(\sum_{i=1}^d w_i x_i \right) + w_0 \right) \quad (3)$$

- Introduce an artificial coordinate $x_0 = 1$

$$h(x) = h_{\mathbf{w}}(x) = \text{sign} \left(\sum_{i=0}^d w_i x_i \right) \quad (4)$$


- In vector form, the perceptron implements

$$h(x) = h_{\mathbf{w}}(x) = \text{sign}(\mathbf{w}^T \mathbf{x}) \quad (5)$$

2D Model Visualization



- **Decision boundaries:** line
- **Decision regions:** approve and deny regions





A Simple Learning Algorithm

- **The performance measure:** *the error rate*
- We use the simple learning algorithm (**perceptron learning algorithm - PLA**) to find w

$$\arg \min_w E(h_w(x), y \mid \mathcal{D}) \quad (6)$$



A Simple Learning Algorithm (cont.)

- Given the training set

$$\mathcal{D} = \{(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots, (\mathbf{x}_N, y_N)\}$$

1. Init \mathbf{w}

2. Repeat until satisfied

- At iteration $t = 1, 2, 3, \dots$, pick a *misclassified* point (\mathbf{x}_i, y_i)



$$\text{sign}(\mathbf{w}^\top \mathbf{x}_i) \neq y_i \quad (7)$$

- and update the weight vector







$$\mathbf{w} \leftarrow \mathbf{w} + y_i \mathbf{x}_i \quad (8)$$



A Simple Explanation



Is It Learning Algorithm?





A Learning Puzzle



$y = -1$



$y = +1$



$y = ?$



Feasibility Of Learning

- Probability to the rescue



Feasibility Of Learning

The **feasibility of learning** is thus split into two questions:

1. Can we make **the performance** good enough?
 - run our learning algorithm on the actual data \mathcal{D} and see how good we can get.
2. Can we make sure that **the performance** inside of \mathcal{D} is close enough to **the performance** outside of \mathcal{D} ?
 - probability theory




A Related Experiment - Bin Problem

- Consider a **BIN** with red and green marbles


$$P[\text{picking a red marble}] = \mu$$

$$P[\text{picking a green marble}] = 1 - \mu$$

- The value of μ is unknown to us
- We pick N marbles independently
- The fraction of red marbles in **SAMPLE** $= \nu$



Does ν say anything about μ ?



- **No!** (certain answer): Sample can be mostly red while bin is mostly red
- **Yes!** (uncertain answer): Sample frequency ν is likely close to bin frequency μ



What does ν say about μ ?

- In a big sample (large N), ν is probably close μ (within ϵ)
- Formally,

$$P[|\nu - \mu| > \epsilon] \leq 2e^{-2\epsilon^2 N} \text{ for any } \epsilon > 0 \quad (9)$$

This is called **Hoeffding's Inequality**

- **Bound** does not depend on μ ; tradeoff: N, ϵ and the bound
- We have

$$\nu \approx \mu \implies \mu \approx \nu$$

- In other words, the statement " $\mu = \nu$ " is **probably approximately correct** (P.A.C)

Connection to Learning



Bin problem
The unknown is a number μ a marble ●
<div><div>●</div><div>●</div></div>

Learning problem
The unknown is a function $f : \mathcal{X} \rightarrow \mathcal{Y}$ a point $\mathbf{x} \in \mathcal{X}$
hypothesis got it right $h(\mathbf{x}) = f(\mathbf{x})$ hypothesis got it wrong $h(\mathbf{x}) \neq f(\mathbf{x})$



Connection to Learning (cont.)

- The *error rate* within the sample \mathcal{D} , which corresponds to ν in the bin model, will be called the *in-sample error*

$$\begin{aligned} E_{in}(h) &= \text{fraction of } \mathcal{D} \text{ where } f \text{ and } h \text{ disagree} \\ &= \frac{1}{N} \sum_{n=1}^N \mathbb{I}(h(\mathbf{x}_n) \neq f(\mathbf{x}_n)) \end{aligned}$$

where $\mathbb{I}(\dots) = 1$ if the statement is **true**, and $\mathbb{I}(\dots) = 0$ if the statement is **false**

- In the same way, we define the *out-of-sample error*, (domain \mathcal{X})

$$E_{out}(h) = P(h(\mathbf{x}) \neq f(\mathbf{x})), \mathbf{x} \in \mathcal{X}$$

which corresponds to μ in the bin model.

Connection to Learning (cont.)



- The Hoeffding inequality becomes:

$$P[|E_{in}(h) - E_{out}(h)| > \epsilon] \leq 2e^{-2\epsilon^2 N} \text{ for any } \epsilon > 0 \quad (10)$$

*In a big sample \mathcal{D} , **the performance** inside of \mathcal{D} is close enough to **the performance** outside of \mathcal{D}*



Risk and Empirical Risk

- Loss function
- Empirical risk
- Regularizer



Loss function

Concept 3

Given a hypothesis $\hat{y} = h(\mathbf{x}) \in \mathcal{H}$, a non-negative real-valued **loss function** $\ell(\hat{y}, y)$ which measures how different the prediction \hat{y} of a hypothesis is from the true outcome y .



Loss Functions for Binary Classification

- Zero-one loss

$$\mathbb{I}(h(\mathbf{x}) \neq y) \quad (11)$$

- Log loss (logistic regression)

$$\log(1 + e^{-h(\mathbf{x})y}) \quad (12)$$

- Exponential loss (AdaBoost)

$$e^{-h(\mathbf{x})y} \quad (13)$$

Loss Functions for Regression



- Squared loss

$$(h(\mathbf{x}) - y)^2 \quad (14)$$

- Absolute loss

$$|h(\mathbf{x}) - y| \quad (15)$$



Risk

Concept 4

The **risk** E associated with hypothesis $h(\mathbf{x})$ is defined as the expectation of the loss function

$$E(h) = \mathbb{E}[\ell(h(\mathbf{x}), y)] = \int \ell(h(\mathbf{x}), y) dp(\mathbf{x}, y) \quad (16)$$



Empirical Risk

Concept 5

The **empirical risk** \hat{E} is the average of the loss function on the training set $\mathcal{D} = \{(\mathbf{x}_1, y_1), (\mathbf{x}_2, y_2), \dots, (\mathbf{x}_N, y_N)\}$

$$\hat{E} = \frac{1}{N} \sum_{i=1}^N \ell(h_{\mathbf{w}}(\mathbf{x}_i), y_i) \quad (17)$$

Theorem 2

The empirical risk is unbiased estimate of the risk



Empirical Risk (cont.)

Concept 6

Empirical risk of hypothesis $h_{\mathbf{w}}(x)$ with a loss function ℓ and a regularizer reg

$$\hat{E} = \frac{1}{N} \sum_{i=1}^N \underbrace{\ell(h_{\mathbf{w}}(\mathbf{x}_i), y_i)}_{\text{Loss}} + \underbrace{\lambda reg(\mathbf{w})}_{\text{Regularizer}} \quad (18)$$



The empirical risk minimization principle

Principle

The learning algorithm should choose a hypothesis h_w which minimizes the empirical risk

$$h_w = \arg \min_{h_w \in \mathcal{H}} \hat{E}(h_w | \mathcal{D}) \quad (19)$$



Regularizers

Theorem 3

For each $\lambda \geq 0$, there exists $B \geq 0$. such that the two formulations are equivalent,

$$\arg \min_{\mathbf{w}} \sum_{i=1}^N \ell(h_{\mathbf{w}}(\mathbf{x}_i), y_i) + \lambda \text{reg}(\mathbf{w}) \quad (20)$$

$$\arg \min_{\mathbf{w}} \sum_{i=1}^N \ell(h_{\mathbf{w}}(\mathbf{x}_i), y_i) \text{ subject to } \text{reg}(\mathbf{w}) \leq B \quad (21)$$

Regularizers (cont.)



- L_2 -regularization

$$\text{reg}(\mathbf{w}) = \mathbf{w}^\top \mathbf{w} = \|\mathbf{w}\|_2^2 \quad (22)$$

- L_1 -regularization

$$\text{reg}(\mathbf{w}) = \|\mathbf{w}\|_1 \quad (23)$$

References



Goodfellow, I., Bengio, Y., and Courville, A. (2016).

Deep learning.

MIT press.



Lê, B. and Tô, V. (2014).

Cở sở trí tuệ nhân tạo.

Nhà xuất bản Khoa học và Kỹ thuật.



Russell, S. and Norvig, P. (2021).

Artificial intelligence: a modern approach.

Pearson Education Limited.