

Instance Based Learning

Bùi Tiến Lên

2022



KHOA CÔNG NGHỆ THÔNG TIN
TRƯỜNG ĐẠI HỌC KHOA HỌC TỰ NHIÊN

Contents



1. **Classification**

2. **Metric Learning**

3. **Regression**

4. **Clustering**



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Notation

symbol	meaning
$a, b, c, N \dots$	scalar number
$\mathbf{w}, \mathbf{v}, \mathbf{x}, \mathbf{y} \dots$	column vector
$\mathbf{X}, \mathbf{Y} \dots$	matrix
\mathbb{R}	set of real numbers
\mathbb{Z}	set of integer numbers
\mathbb{N}	set of natural numbers
\mathbb{R}^D	set of vectors
$\mathcal{X}, \mathcal{Y}, \dots$	set
\mathcal{A}	algorithm

operator	meaning
\mathbf{w}^T	transpose
$\mathbf{X}\mathbf{Y}$	matrix multiplication
\mathbf{X}^{-1}	inverse



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Parametric vs Non-parametric Models

Parametric Models

- In the models that we have seen, we select a hypothesis space \mathcal{H} and adjust a *fixed set of parameters* \mathbf{w} with the training data \mathcal{D}
- We assume that the parameters \mathbf{w} summarize the training data \mathcal{D} and we can forget about it

$$y = f(\mathbf{x}; \mathbf{w}) \quad (1)$$

Non-parametric Models

- A non parametric model is one that can not be characterized by a fixed set of parameters
- A family of non parametric models is **Instance Based Learning**. The function is based on the training data $\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n\}$

$$y = f(\mathbf{x}; \mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_n) \quad (2)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Inductive Bias

Concept 1

In nonparametric model, we assume that ***similar** inputs have **similar** outputs.*

- This is a reasonable assumption: The world is smooth, and functions, whether they are densities, discriminants, or regression functions, change slowly. Similar instances mean similar things.



Classification

- k-Nearest Neighbor (k-NN)
- Effects of Hyper-parameters



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

When To Consider Nearest Neighbor

- Data points $\mathbf{x} \in \mathbb{R}^D$
- Less than $D < 20$ attributes
- Lots of training data \mathcal{D}



Nearest Neighbor

Learning mode

- Store all training examples $\mathcal{D} = \{(\mathbf{x}_i, y_i) \mid i = 1, \dots, N\}$

Running mode

- **Nearest neighbor:** Given query instance \mathbf{x}_q , first locate *the nearest neighbor* $\mathbf{x}^{(1)}$, then estimate

$$h(\mathbf{x}_q) = y^{(1)} \quad (3)$$

- **k -Nearest neighbor:** Given \mathbf{x}_q , take vote among its k *nearest neighbors* $\{\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(k)}\}$

$$h(\mathbf{x}_q) = \text{majority vote}\{y^{(1)}, y^{(2)}, \dots, y^{(k)}\} \quad (4)$$



Distance

Some common distances in space \mathbb{R}^D

- The Minkowski distance of order $p > 0$

$$d(\mathbf{x}, \mathbf{y}) = L_p(\mathbf{x}, \mathbf{y}) = \left(\sum_{i=1}^D |x_i - y_i|^p \right)^{1/p} \quad (5)$$

- Euclidean distance (popular)

$$d(\mathbf{x}, \mathbf{y}) = L_2(\mathbf{x}, \mathbf{y}) = \sqrt{\sum_{i=1}^D (x_i - y_i)^2} \quad (6)$$



Distance (cont.)

- Manhattan distance

$$d(\mathbf{x}, \mathbf{y}) = L_1(\mathbf{x}, \mathbf{y}) = \sum_{i=1}^D |x_i - y_i| \quad (7)$$




Figure 1: Contours of the distance from the origin O for various values of the parameter p



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering


k-Means

Hierarchical Clustering

k-d Tree

The Curse of dimensionality

- The more dimensions we have, the more examples we need
- The number of examples that we have in a volume of space *decreases exponentially* with the number of dimensions
 - If the number of dimensions is very high, the nearest neighbours can be very far away





Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Analysis

Advantages

- No training, just store data
- Learn complex target functions
- Don't lose information

Disadvantages

- Slow at query time
- Easily fooled by irrelevant attributes



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering


k-d Tree

Parameter k

- if $k = 1$ the *cross point* x should be classified to *square class*
- if $k = 3$?
- if $k = 5$?

■ square class

● circle class





Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering


k-Means

Hierarchical Clustering

k-d Tree

Parameter k (cont.)

- Data set \mathcal{D} with 500 samples belonging to two classes {blue, orange}





Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering


k-Means

Hierarchical Clustering

k-d Tree

Parameter k (cont.)

- Decision regions for various values of k





Metric Learning

- Motivation
- Metric Learning
- Loss Function



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning
Loss Function

Regression


Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Motivation

- Nearest neighbor classification





Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering


k-Means

Hierarchical Clustering

k-d Tree

Motivation (cont.)

- Clustering





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model


Clustering

k-Means
Hierarchical Clustering
k-d Tree

Motivation (cont.)

- Information retrieval

Query image



Most similar images



Classification

k-Nearest Neighbor
(k-NN)

Effects of

Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering


k-Means

Hierarchical Clustering

k-d Tree

Motivation (cont.)

- Data visualization





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

Metric Learning

- Given a set of data points \mathcal{X} and their corresponding labels \mathcal{Y}
- Select a **parametric distance** or **similarity function**

$$d_{\mathbf{w}}(\mathbf{x}, \mathbf{x}') = L(f_{\mathbf{w}}(\mathbf{x}), f_{\mathbf{w}}(\mathbf{x}')) \quad (8)$$

- An embedding function (parametric function)

$$f_{\mathbf{w}}(\mathbf{x}): \mathcal{X} \rightarrow \mathbb{R}^n \quad (9)$$

- A distance function (which is usually fixed beforehand)

$$L(\mathbf{x}, \mathbf{x}'): \mathbb{R}^n \times \mathbb{R}^n \rightarrow \mathbb{R} \quad (10)$$

- The goal is to train the parametric distance, so that the combination $d_{\mathbf{w}}(\mathbf{x}, \mathbf{x}')$ produces small values if the labels $y, y' \in \mathcal{Y}$ of the samples $\mathbf{x}, \mathbf{x}' \in \mathcal{X}$ are equal, and larger values if they aren't.



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Metric Learning (cont.)

- Collect **similarity judgements** on data pairs/triplets

$$\begin{aligned}\mathcal{S} &= \{(\mathbf{x}_i, \mathbf{x}_j) : \mathbf{x}_i \text{ and } \mathbf{x}_j \text{ should be similar}\}, \\ \mathcal{D} &= \{(\mathbf{x}_i, \mathbf{x}_j) : \mathbf{x}_i \text{ and } \mathbf{x}_j \text{ should be dissimilar}\}. \\ \mathcal{R} &= \{(\mathbf{x}_i, \mathbf{x}_j, \mathbf{x}_k) : \mathbf{x}_i \text{ should be more similar to } \mathbf{x}_j \text{ than to } \mathbf{x}_k\}.\end{aligned}\tag{11}$$

- Estimate parameters s.t. metric best agrees with judgements

$$\hat{\mathbf{W}} = \arg \min_{\mathbf{W}} \left[\underbrace{\ell(d_{\mathbf{W}}, \mathcal{S}, \mathcal{D}, \mathcal{R})}_{\text{loss function}} + \underbrace{\lambda R(\mathbf{W})}_{\text{regularization}} \right]\tag{12}$$



Classification

- k-Nearest Neighbor (k-NN)
- Effects of Hyper-parameters

Metric Learning

- Motivation

Metric Learning

- Loss Function


Regression

- Kernel Function
- Kernel Regression
- k-NN Regression
- Nadaraya-Watson Model
- Nadaraya-Watson Parametric Model

Clustering

- k-Means
- Hierarchical Clustering
- k-d Tree

Metric Learning (cont.)





Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model


Clustering

k-Means

Hierarchical Clustering

k-d Tree

Metric Learning (cont.)





Classification

k-Nearest Neighbor
(k-NN)

Effects of

Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

Contrastive Approaches

- An embedding function is usually a neural network
- A distance function is L_2 distance
- A loss function



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Contrastive Loss

Contrastive Loss (Chopra et al. 2005)

- Let $\mathbf{x}_1, \mathbf{x}_2$ be some samples in the dataset, and y_1, y_2 are their corresponding labels. Also, for some condition A , let's denote \mathbb{I}_A as the identity function that is equal to 1 if A is true, and 0 otherwise. The loss function is then defined as follows:

$$\ell_{\text{contrast}} = \mathbb{I}_{y_1=y_2} d_{\text{W}}(\mathbf{x}_1, \mathbf{x}_2) + \mathbb{I}_{y_1 \neq y_2} \max(0, \alpha - d_{\text{W}}(\mathbf{x}_1, \mathbf{x}_2)) \quad (13)$$

where α is the margin.



Classification

k-Nearest Neighbor

(k-NN)

Effects of

Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson

Model

Nadaraya-Watson

Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

Triplet Loss

Triplet Loss (Schroff et al. 2015)

- Let $\mathbf{x}_a, \mathbf{x}_p, \mathbf{x}_n$ be some samples from the dataset and $\mathbf{y}_a, \mathbf{y}_p, \mathbf{y}_n$ be their corresponding labels, so that $y_a = y_p$ and $y_a \neq y_n$. Usually, \mathbf{x}_a is called **anchor** sample, \mathbf{x}_p is called **positive** sample because it has the same label as \mathbf{x}_a , and \mathbf{x}_n is called **negative** sample because it has a different label. It is defined as:

$$\ell_{\text{triplet}} = \max(0, d_W(\mathbf{x}_a, \mathbf{x}_p) - d_W(\mathbf{x}_a, \mathbf{x}_n) + \alpha) \quad (14)$$

where α is the margin.



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model


Clustering

k-Means


Hierarchical Clustering

k-d Tree

Contrastive Loss vs. Triplet Loss



contrastive lost



triplet lost



Regression

- Kernel Function
- Kernel Regression
- k-NN Regression
- Nadaraya-Watson Model
- Nadaraya-Watson Parametric Model



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Feature Space

Project the data into a **higher dimensional space** (feature space) \mathcal{F}

- **Transformation function**

$$\begin{aligned}\phi &: \mathbb{R}^D \rightarrow \mathcal{F} \\ \mathbf{x}_i &\rightarrow \phi(\mathbf{x}_i)\end{aligned}\tag{15}$$

- Work with $\phi(\mathbf{x}_i)$ instead of working with \mathbf{x}_i .



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

The Kernel Function

Concept 2

A **kernel** is a function $k(\mathbf{x}, \mathbf{z})$ which represents a dot product in a “hidden” feature space of ϕ .

$$k(\mathbf{x}, \mathbf{z}) = \phi(\mathbf{x}) \cdot \phi(\mathbf{z}) \quad (16)$$

- **Note that:** we have only dot products $\phi(\mathbf{x}_i) \cdot \phi(\mathbf{x}_j)$ to compute; however, this could be very expensive in a high dimensional space.
- **Kernel trick:**

$$\text{instead of } \phi(\mathbf{x}) = \phi \begin{pmatrix} x_1 \\ x_2 \end{pmatrix} = \begin{pmatrix} x_1^2 \\ \sqrt{2}x_1x_2 \\ x_2^2 \end{pmatrix}, \text{ use } k(\mathbf{x}, \mathbf{z}) = (\mathbf{x} \cdot \mathbf{z})^2$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Common Kernels

- Polynomial:

$$k(\mathbf{x}, \mathbf{z}) = (u\mathbf{x} \cdot \mathbf{z} + v)^p \quad (u \in \mathbb{R}, v \in \mathbb{R}, p \in \mathbb{N}) \quad (17)$$

- Gaussian:

$$k(\mathbf{x}, \mathbf{z}) = \exp\left(-\frac{\|\mathbf{x} - \mathbf{z}\|^2}{\sigma^2}\right), \quad \sigma \in \mathbb{R}^+ \quad (18)$$

Note: feature space is infinite-dimensional



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Techniques for Construction of Kernels

In all the following, k_1, k_2, \dots, k_j are assumed to be valid kernel functions

- 1. Scalar multiplication:** The validity of a kernel is conserved after multiplication by a positive scalar, i.e., for any $\alpha > 0$, the function

$$k(\mathbf{x}, \mathbf{z}) = \alpha k_1(\mathbf{x}, \mathbf{z}) \quad (19)$$

- 2. Adding a positive constant:** For any positive constant $\alpha > 0$, the function

$$k(\mathbf{x}, \mathbf{z}) = \alpha + k_1(\mathbf{x}, \mathbf{z}) \quad (20)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Techniques for Construction of Kernels (cont.)

- 3. Linear combination:** A linear combination of kernel functions involving only positive weights, i.e.,

$$k(\mathbf{x}, \mathbf{z}) = \sum_{j=1}^m \alpha_j k_j(\mathbf{x}, \mathbf{z}), \quad \text{with } \alpha_j > 0 \quad (21)$$

is a valid kernel function.

- 4. Product:** The product of two kernel functions, i.e.,

$$k(\mathbf{x}, \mathbf{z}) = k_1(\mathbf{x}, \mathbf{z}) k_2(\mathbf{x}, \mathbf{z}) \quad (22)$$

is a valid kernel function.



Techniques for Construction of Kernels (cont.)

Classification
k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning
Motivation
Metric Learning
Loss Function

Regression
Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering
k-Means
Hierarchical Clustering
k-d Tree

- 5. Polynomial functions of a kernel output:** Given a polynomial $f : \mathbb{R} \rightarrow \mathbb{R}$ with positive coefficients, the function

$$k(\mathbf{x}, \mathbf{z}) = f(k_1(\mathbf{x}, \mathbf{z})) \quad (23)$$

is a valid kernel function.

- 6. Exponential function of a kernel output:** The function

$$k(\mathbf{x}, \mathbf{z}) = \exp(k_1(\mathbf{x}, \mathbf{z})) \quad (24)$$

is a valid kernel function.

- 7. Product of matrix and vectors:**

$$k(\mathbf{x}, \mathbf{z}) = \mathbf{x}^T A \mathbf{z} \quad (25)$$

where A is a symmetric positive semidefinite matrix.



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Linear Regression Revisted

Problem: Given a dataset of input-output pairs $\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$, find the best linear regression

- **Primal form**

$$\hat{y} = f(\mathbf{x}) = \sum_{i=1}^D \mathbf{w}_i x_i \quad (26)$$

where

$$\mathbf{w} = (\mathbf{X}^T \mathbf{X} + \lambda \mathbf{I}_D)^{-1} \mathbf{X}^T \mathbf{y} \quad (27)$$

- **Dual Form**

$$\hat{y} = f(\mathbf{x}) = \sum_{i=1}^N \alpha_i \mathbf{x}_i^T \mathbf{x} \quad (28)$$

where

$$\boldsymbol{\alpha} = (\mathbf{X} \mathbf{X}^T + \lambda \mathbf{I}_N)^{-1} \mathbf{y} \quad (29)$$



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

The Kernel Trick

- **Question:** How introduce nonlinearity to

$$\hat{y} = f(\mathbf{x}) = \sum_{i=1}^N \alpha_i \mathbf{x}_i^T \mathbf{x}$$

- **Solution:** Replace the inner product $\mathbf{x}_i^T \mathbf{x}$ by $k(\mathbf{x}, \mathbf{x}_i)$, we have

$$\hat{y} = f(\mathbf{x}) = \sum_{i=1}^N \alpha_i k(\mathbf{x}, \mathbf{x}_i) \quad (30)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Kernel Method

1. Select a kernel function $k(\cdot, \cdot)$
2. Construct a kernel matrix $\mathbf{K} \in \mathbb{R}^{N \times N}$ where

$$[\mathbf{K}]_{ij} = k(\mathbf{x}_i, \mathbf{x}_j) \quad (31)$$

3. Compute the coefficients $\boldsymbol{\alpha} \in \mathbb{R}^N$, with

$$\boldsymbol{\alpha} = (\mathbf{K} + \lambda \mathbf{I}_N)^{-1} \mathbf{y} \quad (32)$$

4. Estimate the predicted value for a new sample \mathbf{x}

$$\hat{y} = \sum_{i=1}^N \alpha_i k(\mathbf{x}, \mathbf{x}_i) \quad (33)$$



Classification

k-Nearest Neighbor

(k-NN)

Effects of

Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

Linear Regression vs. Kernel Method

Linear regression	Kernel method
pick a global model, best fit globally based on the columns (features)	pick a local model, best fit locally based on the rows (samples)
handle linearity	handle nonlinearity



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

k-NN Regression

- **Problem:** Given a dataset of input-output pairs $\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$, how to learn f to predict the output $\hat{y} = f(\mathbf{x})$ for any new input \mathbf{x} ?
- **Solution:** Take the mean of the values of k nearest neighbors $\{\mathbf{x}^{(1)}, \mathbf{x}^{(2)}, \dots, \mathbf{x}^{(k)}\}$

$$\hat{y} = \frac{\sum_{i=1}^k y^{(i)}}{k} \quad (34)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression

Nadaraya-Watson Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Nadaraya-Watson Model

- **Problem:** Given a dataset of input-output pairs $\mathcal{D} = \{(\mathbf{x}_1, y_1), \dots, (\mathbf{x}_N, y_N)\}$, how to learn f to predict the output $\hat{y} = f(\mathbf{x})$ for any new input \mathbf{x} ?
- **Solution:** Consider (\mathbf{x}_i, y_i) as a pair of key-value and \mathbf{x} as query

key	value
\mathbf{x}_1	y_1
\vdots	\vdots
\mathbf{x}_N	y_N

$$\hat{y} = \sum_{i=1}^N \alpha(\mathbf{x}, \mathbf{x}_i) y_i, \quad (35)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression

Nadaraya-Watson Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Nadaraya-Watson Model (cont.)

- We define α using a Gaussian kernel

$$\alpha(\mathbf{x}, \mathbf{x}_i) = \frac{\exp \left[-\frac{1}{2} \|\mathbf{x} - \mathbf{x}_i\|^2 \right]}{\sum_{j=1}^n \exp \left[-\frac{1}{2} \|\mathbf{x} - \mathbf{x}_j\|^2 \right]}. \quad (36)$$

and plug it into equation (17)

$$\begin{aligned} \hat{y} &= \sum_{i=1}^N \alpha(\mathbf{x}, \mathbf{x}_i) y_i \\ &= \sum_{i=1}^N \frac{\exp \left[-\frac{1}{2} \|\mathbf{x} - \mathbf{x}_i\|^2 \right]}{\sum_{j=1}^N \exp \left[-\frac{1}{2} \|\mathbf{x} - \mathbf{x}_j\|^2 \right]} y_i \end{aligned} \quad (37)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression

Nadaraya-Watson Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Nadaraya-Watson Model (cont.)

- A key \mathbf{x}_i that is closer to the given query \mathbf{x} will get more attention via a larger attention weight assigned to the key's corresponding value y_i .



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
**Nadaraya-Watson
Model**
Nadaraya-Watson
Parametric Model

Clustering


k-Means
Hierarchical Clustering
k-d Tree

Example 1

- Generate an artificial dataset including 50 training examples and 50 testing examples according to the following nonlinear function with the noise term $\epsilon \sim \mathcal{N}(0, 0.5)$

$$y = 2 \sin(x) + x^{0.8} + \epsilon \quad (38)$$

- Find the kernel regression





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
**Nadaraya-Watson
Parametric Model**

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Nadaraya-Watson Parametric Model

- Kernel regression enjoys the consistency benefit: given enough data this model converges to the optimal solution.
- Nonetheless, we can easily integrate learnable parameters.
- In the following the distance between the query \mathbf{x} and the key \mathbf{x}_i is multiplied a learnable parameter w :

$$\hat{y} = \sum_{i=1}^N \frac{\exp \left[-\frac{1}{2} (\|\mathbf{x} - \mathbf{x}_i\| w)^2 \right]}{\sum_{j=1}^N \exp \left[-\frac{1}{2} (\|\mathbf{x} - \mathbf{x}_j\| w)^2 \right]} y_i \quad (39)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
**Nadaraya-Watson
Parametric Model**

Clustering


k-Means
Hierarchical Clustering
k-d Tree

Example 2

Generate an artificial dataset including 50 training examples and 50 testing examples according to the following nonlinear function with the noise term $\epsilon \sim \mathcal{N}(0, 0.5)$

$$y = 2 \sin(x) + x^{0.8} + \epsilon \quad (40)$$

- Find the parametric kernel regression





Clustering

- k-Means
- Hierarchical Clustering
- k-d Tree



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model


Clustering

k-Means
Hierarchical Clustering
k-d Tree

Clustering

Concept 3

Cluster analysis or **clustering** is the task of grouping a set of objects in such a way that objects in the same group (called a **cluster**) are more similar (in some sense) to each other than to those in other groups (clusters).





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering
k-d Tree

k-Means

Concept 4

Given a set of observations $\mathcal{D} = \{\mathbf{x}_1, \dots, \mathbf{x}_N\}$, k -means clustering aims to partition the N observations into k ($\leq N$) sets $\mathbf{S} = \{S_1, S_2, \dots, S_k\}$ so as to minimize the within-cluster sum of squares

- The objective to find

$$\arg \min_{\mathbf{S}} \sum_{i=1}^k \sum_{\mathbf{x} \in S_i} \|\mathbf{x} - \boldsymbol{\mu}_i\|^2 \quad (41)$$

where $\boldsymbol{\mu}_i$ is the mean of S_i



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model



Clustering

k-Means

Hierarchical Clustering

k-d Tree

Illustration





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Naive k-Means Algorithm

1. Initialise a set of k means $\mathbf{m}_1^{(0)}, \dots, \mathbf{m}_k^{(0)}$

2. For $t = 1, 2, 3, \dots$ do

- **Assignment step:** Assign each observation to the cluster with the nearest mean: that with the least squared Euclidean distance

$$S_i^{(t)} = \left\{ \mathbf{x} \mid L_2(\mathbf{x}, \mathbf{m}_i^{(t)}) < L_2(\mathbf{x}, \mathbf{m}_j^{(t)}), \forall j \neq i \right\} \quad (42)$$

- **Update step:** Recalculate means (centroids) for observations assigned to each cluster.

$$\mathbf{m}_i^{(t+1)} = \frac{1}{|S_i^{(t)}|} \sum_{\mathbf{x} \in S_i^{(t)}} \mathbf{x} \quad (43)$$

The algorithm has converged when the assignments no longer change



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model


Clustering

k-Means
Hierarchical Clustering
k-d Tree

Hierarchical Clustering

Concept 5

Hierarchical clustering is a method of cluster analysis which seeks to build a hierarchy of clusters.





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Linkage Function

Concept 6

A **linkage function** L is used to calculate the distance (similarity/dissimilarity) between arbitrary subsets of the instance space, given a distance metric d

- *Single linkage*: defines the distance between two clusters as the smallest pairwise distance between elements from each cluster.

$$L_{single}(A, B) = \min\{d(\mathbf{x}, \mathbf{y}) \mid \mathbf{x} \in A, \mathbf{y} \in B\} \quad (44)$$

- *Complete linkage*: defines the distance between two clusters as the largest pointwise distance.

$$L_{complete}(A, B) = \max\{d(\mathbf{x}, \mathbf{y}) \mid \mathbf{x} \in A, \mathbf{y} \in B\} \quad (45)$$



Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression

Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Agglomerative algorithm

- Given a set of observations $\mathcal{D} = \{\mathbf{x}_1, \dots, \mathbf{x}_n\}$

Initialise clusters to singleton data points

Create a leaf node for every singleton cluster

Repeat

find the pair of clusters X, Y with lowest linkage

merge X, Y into Z

create a node for Z (parent node of X, Y)

Until all data points are in one cluster

Return the constructed binary tree



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

k-d Tree

- The fundamental problem of k-NN is that distance computation is costly and the total cost unavoidably linear in the number of points compared.
- To increase the processing speed, it is possible to partition the data space and reduce this number significantly using k-d tree

Concept 7

A **k-d tree** (short for k-dimensional tree) is a space-partitioning data structure for organizing points in a k-dimensional space



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means

Hierarchical Clustering

k-d Tree

Algorithm

Construct k-d tree

- Given and D -dimensional dataset $\mathcal{D} = \{\mathbf{x}_1, \mathbf{x}_2, \dots, \mathbf{x}_N\}$
- **Cut** data with a plane at its **median value** along that dimension
- **Recurse** this procedure to create a balanced binary tree k-d tree

Nearest neighbor search

- To locate the NN of an query vector \mathbf{x} , determine which leaf cell it lies within
- To perform an exhaustive search within this cell.



Classification

k-Nearest Neighbor
(k-NN)

Effects of
Hyper-parameters

Metric Learning

Motivation

Metric Learning

Loss Function

Regression

Kernel Function

Kernel Regression

k-NN Regression

Nadaraya-Watson
Model

Nadaraya-Watson
Parametric Model

Clustering

k-Means



Hierarchical Clustering

k-d Tree

Example

Given a dataset $\mathcal{D} = \{(x_1, x_2)\} = \{(2, 3), (5, 4), (9, 6), (4, 7), (8, 1), (7, 2)\}$

- Construct k-d tree





Classification

k-Nearest Neighbor
(k-NN)
Effects of
Hyper-parameters

Metric Learning

Motivation
Metric Learning
Loss Function

Regression


Kernel Function
Kernel Regression
k-NN Regression
Nadaraya-Watson
Model
Nadaraya-Watson
Parametric Model

Clustering

k-Means
Hierarchical Clustering
k-d Tree

Example (cont.)

- Nearest neighbor search



References



Goodfellow, I., Bengio, Y., and Courville, A. (2016).

Deep learning.

MIT press.



Lê, B. and Tô, V. (2014).

Cở sở trí tuệ nhân tạo.

Nhà xuất bản Khoa học và Kỹ thuật.



Russell, S. and Norvig, P. (2021).

Artificial intelligence: a modern approach.

Pearson Education Limited.