

mandel_sema.c

```
1  /*
2   * mandel_sema.c
3   *
4   * A program to draw the Mandelbrot Set on a 256-color xterm, with semaphores.
5   *
6   */
7
8  #include <signal.h>
9  #include <errno.h>
10 #include <pthread.h>
11 #include <stdio.h>
12 #include <unistd.h>
13 #include <assert.h>
14 #include <string.h>
15 #include <math.h>
16 #include <stdlib.h>
17 #include <semaphore.h>
18
19 #include "mandel-lib.h"
20
21 #define MANDEL_MAX_ITERATION 100000
22
23 /*****
24  * Compile-time parameters *
25  *****/
26
27 /*
28  * POSIX thread functions do not return error numbers in errno,
29  * but in the actual return value of the function call instead.
30  * This macro helps with error reporting in this case.
31  */
32 #define perror_pthread(ret, msg) \
33     do { errno = ret; perror(msg); } while (0)
34
35 /*
36  * Output at the terminal is is x_chars wide by y_chars long
37  */
38 int y_chars = 50;
39 int x_chars = 90;
40
41 /*
42  * The part of the complex plane to be drawn:
43  * upper left corner is (xmin, ymax), lower right corner is (xmax, ymin)
44  */
45 double xmin = -1.8, xmax = 1.0;
46 double ymin = -1.0, ymax = 1.0;
47
48 /*
49  * Every character in the final output is
50  * xstep x ystep units wide on the complex plane.
51  */
52 double xstep;
53 double ystep;
54
55 void sig_handler(int signum)
56 {
57     reset_xterm_color(1);
```

```
58     exit(1);
59 }
60
61 /*
62  * A (distinct) instance of this structure
63  * is passed to each thread
64  */
65 struct thread_info_struct {
66     pthread_t tid; /* POSIX thread id, as returned by the library */
67
68     int *color_val; /* Pointer to array to manipulate */
69     int thrid; /* Application-defined thread id */
70     int thrcnt;
71 };
72
73 int safe_atoi(char *s, int *val)
74 {
75     long l;
76     char *endp;
77
78     l = strtol(s, &endp, 10);
79     if (s != endp && *endp == '\0') {
80         *val = l;
81         return 0;
82     } else
83         return -1;
84 }
85
86 void usage(char *argv0)
87 {
88     fprintf(stderr, "Usage: %s thread_count array_size\n\n"
89             "Exactly one argument required:\n"
90             "    thread_count: The number of threads to create.\n",
91             argv0);
92     exit(1);
93 }
94
95 void *safe_malloc(size_t size)
96 {
97     void *p;
98
99     if ((p = malloc(size)) == NULL) {
100         fprintf(stderr, "Out of memory, failed to allocate %zd bytes\n",
101                 size);
102         exit(1);
103     }
104
105     return p;
106 }
107
108 /*
109  * This function computes a line of output
110  * as an array of x_char color values.
111  */
112 void compute_mandel_line(int line, int color_val[])
113 {
114     /*
115      * x and y traverse the complex plane.
116      */
117     double x, y;
```

```
118
119     int n;
120     int val;
121
122     /* Find out the y value corresponding to this line */
123     y = ymax - ystep * line;
124
125     /* and iterate for all points on this line */
126     for (x = xmin, n = 0; n < x_chars; x+= xstep, n++) {
127
128         /* Compute the point's color value */
129         val = mandel_iterations_at_point(x, y, MANDEL_MAX_ITERATION);
130         if (val > 255)
131             val = 255;
132
133         /* And store it in the color_val[] array */
134         val = xterm_color(val);
135         color_val[n] = val;
136     }
137 }
138
139 /*
140  * This function outputs an array of x_char color values
141  * to a 256-color xterm.
142  */
143 void output_mandel_line(int fd, int color_val[]) {
144     char point = '@';
145     char newline = '\n';
146
147     for (int i = 0; i < x_chars; i++) {
148         /* Set the current color, then output the point */
149         set_xterm_color(fd, color_val[i]);
150         if (write(fd, &point, 1) != 1) {
151             perror("compute_and_output_mandel_line: write point");
152             exit(1);
153         }
154     }
155
156     /* Now that the line is done, output a newline character */
157     if (write(fd, &newline, 1) != 1) {
158         perror("compute_and_output_mandel_line: write newline");
159         exit(1);
160     }
161 }
162
163 /* Start function for each thread */
164 sem_t *sem;
165
166 void *compute_and_output_mandel_line(void *arg)
167 {
168     struct thread_info_struct *thr = arg;
169
170     for (int i = thr->thrid; i < y_chars; i += thr->thrcnt) {
171         compute_mandel_line(i, thr->color_val);
172         sem_wait(&sem[i % thr->thrcnt]);
173         output_mandel_line(1, thr->color_val);
174         sem_post(&sem[(i+1) % thr->thrcnt]);
175     }
176     return NULL;
177 }
```

```
178
179 int main(int argc, char *argv[])
180 {
181     int thrcnt, ret;
182     struct thread_info_struct *thr;
183
184     // Signal Handler
185     struct sigaction sa;
186     sa.sa_flags = SA_RESTART;
187     sa.sa_handler = sig_handler;
188     if (sigaction(SIGINT, &sa, NULL) < 0)
189     {
190         perror("sigaction");
191         exit(1);
192     }
193
194     /*
195     * Parse the command line
196     */
197     if (argc != 2)
198         usage(argv[0]);
199     if (safe_atoi(argv[1], &thrcnt) < 0 || thrcnt <= 0) {
200         fprintf(stderr, "'%s' is not valid for `thread_count'\n", argv[1]);
201         exit(1);
202     }
203
204     xstep = (xmax - xmin) / x_chars;
205     ystep = (ymax - ymin) / y_chars;
206
207     thr = safe_malloc(thrcnt * sizeof(*thr));
208     sem = safe_malloc(thrcnt * sizeof(sem_t));
209
210     for(int i=0; i<thrcnt; i++)
211     {
212         thr[i].thrcnt = thrcnt;
213         thr[i].thrid = i;
214         thr[i].color_val = safe_malloc(x_chars * sizeof(int));
215         if(i == 0) sem_init(&sem[i], 0, 1);
216         else sem_init(&sem[i], 0, 0);
217
218         /* Spawn new thread */
219         ret = pthread_create(&thr[i].tid, NULL, compute_and_output_mandel_line, &thr[i]);
220         if (ret) {
221             perror_pthread(ret, "pthread_create");
222             exit(1);
223         }
224     }
225
226     /*
227     * Wait for all threads to terminate
228     */
229     for (int i=0; i<thrcnt; i++) {
230         ret = pthread_join(thr[i].tid, NULL);
231         if (ret) {
232             perror_pthread(ret, "pthread_join");
233             exit(1);
234         }
235     }
236
237     for(int i=0; i<thrcnt; i++)
```

```
238     sem_destroy(&sem[i]);  
239  
240     reset_xterm_color(1);  
241     return 0;  
242 }  
243
```