

# Joint Intensity Fusion

Brian B. Avants<sup>1†</sup>, Nicholas J. Tustison<sup>2</sup>, ...<sup>3</sup>

<sup>1</sup>Department of Radiology, University of Pennsylvania, Philadelphia, PA

<sup>2</sup>Department of Radiology and Medical Imaging, University of Virginia, Charlottesville, VA

<sup>3</sup>Some other institution

Corresponding author:

Brian B. Avants

Cambridge, MA XXXXX

stnava@gmail.com

---

† Currently employed by Biogen (Cambridge, MA).

## Abstract

Consensus techniques have demonstrated remarkable utility in various medical imaging segmentation tasks. Joint label fusion (JLF) employs spatially normalized atlas sets—gray-scale intensity images with corresponding segmentation labels—to segment unlabeled images using various weighting schemes. The technique of [1, 2] avoids informational redundancy in the atlas voting scheme by considering the atlas set as a whole versus individually in determining the optimal weights. In this work we extend this methodology to the estimation of intensity information in multi-modal image data sets, which we denote as *joint intensity fusion (JIF)*. JIF has several potential applications including removal of imaging artifacts (e.g., motion), removal of pathologies (e.g., tumour, lesions), imputation of missing modality data, and template enhancement. Evaluation is performed on a variety of data [...need more here](#). We provide an open-source implementation in the the well-known Advanced Normalization Tools (ANTs) software package which subsumes the functionality reported in [2] in addition to offering further enhancements such as multi-threading and a non-negative least-squares calculation of the atlas weights.

*Keywords:* ANTs, atlases, denoising, motion correction, non-negative least squares.

## **Introduction**

“Wisdom-of-crowds” [3] approaches to medical image segmentation have proven remarkably successful. Recent international competitions such as the brain labeling challenge associated with the MICCAI 2012 Workshop on Multi-Atlas Labeling and the 2013 MICCAI Challenge Workshop on Segmentation: Algorithms, Theory and Applications have demonstrated the superiority of these consensus-based approaches when coupled with high-performing image spatial normalization algorithms.

Early techniques such as single atlas label assignment [4] and majority voting [5]

## **Methods**

## **Results**

## **Discussion**

1. Wang, H. and Yushkevich, P. A. “**Multi-Atlas Segmentation with Joint Label Fusion and Corrective Learning-an Open Source Implementation**” *Front Neuroinform* 7, (2013): 27. doi:10.3389/fninf.2013.00027
2. Wang, H., Suh, J. W., Das, S. R., Pluta, J. B., Craige, C., and Yushkevich, P. A. “**Multi-Atlas Segmentation with Joint Label Fusion**” *IEEE Trans Pattern Anal Mach Intell* 35, no. 3 (2013): 611–23. doi:10.1109/TPAMI.2012.143
3. Surowiecki, J. “**The Wisdom of Crowds: Why the Many Are Smarter Than the Few and How Collective Wisdom Shapes Business, Economics, Societies and Nations**” (2004):
4. Heckemann, R. A., Hajnal, J. V., Aljabar, P., Rueckert, D., and Hammers, A. “**Automatic Anatomical Brain MRI Segmentation Combining Label Propagation and Decision Fusion**” *Neuroimage* 33, no. 1 (2006): 115–26. doi:10.1016/j.neuroimage.2006.05.061
5. Kittler, J., Hatef, M., Duin, R. P. W., and Matas, J. “**On Combining Classifiers**” *IEEE Trans Pattern Anal Mach Intell*