

Joint Intensity Fusion

Brian B. Avants^{1†}, Nicholas J. Tustison², ...³

¹Department of Radiology, University of Pennsylvania, Philadelphia, PA

²Department of Radiology and Medical Imaging, University of Virginia, Charlottesville, VA

³Some other institution

Corresponding author:

Brian B. Avants

Cambridge, MA XXXXX

stnava@gmail.com

† Currently employed by Biogen (Cambridge, MA).

Abstract

Consensus techniques have demonstrated remarkable utility in various medical imaging segmentation tasks. Joint label fusion (JLF) employs spatially normalized atlas sets—gray-scale intensity images with corresponding segmentation labels—to segment unlabeled images using various weighting schemes. The technique of [1, 2] avoids informational redundancy in the atlas voting scheme by considering the atlas set as a whole (versus individually) in determining the optimal weights. In this work we extend this methodology to the estimation of intensity information in multi-modal image data sets, which we denote as *joint intensity fusion (JIF)*. JIF has several potential applications including removal of imaging artifacts (e.g., motion), removal of pathologies (e.g., tumour, lesions), imputation of missing modality data, and template enhancement. Evaluation is performed on a variety of data **...need more here**. We provide an open-source implementation in the the well-known Advanced Normalization Tools (ANTs) software package, based on the Insight Toolkit coding standards, which subsumes the functionality reported in [2] in addition to offering further enhancements such as multi-threading and a non-negative least-squares calculation of the atlas weights.

Keywords: ANTs, atlases, denoising, motion correction, non-negative least squares.

Introduction

Coupled with advanced image registration algorithms, techniques such as single atlas label assignment [3] and majority voting [4] of atlases provided early, well-performing prior knowledge segmentation alternatives to related segmentation techniques which employ intensity-based partitioning of the gray-scale histogram constrained by local image neighborhood-based spatial priors (e.g., Markov Random Field) [5–7]. As pointed out in a recent comprehensive survey of the field [8], the popularization of multi-atlas segmentation techniques extend more than a decade ago with early pioneering efforts (e.g., [9–11]).

These multi-atlas techniques, which is an instantiation of “wisdom-of-crowds” [12] solution strategies, have proven remarkably successful. Recent international competitions such as the brain labeling challenge of the *MICCAI 2012 Workshop on Multi-Atlas Labeling* and the *2013 MICCAI Challenge Workshop on Segmentation: Algorithms, Theory and Applications* have demonstrated the superiority of these consensus-based approaches when paired with high-performing image spatial normalization algorithms (e.g., [13]).

Methods

A brief review of joint label fusion

Joint intensity fusion

ITK implementation

Similar to the other ANTs programs, the software encapsulating the methods discussed in this work are built upon the Insight Toolkit (ITK) and conform to ITK coding standards. In this section we describe the implementation and usage interface. The program `antsJointFusion.cxx` uses an intuitive command line interface developed specifically for the ANTs toolkit.

See Listing 1 for the short help menu available at the command line. A more comprehensive long help menu can be produced (not shown). The latter provides references and documentation concerning parameter options. `antsJointFusion.cxx` is the interface for the underlying ITK-style class:

- `itkWeightedVotingFusionImageFilter.h`
- `itkWeightedVotingFusionImageFilter.hxx`

```
COMMAND:
  antsJointFusion

OPTIONS:
  -d, --image-dimensionality 2/3/4
  -t, --target-image targetImage
      [targetImageModality0,...,targetImageModalityN]
  -g, --atlas-image atlasImage
      [atlasImageModality0,...,atlasImageModalityN]
  -l, --atlas-segmentation atlasSegmentation
  -a, --alpha 0.1
  -b, --beta 2.0
  -c, --constrain-nonnegative (0)/1
  -p, --patch-radius 2
      2x2x2
  -m, --patch-metric (PC)/MSQ
  -s, --search-radius 3
      3x3x3
```

```

searchRadiusMap.nii.gz
-e, --exclusion-image label[exclusionImage]
-x, --mask-image maskImageFilename
-o, --output labelFusionImage
    intensityFusionImageFileNameFormat
    [labelFusionImage,intensityFusionImageFileNameFormat,
    <labelPosteriorProbabilityImageFileNameFormat>,
    <atlasVotingWeightImageFileNameFormat>]
--version
-v, --verbose (0)/1
-h
--help

```

Listing 1: The antsJointFusion short command line menu which is invoked using the ‘-h’ option. The expanded menu, which provides details regarding the possible parameters and usage options, is elicited using the ‘-help’ option.

antsJointFusion has a number of available parameters (see Listing 1) permitting operation on 2-, 3- or 4-dimensional data. The default input parameters and corresponding definitions are given below:

Target image set. This input (or set of inputs) comprises the image set to be matched by the input atlases. If more than one target image is specified, it is assumed that all modalities are spatially normalized. If JIF is to be performed then all target modalities are inferred with only the first image being used for atlas weighting. For example, suppose the set of input atlases consists of N modality images per atlas. Only the first image needs to be specified for the set of target input images although all N target modalities will be estimated using JIF.

Atlas images. Each atlas set specified by the -g option consists of one or more modality. It is assumed that these atlases have already been normalized to the target image. The ordering of the modalities for each atlas is assumed to match the ordering specified for the target image and the other atlases.

Atlas labels. When performing JLF, a set of atlas labels is provided with each atlas set. Pairing of each atlas label, -l option, with each atlas, -g is assumed from the order of appearance on the command line. Note that specification of the atlas labels

is optional for performing JIF.

Alpha. The damping parameter Alpha is the constant value added to the diagonal elements of the weight(???) matrix (see Equation ()) to prevent the possible inversion of a singular matrix. The larger the value, the greater the stability for matrix inversion but the further away from the true solution. The default value is 0.1.

Beta.

Constrain non-negative. To estimate the matrix inversion.

Results

Discussion

References

1. Wang, H. and Yushkevich, P. A. “**Multi-Atlas Segmentation with Joint Label Fusion and Corrective Learning-an Open Source Implementation**” *Front Neuroinform* 7, (2013): 27. doi:10.3389/fninf.2013.00027
2. Wang, H., Suh, J. W., Das, S. R., Pluta, J. B., Craige, C., and Yushkevich, P. A. “**Multi-Atlas Segmentation with Joint Label Fusion**” *IEEE Trans Pattern Anal Mach Intell* 35, no. 3 (2013): 611–23. doi:10.1109/TPAMI.2012.143
3. Heckemann, R. A., Hajnal, J. V., Aljabar, P., Rueckert, D., and Hammers, A. “**Automatic Anatomical Brain MRI Segmentation Combining Label Propagation and Decision Fusion**” *Neuroimage* 33, no. 1 (2006): 115–26. doi:10.1016/j.neuroimage.2006.05.061
4. Kittler, J., Hatef, M., Duin, R. P. W., and Matas, J. “**On Combining Classifiers**” *IEEE Trans Pattern Anal Mach Intell*
5. Zhang, Y., Brady, M., and Smith, S. “**Segmentation of Brain MR Images Through a Hidden Markov Random Field Model and the Expectation-Maximization Algorithm**” *IEEE Trans Med Imaging* 20, no. 1 (2001): 45–57. doi:10.1109/42.906424
6. Ashburner, J. and Friston, K. J. “**Unified Segmentation**” *Neuroimage* 26, no. 3 (2005): 839–51. doi:10.1016/j.neuroimage.2005.02.018
7. Avants, B. B., Tustison, N. J., Wu, J., Cook, P. A., and Gee, J. C. “**An Open Source Multivariate Framework for n -Tissue Segmentation with Evaluation on Public Data**” *Neuroinformatics* 9, no. 4 (2011): 381–400. doi:10.1007/s12021-011-9109-y
8. Iglesias, J. E. and Sabuncu, M. R. “**Multi-Atlas Segmentation of Biomedical**

Images: A Survey” *Med Image Anal* 24, no. 1 (2015): 205–19. doi:10.1016/j.media.2015.06.012

9. Rohlfing, T., Russakoff, D. B., and Maurer, C. R. “**Expectation Maximization Strategies for Multi-Atlas Multi-Label Segmentation**” *Inf Process Med Imaging* 18, (2003): 210–21.

10. Warfield, S. K., Zou, K. H., and Wells, W. M. “**Simultaneous Truth and Performance Level Estimation (STAPLE): An Algorithm for the Validation of Image Segmentation**” *IEEE Trans Med Imaging* 23, no. 7 (2004): 903–21. doi:10.1109/TMI.2004.828354

11. Klein, A., Mensh, B., Ghosh, S., Tourville, J., and Hirsch, J. “**Mindboggle: Automated Brain Labeling with Multiple Atlases**” *BMC Med Imaging* 5, (2005): 7. doi:10.1186/1471-2342-5-7

12. Surowiecki, J. “**The Wisdom of Crowds: Why the Many Are Smarter Than the Few and How Collective Wisdom Shapes Business, Economics, Societies and Nations**” (2004):

13. Avants, B. B., Tustison, N. J., Song, G., Cook, P. A., Klein, A., and Gee, J. C. “**A Reproducible Evaluation of ANTs Similarity Metric Performance in Brain Image Registration**” *Neuroimage* 54, no. 3 (2011): 2033–44. doi:10.1016/j.neuroimage.2010.09.025