


# Anonymization Techniques & Attacks

Dr. Elena Nazarenko

# Recap: Direct vs Indirect Identifiers

## Direct Identifiers

Uniquely identify individuals on their own

- Full names and aliases
- Social Security Numbers
- Physical and email addresses
- Biometric data

## Indirect Identifiers (Quasi-Identifiers)

Seemingly innocuous attributes that become identifying when combined

- Gender and age
- Birthdate and ZIP code
- Occupation and education level
- Geographic location data

# The Quasi-Identifier Dilemma

> Individually, quasi-identifiers appear harmless. Combined, they create a unique fingerprint that can pinpoint specific individuals with alarming accuracy.

Research shows that 87% of the U.S. population can be uniquely identified using just three attributes: ZIP code, birthdate, and gender.






# Classical Anonymization Models

# K-Anonymity: Hiding in a Crowd

K-anonymity ensures that each record in a dataset is indistinguishable from at least k-1 other records based on quasi-identifiers, creating protective anonymity through similarity.

### Group Protection

If k=5, your record looks identical to 4 others



### Prevents Isolation

No individual stands out as unique

### Privacy Through Ambiguity

Attackers cannot distinguish between group members

# How K-Anonymity Works



## Generalization

Replace specific values with broader categories

- Age 27 → 20-30
- ZIP 94301 → 943**
- Salary $87,500 → $80K-$90K



## Suppression

Remove or mask outlier values

- Rare occupations replaced with asterisks
- Extreme ages removed entirely
- Unique combinations eliminated

# Original Dataset

| Nr | Age | Sex | City | Disease |
|---|---|---|---|---|
| 1 | 16 | Male | Rotterdam | Viral infection |
| 2 | 18 | Male | Rotterdam | Heart-related |
| 3 | 19 | Male | Rotterdam | Cancer |
| 4 | 22 | Female | Rotterdam | Viral infection |
| 5 | 22 | Male | Zwolle | No illness |
| 6 | 23 | Male | Zwolle | Tuberculosis |
| 7 | 24 | Male | Zwolle | Heart-related |
| 8 | 25 | Female | Utrecht | Cancer |
| 9 | 26 | Female | Rotterdam | Heart-related |
| 10 | 28 | Female | Utrecht | Tuberculosis |

# 2-anonymous dataset

| Nr | Age | Sex | City | Disease |
|---|---|---|---|---|
| 1 | =< 20 | Male | Rotterdam | Viral infection |
| 2 | =< 20 | Male | Rotterdam | Heart-related |
| 3 | =< 20 | Male | Rotterdam | Cancer |
| 4 | 20-30 | Female | Rotterdam | Viral infection |
| 5 | 20-30 | Male | Zwolle | No illness |
| 6 | 20-30 | Male | Zwolle | Tuberculosis |
| 7 | 20-30 | Male | Zwolle | Heart-related |
| 8 | 20-30 | Female | Utrecht | Cancer |
| 9 | 20-30 | Female | Rotterdam | Heart-related |
| 10 | 20-30 | Female | Utrecht | Tuberculosis |

# Choosing k: It’s a Trade-Off, Not a Rule

There is **no universal value** of *k* that works for all datasets.

- **Higher k** → Greater anonymity
  But also → **More generalization**, **less detail**, potentially **lower data utility**

- **Lower k** → More detailed, useful data
  But also → **Higher risk of re-identification**

**Selecting k is a risk management decision, not a purely technical one!**



# Limitations of K-Anonymity

## Homogeneity Attack

When all k records in a group share identical sensitive attributes, privacy is compromised despite k-anonymity. Example: if 5 indistinguishable records all have "diabetes," any one of them is revealed to have diabetes.

## Background Knowledge Attack

Adversaries leverage external information to narrow down possibilities within anonymous groups. Knowing someone's habits or associations can eliminate candidates and reveal identity.

# L-Diversity: Adding Diversity to Privacy

L-diversity strengthens k-anonymity by requiring that sensitive attributes within each equivalence group have at least l "well-represented" distinct values, protecting against homogeneity and background knowledge attacks.



### Diverse Values

Ensures variety in sensitive attributes



### Enhanced Protection

Guards against attribute disclosure



### Balanced Distribution

Maintains meaningful heterogeneity

# 2-anonymous dataset

| Nr | Age | Sex | City | Disease |
|---|---|---|---|---|
| 1 | =< 20 | Male | Rotterdam | Viral infection |
| 2 | =< 20 | Male | Rotterdam | Heart-related |
| 3 | =< 20 | Male | Rotterdam | Cancer |
| 4 | 20-30 | Female | Rotterdam | Viral infection |
| 5 | 20-30 | Male | Zwolle | No illness |
| 6 | 20-30 | Male | Zwolle | Tuberculosis |
| 7 | 20-30 | Male | Zwolle | Heart-related |
| 8 | 20-30 | Female | Utrecht | Cancer |
| 9 | 20-30 | Female | Rotterdam | Viral infection |
| 10 | 20-30 | Female | Utrecht | Cancer |

# 2-anonymous 2-diverse dataset

| Nr | Age | Sex | City | Disease |
|---|---|---|---|---|
| 1 | =< 20 | Male | Rotterdam | Viral infection |
| 2 | =< 20 | Male | Rotterdam | Heart-related |
| 3 | =< 20 | Male | Rotterdam | Cancer |
| 4 | 20-30 | Female | • | Viral infection |
| 5 | 20-30 | Male | Zwolle | No illness |
| 6 | 20-30 | Male | Zwolle | Tuberculosis |
| 7 | 20-30 | Male | Zwolle | Heart-related |
| 8 | 20-30 | Female | • | Cancer |
| 9 | 20-30 | Female | • | Viral infection |
| 10 | 20-30 | Female | • | Cancer |

# Example of L-Diversity

### Practical Application

In a medical dataset with k=5 (five indistinguishable records per group) and l=3, each group must contain at least 3 different disease diagnoses

## Group Meeting L-Diversity

- Record 1: Diabetes
- Record 2: Hypertension
- Record 3: Asthma
- Record 4: Diabetes
- Record 5: Hypertension

✓ **3 distinct diseases present**

## Group Failing L-Diversity

- Record 1: Diabetes
- Record 2: Diabetes
- Record 3: Diabetes
- Record 4: Hypertension
- Record 5: Hypertension

× Only 2 distinct diseases

# Challenges with L-Diversity

### Implementation Difficulty

Achieving l-diversity in datasets with highly skewed sensitive attribute distributions can be mathematically impossible without excessive data loss

### Reduced Data Utility

Aggressive generalization and suppression required to meet l-diversity requirements often significantly diminish the analytical value and accuracy of the dataset

### Computational Complexity

Finding optimal l-diverse partitions becomes computationally expensive for large datasets with multiple quasi-identifiers and sensitive attributes

**Like k-anonymity, there is no perfect value of L, although it is usually less or equal to k and more than 1.**

- K-anonymity protects **identity**, but not **attribute privacy**.

- L-diversity strengthens privacy by ensuring that each anonymized group contains **multiple different sensitive values**, making it harder to infer the sensitive attribute.

# Progression of Privacy Models




While previous models ensure adequate group sizes and value variety, they fail to account for the overall distribution of sensitive values. A diverse group can still leak data if it skews far from the global norm.

# The Vulnerability in Standard Anonymization


General knowledge: Bob has a comparatively low income and specific ZIP/Age brackets.

| | | | | |
|---|---|---|---|---|
| ID: 1021 | Age: 35-40 | ZIP: 940xx | Income: High | Condition: Diabetes |
| ID: 1022 | Age: 35-40 | ZIP: 940xx | Income: Medium | Condition: Hypertension |
| ID: 1023 | Age: 35-40 | ZIP: 940xx | Income: Low | Condition: Gastric Disease |
| ID: 1024 | Age: 41-45 | ZIP: 941xx | Income: Low | Condition: Gastric Disease |
| ... | ... | ... | ... | ... |

Hidden data: Stomach problems.

If an equivalence class meets K-Anonymity and L-Diversity, but all its low-income members happen to share similar gastric diseases, Bob's specific condition can still be inferred. How do we measure this risk?

# Defining the Threshold of Closeness




T-Closeness demands that the distribution of a sensitive attribute within any given equivalence class must closely mirror the distribution of that attribute in the entire original database. The threshold **t** represents the maximum allowable distance between these two curves, quantifying the acceptable level of deviation.

# T-closeness

T-closeness ensures that the distribution of a sensitive attribute within a generalisation of a quasi-identifier is close to the distribution of the sensitive attribute in the entire dataset.

T-closeness can get complicated quite fast.

It ensures that the sensitive attribute is not skewed towards a specific value within a group of similar individuals, which could potentially be used to re-identify someone.

For example, if a dataset contains information on Age (quasi-identifier), Sex (quasi-identifier), and Income (sensitive attribute), and t-closeness is applied with a value of t = 0.1, then for each combination of Age and Sex, the distribution of income must be within 10% of the distribution of income in the entire dataset.


https://www.youtube.com/watch?v=Upb8jqlsbFM

# The Fully Anonymized Database

- Bob's data is now secure. By strategically generalizing quasi-identifiers and grouping equivalence classes, the database achieves:
  - 3-Anonymous (Group Size)
  - 3-Diverse (Attribute Variance)
  - 0.167 Close for Salary (Numerical EMD)
  - 0.278 Close for Disease (Categorical EMD)
- No specific sensitive information can be reliably inferred.

| ID | Age | ZIP Code | Salary | Disease |
|---|---|---|---|---|
| 001 | 40-50 | 1234* | $80k-90k | Flu |
| 002 | 40-50 | 1234* | $80k-90k | Gastritis |
| 003 | 40-50 | 1234* | $90k-110k | Heart Disease |
| 004 | 40-50 | 1234* | $80k-90k | Gastritis |
| 005 | 40-50 | 1234* | $80k-90k | Gastritis |
| 006 | 40-50 | 1234* | $80k-110k | Heart Disease |
| 007 | 50-60 | 5678* | $100k-110k | Heart Disease |
| 008 | 60-70 | 5678* | $100k-110k | Heart Disease |
| 009 | 50-70 | 5678* | $100k-110k | Heart Disease |

# The Anonymization Hierarchy




True structural database security requires layered defense. We must hide individuals in a crowd (K), ensure the crowd holds varied secrets (L), and prove the crowd accurately reflects the real world (T). Up next: Differential Privacy.



Re-Identification Attacks

# The Privacy Threat Reality

# What is Re-Identification?

> Re-identification, also called de-anonymization, is the process of matching anonymized data with external datasets or background knowledge to successfully reveal the true identities of individuals.

01

## Obtain Anonymized Data

Access target dataset lacking direct identifiers

02

## Identify Auxiliary Data

Find external sources with overlapping attributes

03

## Link Records

Match records across datasets using quasi-identifiers

04

## Reveal Identity

Successfully associate anonymous records with real individuals

# Attack Taxonomy Overview

Re-identification attacks can be categorized into four primary types, each exploiting different vulnerabilities in anonymization schemes. Understanding these attack vectors is essential for implementing appropriate countermeasures.



## Linkage Attacks

Matching quasi-identifiers across datasets



## Inference Attacks

Deducing sensitive attributes from group membership



## Similarity Attacks

Exploiting semantic similarity in sensitive values



## Homogeneity Attacks

Leveraging identical sensitive values within groups

# Linkage Attacks: The Classic Threat

Linkage attacks cross-reference anonymized data with publicly available records such as voter registration lists, property records, or social media profiles to reveal identities.

**Classic Example:** Combining just three quasi-identifiers—birthdate, gender, and ZIP code—can uniquely identify 87% of the U.S. population when linked with voter registration data.

# Types of Linkage Attacks



## Exact Matching

Linking records with identical attribute values across datasets



## Robust Matching

Linking records even when values differ due to noise or inconsistencies



## Profiling Attacks

Extracting behavioral patterns to link records across different time periods

# Linkage Attacks


## Attack Mechanism

Linkage attacks match **quasi-identifiers** (QIDs) from an anonymized dataset to external public or auxiliary datasets containing the same attributes along with direct identifiers.
Common quasi-identifiers include:

- Birth date or age
- Gender
- ZIP code or geographic location
- Race/ethnicity
- Occupation

When combined, these attributes often uniquely identify individuals, even when each attribute alone appears non-identifying.

# The Famous Massachusetts Governor Attack




## A Landmark Discovery

In 1997, researcher Latanya Sweeney re-identified Massachusetts Governor William Weld in supposedly anonymous medical records by linking them with public voter data using just three attributes: birth date, sex, and postal code.

This attack demonstrated that pseudonymization alone cannot protect privacy.




# Netflix Prize Re-Identification

1

## October 2006

Netflix releases anonymized movie ratings for 480,000 users in a public competition

2

## December 2007

University of Texas researchers successfully re-identify users by linking anonymous ratings with public IMDb profiles

3

## Result

Private viewing habits exposed for hundreds of thousands of users, revealing sensitive personal preferences and potentially embarrassing information

# The Netflix Prize Dataset

In 2006, Netflix released a dataset of 100 million movie ratings from 500,000 subscribers to improve its recommendation algorithm. The company removed names and other obvious identifiers, believing the data was anonymous.

The dataset included:

- Anonymized user IDs
- Movie titles
- Ratings (1-5 stars)
- Rating timestamps

Researchers at UT Austin demonstrated that by linking this dataset with public ratings on IMDb, they could re-identify individual Netflix subscribers with high accuracy.

**Key insight:** Even sparse rating patterns and timestamps served as unique quasi-identifiers that could be matched across datasets.

# Attack Execution

1

## Step 1: Auxiliary Data

Collect public movie ratings from IMDb with user identities

2

## Step 2: Pattern Matching

Match rating patterns and timestamps between Netflix and IMDb datasets

3

## Step 3: Re-identification

Link anonymous Netflix IDs back to real IMDb usernames

The researchers found that knowing just 8 movie ratings (of which 2 might be incorrect) and their approximate dates was sufficient to uniquely identify 99% of records in the Netflix dataset.

# Impact and Consequences

## Legal Ramifications

Netflix canceled the planned second iteration of the Prize competition. A class-action lawsuit was filed citing privacy violations, eventually settled out of court.

## Research Impact

The attack demonstrated that naive anonymization is insufficient. It catalyzed academic and industry focus on rigorous privacy definitions like differential privacy.

## Industry Shift

Organizations began recognizing that releasing detailed behavioral data—even without names—poses significant re-identification risks.


# Monsignor Jeffrey Burrill Outed by Grindr Data



In July 2021, Monsignor Jeffrey Burrill, a high-ranking official at the United States Conference of Catholic Bishops, was forced to resign after The Pillar, a Catholic newsletter, published an investigation linking him to the gay dating app Grindr.

The investigation relied on **commercially available location data** spanning 2018-2020, revealing patterns of app usage, visits to gay bars, and travel to private residences. This wasn't hacked data—it was purchased openly from data brokers.

The case exposed a chilling reality: your location data can be bought, analyzed, and used to identify and expose you, regardless of promises of anonymity.




# "When Private Data Becomes a Public Weapon"

The Burrill case demonstrates how surveillance capitalism transforms personal information into tools for exposure, blackmail, and harm.

# How Did This Happen? The Data Trail

1

## Data Collection

Grindr allegedly shared hashed device IDs, precise GPS coordinates, age, gender, and app activity with third-party advertising partners through software development kits (SDKs) embedded in the app.

2

## Data Aggregation

Data brokers purchased and aggregated this supposedly "anonymized" data from multiple sources, creating comprehensive profiles of device movements and behaviors over extended periods.

3

## De-anonymization

The Pillar correlated device presence at known locations—USCCB headquarters, Burrill's family home, and public events—with timestamps to conclusively identify him despite data anonymization efforts.

# The Scale of Location Data Collection

## Continuous Tracking


Mobile apps collect GPS coordinates, WiFi networks, Bluetooth beacons, and cell tower data continuously—often even when apps aren't actively in use or running in the background.

## Massive Marketplace

Data brokers operate a multi-billion dollar industry, buying and reselling location information to advertisers, political campaigns, law enforcement, and anyone willing to pay.

## Regulatory Vacuum

No comprehensive US federal law mandates meaningful user consent or data protection for location information, leaving consumers vulnerable to exploitation.



# Why Location Data Isn't Truly Anonymous

The promise of "anonymized" data is fundamentally flawed when it comes to location information. Research has consistently shown that **just four spatiotemporal points** are enough to uniquely identify 95% of individuals.


In Burrill's case, his device was repeatedly tracked at highly identifiable locations:

- His workplace at USCCB headquarters
- His family's residential addresses
- Public Catholic events where he was speaking
- Gay bars and private residences in multiple cities

Privacy experts universally agree: location data cannot be reliably anonymized. The patterns of human movement are simply too unique.



# Conclusion: The Burrill Case



## Key Takeaways

The Monsignor Burrill case is not an isolated incident—it's a preview of privacy threats we all face:

**Location data is never truly anonymous** and can identify and harm individuals

**Data brokers operate unchecked**, selling sensitive information to anyone who pays

**Cybersecurity professionals must understand** data flows, attack vectors, and risks

**Protection requires vigilance** across technical, legal, and ethical dimensions

> **The future of digital privacy depends on informed defenders** who understand both technology and human rights. That defender is you.


# Inference Attacks

## Statistical Methods

Attackers use statistical techniques to infer sensitive information from patterns and correlations within anonymized data

## Machine Learning

Advanced AI algorithms identify subtle relationships between attributes that humans might miss




These attacks exploit the inherent structure and relationships in data rather than relying on external linkage sources.

# Inference Attacks

## Attack Mechanism

Inference attacks exploit the relationship between group membership and sensitive attributes. Even if an attacker cannot identify a specific individual, they can infer sensitive information with high confidence based on group characteristics.
These attacks target the fundamental assumption that placing individuals in groups with diverse sensitive attributes protects privacy.

## The l-Diversity Failure

The classic example involves a dataset where all individuals under age 30 in a particular ZIP code have the same sensitive attribute value (e.g., "stomach disease").
An attacker knowing someone is in this group can infer their sensitive attribute without identifying them specifically—a clear privacy breach.

# Inference Attack Example

| Age Group | ZIP Code | Gender | Medical Condition |
|---|---|---|---|
| 25-30 | 94101 | M | Stomach Disease |
| 25-30 | 94101 | F | Stomach Disease |
| 25-30 | 94101 | M | Stomach Disease |
| 25-30 | 94101 | F | Stomach Disease |

**Privacy breach:** Knowing someone is 25-30 years old in ZIP 94101 reveals their medical condition with 100% certainty, regardless of k-anonymity guarantees.

# Why l-Diversity Fails

### Lack of Semantic Diversity

l-Diversity requires l distinct values per equivalence class, but doesn't account for semantic similarity. "Gastric ulcer," "Stomach cancer," and "Intestinal disease" are technically distinct but semantically related.

### Insufficient Protection Against Background Knowledge

Attackers with external knowledge about attribute distributions can still make high-confidence inferences even when l-diversity is satisfied.

### Skewness Vulnerabilities

When sensitive attributes follow highly skewed distributions, l-diversity provides weak protection. If 90% of a population has attribute A, even diverse groups leak information.

# Similarity Attacks

## Exploiting Semantic Proximity

Similarity attacks target datasets that satisfy l-diversity by exploiting the semantic similarity of sensitive attribute values within an equivalence class.
Even when values are technically distinct, if they're semantically similar, an attacker can narrow down the possible values to a small, related set.

# Similarity Attack Example

| Age | ZIP | Gender | Medical Condition |
|---|---|---|---|
| 35-40 | 94102 | M | Gastric Ulcer |
| 35-40 | 94102 | F | Stomach Cancer |
| 35-40 | 94102 | M | Gastritis |
| 35-40 | 94102 | F | Intestinal Disease |

This equivalence class satisfies 4-diversity with four distinct medical conditions. However, all conditions relate to digestive system problems. An attacker can confidently infer: "The individual has a gastrointestinal disorder."

# Defending Against Similarity Attacks

01

## Semantic Distance Requirements

Enforce minimum semantic distance between sensitive values using taxonomies or ontologies

02

## t-Closeness

Require that the distribution of sensitive attributes in each equivalence class closely matches the distribution in the overall dataset

03

## Differential Privacy

Apply noise addition techniques that provide mathematical guarantees regardless of semantic relationships

# Homogeneity Attacks

## The k-Anonymity Flaw

Homogeneity attacks exploit a fundamental weakness in basic k-anonymity: when all records in an equivalence class share the same sensitive attribute value, the sensitive information is revealed regardless of k.

This represents the **most straightforward privacy breach** in anonymized datasets.

# Homogeneity Attack Example

| Age Group | ZIP Code | Gender | Disease |
|---|---|---|---|
| 30-35 | 94103 | * | HIV+ |
| 30-35 | 94103 | * | HIV+ |
| 30-35 | 94103 | * | HIV+ |
| 30-35 | 94103 | * | HIV+ |
| 30-35 | 94103 | * | HIV+ |

This table satisfies 5-anonymity (k=5), yet reveals that every individual aged 30-35 in ZIP 94103 is HIV-positive. Privacy is completely compromised.

# Why Homogeneity is Dangerous

### Zero Uncertainty

Attacker gains 100% confidence about sensitive attribute without identifying specific individual

### Common in Real Data


Natural clustering in datasets often creates homogeneous groups (e.g., specialty clinics, demographic patterns)

### k-Anonymity Blind Spot

Basic k-anonymity only protects against re-identification, not attribute disclosure

# Attack Summary and Evolution

These four attack types represent the foundational threats to anonymized data. Modern attacks build upon these principles, applying them to new data types and contexts.



# AI-Powered Re-Identification Attacks

Modern machine learning techniques have dramatically increased the effectiveness of re-identification attacks, analyzing behavioral patterns and auxiliary data with unprecedented accuracy.



## Deep Learning

Neural networks identify complex patterns invisible to traditional methods, finding hidden connections between seemingly unrelated attributes




## Graph Analysis

Social network structures and relationship graphs provide powerful auxiliary information for linking anonymous profiles



## Behavioral Fingerprinting

Unique patterns in browsing, purchasing, or movement data create distinctive signatures that persist despite anonymization



# AI Breaks Traditional Privacy Barriers

# Why Re-Identification is Easier Than You Think

**99.98%**

Americans Identifiable

Percentage uniquely identifiable with just 15 demographic attributes (2019 study)

**60%**

Basic Attributes Sufficient

Population identifiable using only gender, birthdate, and ZIP code

**87%**

Three-Attribute Match

U.S. residents uniquely identified by birthdate, gender, and ZIP code alone

The illusion of anonymity collapses when we realize how few data points are needed for re-identification in practice.

Limitations of Classical Models

# Why Traditional Methods Fall Short



# Fragility of Quasi-Identifier Selection

> The fundamental challenge: it's impossible to anticipate every external dataset an attacker might leverage for re-identification.



## Unknown Unknowns

Attributes not identified as quasi-identifiers during anonymization may become identifying when combined with unanticipated external sources

## Expanding Data Landscape

New public datasets emerge constantly—social media, IoT devices, public cameras—creating fresh linkage opportunities

## Context Dependency

What constitutes a quasi-identifier changes based on the attacker's background knowledge and available resources



# Trade-Off: Privacy vs Data Utility

### Stronger Anonymization

- Higher k-anonymity values
- Greater l-diversity requirements
- More aggressive generalization

**Result:** Reduced data accuracy and analytical value

### Preserved Data Utility

- Minimal generalization
- Specific attribute values retained
- Rich, detailed datasets

**Result:** Increased re-identification risk

Finding the optimal balance remains one of the central challenges in privacy-preserving data publishing.

# Residual Risk of Re-Identification

## The Uncomfortable Truth

No anonymization method provides absolute guarantees. Some level of re-identification risk always persists, no matter how sophisticated the protection techniques.




### Low Risk Threshold

Often considered acceptable for research data

### Moderate Risk

Requires additional safeguards and access controls

### Minimal Risk

Difficult to achieve without severe utility loss

Organizations must transparently assess, document, and accept residual risk when publishing anonymized data.

# Regulatory Perspectives

## GDPR Standard

Data must be "not reasonably re-identifiable" considering available technology and resources. Emphasizes context-dependent risk assessment.

## HIPAA Safe Harbor


Requires removal of 18 specific identifiers but often proves insufficient alone against sophisticated linkage attacks. Additional de-identification methods recommended.

## CCPA Requirements

California law mandates that anonymized data cannot be reasonably linked back to individuals or households, with ongoing monitoring obligations.

# Differential Privacy: A Modern Approach

Differential privacy represents a paradigm shift in privacy protection, providing mathematical guarantees by adding carefully calibrated statistical noise to data or query results.



## Key Principles

- Formal privacy guarantees through epsilon parameters
- Plausible deniability for individual participation
- Resistant to auxiliary information attacks
- Composable across multiple queries

Unlike k-anonymity and l-diversity, differential privacy offers provable protection even when attackers possess arbitrary background knowledge.

# Two Core Techniques for Data Protection



## Generalizing the Data

Removing or replacing portions of data elements that could identify individuals, like area codes or phone numbers.



## Adding Noise to Data

Introducing mathematical noise that makes it difficult to determine if any individual is part of a data set.


# Differential Privacy: Mathematical Noise Protection

Differential privacy adds mathematical noise to data, making it nearly impossible to determine if any individual is part of a data set. The algorithm's output appears essentially the same whether any one person's information is included or excluded.




### Original Data Set

Raw data containing individual information.



### Add Mathematical Noise

Introduce controlled variations to obscure individual contributions.



### Protected Output

Results remain useful while protecting individual privacy.

# How Google anonymizes data



# Risk Assessment Methodologies

### Identify Assets

Catalog sensitive attributes and quasi-identifiers

### Analyze Threats

Model attacker capabilities and motivations



### Calculate Risk

Quantify likelihood and impact of re-identification

### Implement Controls

Deploy appropriate anonymization and access restrictions

### Monitor & Review

Continuously assess effectiveness and adapt to new threats




Defenses Against
Re-Identification Attacks

# Building Robust Privacy Protection

# Data Minimization

> The most effective defense is not collecting unnecessary data in the first place. Less data means less risk.



## Collection Limits

Gather only data essential for specific, defined purposes



## Retention Policies

Delete data when no longer needed; implement automatic expiration



## Access Control

Restrict data access to authorized personnel with legitimate needs



## Sharing Restrictions

Limit external data sharing to essential parties under strict agreements

# Strong Anonymization Protocols


Effective privacy protection requires layering multiple complementary techniques rather than relying on a single method.

### K-Anonymity

Ensure group indistinguishability

### L-Diversity

Maintain attribute variety



### Differential Privacy


Add statistical noise

### Testing

Validate effectiveness

### Regular Updates

Adapt to emerging threats



# Monitoring and Auditing

## Continuous Review

Establish ongoing monitoring programs to assess anonymization effectiveness:

- Track data access patterns
- Review re-identification attempts
- Monitor external data sources
- Audit compliance with protocols

## Simulated Attacks

Proactively test defenses through controlled re-identification attempts:

- Red team exercises
- Penetration testing
- Linkage attack simulations
- Vulnerability assessments

# Legal and Contractual Controls



## Data Sharing Agreements

Comprehensive contracts with strict privacy clauses, usage restrictions, breach notification requirements, and financial penalties for violations



## Regulatory Compliance

Adherence to GDPR, CCPA, HIPAA, FERPA, and industry-specific privacy regulations with regular compliance audits and documentation



## Ethical Guidelines

Institutional review board oversight, ethical impact assessments, and transparency with data subjects about anonymization limitations

# Synthetic Data as a Privacy-Preserving Alternative

Synthetic data generation creates artificial datasets that preserve statistical properties while eliminating links to real individuals, offering a powerful alternative to traditional anonymization.

### Statistical Fidelity

Maintains correlations and distributions for accurate analysis

### No Real Records

Immune to traditional linkage attacks since no actual individuals exist in data

### Validation Required

Must verify synthetic data doesn't accidentally memorize real patterns

# Summary and Key Takeaways



# Classical Models Provide Foundation but Have Limits

### K-Anonymity Benefits

Creates group indistinguishability and prevents unique record identification through generalization and suppression

### L-Diversity Enhancement


Addresses homogeneity attacks by ensuring diversity in sensitive attributes within equivalence groups

### Persistent Vulnerabilities

Both methods remain susceptible to sophisticated linkage attacks, background knowledge exploitation, and AI-powered inference techniques


# Quasi-Identifiers Are the Weak Link

> The seemingly innocuous attributes we overlook—ZIP code, birthdate, gender—become powerful identifiers when combined, creating unique fingerprints that betray anonymization efforts.




### Three Attributes

U.S. population uniquely identified by just ZIP, birthdate, gender




### Two Attributes

Identifiable with gender and detailed birthdate alone




### Fifteen Attributes

Nearly complete population identification with common demographic data

# Re-Identification Attacks Are Increasingly Sophisticated

The evolution of attack methodologies has dramatically outpaced traditional anonymization defenses, driven by AI capabilities and data abundance.



### Linkage Attacks

Cross-referencing with public records and databases



### Inference Attacks

Statistical and machine learning pattern exploitation



### AI-Powered Methods

Neural networks finding hidden relationships at scale

# Risk Assessment and Advanced Techniques Are Essential

### Differential Privacy

Provides mathematical guarantees through controlled noise addition, offering provable protection even against adversaries with extensive background knowledge

### Synthetic Data

Generates artificial datasets preserving statistical properties while eliminating direct links to real individuals, immune to traditional linkage attacks

Modern privacy protection requires moving beyond k-anonymity and l-diversity to leverage techniques with stronger theoretical foundations and practical resilience.




## Protecting Privacy in a Data-Driven World

# The Ongoing Challenge

> As data collection accelerates and attack methods evolve, safeguarding anonymity requires continuous vigilance, technological innovation, regulatory adaptation, and unwavering organizational commitment to privacy as a fundamental right.

### Vigilance

Constant monitoring of threats and vulnerabilities


### Innovation

Advancing privacy-enhancing technologies

### Responsibility

Ethical stewardship of personal data

# Adversarial Prompting with Lakera




https://gandalf.lakera.ai/baseline