OpenAl Platform

Speech to text

Copy page

Learn how to turn audio into text.

Overview

The Audio API provides two speech to text endpoints, [transcriptions] and [translations], based on our state-of-the-art open source large-v2 Whisper model. They can be used to:

Transcribe audio into whatever language the audio is in.

Translate and transcribe the audio into english.

File uploads are currently limited to 25 MB and the following input file types are supported:

```
mp3 , mp4 , mpeg , mpga , m4a , wav , and webm .
```

Quickstart

Transcriptions

The transcriptions API takes as input the audio file you want to transcribe and the desired output file format for the transcription of the audio. We currently support multiple input and output file formats.

```
Transcribe audio
                                                                                python $
                                                                                           币
1 from openai import OpenAI
2
   client = OpenAI()
3
  audio_file= open("/path/to/file/audio.mp3", "rb")
4
   transcription = client.audio.transcriptions.create(
5
       model="whisper-1",
6
       file=audio file
7
   )
8
9
10 print(transcription.text)
```

By default, the response type will be json with the raw text included.

```
{
    "text": "Imagine the wildest idea that you've ever had, and you're curious about how it
    might scale to something that's a 100, a 1,000 times bigger.
```

```
}
```

The Audio API also allows you to set additional parameters in a request. For example, if you want to set the response_format as text, your request would look like the following:

```
凸
Additional options
                                                                                python $
   from openai import OpenAI
   client = OpenAI()
3
   audio_file = open("/path/to/file/speech.mp3", "rb")
4
   transcription = client.audio.transcriptions.create(
       model="whisper-1",
6
7
       file=audio_file,
       response_format="text"
8
9
   )
10
11 print(transcription.text)
```

The API Reference includes the full list of available parameters.

Translations

The translations API takes as input the audio file in any of the supported languages and transcribes, if necessary, the audio into English. This differs from our /Transcriptions endpoint since the output is not in the original input language and is instead translated to English text.

```
Translate audio
                                                                                python 🗘
                                                                                            凸
  from openai import OpenAI
   client = OpenAI()
2
3
   audio_file = open("/path/to/file/german.mp3", "rb")
4
   transcription = client.audio.translations.create(
5
       model="whisper-1",
6
7
       file=audio file,
8
   )
9
10 print(transcription.text)
```

In this case, the inputted audio was german and the outputted text looks like:

```
Hello, my name is Wolfgang and I come from Germany. Where are you heading today?
```

We only support translation into English at this time.

Supported languages

We currently support the following languages through both the transcriptions and translations endpoint:

Afrikaans, Arabic, Armenian, Azerbaijani, Belarusian, Bosnian, Bulgarian, Catalan, Chinese, Croatian, Czech, Danish, Dutch, English, Estonian, Finnish, French, Galician, German, Greek, Hebrew, Hindi, Hungarian, Icelandic, Indonesian, Italian, Japanese, Kannada, Kazakh, Korean, Latvian, Lithuanian, Macedonian, Malay, Marathi, Maori, Nepali, Norwegian, Persian, Polish, Portuguese, Romanian, Russian, Serbian, Slovak, Slovenian, Spanish, Swahili, Swedish, Tagalog, Tamil, Thai, Turkish, Ukrainian, Urdu, Vietnamese, and Welsh.

While the underlying model was trained on 98 languages, we only list the languages that exceeded <50% word error rate (WER) which is an industry standard benchmark for speech to text model accuracy. The model will return results for languages not listed above but the quality will be low.

Timestamps

By default, the Whisper API will output a transcript of the provided audio in text. The timestamp_granularities[] parameter enables a more structured and timestamped json output format, with timestamps at the segment, word level, or both. This enables word-level precision for transcripts and video edits, which allows for the removal of specific frames tied to individual words.

```
python 🗘
                                                                                            Ð
Timestamp options
1 from openai import OpenAI
   client = OpenAI()
2
3
   audio_file = open("/path/to/file/speech.mp3", "rb")
4
5
   transcription = client.audio.transcriptions.create(
6
       file=audio_file,
7
       model="whisper-1",
       response format="verbose_json",
8
       timestamp_granularities=["word"]
9
10 )
11
12 print(transcription.words)
```

Longer inputs

By default, the Whisper API only supports files that are less than 25 MB. If you have an audio file that is longer than that, you will need to break it up into chunks of 25 MB's or less or used a compressed audio format. To get the best performance, we suggest that you avoid breaking the audio up mid-sentence as this may cause some context to be lost.

One way to handle this is to use the PyDub open source Python package to split the audio:

```
币
  from pydub import AudioSegment
1
2
  song = AudioSegment.from_mp3("good_morning.mp3")
3
4
5
  # PyDub handles time in milliseconds
  ten_minutes = 10 * 60 * 1000
6
7
8
  first_10_minutes = song[:ten_minutes]
9
10 first_10_minutes.export("good_morning_10.mp3", format="mp3")
```

OpenAl makes no guarantees about the usability or security of 3rd party software like PyDub.

Prompting

You can use a prompt to improve the quality of the transcripts generated by the Whisper API. The model tries to match the style of the prompt, so it's more likely to use capitalization and punctuation if the prompt does too. However, the current prompting system is more limited than our other language models and provides limited control over the generated audio.

Here are some examples of how prompting can help in different scenarios:

- Prompts can help correct specific words or acronyms that the model misrecognizes in the audio. For example, the following prompt improves the transcription of the words DALL-E and GPT-3, which were previously written as "GDP 3" and "DALI": "The transcript is about OpenAI which makes technology like DALL-E, GPT-3, and ChatGPT with the hope of one day building an AGI system that benefits all of humanity."
- To preserve the context of a file that was split into segments, prompt the model with the transcript of the preceding segment. The model uses relevant information from the previous audio, improving transcription accuracy. The model only considers the final 224 tokens of the prompt and ignores anything earlier. For multilingual inputs, Whisper uses a custom tokenizer. For English-only inputs, it uses the standard GPT-2 tokenizer. Find both tokenizers in the open source Whisper Python package.
- 3 Sometimes the model skips punctuation in the transcript. To prevent this, use a simple prompt that includes punctuation: "Hello, welcome to my lecture."
- 4 The model may also leave out common filler words in the audio. If you want to keep the filler words in your transcript, use a prompt that contains them: "Umm, let me think like, hmm... Okay, here's what I'm, like, thinking."
- Some languages can be written in different ways, such as simplified or traditional Chinese. The model might not always use the writing style that you want for your transcript by default. You can improve this by using a prompt in your preferred writing style.

Improving reliability

One of the most common challenges faced when using Whisper is the model often does not recognize uncommon words or acronyms. Here are some different techniques to improve the reliability of Whisper in these cases:

- > Using the prompt parameter
- > Post-processing with GPT-4