Rapport de tests baseline (couverture de la build cert)

Date et révision : voir l'en-tête du bloc « Totaux de tests » (généré). **Toolchain :** Rust 1.98.1 épinglée (`rust-toolchain.toml`), edition 2024, workspace Cargo, Tauri v2. **Objet :** Photographier la posture de tests à la date de soumission, afin que tout mouvement de tests ultérieur puisse être tracé et attribué à des modifications futures.

Vérification de build

Configuration	Commande	Résultat
Par défaut (dev)	`cargo check --package pili-pos`	OK vert
Certification	`cargo check --package pili-pos --no-default-features --features cert`	OK vert

Vérification du périmètre du binaire cert (`scripts/build_and_hash.sh`) :

```
strings target/release/pili-pos | grep -c integration_switch_log  # > 0 : commandes en ligne présente
nm target/release/pili-pos | grep -c pos_peppol                   # 0 : facturation B2B absente
```

Les commandes en ligne font partie du binaire certifié et s'activent par installation (`COMMANDES_EN_LIGNE_FR.md`) ; la facturation B2B (feature `peppol`) en est absente.

—|—| | Par défaut | **493** | | Cert (`--no-default-features --features cert`) | **0** |

Les colonnes de schéma liées aux intégrations webshop (noms de colonnes du schéma SQL embarqué dans `pos-db`) restent présentes dans la définition du schéma pour compatibilité de lecture avec des bases créées par une build dev. Aucun chemin de code vivant n'écrit ces colonnes dans la build cert.

Totaux de tests

Les totaux ci-dessous ne sont jamais recopiés à la main : ils sont régénérés par `scripts/generate_test_report.py`, qui exécute les deux suites et réécrit le bloc. La colonne « Couche » reprend la première phrase du commentaire de module (`//!`) de chaque binaire de test. Le script est relancé sur la révision soumise, avant l'envoi ; la CI exécute les mêmes suites à chaque push.

Généré le 2026-09-26 13:16 (Europe/Brussels) sur la révision `3c91719`.

Workspace, fonctionnalités par défaut (`cargo test --workspace`)

Binaire de test	Couche	Passants	Échecs	Ignorés
`pili_pos` (unit)	Library facade for the pili-pos binary.	48	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`access_control` (intégration)	Who may do what (`PROFILS_UTILISATEURS_FR.md` §2–3), enforced by the backend whatever the UI shows	17	0	0
`admission_mock` (intégration)	The admission image runs pili-pos against `pos-fdm-mock` (the examiners' machine has no real FDM until the kit arrives).	3	0	0
`config_check` (intégration)	A fiscal identity the FDM would refuse is reported by the settings the UI reads at start-up, so it is fixed before the first sale.	2	0	0
`error_codes` (intégration)	Every error code the backend can return has a text in the three languages of the screen (`ui/src/i18n.ts`, key `err_<code>`), so a refusal is never shown as…	3	0	0
`order_commands` (intégration)	The order commands the order screen calls on every tap: start an order, add / change / remove lines, reload it.	22	0	0
`refund_guards` (intégration)	A refund pays money out: whatever stops it must leave nothing a cashier could complete later.	5	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`remote_support` (intégration)	Remote support (RustDesk) is started from the POS by the logged-in manager, confirmed by their PIN, one session at a time, and stopped by a manager…	11	0	0
`spf_e2e_basic` (intégration)	Application-level e2e tests for the SPF Finances Basic Set v1.7.	16	0	0
`spf_e2e_concurrency` (intégration)	Two sign calls firing at once on the same order/label.	3	0	0
`spf_e2e_crash_safety` (intégration)	Crash safety: what happens when something goes wrong strictly AFTER the FDM has successfully signed an event, but BEFORE the local commit finishes.	2	0	0
`spf_e2e_digital` (intégration)	Ticket delivery end to end: paper, email, or both (cert manual §III.H), through the real checkout, refund and copy commands.	30	0	0
`spf_e2e_fdm_failures` (intégration)	Exhaustive FDM-failure matrix for every fiscal command.	26	0	0
`spf_e2e_fdm_response_schema` (intégration)	Every fiscal command refuses an FDM response that does not answer its request.	13	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_fixtures` (intégration)	SPF Finances Basic Set v1.7, replayed from the official fixtures.	16	0	0
`spf_e2e_journal` (intégration)	Order-journal semantics through the command layer.	4	0	0
`spf_e2e_no_gap` (intégration)	Regression test: SCE 2.0 “strictly sequential, no gaps” counter.	3	0	0
`spf_e2e_peripherals` (intégration)	Printer, cash drawer and back-office commands, end to end.	18	0	0
`spf_e2e_report_fixtures` (intégration)	SPF Reports v1.3, replayed end to end through the real commands.	5	0	0
`spf_e2e_reports` (intégration)	Application-level e2e tests for the SPF Finances Reports v1.3 set.	4	0	0
`spf_e2e_service_day` (intégration)	A long, realistic service day driven entirely through the Tauri command layer: several tables, interleaved orders/corrections/…	1	0	0
`spf_e2e_validation` (intégration)	Input validation and auth checks across the command layer: unknown or inactive menu items, non-positive quantities, empty/zero-total checkouts, unknown ids…	16	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`ticket_copies` (intégration)	The copy picker lists what a customer can ask a copy of (manual §III, event C): sales, refunds, pre-bills and training tickets the FDM signed.	4	0	0
`pos_core` (unit)	Business types of the POS: configuration, catalogue, orders, tables, users and VAT.	57	0	0
`pos_db` (unit)	SQLite persistence: schema, migrations and typed queries, with the fiscal archive append-only.	107	0	0
`pos_fdm_mock` (unit)	Mock FDM (GraphQL SCE 2.0, erreurs au format de la spécification) and mock Scaleway TEM, for development, the admission image and screenshots.	15	0	0
`pos_fiscal` (unit)	SCE 2.0 protocol: event building, FDM client, counters, archive, tickets and reports.	139	0	0
`advanced_set_fixtures` (intégration)	SCE 2.0 Advanced Set v1.5 fixture validation.	1	0	0
`client_status` (intégration)	FdmClient status-query contract tests (Q100 / Q110).	3	0	0
`e2e_staging` (intégration)	Pre-submission rehearsal against a real virtual FDM.	0	0	2

Binaire de test	Couche	Passants	Échecs	Ignorés
`fdm_client_errors` (intégration)	fdm_client error-handling contract tests.	19	0	0
`full_service` (intégration)	Full Service Integration Test	1	0	0
`report_totals_fixtures` (intégration)	The SPF Reports v1.3 scenario, replayed through `report_totals`: the eight input tickets T1–T8 (their published requests and FDM responses) must add up to…	6	0	0
`reports_fixtures` (intégration)	SCE 2.0 Reports v1.3 fixture validation.	8	0	0
`spf_basic_set` (intégration)	SPF BasicSet Integration Tests	10	0	0
`uc_fixtures` (intégration)	SCE 2.0 Basic Set v1.7 fixture validation.	6	0	0
`pos_mail` (unit)	Digital ticket delivery: renders a signed [`pos_fiscal::ticket::FiscalTicket`] into an email, sends it via the Scaleway Transactional Email HTTP API, and…	46	0	0
`outbox` (intégration)	End-to-end outbox tests: `send_now` / `run_once` driving real SQLite (`pos-db`) rows against a mocked TEM endpoint (`wiremock`).	13	0	0
`tem_client` (intégration)	`TemClient` contract tests against a mocked Scaleway TEM endpoint.	15	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`pos_print` (unit)	ESC/POS printing: tickets, reports and cash drawer, in CP858.	99	0	0
`receipt_matrix` (intégration)	Every ticket type (N sale, N refund, P, C, T) in every ticket language (FR/NL/DE), rendered through the real `for-mat_receipt` pipeline: each must fit the 80…	9	0	0
`report_matrix` (intégration)	Every report type (X, Z, user X, user Z) in every ticket language (FR/NL/DE), rendered through the real `for-mat_report` / `for-mat_user_report` pipeline:…	7	0	0
`ticket_examples` (intégration)	§VI ticket-example generator.	9	0	0
Crates exclues de la build cert (unit)	intégrations hors v1.0.0	24	0	0
Total		**866**	**0**	**2**

Application, build cert (`cargo test -p pili-pos --no-default-features --features cert`)

Binaire de test	Couche	Passants	Échecs	Ignorés
`pili_pos` (unit)	Library facade for the pili-pos binary.	48	0	0
`access_control` (intégration)	Who may do what (`PROFILS_UTILISATEURS_FR.md` §2–3), enforced by the backend whatever the UI shows	17	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`admission_mock` (intégration)	The admission image runs pili-pos against `pos-fdm-mock` (the examiners' machine has no real FDM until the kit arrives).	3	0	0
`config_check` (intégration)	A fiscal identity the FDM would refuse is reported by the settings the UI reads at start-up, so it is fixed before the first sale.	2	0	0
`error_codes` (intégration)	Every error code the backend can return has a text in the three languages of the screen (`ui/src/i18n.ts`, key `err_<code>`), so a refusal is never shown as…	3	0	0
`order_commands` (intégration)	The order commands the order screen calls on every tap: start an order, add / change / remove lines, reload it.	22	0	0
`refund_guards` (intégration)	A refund pays money out: whatever stops it must leave nothing a cashier could complete later.	5	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`remote_support` (intégration)	Remote support (RustDesk) is started from the POS by the logged-in manager, confirmed by their PIN, one session at a time, and stopped by a manager…	11	0	0
`spf_e2e_basic` (intégration)	Application-level e2e tests for the SPF Finances Basic Set v1.7.	14	0	0
`spf_e2e_concurrency` (intégration)	Two sign calls firing at once on the same order/label.	3	0	0
`spf_e2e_crash_safety` (intégration)	Crash safety: what happens when something goes wrong strictly AFTER the FDM has successfully signed an event, but BEFORE the local commit finishes.	2	0	0
`spf_e2e_digital` (intégration)	Ticket delivery end to end: paper, email, or both (cert manual §III.H), through the real checkout, refund and copy commands.	30	0	0
`spf_e2e_fdm_failures` (intégration)	Exhaustive FDM-failure matrix for every fiscal command.	26	0	0
`spf_e2e_fdm_response_schema` (intégration)	Every fiscal command refuses an FDM response that does not answer its request.	13	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_fixtures` (intégration)	SPF Finances Basic Set v1.7, replayed from the official fixtures.	16	0	0
`spf_e2e_journal` (intégration)	Order-journal semantics through the command layer.	4	0	0
`spf_e2e_no_gap` (intégration)	Regression test: SCE 2.0 “strictly sequential, no gaps” counter.	3	0	0
`spf_e2e_peripherals` (intégration)	Printer, cash drawer and back-office commands, end to end.	18	0	0
`spf_e2e_report_fixtures` (intégration)	SPF Reports v1.3, replayed end to end through the real commands.	5	0	0
`spf_e2e_reports` (intégration)	Application-level e2e tests for the SPF Finances Reports v1.3 set.	4	0	0
`spf_e2e_service_day` (intégration)	A long, realistic service day driven entirely through the Tauri command layer: several tables, interleaved orders/corrections/…	1	0	0
`spf_e2e_validation` (intégration)	Input validation and auth checks across the command layer: unknown or inactive menu items, non-positive quantities, empty/zero-total checkouts, unknown ids…	16	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`ticket_copies` (intégration)	The copy picker lists what a customer can ask a copy of (manual §III, event C): sales, refunds, pre-bills and training tickets the FDM signed.	4	0	0
Total		**270**	**0**	**0**

Les tests ignorés de `e2e_staging` (niveau client FDM) et de `live_fdm` (journée d'exploitation par les vraies commandes) constituent le harness de répétition pré-soumission ; ils requièrent un vrai FDM, le simulateur en ligne module2, et s'exécutent via `scripts/live_fdm.sh` (ou `cargo test --package pos-fiscal --test e2e_staging -- --ignored`). Ils ne font PAS partie de la barrière CI hors-ligne.

L'interface est couverte à part, par Playwright (`ui/e2e/`, IPC Tauri simulée) : `cd ui && npx playwright test`. Dernier passage (2026-09-26) : 157 passants, 0 échec, 0 ignoré.

Le vrai binaire de certification, avec sa base SQLite et son IPC réels, est piloté à part par WebDriver (`tauri-driver` + `WebKitWebDriver`) : `ui/e2e/real-binary/integration.test.mjs`, job CI `integration` (connexion, tables, menu du jeu d'essai, ajout d'une ligne et total).

Familles de tests

Finalité	Binaires de test
Domaine et noyau fiscal (unit)	`pos_core`, `pos_db`, `pos_fiscal`, `pos_print`, `pos_mail`, `pos_fdm_mock`
Formes des fixtures SPF Finances (requêtes et réponses officielles)	`uc_fixtures`, `reports_fixtures`, `advanced_set_fixtures`
Client FDM : aller-retour par mutation, statut, erreurs	`spf_basic_set`, `full_service`, `client_status`, `fdm_client_errors`
Rejeu des UC officiels à travers les commandes réelles (requête construite par pili-pos comparée à la fixture)	`spf_e2e_fixtures`, `spf_e2e_report_fixtures`, `report_totals_fixtures`
Orchestration applicative (commande → FDM → transaction → archive)	`spf_e2e_basic`, `spf_e2e_reports`, `spf_e2e_journal`, `spf_e2e_service_day`, `order_commands`
Numérotation sans trou, pannes FDM, crash, concurrence	`spf_e2e_no_gap`, `spf_e2e_fdm_failures`, `spf_e2e_crash_safety`, `spf_e2e_concurrency`
Profils utilisateurs, validation des entrées, remboursements, configuration	`access_control`, `spf_e2e_validation`, `refund_guards`, `config_check`
Ticket numérique, impression, tiroir	`spf_e2e_digital`, `outbox`, `tem_client`, `spf_e2e_peripherals`, `receipt_matrix`, `ticket_examples`
Image d'admission (POS contre `pos-fdm-mock`)	`admission_mock`

Rot de tests pré-existant corrigé lors du baselining

Les deux tests d'intégration pos-fiscal ne compilaient plus contre l'API actuelle. Corrigé :

Fichier	Sites	Raison
`crates/pos-fiscal/tests/full_service.rs`	5	Champ `backup_dir` manquant sur `PosConfig` ; champ `rounding` manquant sur `TicketParams` (×2) ; 8e argument `Option<&FdmReference>` manquant sur `build_sale_input` (×2).
`crates/pos-fiscal/tests/spf_basic_set.rs`	6	`backup_dir` manquant sur `PosConfig` ; 8e argument manquant sur `build_sale_input` (×5).

Toutes les corrections étaient mécaniques - `None` pour les nouveaux champs/arguments optionnels. Aucun changement de sémantique de test.

Mises en conformité lors de cette baseline

Fichier	Changement
`src-tauri/Cargo.toml`	Feature `cert` = `custom-protocol` + `hubrise` ; la facturation B2B (`peppol`) reste hors du binaire cert.
`src-tauri/src/main.rs`	Commandes Tauri de la facturation B2B gardées derrière `#[cfg(feature = "peppol")]`.
`src-tauri/src/commands/checkout.rs`	**Bug fix** : passait `restaurant_est_no: ""` à `TicketParams`, passe désormais `&config.restaurant_est_no`.
`ui/src/router/index.ts`	Écran des commandes en ligne accessible seulement si l'intégration est activée pour l'installation.

Limitations connues / suivis

- **Commandes en ligne** : présentes dans le binaire cert, coupées par défaut (`hubrise_enabled: false`) ; un Gérant les active dans Réglages, chaque changement est journalisé.
- **Endpoint healthcheck** (`127.0.0.1:9999`) : une variante liveness-only cert-friendly est planifiée pour un futur polissage UI.
- **Playwright** : hors du tableau ci-dessus (généré depuis `cargo test`), totaux donnés plus haut ; la CI (`.github/workflows/test.yml`) le relance à chaque push.

Reproductibilité

```
cd pili-pos

# Build dev (features par défaut)
cargo test --workspace --no-fail-fast

# Build certification
```

```
cargo build --package pili-pos --no-default-features --features cert
nm target/debug/pili-pos | grep -c pos_peppol   # → 0

# Build UI (un seul bundle, commandes en ligne activées à l'exécution)
npm --prefix ui run build
```