Rapport de tests baseline (couverture de la build cert)

Date et révision : voir l'en-tête du bloc « Totaux de tests » (généré). **Toolchain :** Rust 1.99.0 épinglée (`rust-toolchain.toml`), edition 2024, workspace Cargo, Tauri v2. **Objet :** Photographier la posture de tests à la date de soumission, afin que tout mouvement de tests ultérieur puisse être tracé et attribué à des modifications futures.

Vérification de build

Configuration	Commande	Résultat
Par défaut (dev)	`cargo check --package pili-pos`	OK vert
Certification	`cargo check --package pili-pos --no-default-features --features cert`	OK vert

Vérification du périmètre du binaire cert (`scripts/build_and_hash.sh`) :

```
strings target/release/pili-pos | grep -c integration_switch_log  # > 0 : commandes en ligne présente
nm target/release/pili-pos | grep -c pos_peppol                   # compte informatif : code de facturation
```

Les commandes en ligne font partie du binaire certifié et s'activent par installation (`COMMANDES_EN_LIGNE_FR.md`) ; la facturation B2B (événement I) et la file d'envoi Peppol en font partie aussi, sans fonction Cargo (`FACTURATION_PEPPOL_FR.md`).

—|—| | Par défaut | **493** | | Cert (`--no-default-features --features cert`) | **0** |

Les colonnes de schéma liées aux intégrations webshop (noms de colonnes du schéma SQL embarqué dans `pos-db`) restent présentes dans la définition du schéma pour compatibilité de lecture avec des bases créées par une build dev. Aucun chemin de code vivant n'écrit ces colonnes dans la build cert.

Totaux de tests

Les totaux ci-dessous ne sont jamais recopiés à la main : ils sont régénérés par `scripts/generate_test_report.py`, qui exécute les deux suites et réécrit le bloc. La colonne « Couche » reprend la première phrase du commentaire de module (`//!`) de chaque binaire de test. Le script est relancé sur la révision soumise, avant l'envoi ; la CI exécute les mêmes suites à chaque push.

Généré le 2026-10-18 15:30 (Europe/Brussels) sur la révision `fd521e60`.

Workspace, fonctionnalités par défaut (`cargo test --workspace`)

Binaire de test	Couche	Passants	Échecs	Ignorés
`pili_pos` (unit)	Library facade for the pili-pos binary.	8	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`ipc_wrappers` (intégration)	The IPC wrappers of the table transfer, the payment correction, the till discounts and the kitchen note, called as the webview calls them: the command name…	6	0	0
`pos_accounting` (unit)	Accountant export of the till's signed archive.	32	0	0
`cli` (intégration)	The pili-accounting command line: exit codes and messages.	4	0	0
`isolation` (intégration)	V12-D5: the accountant export is outside the certified binary.	4	0	0
`reconcile_report` (intégration)	The day export on real archives built by the engine.	3	0	0
`synthetic` (intégration)	The export on a synthetic archive: golden files, the files' semantics (what is read and what is ignored), the journal, the profiles and the guards on the…	27	0	0
`pos_catalog` (unit)	The POS menu as a mirror of an external catalog.	13	0	0
`apply` (intégration)	Applying a catalog to a real POS database.	20	0	0
`pos_core` (unit)	Business types of the POS: configuration, catalogue, orders, tables, users and VAT.	99	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`pos_db` (unit)	SQLite persistence: schema, migrations and typed queries, with the fiscal archive append-only.	212	0	0
`pos_eft` (unit)	The card payment terminal linked to the till (EFT).	66	0	0
`control` (intégration)	The control API and the page, over real HTTP.	3	0	0
`pos_eft_probe` (unit)	The logic of pos-eft-probe: the four commands against a [Terminal], the YES prompt, the masked trace file.	4	0	0
`probe` (intégration)	The probe's commands against pos-eft-mock (OPI), with a scripted stdin: nothing leaves 127.0.0.1.	5	0	0
`pos_engine` (unit)	Tauri-free engine of pili-pos.	208	0	0
`access_control` (intégration)	Who may do what (PROFILS_UTILISATEURS_FR.md §2–3), enforced by the backend whatever the UI shows	30	0	0
`admission_mock` (intégration)	The admission image runs pili-pos against pos-fdm-mock (the examiners' machine has no real FDM until the kit arrives).	4	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`allergens` (intégration)	The 14 EU allergens (V12-D17 to D21): the catalog import with its change log, the local edit and its lock while a source manages the menu, the sheet shown…	15	0	0
`background` (intégration)	The engine's background loops: they run on the runtime the shell hands over, tick at the configured intervals, and stop on shutdown.	2	0	0
`badges` (intégration)	Staff badges (lane 5): the setting, enrolment, revocation and the scan (badge_tap).	44	0	0
`config_check` (intégration)	A fiscal identity the FDM would refuse is reported by the settings the UI reads at start-up, so it is fixed before the first sale.	5	0	0
`courses` (intégration)	Courses and "Envoyer la suite" (V12-D22 and V12-D23).	23	0	0
`eft_drivers` (intégration)	A card payment through the real terminal drivers (pos-eft) against the terminal mock (pos-eft-mock, served in-process), from the terminal call to the signed…	4	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`eft_payments` (intégration)	A card payment taken on the linked terminal, from the request to the sale that settles it (commands::eft, commands::checkout).	38	0	0
`eft_signing` (intégration)	Card payments taken on the linked terminal and the signature of the sale that settles them: they are marked used in the sale's own commit, also when the…	11	0	0
`error_codes` (intégration)	Every error code the backend can return has a text in the three languages of the screen (ui/src/i18n.ts, key err_), so a refusal is never shown as a…	10	0	0
`export_nightly` (intégration)	The nightly export in the engine (phase X1, card X1-T6): after a real Z the engine builds the three files and uploads them to the endpoint of the export…	13	0	0
`fdm_monitor` (intégration)	The engine monitors the FDM status (planner decision PD36): while a session is open, never without one.	11	0	0
`fdm_status_cache` (intégration)	The header polls the FDM status from every screen that shows it.	3	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`gift_vouchers` (intégration)	Multi-purpose gift vouchers (V12-D24 to V12-D31): sale as a VAT X line, redemption as a VOUCHER_STORE payment, balance and expiry, refunds, prints, lookup.	41	0	0
`hubrise_cancellations` (intégration)	Online orders HubRise cancels or changes after the POS got them.	15	0	0
`hubrise_catalog` (intégration)	The POS menu mirrors the HubRise catalog: applied at start, on a catalog event and by the drift check, with stable product ids, the VAT labels of the…	13	0	0
`hubrise_config` (intégration)	The installation's HubRise client comes from the hubrise section of pos.json, its secret from a file.	5	0	0
`hubrise_discounts` (intégration)	Discounts on online orders: each is spread over the product lines (the cent to the largest share) and sent as a priceChange of scope EVENT on every line it…	4	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`hubrise_gift_vouchers` (intégration)	What the HubRise echo of a till sale does with gift vouchers (V12-D31): a sale that sells a voucher is not echoed, a voucher payment goes out as HubRise's…	2	0	0
`hubrise_inventory` (intégration)	Sold-out products pushed to the HubRise inventory (V11-D15), against the in-process mock.	12	0	0
`hubrise_modifiers` (intégration)	Products with options on the order screen: the groups come from the mirrored catalog, the backend checks each group's minimum and maximum, prices the…	6	0	0
`hubrise_orders_ingest` (intégration)	Online orders from the mock reach the board resolved against the menu, acknowledged, and never among the POS's tables and takeaways.	9	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`hubrise_orders_engine` (intégration)	Ordering orders signed by the FDM: prepaid ones end in an N at acceptance (APP or ONLINE), unpaid ones in a P at acceptance then an N at handover with the…	16	0	0
`hubrise_print_access` (intégration)	Workshop slips are reprinted by logged-in staff only.	1	0	0
`hubrise_switch` (intégration)	The installation's HubRise switch.	5	0	0
`hubrise_transport` (intégration)	HubRise transport against the in-process mock: callback registration, event polling, acknowledge-ments, the outbox, errors.	17	0	0
`idle_lock` (intégration)	The engine owns the idle lock (planner decision PD35): a session with no activity for timers.idle_lock is locked by the idle loop of background.rs, through…	7	0	0
`invoice_advanced` (intégration)	UC4121 (invoice of three sales) and UC4122 (invoice of a refund and two sales) of the Advanced Set 1.6, replayed field by field against the published…	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`invoice_content` (intégration)	What an invoice contains (V11-D3): the lines, the price changes and the VAT are read from the archive of the signed sales, never supplied by the screen.	1	0	0
`invoice_rules` (intégration)	The rules of B2B invoices (event I, M150): one invoice per sale, no invoice in training mode, only normal sales, a continuous numbering, a crash between the…	14	0	0
`kitchen_notes` (intégration)	Kitchen notes on order lines (migration 31, do_set_line_note): the validation, the rule that a note is local data and never part of any fiscal message or…	18	0	0
`lane_interactions` (intégration)	Where lane 4 (owner features: allergens, courses, gift vouchers) meets the till work of the other lanes on android/int (decisions INT-D12 to INT-D21 in…	16	0	0
`live_combined` (intégration)	Online orders end to end, live on both sides: the orders come from the real HubRise API (test location), and their events are signed by a live FDM (the…	0	0	2

Binaire de test	Couche	Passants	Échecs	Ignorés
`live_fdm` (intégration)	An operator day signed by a live FDM (the module2 cloud simulator).	0	0	6
`live_hubrise` (intégration)	The HubRise integration against the real HubRise API, on a test location, with the FDM mock signing.	0	0	3
`menu_editor` (intégration)	The on-screen menu editor (V11-D17, V11-D18): create and update of the four entities, the validation codes, the append-only log, the lock while a source…	11	0	0
`order_commands` (intégration)	The order commands the order screen calls on every tap: start an order, add / change / remove lines, reload it.	22	0	0
`owner_alerts` (intégration)	The owner alerts: a Telegram message when the FDM, a printer or the card terminal is down, the day has no Z, or an online order waits.	31	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`payment_correction` (intégration)	Correcting the payment method of a sale (event F, signPayment-Correction, Basic Set M132, com-mands/payment_correction.rs): every refusal, one correction per…	25	0	0
`peppol_queue` (intégration)	The Peppol delivery queue (V11-D12) against the Storecove mock of pos-fdm-mock: accepted, a 503 then accepted after the backoff, a refusal parked, a…	15	0	0
`presence` (intégration)	Presence belongs to the engine	9	0	0
`presence_manager` (intégration)	A manager registers the presence of another employee (kitchen staff who never use the till, or anyone who forgot): clock_in_employee and clock_out_employee.	18	0	0
`printer_status_timeout` (intégration)	The wait for the printer's DLE EOT answer is the engine's Engine-Timers::printer_status_read (PD37): a printer that answers late is read with a longer wait…	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`refund_guards` (intégration)	A refund pays money out: whatever stops it must leave nothing a cashier could complete later.	7	0	0
`remote_support` (intégration)	Remote support (RustDesk) is started from the POS by the logged-in manager, confirmed by their PIN, one session at a time.	14	0	0
`sales_report` (intégration)	Non-fiscal sales reports (V11-D20): the Reports 1.3 service day replayed through the real commands must give a sales report whose total is the turnover of…	12	0	0
`screen_state` (intégration)	State the screens read back from the backend, beyond the fiscal record itself	3	0	0
`session_rules` (intégration)	The engine owns leaving an order and the screen lock	19	0	0
`settings_version` (intégration)	get_settings carries the software version (posSwVersion, AM Art.	1	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`sold_out` (intégration)	Sold-out products (“Épuisé”, V11-D14): the till refuses a sold-out product, the state expires by time, every change is logged, and nothing fiscal is touched.	10	0	0
`spf_e2e_auto_z` (intégration)	Producers FAQ Q501c: “En cas de dépassement, la caisse créera automatique-ment un event R par période de booking date manquante.”	5	0	0
`spf_e2e_bar_slip` (intégration)	Bar / kitchen order slip (traceability ID VI_BAR, SPF example bar ticket of 2026-09-24).	11	0	0
`spf_e2e_basic` (intégration)	Application-level e2e tests for the SPF Finances Basic Set v1.8.	17	0	0
`spf_e2e_concurrency` (intégration)	Two sign calls firing at once on the same order/label.	3	0	0
`spf_e2e_copy_refund` (intégration)	What the copy and refund tickets show (SPF example tickets of 2026-09-24, POS description v2.2 §1.8, §6.5, §6.6).	9	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_crash_safety` (intégration)	Crash safety: what happens when something goes wrong strictly AFTER the FDM has successfully signed an event, but BEFORE the local commit finishes.	2	0	0
`spf_e2e_digital` (intégration)	Ticket delivery end to end: paper, email, or both (cert manual §III.H), through the real checkout, refund and copy commands.	34	0	0
`spf_e2e_faq` (intégration)	Rules of the SPF producers' FAQ (20260717) that no Basic Set or Reports scenario exercises on its own, played through the commands the UI calls.	7	0	0
`spf_e2e_fdm_failures` (intégration)	Exhaustive FDM-failure matrix for every fiscal command.	29	0	0
`spf_e2e_fdm_response_check` (intégration)	Every fiscal command refuses an FDM response that does not answer its request.	13	0	0
`spf_e2e_fixtures` (intégration)	SPF Finances Basic Set v1.8, replayed from the official fixtures.	27	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_gift_vouchers` (intégration)	SPF Finances Advanced Set v1.6, multi-purpose vouchers (UC260 sale, UC261 and UC262 use), replayed from the official fixtures.	3	0	0
`spf_e2e_journal` (intégration)	Order-journal semantics through the command layer.	4	0	0
`spf_e2e_no_gap` (intégration)	Regression test: SCE 2.0 “strictly sequential, no gaps” counter.	2	0	0
`spf_e2e_payments` (intégration)	How a sale’s payment reaches the FDM.	8	0	0
`spf_e2e_peripherals` (intégration)	Printer, cash drawer and back-office commands, end to end.	18	0	0
`spf_e2e_report_fixtures` (intégration)	SPF Reports v1.3, replayed end to end through the real commands.	14	0	0
`spf_e2e_report_print` (intégration)	The printed X and Z turnover reports carry what the AM of 29 April 2024 art.	2	0	0
`spf_e2e_reports` (intégration)	Application-level e2e tests for the SPF Finances Reports v1.3 set.	4	0	0
`spf_e2e_rounding` (intégration)	Certification manual, “Arrondissement des méthodes de paiement”: the five situations, with their evidence.	6	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_service_day` (intégration)	A long, realistic service day driven entirely through the Tauri command layer: several tables, interleaved orders/corrections/…	1	0	0
`spf_e2e_signing_sessions` (intégration)	Concurrent signing lock, and requests whose answer was lost.	14	0	0
`spf_e2e_split_payment` (intégration)	A sale paid in several parts: card, meal vouchers and cash for the rest, through the command the checkout screen calls.	9	0	0
`spf_e2e_unpaid` (intégration)	A sale closed without payment: the customer left without paying (Advanced Set UC4109, commands/unpaid.rs).	10	0	0
`spf_e2e_validation` (intégration)	Input validation and auth checks across the command layer: unknown or inactive menu items, non-positive quantities, empty/zero-total checkouts, unknown ids…	16	0	0
`table_plan` (intégration)	The table plan: the numbers the Tables screen shows, set by a manager, every change logged, and no open order ever hidden.	5	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`table_transfer` (intégration)	Moving an open order to another table (event P, signCostCenter-Change, Basic Set M122): the refusals, the order of the events, the table that changes only…	22	0	0
`ticket_copies` (intégration)	The copy picker lists what a customer can ask a copy of (manual §III, event C): sales, refunds, pre-bills and training tickets the FDM signed.	4	0	0
`till_discounts` (intégration)	Discounts at the till (manager PIN): an order discount in percent, amount or “Offert”, and one free line, as priceChanges inside the sale N and the table…	36	0	0
`pos_export` (unit)	Nightly export of a pili-pos installation (phase X1, decisions X1D4 to X1D9).	50	0	0
`outbox` (intégration)	-	17	0	0
`outbox_upload` (intégration)	The upload passes of the outbox against the mock receiver (card X1-T5, decision X1D8): order, hashes, backoff, unauthorized, retry now, retention of sent…	11	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`stats_build` (intégration)	Content of the statistics file built from the shared fixture (card X1-T3).	15	0	0
`stats_privacy` (intégration)	The privacy proof of the statistics file (card X1-T3): a database full of personal data goes in, nothing of it comes out.	11	0	0
`upload` (intégration)	The upload client against the mock receiver (card X1-T4, decision X1D8).	15	0	0
`pos_export_mock` (unit)	Test receiver of the nightly export (phase X1, decision X1D8): the HTTPS PUT endpoint the POS uploads the encrypted backup, the statistics file and the…	14	0	0
`pos_export_mock` (unit)	pos-export-mock –listen ADDR –token-file FILE [–dir DIR]: the test receiver of the nightly export as a standalone process, for manual runs and for the…	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`pos_fdm_mock` (unit)	Mock FDM (SCE 2.0 GraphQL) and mock Scaleway TEM, for development, the admission image, screenshots and the certification evidence.	30	0	0
`module2_shape` (intégration)	The mock answers in the shape of module2's simulator.	1	0	0
`pos_fiscal` (unit)	SCE 2.0 protocol: event building, FDM client, counters, archive, tickets and reports.	205	0	0
`advanced_set_fixtures` (intégration)	SCE 2.0 Advanced Set v1.6 fixture validation.	1	0	0
`client_auth` (intégration)	FdmClient bearer token: a cloud FDM (the module2 simulator) needs Authorization: Bearer ; a LAN FDM gets no such header.	4	0	0
`client_status` (intégration)	FdmClient status-query contract tests (Q100 / Q110).	5	0	0
`e2e_staging` (intégration)	Pre-submission rehearsal against a real virtual FDM.	0	0	2
`fdm_client_errors` (intégration)	fdm_client error-handling contract tests.	21	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`fdm_https_mock` (intégration)	The POS's HTTPS to the FDM, offline: the mock FDM serves TLS like module2 (an X.509 v1 server certificate without names, signed by its CA) and here requires…	3	0	0
`fdm_tls` (intégration)	The FDM's certificate is trusted on its CA's signature and its dates (pos_fiscal::fdm_tls), with module2's real certificates: fix- tures/module2_tls/ca.crt…	6	0	0
`full_service` (intégration)	Full Service Integration Test	1	0	0
`module2_recorded` (intégration)	What module2's simulator really answered (recorded on 2026-09-27 in crates/pos-fdm-mock/fixtures/module2/) goes through the POS's own parsing and response…	3	0	0
`price_change_uc` (intégration)	Price changes against the SPF's own examples: the transaction the POS builds for Advanced Set UC223 (a 50 % ticket discount spread over two lines at B and…	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`report_totals_fixtures` (intégration)	The SPF Reports v1.3 scenario, replayed through report_totals: the eight input tickets T1–T8 (their published requests and FDM responses) must add up to the…	6	0	0
`reports_fixtures` (intégration)	SCE 2.0 Reports v1.3 fixture validation.	8	0	0
`sign_messages` (intégration)	POS description v2.2, Message: a warning the FDM attaches to a mutation's response is shown at least once per bookingDate.	1	0	0
`sign_request` (intégration)	Sign requests are kept byte for byte, so one whose answer was lost is sent again identically (POS description v2.2, duplicate requests).	6	0	0
`spf_basic_set` (intégration)	SPF BasicSet Integration Tests	10	0	0
`uc_fixtures` (intégration)	SCE 2.0 Basic Set v1.8 fixture validation.	6	0	0
`webshop_resolve` (intégration)	Online orders resolved against a POS menu that mirrors the mock's seed catalog: every template, and every reason an order is held.	23	0	0
`hubrise_shape` (intégration)	The mock answers in the shape of the real HubRise API.	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`router` (intégration)	The mock's HTTP API, driven in-process with tower::oneshot.	24	0	0
`doc_samples` (intégration)	The JSON samples of the HubRise API documentation (copied to tests/fixtures/) parse into the wire types, keep their ref fields, and survive a round trip.	10	0	0
`pos_mail` (unit)	Digital ticket delivery: renders a signed [pos_fiscal::ticket::FiscalTicket] into an email, sends it via the Scaleway Transactional Email HTTP API, and…	46	0	0
`outbox` (intégration)	-	13	0	0
`tem_client` (intégration)	TemClient contract tests against a mocked Scaleway TEM endpoint.	15	0	0
`pos_print` (unit)	ESC/POS printing: tickets, reports and cash drawer, in CP858.	163	0	0
`official_examples` (intégration)	Golden tests of the six SPF example tickets of 2026-09-24 (docs/20260904_Example_tickets/): the example's own data goes through the real print pipeline, and…	6	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`receipt_matrix` (intégration)	Every ticket type (N sale, N refund, P, C, T) in every ticket language (FR/NL/DE), rendered through the real format_receipt pipeline: each must fit the 80…	9	0	0
`report_matrix` (intégration)	Every report type (X, Z, user X, user Z) in every ticket language (FR/NL/DE), rendered through the real format_report / for-mat_user_report pipeline: each…	8	0	0
`ticket_examples` (intégration)	§VI ticket-example generator.	20	0	0
`pos_printer_mock` (unit)	A network thermal printer for development, demos and tests, standing in for the Epson TM-m30III the POS prints to (raw TCP, port 9100).	7	0	0
Crates exclues de la build cert (unit)	intégrations hors v1.0.0	97	0	0
Total		**2562**	**0**	**13**

Application, build cert (`cargo test -p pili-pos -p pos-engine --no-default-features --features cert`)

Binaire de test	Couche	Passants	Échecs	Ignorés
`pili_pos` (unit)	Library facade for the pili-pos binary.	8	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`ipc_wrappers` (intégration)	The IPC wrappers of the table transfer, the payment correction, the till discounts and the kitchen note, called as the webview calls them: the command name…	6	0	0
`pos_engine` (unit)	Tauri-free engine of pili-pos.	208	0	0
`access_control` (intégration)	Who may do what (PROFILS_UTILISATEURS_FR.md §2–3), enforced by the backend whatever the UI shows	30	0	0
`admission_mock` (intégration)	The admission image runs pili-pos against pos-fdm-mock (the examiners' machine has no real FDM until the kit arrives).	4	0	0
`allergens` (intégration)	The 14 EU allergens (V12-D17 to D21): the catalog import with its change log, the local edit and its lock while a source manages the menu, the sheet shown…	15	0	0
`background` (intégration)	The engine's background loops: they run on the runtime the shell hands over, tick at the configured intervals, and stop on shutdown.	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`badges` (intégration)	Staff badges (lane 5): the setting, enrolment, revocation and the scan (badge_tap).	44	0	0
`config_check` (intégration)	A fiscal identity the FDM would refuse is reported by the settings the UI reads at start-up, so it is fixed before the first sale.	5	0	0
`courses` (intégration)	Courses and “Envoyer la suite” (V12-D22 and V12-D23).	23	0	0
`eft_drivers` (intégration)	A card payment through the real terminal drivers (pos-eft) against the terminal mock (pos-eft-mock, served in-process), from the terminal call to the signed…	4	0	0
`eft_payments` (intégration)	A card payment taken on the linked terminal, from the request to the sale that settles it (commands::eft, com- mands::checkout).	38	0	0
`eft_signing` (intégration)	Card payments taken on the linked terminal and the signature of the sale that settles them: they are marked used in the sale’s own commit, also when the…	11	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`error_codes` (intégration)	Every error code the backend can return has a text in the three languages of the screen (ui/src/i18n.ts, key err_), so a refusal is never shown as a…	10	0	0
`export_nightly` (intégration)	The nightly export in the engine (phase X1, card X1-T6): after a real Z the engine builds the three files and uploads them to the endpoint of the export…	13	0	0
`fdm_monitor` (intégration)	The engine monitors the FDM status (planner decision PD36): while a session is open, never without one.	11	0	0
`fdm_status_cache` (intégration)	The header polls the FDM status from every screen that shows it.	3	0	0
`gift_vouchers` (intégration)	Multi-purpose gift vouchers (V12-D24 to V12-D31): sale as a VAT X line, redemption as a VOUCHER_STORE payment, balance and expiry, refunds, prints, lookup.	41	0	0
`hubrise_cancellations` (intégration)	Online orders HubRise cancels or changes after the POS got them.	15	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`hubrise_catalog` (intégration)	The POS menu mirrors the HubRise catalog: applied at start, on a catalog event and by the drift check, with stable product ids, the VAT labels of the…	13	0	0
`hubrise_config` (intégration)	The installation's HubRise client comes from the hubrise section of pos.json, its secret from a file.	5	0	0
`hubrise_discounts` (intégration)	Discounts on online orders: each is spread over the product lines (the cent to the largest share) and sent as a priceChange of scope EVENT on every line it…	4	0	0
`hubrise_gift_vouchers` (intégration)	What the HubRise echo of a till sale does with gift vouchers (V12-D31): a sale that sells a voucher is not echoed, a voucher payment goes out as HubRise's…	2	0	0
`hubrise_inventory` (intégration)	Sold-out products pushed to the HubRise inventory (V11-D15), against the in-process mock.	12	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`hubrise_modifiers` (intégration)	Products with options on the order screen: the groups come from the mirrored catalog, the backend checks each group's minimum and maximum, prices the…	6	0	0
`hubrise_orders_connect` (intégration)	Online orders from the mock reach the board resolved against the menu, acknowledged, and never among the POS's tables and takeaways.	9	0	0
`hubrise_orders_signing` (intégration)	Online orders signed by the FDM: prepaid ones end in an N at acceptance (APP or ONLINE), unpaid ones in a P at acceptance then an N at handover with the…	16	0	0
`hubrise_print_access` (intégration)	Webshop slips are reprinted by logged-in staff only.	1	0	0
`hubrise_switch` (intégration)	The installation's HubRise switch.	5	0	0
`hubrise_transport` (intégration)	HubRise transport against the in-process mock: callback registration, event polling, acknowledge-ments, the outbox, errors.	17	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`idle_lock` (intégration)	The engine owns the idle lock (planner decision PD35): a session with no activity for timers.idle_lock is locked by the idle loop of background.rs, through…	7	0	0
`invoice_advanced` (intégration)	UC4121 (invoice of three sales) and UC4122 (invoice of a refund and two sales) of the Advanced Set 1.6, replayed field by field against the published…	2	0	0
`invoice_content` (intégration)	What an invoice contains (V11-D3): the lines, the price changes and the VAT are read from the archive of the signed sales, never supplied by the screen.	1	0	0
`invoice_rules` (intégration)	The rules of B2B invoices (event I, M150): one invoice per sale, no invoice in training mode, only normal sales, a continuous numbering, a crash between the…	14	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`kitchen_notes` (intégration)	Kitchen notes on order lines (migration 31, do_set_line_note): the validation, the rule that a note is local data and never part of any fiscal message or…	18	0	0
`lane_interactions` (intégration)	Where lane 4 (owner features: allergens, courses, gift vouchers) meets the till work of the other lanes on android/int (decisions INT-D12 to INT-D21 in…	16	0	0
`live_combined` (intégration)	Online orders end to end, live on both sides: the orders come from the real HubRise API (test location), and their events are signed by a live FDM (the…	0	0	2
`live_fdm` (intégration)	An operator day signed by a live FDM (the module2 cloud simulator).	0	0	6
`live_hubrise` (intégration)	The HubRise integration against the real HubRise API, on a test location, with the FDM mock signing.	0	0	3

Binaire de test	Couche	Passants	Échecs	Ignorés
`menu_editor` (intégration)	The on-screen menu editor (V11-D17, V11-D18): create and update of the four entities, the validation codes, the append-only log, the lock while a source…	11	0	0
`order_commands` (intégration)	The order commands the order screen calls on every tap: start an order, add / change / remove lines, reload it.	22	0	0
`owner_alerts` (intégration)	The owner alerts: a Telegram message when the FDM, a printer or the card terminal is down, the day has no Z, or an online order waits.	31	0	0
`payment_correction` (intégration)	Correcting the payment method of a sale (event F, signPayment-Correction, Basic Set M132, com-mands/payment_correction.rs): every refusal, one correction per…	25	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`peppol_queue` (intégration)	The Peppol delivery queue (V11-D12) against the Storecove mock of pos-fdm-mock: accepted, a 503 then accepted after the backoff, a refusal parked, a…	15	0	0
`presence` (intégration)	Presence belongs to the engine	9	0	0
`presence_manager` (intégration)	A manager registers the presence of another employee (kitchen staff who never use the till, or anyone who forgot): clock_in_employee and clock_out_employee.	18	0	0
`printer_status_timeout` (intégration)	The wait for the printer's DLE EOT answer is the engine's Engine-Timers::printer_status_read (PD37): a printer that answers late is read with a longer wait…	2	0	0
`refund_guards` (intégration)	A refund pays money out: whatever stops it must leave nothing a cashier could complete later.	7	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`remote_support` (intégration)	Remote support (RustDesk) is started from the POS by the logged-in manager, confirmed by their PIN, one session at a time.	14	0	0
`sales_report` (intégration)	Non-fiscal sales reports (V11-D20): the Reports 1.3 service day replayed through the real commands must give a sales report whose total is the turnover of…	12	0	0
`screen_state` (intégration)	State the screens read back from the backend, beyond the fiscal record itself	3	0	0
`session_rules` (intégration)	The engine owns leaving an order and the screen lock	19	0	0
`settings_version` (intégration)	get_settings carries the software version (posSwVersion, AM Art.	1	0	0
`sold_out` (intégration)	Sold-out products (“Épuisé”, V11-D14): the till refuses a sold-out product, the state expires by time, every change is logged, and nothing fiscal is touched.	10	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_auto_z` (intégration)	Producers FAQ Q501c: “En cas de dépassement, la caisse créera automatique-ment un event R par période de booking date manquante.”	5	0	0
`spf_e2e_bar_slip` (intégration)	Bar / kitchen order slip (traceability ID VI_BAR, SPF example bar ticket of 2026-09-24).	11	0	0
`spf_e2e_basic` (intégration)	Application-level e2e tests for the SPF Finances Basic Set v1.8.	17	0	0
`spf_e2e_concurrency` (intégration)	Two sign calls firing at once on the same order/label.	3	0	0
`spf_e2e_copy_refund_tickets` (intégration)	What the copy and refund tickets show (SPF example tickets of 2026-09-24, POS description v2.2 §1.8, §6.5, §6.6).	9	0	0
`spf_e2e_crash_safety` (intégration)	Crash safety: what happens when something goes wrong strictly AFTER the FDM has successfully signed an event, but BEFORE the local commit finishes.	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_digital` (intégration)	Ticket delivery end to end: paper, email, or both (cert manual §III.H), through the real checkout, refund and copy commands.	34	0	0
`spf_e2e_faq` (intégration)	Rules of the SPF producers' FAQ (20260717) that no Basic Set or Reports scenario exercises on its own, played through the commands the UI calls.	7	0	0
`spf_e2e_fdm_failures` (intégration)	Exhaustive FDM-failure matrix for every fiscal command.	29	0	0
`spf_e2e_fdm_response` (intégration)	Every fiscal command refuses an FDM response that does not answer its request.	13	0	0
`spf_e2e_fixtures` (intégration)	SPF Finances Basic Set v1.8, replayed from the official fixtures.	27	0	0
`spf_e2e_gift_vouchers` (intégration)	SPF Finances Advanced Set v1.6, multi-purpose vouchers (UC260 sale, UC261 and UC262 use), replayed from the official fixtures.	3	0	0
`spf_e2e_journal` (intégration)	Order-journal semantics through the command layer.	4	0	0
`spf_e2e_no_gap` (intégration)	Regression test: SCE 2.0 "strictly sequential, no gaps" counter.	2	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_payments` (intégration)	How a sale's payment reaches the FDM.	8	0	0
`spf_e2e_peripherals` (intégration)	Printer, cash drawer and back-office commands, end to end.	18	0	0
`spf_e2e_report_fixtures` (intégration)	SPF Reports v1.3, replayed end to end through the real commands.	14	0	0
`spf_e2e_report_print` (intégration)	The printed X and Z turnover reports carry what the AM of 29 April 2024 art.	2	0	0
`spf_e2e_reports` (intégration)	Application-level e2e tests for the SPF Finances Reports v1.3 set.	4	0	0
`spf_e2e_rounding` (intégration)	Certification manual, "Arrondissement des méthodes de paiement": the five situations, with their evidence.	6	0	0
`spf_e2e_service_day` (intégration)	A long, realistic service day driven entirely through the Tauri command layer: several tables, interleaved orders/corrections/…	1	0	0
`spf_e2e_signing_versioning` (intégration)	One signing lock, and requests whose answer was lost.	14	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`spf_e2e_split_payment` (intégration)	A sale paid in several parts: card, meal vouchers and cash for the rest, through the command the checkout screen calls.	9	0	0
`spf_e2e_unpaid` (intégration)	A sale closed without payment: the customer left without paying (Advanced Set UC4109, commands/unpaid.rs).	10	0	0
`spf_e2e_validation` (intégration)	Input validation and auth checks across the command layer: unknown or inactive menu items, non-positive quantities, empty/zero-total checkouts, unknown ids…	16	0	0
`table_plan` (intégration)	The table plan: the numbers the Tables screen shows, set by a manager, every change logged, and no open order ever hidden.	5	0	0
`table_transfer` (intégration)	Moving an open order to another table (event P, signCostCenter-Change, Basic Set M122): the refusals, the order of the events, the table that changes only…	22	0	0

Binaire de test	Couche	Passants	Échecs	Ignorés
`ticket_copies` (intégration)	The copy picker lists what a customer can ask a copy of (manual §III, event C): sales, refunds, pre-bills and training tickets the FDM signed.	4	0	0
`till_discounts` (intégration)	Discounts at the till (manager PIN): an order discount in percent, amount or “Offert”, and one free line, as priceChanges inside the sale N and the table…	36	0	0
Total		**1173**	**0**	**11**

Les tests ignorés de `e2e_staging` (niveau client FDM) et de `live_fdm` (journée d’exploitation par les vraies commandes) constituent le harness de répétition pré-soumission ; ils requièrent un vrai FDM, le simulateur en ligne module2, et s’exécutent via `scripts/live_fdm.sh` (ou `cargo test --package pos-fiscal --test e2e_staging -- --ignored`). Ils ne font PAS partie de la barrière CI hors-ligne.

L’interface est couverte à part, par Playwright (`ui/e2e/`, IPC Tauri simulée) : `cd ui && npx playwright test`. Dernier passage (2026-09-26) : 157 passants, 0 échec, 0 ignoré.

Le vrai binaire de certification, avec sa base SQLite et son IPC réels, est piloté à part par WebDriver (`tauri-driver` + `WebKitWebDriver`) : `ui/e2e/real-binary/integration.test.mjs`, job CI `integration` (connexion, tables, menu du jeu d’essai, ajout d’une ligne et total).

Familles de tests

Finalité	Binaires de test
Domaine et noyau fiscal (unit)	`pos_core`, `pos_db`, `pos_fiscal`, `pos_print`, `pos_mail`, `pos_fdm_mock`
Formes des fixtures SPF Finances (requêtes et réponses officielles)	`uc_fixtures`, `reports_fixtures`, `advanced_set_fixtures`
Client FDM : aller-retour par mutation, statut, erreurs	`spf_basic_set`, `full_service`, `client_status`, `fdm_client_errors`
Rejeu des UC officiels à travers les commandes réelles (requête construite par pili-pos comparée à la fixture)	`spf_e2e_fixtures`, `spf_e2e_report_fixtures`, `report_totals_fixtures`
Orchestration applicative (commande → FDM → transaction → archive)	`spf_e2e_basic`, `spf_e2e_reports`, `spf_e2e_journal`, `spf_e2e_service_day`, `order_commands`
Numérotation sans trou, pannes FDM, crash, concurrence	`spf_e2e_no_gap`, `spf_e2e_fdm_failures`, `spf_e2e_crash_safety`, `spf_e2e_concurrency`
Profils utilisateurs, validation des entrées, remboursements, configuration	`access_control`, `spf_e2e_validation`, `refund_guards`, `config_check`

Finalité	Binaires de test
Ticket numérique, impression, tiroir	`spf_e2e_digital`, `outbox`, `tem_client`, `spf_e2e_peripherals`, `receipt_matrix`, `ticket_examples`
Image d'admission (POS contre `pos-fdm-mock`)	`admission_mock`

Rot de tests pré-existant corrigé lors du baselining

Les deux tests d'intégration pos-fiscal ne compilaient plus contre l'API actuelle. Corrigé :

Fichier	Sites	Raison
`crates/pos-fiscal/tests/full_service.rs`	5	Champ `backup_dir` manquant sur `PosConfig` ; champ `rounding` manquant sur `TicketParams` (×2) ; 8e argument `Option<&FdmReference>` manquant sur `build_sale_input` (×2).
`crates/pos-fiscal/tests/spf_basic_set.rs`	6	`backup_dir` manquant sur `PosConfig` ; 8e argument manquant sur `build_sale_input` (×5).

Toutes les corrections étaient mécaniques - `None` pour les nouveaux champs/arguments optionnels. Aucun changement de sémantique de test.

Mises en conformité lors de cette baseline

Fichier	Changement
`src-tauri/Cargo.toml`	Feature `cert` = `custom-protocol` + `hubrise` ; la facturation B2B et la file Peppol sont compilées dans toute build, sans fonction Cargo.
`src-tauri/src/main.rs`, `src-tauri/src/ipc/mod.rs`	Commandes Tauri de la facturation B2B (liste unique, sans condition de compilation).
`crates/pos-engine/src/commands/checkout.rs`	**Bug fix** : passait `restaurant_est_no: ""` à `TicketParams`, passe désormais `&config.restaurant_est_no`.
`ui/src/router/index.ts`	Écran des commandes en ligne accessible seulement si l'intégration est activée pour l'installation.

Limitations connues / suivis

- **Commandes en ligne** : présentes dans le binaire cert, coupées par défaut (`hubrise_enabled: false`) ; un Gérant les active dans Réglages, chaque changement est journalisé.

- **Endpoint healthcheck** (`127.0.0.1:9999`) : une variante liveness-only cert-friendly est planifiée pour un futur polissage UI.
- **Playwright** : hors du tableau ci-dessus (généré depuis `cargo test`), totaux donnés plus haut ; la CI (`.github/workflows/test.yml`) le relance à chaque push.

Reproductibilité

```
cd pili-pos

# Build dev (features par défaut)
cargo test --workspace --no-fail-fast

# Build certification
cargo build --package pili-pos --no-default-features --features cert
nm target/debug/pili-pos | grep -c pos_peppol   # compte informatif

# Build UI (un seul bundle, commandes en ligne activées à l'exécution)
npm --prefix ui run build
```