

Aufgabenblatt 9

9.1 Aufgabe

Based on the given conceptual schema, please provide SQL statements to create the according tables described in the schema.

```
1  -- Employee gehört zu einer bestimmten Abteilung.
2  CREATE TABLE Employee (
3      empNr          int(11) NOT NULL AUTO_INCREMENT,
4      name           varchar(255),
5      department     int(10) NOT NULL,
6      departmentnr   int(10) NOT NULL,
7      PRIMARY KEY (empNr));
8
9  -- Telefonnummer kann mehrwertig sein.
10 -- Also Tabelle für Telefonnummer erstellen
11 CREATE TABLE PhoneNumbers (
12     employeeempnr  int(11) NOT NULL,
13     phoneNr        varchar(255));
14
15 -- Die Abteilung hat einen Leiter
16 CREATE TABLE Department (
17     house          int(10) NOT NULL,
18     nr             int(10) NOT NULL,
19     manager        int(11) NOT NULL,
20     budget         int(10),
21     PRIMARY KEY (house, nr));
22
23 -- Das Projekt wird über eine Relationentabelle mit den
24 -- Mitarbeitern verknüpft.
25 CREATE TABLE Project (
26     name           varchar(255) NOT NULL,
27     description    varchar(255),
28     PRIMARY KEY (name));
29
30 -- Relationentabelle um Mitarbeiter mit einem Projekt zu verknüpfen
31 CREATE TABLE Employee_Project (
32     employeeempnr  int(11) NOT NULL,
33     projectname    varchar(255) NOT NULL,
34     PRIMARY KEY (employeeempnr, projectname));
35
36 -- Die offenen Tickets werden hier gespeichert.
37 CREATE TABLE Ticket (
38     nr             int(10) NOT NULL AUTO_INCREMENT,
```

```

39     title          varchar(255),
40     description    varchar(255),
41     importance     int(10),
42     PRIMARY KEY (nr));
43
44 -- Relationentabelle um Tickets einem Projekt zuzuordnen
45 CREATE TABLE Project_Ticket (
46     projectname    varchar(255) NOT NULL,
47     ticketnr       int(10) NOT NULL,
48     PRIMARY KEY (projectname,
49     ticketnr));
50
51 -- Relationentabelle um die Arbeit eines Mitarbeiters
52 -- an einem Ticket zu dokumentieren.
53 CREATE TABLE Employee_Ticket (
54     employeeempnr  int(11) NOT NULL,
55     ticketnr       int(10) NOT NULL,
56     start          timestamp NOT NULL,
57     end            timestamp NULL,
58     PRIMARY KEY (employeeempnr,
59     ticketnr));
60
61 -- Fremdschlüsselabhängigkeiten erstellen
62 ALTER TABLE PhoneNumbers
63     ADD INDEX FKPhoneNumbe658372 (employeeempnr),
64     ADD CONSTRAINT FKPhoneNumbe658372
65     FOREIGN KEY (employeeempnr) REFERENCES Employee (empNr);
66 ALTER TABLE Employee_Project
67     ADD INDEX FKEmployee_P990046 (employeeempnr),
68     ADD CONSTRAINT FKEmployee_P990046
69     FOREIGN KEY (employeeempnr) REFERENCES Employee (empNr);
70 ALTER TABLE Employee_Project
71     ADD INDEX FKEmployee_P943600 (projectname),
72     ADD CONSTRAINT FKEmployee_P943600
73     FOREIGN KEY (projectname) REFERENCES Project (name);
74 ALTER TABLE Department
75     ADD INDEX FKDepartment689529 (manager),
76     ADD CONSTRAINT FKDepartment689529
77     FOREIGN KEY (manager) REFERENCES Employee (empNr);
78 ALTER TABLE Employee
79     ADD INDEX FKEmployee366382 (department, departmentnr),
80     ADD CONSTRAINT FKEmployee366382
81     FOREIGN KEY (department, departmentnr) REFERENCES Department (house, nr);
82 ALTER TABLE Project_Ticket
83     ADD INDEX FKProject_Ti16548 (projectname),
84     ADD CONSTRAINT FKProject_Ti16548
85     FOREIGN KEY (projectname) REFERENCES Project (name);
86 ALTER TABLE Project_Ticket
87     ADD INDEX FKProject_Ti360860 (ticketnr),
88     ADD CONSTRAINT FKProject_Ti360860
89     FOREIGN KEY (ticketnr) REFERENCES Ticket (nr);

```

```

90 ALTER TABLE Employee_Ticket
91     ADD INDEX FKEmployee_T249102 (employeeempnr),
92     ADD CONSTRAINT FKEmployee_T249102
93     FOREIGN KEY (employeeempnr) REFERENCES Employee (empNr);
94 ALTER TABLE Employee_Ticket
95     ADD INDEX FKEmployee_T659766 (ticketnr),
96     ADD CONSTRAINT FKEmployee_T659766
97     FOREIGN KEY (ticketnr) REFERENCES Ticket (nr);

```

9.2 Aufgabe

Based on the given statements and data, explain the consequences of the following operations:

- a) `INSERT INTO connection VALUES(2, 5, 'sequel')`
- b) `DELETE FROM actor WHERE role = 'forest_ranger'`
- c) `DELETE FROM movie WHERE title = 'Adventures_with_RDB'`
- d) `INSERT INTO actor VALUES(6, 85, 'important_looking_man')`
- e) `DROP TABLE person`

Die gesamte Tabelle Person wird aus der Datenbank gelöscht. Da diese Tabelle nur die Primärschlüsselspalte besitzt, welche mit den Spalten person aus den Relationen director und actor in Beziehung stehen, wird die Spalte person dieser beiden Tabellen, also alle Zeilen aus person aus director und actor gelöscht. Der Rest der Datenbank wird nicht beeinflusst.