

Python Programming Fundamentals Cheat Sheet

Package/Method	Description	Syntax and Code Example
AND	Returns `True` if both statement1 and statement2 are `True`. Otherwise, returns `False`.	Syntax: <pre>statement1 and statement2</pre> Example: <pre>marks = 90 attendance_percentage = 87 if marks >= 80 and attendance_percentage >= 85: print("qualify for honors") else: print("Not qualified for honors") # Output = qualify for honors</pre>
Class Definition	Defines a blueprint for creating objects and defining their attributes and behaviors.	Syntax: <pre>class ClassName: # Class attributes and methods</pre> Example: <pre>class Person: def __init__(self, name, age): self.name = name self.age = age</pre>
Define Function	A `function` is a reusable block of code that performs a specific task or set of tasks when called.	Syntax: <pre>def function_name(parameters): # Function body</pre> Example: <pre>def greet(name): print("Hello,", name)</pre>

Equal(==)	Checks if two values are equal.	Syntax: <pre>variable1 == variable2</pre> Example 1: <pre>5 == 5</pre> returns True Example 2: <pre>age = 25 age == 30</pre> returns False
For Loop	A 'for' loop repeatedly executes a block of code for a specified number of iterations or over a sequence of elements (list, range, string, etc.).	Syntax: <pre>for variable in sequence: # Code to repeat</pre> Example 1: <pre>for num in range(1, 10): print(num)</pre> Example 2: <pre>fruits = ["apple", "banana", "orange", "grape", "kiwi"] for fruit in fruits: print(fruit)</pre>

Function Call	A function call is the act of executing the code within the function using the provided arguments.	Syntax: <pre>function_name(arguments)</pre> Example: <pre>greet("Alice")</pre>
Greater Than or Equal To(>=)	Checks if the value of variable1 is greater than or equal to variable2.	Syntax: <pre>variable1 >= variable2</pre> Example 1: <pre>5 >= 5 and 9 >= 5</pre> returns True Example 2: <pre>quantity = 105 minimum = 100 quantity >= minimum</pre> returns True
Greater Than(>)	Checks if the value of variable1 is greater than variable2.	Syntax: <pre>variable1 > variable2</pre>

		Example 1: $9 > 6$ returns True Example 2: <pre>age = 20 max_age = 25 age > max_age</pre> returns False
If Statement	Executes code block `if` the condition is `True`.	Syntax: <pre>if condition: #code block for if statement</pre> Example: <pre>if temperature > 30: print("It's a hot day!")</pre>
If-Elif-Else	Executes the first code block if condition1 is `True`, otherwise checks condition2, and so on. If no condition is `True`, the else block is executed.	Syntax: <pre>if condition1: # Code if condition1 is True elif condition2: # Code if condition2 is True else: # Code if no condition is True</pre> Example: <pre>score = 85 # Example score if score >= 90: print("You got an A!") elif score >= 80: print("You got a B.") else: print("You need to work harder.") # Output = You got a B.</pre>

If-Else Statement	Executes the first code block if the condition is `True`, otherwise the second block.	Syntax: <pre>if condition: # Code, if condition is True else: # Code, if condition is False</pre> Example: <pre>if age >= 18: print("You're an adult.") else: print("You're not an adult yet.")</pre>
Less Than or Equal To(<=)	Checks if the value of variable1 is less than or equal to variable2.	Syntax: <pre>variable1 <= variable2</pre> Example 1: <pre>5 <= 5 and 3 <= 5</pre> returns True Example 2: <pre>size = 38 max_size = 40 size <= max_size</pre> returns True

Less Than(<)	Checks if the value of variable1 is less than variable2.	Syntax: <pre>variable1 < variable2</pre> Example 1: <pre>4 < 6</pre> returns True Example 2: <pre>score = 60 passing_score = 65 score < passing_score</pre> returns True
Loop Controls	'break' exits the loop prematurely. 'continue' skips the rest of the current iteration and moves to the next iteration.	Syntax: <pre>for: # Code to repeat if # boolean statement break for: # Code to repeat if # boolean statement continue</pre> Example 1: <pre>for num in range(1, 6): if num == 3: break print(num)</pre> Example 2: <pre>for num in range(1, 6): if num == 3: continue print(num)</pre>

NOT	Returns `True` if variable is `False`, and vice versa.	Syntax: <pre>not variable</pre> Example: <pre>isLocked = False print(not isLocked)</pre> returns True if the variable is False (i.e., unlocked).
Not Equal(!=)	Checks if two values are not equal.	Syntax: <pre>variable1 != variable2</pre> Example: <pre>a = 10 b = 20 a != b</pre> returns True Example 2: <pre>count=0 count != 0</pre> returns False

Object Creation	Creates an instance of a class (object) using the class constructor.	Syntax: <pre>object_name = ClassName(arguments)</pre> Example: <pre>person1 = Person("Alice", 25)</pre>
OR	Returns `True` if either statement1 or statement2 (or both) are `True`. Otherwise, returns `False`.	Syntax: <pre>statement1 or statement2</pre> Example: <pre>"Farewell Party Invitation" grade = 12 if grade == 11 or grade == 12: print("Farewell Party Invitation") else: print("Not eligible")</pre> returns True
range()	Generates a sequence of numbers within a specified range.	Syntax: <pre>range(stop) range(start, stop) range(start, stop, step)</pre> Example: <pre>range(5) #generates a sequence of integers from 0 to 4. range(2, 10) #generates a sequence of integers from 2 to 9. range(1, 11, 2) #generates odd integers from 1 to 9.</pre>

Return Statement	'Return' is a keyword used to send a value back from a function to its caller.	Syntax: <pre>return value</pre> Example: <pre>def add(a, b): return a + b result = add(3, 5)</pre>
Try-Except Block	Tries to execute the code in the try block. If an exception of the specified type occurs, the code in the except block is executed.	Syntax: <pre>try: # Code that might raise an exception except ExceptionType: # Code to handle the exception</pre> Example: <pre>try: num = int(input("Enter a number: ")) except ValueError: print("Invalid input. Please enter a valid number.")</pre>
Try-Except with Else Block	Code in the 'else' block is executed if no exception occurs in the try block.	Syntax: <pre>try: # Code that might raise an exception except ExceptionType: # Code to handle the exception else: # Code to execute if no exception occurs</pre> Example: <pre>try: num = int(input("Enter a number: ")) except ValueError: print("Invalid input. Please enter a valid number") else: print("You entered:", num)</pre>

Try-Except with Finally Block	Code in the 'finally' block always executes, regardless of whether an exception occurred.	Syntax: <pre>try: # Code that might raise an exception except ExceptionType: # Code to handle the exception finally: # Code that always executes</pre> Example: <pre>try: file = open("data.txt", "r") data = file.read() except FileNotFoundError: print("File not found.") finally: file.close()</pre>
While Loop	A 'while' loop repeatedly executes a block of code as long as a specified condition remains 'True'.	Syntax: <pre>while condition: # Code to repeat</pre> Example: <pre>count = 0 while count < 5: print(count) count += 1</pre>



Skills Network