50.012 Networks

Lecture 13: IP

2021 Term 6

Assoc. Prof. CHEN Binbin

SINGAPORE UNIVERSITY OF TECHNOLOGY AND DESIGN

Outline

IP: Internet Protocol

- datagram format
- fragmentation
- IPv4 addressing
- DHCP
- NAT
- IPv6

Read textbook Section 4.3

The Internet network layer

host, router network layer functions:



IP datagram format



how much overhead?

- 20 bytes of TCP
- 20 bytes of IP
- = 40 bytes + app layer overhead

IP fragmentation, reassembly

- network links have MTU (max.transfer size) - largest possible link-level frame
  - different link types, different MTUs
- large IP datagram divided ("fragmented") within net
  - one datagram becomes several datagrams
  - "reassembled" only at final destination
  - IP header bits used to identify, order related fragments



IP fragmentation, reassembly

example:

- 4000 byte datagram
- MTU = 1500 bytes



1480 bytes in data field

offset = 1480/8

Outline

IP: Internet Protocol

- datagram format
- fragmentation
- IPv4 addressing
- DHCP
- NAT
- IPv6

IP addressing: introduction

- *IP address:* 32-bit identifier for host, router *interface*
- *interface:* connection between host/router and physical link
  - router's typically have multiple interfaces
  - host typically has one or two interfaces (e.g., wired Ethernet, wireless 802.11)
- *IP addresses associated with each interface*



$$223.1.1.1 = \underbrace{11011111}_{223}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}\ \underbrace{00000001}_{1}$$

IP addressing: introduction

Q: how are interfaces actually connected?



A: wired Ethernet interfaces connected by Ethernet switches

For now: don't need to worry about how one interface is connected to another

A: wireless WiFi interfaces connected by WiFi base station

Subnets

- IP address:
  - –subnet part - high order bits
  - –host part - low order bits
- *what's a subnet ?*
  - –device interfaces with same subnet part of IP address
  - –can physically reach each other *without intervening router*



network consisting of 3 subnets

Subnets

recipe

- to determine the subnets, detach each interface from its host or router, creating islands of isolated networks
- each isolated network is called a *subnet*



subnet mask: /24

Subnets

how many?



IP addressing: CIDR

CIDR: Classless InterDomain Routing

- subnet portion of address of arbitrary length
- address format: a.b.c.d/x, where x is # bits in subnet portion of address

subnet part | host part

11001000 00010111 00010000 00000000

200.23.16.0/23

In-class activity

- (textbook chapter 4, problem P8) Consider a router that interconnects three subnets: Subnet 1, Subnet 2, and Subnet 3. Suppose all of the interfaces in each of these three subnets are required to have the prefix 223.1.17.0/24. Also suppose that Subnet 1 is required to support at least 60 interfaces, Subnet 2 is to support at least 90 interfaces, and Subnet 3 is to support at least 12 interfaces. Provide three network addresses (of the form a.b.c.d/x) that satisfy these constraints.

Outline

IP: Internet Protocol

- datagram format
- fragmentation
- IPv4 addressing
- DHCP
- NAT
- IPv6

IP addresses: how to get one?

Q: How does a *host* get IP address?

- hard-coded by system admin in a file
  - Windows: control-panel->network->configuration->tcp/ip->properties
- DHCP: Dynamic Host Configuration Protocol: dynamically get address from a server
  - "plug-and-play"

DHCP: Dynamic Host Configuration Protocol

goal: allow host to dynamically obtain its IP address from network server when it joins network

- can renew its lease on address in use
- allows reuse of addresses (only hold address while connected / "on")
- support for mobile users who want to join network

DHCP overview:

- host broadcasts "DHCP discover" msg [optional]
- DHCP server responds with "DHCP offer" msg [optional]
- host requests IP address: "DHCP request" msg
- DHCP server sends address: "DHCP ack" msg

DHCP client-server scenario



DHCP client-server scenario



DHCP: more than IP addresses

DHCP can return more than just allocated IP address on subnet:

- address of first-hop router for client
- name and IP address of DNS sever
- network mask (indicating network versus host portion of address)

DHCP: example



- connecting laptop needs its IP address, addr of first-hop router, addr of DNS server: use DHCP

- DHCP request encapsulated in UDP, encapsulated in IP, encapsulated in 802.1 Ethernet
- Ethernet frame broadcast (dest: FFFFFFFFFFFF) on LAN, received at router running DHCP server

- Ethernet demuxed to IP demuxed, UDP demuxed to DHCP

DHCP: example



- DHCP server formulates DHCP ACK containing client's IP address, IP address of first-hop router for client, name & IP address of DNS server
- encapsulation of DHCP server, frame forwarded to client, demuxing up to DHCP at client
- client now knows its IP address, name and IP address of DSN server, IP address of its first-hop router

IP addresses: how to get one?

Q: how does *network* get subnet part of IP addr?

A: gets allocated portion of its provider ISP's address space

ISP's block	<u>11001000 00010111 0001</u>0000 00000000	200.23.16.0/20
Organization 0	<u>11001000 00010111 0001000</u>0 00000000	200.23.16.0/23
Organization 1	<u>11001000 00010111 0001001</u>0 00000000	200.23.18.0/23
Organization 2	<u>11001000 00010111 0001010</u>0 00000000	200.23.20.0/23
...	....	....
Organization 7	<u>11001000 00010111 0001111</u>0 00000000	200.23.30.0/23

Hierarchical addressing: route aggregation

hierarchical addressing allows efficient advertisement of routing information:



Hierarchical addressing: more specific routes

ISP B has a more specific route to Organization 1



Q: how does an ISP get block of addresses?

A: ICANN: Internet Corporation for Assigned Names and Numbers http://www.icann.org/

- allocates addresses
- manages DNS
- assigns domain names, resolves disputes

Outline

IP: Internet Protocol

- datagram format
- fragmentation
- IPv4 addressing
- DHCP
- NAT
- IPv6

NAT: network address translation



all datagrams *leaving* local network have *same* single source NAT IP address: 138.76.29.7,different source port numbers

datagrams with source or destination in this network have 10.0.0/24 address for source, destination (as usual)

NAT: network address translation

motivation: local network uses just one IP address as far as outside world is concerned:

- range of addresses not needed from ISP: just one IP address for all devices
- can change addresses of devices in local network without notifying outside world
- can change ISP without changing addresses of devices in local network
- devices inside local net not explicitly addressable, visible by outside world (a security plus)

NAT: network address translation

implementation: NAT router must:

- *outgoing datagrams: replace* (source IP address, port #) of every outgoing datagram to (NAT IP address, new port #)
  . . . remote clients/servers will respond using (NAT IP address, new port #) as destination addr
- *remember (in NAT translation table)* every (source IP address, port #) to (NAT IP address, new port #) translation pair
- *incoming datagrams: replace* (NAT IP address, new port #) in dest fields of every incoming datagram with corresponding (source IP address, port #) stored in NAT table

NAT: network address translation



* Check out the online interactive exercises for more examples: http://gaia.cs.umass.edu/kurose_ross/interactive/

NAT: network address translation

- 16-bit port-number field:
  - 60,000+ simultaneous connections with a single WAN-side address!
- NAT is controversial:
  - routers should only process up to layer 3
  - address shortage should be solved by IPv6
  - violates end-to-end argument
    - NAT possibility must be taken into account by app designers, e.g., P2P applications
  - NAT traversal: what if client wants to connect to server behind NAT?

STUN, ICE, TURN

- A set of IETF standard protocols for negotiating traversing NATs when establishing peer-to-peer communication sessions.

- STUN [RFC5389]: Session Traversal Utilities for NAT
  - A request/response protocol over UDP or TCP (port 3478)
  - Somewhat like http://whatismyip.com

- ICE [RFC5245]: Interactive Connectivity Establishment

- TURN [RFC5766]: Traversal Using Relay around NAT
  - A server which relays media between two peers

Outline

IP: Internet Protocol

- datagram format
- fragmentation
- IPv4 addressing
- DHCP
- NAT
- IPv6

IPv6: motivation

- *initial motivation:* 32-bit address space soon to be completely allocated.
- additional motivation:
  - header format helps speed processing/forwarding
  - header changes to facilitate QoS

IPv6 datagram format:

- fixed-length 40 byte header
- no fragmentation allowed

IPv6 datagram format

priority: identify traffic class
flow Label: identify datagrams in same "flow"
(concept of "flow" not well defined)
next header: identify upper layer protocol for data



IPv6 vs. IPv4





- *checksum*: removed entirely to reduce processing time at each hop
- *Fragmentation in routers:* not allowed
- *options:* allowed, but outside of header, indicated by "Next Header" field

Transition from IPv4 to IPv6

- not all routers can be upgraded simultaneously
  - no "flag days"
  - how will network operate with mixed IPv4 and IPv6 routers?
- *tunneling:* IPv6 datagram carried as *payload* in IPv4 datagram among IPv4 routers



Tunneling



logical view:
A
B
IPv4 tunnel
connecting IPv6 routers
E
F
IPv6
IPv6
IPv6
IPv6
physical view:
A
B
C
D
E
F
IPv6
IPv6
IPv4
IPv4
IPv6
IPv6

Tunneling



logical view:
A
B
IPv4 tunnel
connecting IPv6 routers
E
F
IPv6
IPv6
IPv6
IPv6
physical view:
A
B
C
D
E
F
IPv6
IPv6
IPv4
IPv4
IPv6
IPv6
flow: X
src: A
dest: F
data
src:B
dest: E
Flow: X
Src: A
Dest: F
data
src:B
dest: E
Flow: X
Src: A
Dest: F
data
flow: X
src: A
dest: F
data
A-to-B:
IPv6
B-to-C:
IPv6 inside
IPv4
D-to-E:
IPv6 inside
IPv4
E-to-F:
IPv6

IPv6: adoption

- Google: 8% of clients access services via IPv6
- NIST: 1/3 of all US government domains are IPv6 capable

- *Long (long!) time for deployment, use*
  - 20 years and counting!
  - think of application-level changes in last 20 years: WWW, Facebook, streaming media, Skype, …
  - *Why?*