## CIT SOLE CO.,LTD

**QOUTATION** 

Houayhong Village, Chanthabouli District, Vientaine Capital.

CIT0057 17/05/2021

Mobile: 02058189995, 58189996, 55556905 Web: www.citgroup.la or www.citsole.com

Email: <a href="mailto:citgrouplao@gmail.com">citgrouplao@gmail.com</a> or <a href="mailto:dahualaos@gmail.com">dahualaos@gmail.com</a>

To: Sokxay GROUP

Address:

•			Currency:		USD		
No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
				69			
1	SD49225T-HN	2MP 25x Starlight IR PTZ Network Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 1080P/720P/D1(1 ~ 25/30fps) > IVS, Support PoE+, IR distance up to 100m, IP66	2Y	6	380	2.280	Full HD Starligth
2	DH-SD6C3220-HN-UE	Powerful 20x/30x optical zoom Starlight Technology  • H.264 &MJPEG dual-stream encoding  • Max. 15fps@3Mp, 25/30fps@1080p resolution(320)  • Max 25/30fps@1080p, 50/60fps@720P(220/230)  • Defog(220/230), EIS(220/230), WDR, Day/Night(ICR), DNR(2D&3D),  Auto iris, Auto focus, AWB, AGC,BLC  • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS  • Max 240°/s pan speed, 360° endless pan rotation  • Up to 255 presets, 5 auto scan, 8 tour, 5 pattern  • Built-in 7/2 alarm in/out  • Support intelligent 3D positioning with DH-SD protocol  • Micro SD memory, IP66  • IR Distance up to 150m	2Y	4	380	1.520	Full HD Starligth
3	Wiz Sense	2MP IR Fixed focal Bullet WizSense Network Camera  > 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition  > Outputs max. 2MP (1920 x 1080)@30 fps  > H.265 codec, high compression rate, low bit rate  > Built-in IR LED, max. IR distance: 50 m  > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments  > Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes  > Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)  > Supports max. 256 G Micro SD card, built-in Mic  > 12V DC/POE power supply  > IP67 protection  > SMD Plus	2Y	9	130	1.170	Al Perimeter Protection Order
4	DH-IPC- HFW2439MP- AS-LED-B- 0360B-S2	4MP Lite Full-color Fixed-focal Bullet Network Camera ฏิ LED เป็ม	2 Y	10	90	900	ກາງຄືນເປັນສີ

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
5	IPC-HFW2439S- SA-LED-S2	4MP Lite Full-color Fixed-focal Bullet Network Camera > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP > H.265 codec, high compression rate, ultra-low bit rate > Built-in warm lights, max. illumination distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, scene > Supports max. 256 GB Micro SD card and built-in Mic > 12V DC/PoE power supply > IP67 protection	2 Y	40	50	2.000	ບັນທຶກສຽງ ກາງຄືນເປັນ ພາບສີ Order
6	ASI1212D	Water-proof Fingerprint Standalone  > Touch keyboard and LCD display  > Support 30,000 valid cards & 150,000 records  > Support multiple cards(default IC card) ("-D" means ID EM card)  > Support card, password, fingerprint and combination  > TCP/IP to PC, support WAN communication  > Support P2P add device  > Wiegand or RS-485 interface to reader  > Door time out alarm, intrusion alarm, duress alarm and tamper alarm  > Anti-passback, multi-card open  > Software attendance  > Support 128 efficient time and holiday schedules	1Y	3	210	630	
7	IC-S50	>Mifare card, 13.56MHz; >8K bit EEPROM memory; >86*54*1mm;	1Y	100	1	100	
8	DHI-ASF280A	> Power on-NC; > Single Door; > Relay Input&output > Anti-pull 280kg; > Working Temperature: -30°C~60°C; > DC12V/24V; > 250°47*26mm;	1Y	3	62	186	
9	ASF900	>ABS plastic; >86*86*25mm; >-30°C~60°C;	1Y	3	3	9	
10	2822) 1222)	64 Channel 3U 16HDDs Ultra series Network Video Recorder  > New 4.0 user interface > 16-channel decoding @1080p (30 fps); self-adaptive decoding capability > Access, storage or forwarding at 384 Mbps > Simultaneous video output for VGA and HDMI1; 4K heterogeneous output for the 2 HDMI ports > Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10 > Remote configuration and management of IPCs, such as setting pa rameters, acquiring information and upgrading IPCs of the same model in batches > AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis > N+M cluster. When the host fails, the standbydevice will continue to record; once the host recovers,video recorded on the standby device will be transmitted back	1 Y	1	4.350	4.350	ກ້ອງ 46 ໝ 4 ລ້ານຝຶກ ເຊວ ບັນທຶກໄດ້ ຫຼາຍກວ່າ > 90 days  Order
11	ST10000VX0004	10TB/7200RPM/256M/ SATA 6Gb/s	1 Y	16	440	7.040	
12	PFS3206-4P-96	4-Port PoE Switch (Unmanaged)  > Two-layer PoE Ethernet switch  > MAC auto study and aging, MAC address list capacity is 1K  > Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards  > Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation.  > Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission distance of power and network data is up to 250m.	1 Y	12	48	576	,

No	Name/Images	Specification	Wty	Qty	Price	Amount	Remark
13	PFS3110-8P-96	8-Port PoE Switch (Unmanaged) > Layer two commercial switch > Supports PoE power management > Supports wall-mount installation > Supports anti-theft lock hole > MAC auto learning and aging, MAC address capacity is 16K > Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards > RJ45 port supports 10/100 Mbps self-adaptation > Supports 250 meters long distance PoE transmission > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply	1 Y	8	90	720	
14	PFS4226-24ET- 240	24-Port PoE Switch 27 Port LAN  > Layer 2 management PoE switch  > PoE budget: 240W  > Support PoE, PoE+, Hi-PoE  > 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300)  > 250 meters long distance PoE transmission  > PoE management, PoE Setting/Event Statistics/Green PoE  > Search and upgrade via ConfigTool  > Support Web management  > High lightning protection design  > Non-blocking video transmission	1 Y	8	400	3.200	
15	PFS5428-24GT	L2+ Managed Switch > Hardened L2+ managed aggregation Switch > 24GE+4 x GE/10GE SFP+ > Switching Capacity: 128Gbps > High lightning protection: Common/Differential mode 4KV/2KV > Wide working temperature: -20~55°C > SFP+ fiber uplink > Fanless thermal design > Rack mounting	1 Y	1	840	840	Aggregation Switch Order
16	DHI-NKB1000	Keyboard to Control  > Dahua High Speed Dome (all models)  > Dahua Standalone DVR (KBD1000 &NKB1000 only)  > Dahua Network High Speed Dome NKB1000 only)  > Network Video Server NKB1000 only)  Connection  > NKB1000: RS485, RS422, USB, RS232 & Network  Functions  > Three Dimensional Joystick Control of PTZ Functions  > Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions  Auxiliary Functions  > On-Screen Menu & User Operation Procedure Tips  > Connect to SmartPSS via USB NKB1000 only)	1 Y	1	187	187	Keyboard
Total:			225	7.661	25.708	-	
		VAT:		<u>10</u> %		2.571	
	Grand Total:					28.279	

Order 60 days and conditions must be contracted and reimbursed 50% of the value to deposit in the purchase order.

This bill of quantity is not a contract or a bill. It is our best quess at the total price for the service and goods described above and can use <= 30 days.

ທ່ານທະວິໂລ ບຸນທະລາ Mr Chanthavilay BOUNTHALA

Director)