## CIT SOLE CO.,LTD

**QOUTATION** 

 $\label{thm:local_point} \mbox{Houayhong Village, Chanthabouli District, Vientaine Capital.}$ 

CIT0054 10/05/2021

Mobile: 02058189995, 58189996, 55556905 Web: www.citgroup.la or www.citsole.com

Email: citgrouplao@gmail.com or dahualaos@gmail.com

To: Sokxay GROUP

Address:

|    |  | ·   | Currency: |     | USD   |        |  |
|----|--|---|-----------|-----|-------|--------|--|
| No | Name/Images                                    | Specification   | Wty       | Qty | Price | Amount | Remark                                 |
|    |  |   |           | 59  |       |        |  |
| 1  | SD49225T-HN                                    | 2MP 25x Starlight IR PTZ Network Camera > 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 1080P/720P/D1(1 ~ 25/30fps) > IVS, Support PoE+, IR distance up to 100m, IP66  | 2Y        | 2   | 400   | 800    | Full HD<br>Starligth                   |
| 2  | DH-SD6C3220-HN-<br>UE                          | Powerful 20x/30x optical zoom Starlight Technology  • H.264 &MJPEG dual-stream encoding  • Max. 15fps@3Mp, 25/30fps@1080p resolution(320)  • Max 25/30fps@1080p, 50/60fps@720P(220/230)  • Defog(220/230), EIS(220/230), WDR, Day/Night(ICR), DNR(2D&3D), Auto iris, Auto focus, AWB, AGC,BLC  • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS  • Max 240°/s pan speed, 360° endless pan rotation  • Up to 255 presets, 5 auto scan, 8 tour, 5 pattern  • Built-in 7/2 alarm in/out  • Support intelligent 3D positioning with DH-SD protocol  • Micro SD memory, IP66  • IR Distance up to 150m   | 2Y        | 4   | 450   | 1.800  | Full HD<br>Starligth                   |
| 3  | Wiz Sense                                      | 2MP IR Fixed focal Bullet WizSense Network Camera  > 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition  > Outputs max. 2MP (1920 x 1080)@30 fps  > H.265 codec, high compression rate, low bit rate  > Built-in IR LED, max. IR distance: 50 m  > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments  > Rotation mode, WDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes  > Intelligent detection: Intrusion, tripwire (support the classification and accurate detection of vehicle and human)  > Supports max. 256 G Micro SD card, built-in Mic  > 12V DC/POE power supply  > IP67 protection  > SMD Plus  | 2Y        | 13  | 130   | 1.690  | AI<br>Perimeter<br>Protection<br>Order |
| 4  | DH-IPC-<br>HFW2439MP-<br>AS-LED-B-<br>0360B-S2 | 4MP Lite Full-color Fixed-focal Bullet Network Camera ฏิ LED เป็ม<br><b>สิภาาูถิ้</b> ม  > 2MP, 1/2.8" CMOS image sensor, low illuminance, high image definition  > Outputs 2MP (1920 × 1080)@25/30 fps  > H.265 codec, high compression rate, ultra-low bit rate  > Built-in LEDs, max LED distance: 40 m  > ROI, SMART H.264/H.265, flexible coding, applicable to various bandwidth and storage environments  > Rotation mode, DWDR, 3D DNR, HLC, BLC, digital watermarking, applicable to various monitoring scenes  > Abnormality detection: Motion detection, video tampering, scene changing, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, voltage detection  > Alarm: 2 in, 2 out; audio: 1 in, 1 out; supports max. 128 GB Micro SD card  > 12V DC/PoE power support; 12V DC power output, max. current 165mA  > IP67 protection | 2 Y       | 10  | 90    | 900    | ກາງຄືນເປັນສີ                           |

| No | Name/Images                | Specification   | Wty | Qty | Price | Amount | Remark  |
|----|----------------------------|---|-----|-----|-------|--------|---|
| 5  | IPC-HFW2439S-<br>SA-LED-S2 | 4MP Lite Full-color Fixed-focal Bullet Network Camera > 4MP, 1/3" CMOS image sensor, low illuminance, high image definition > Outputs 4MP (2560 × 1440) @ 25/30 fps, Max. supports 4MP > H.265 codec, high compression rate, ultra-low bit rate > Built-in warm lights, max. illumination distance: 30 m > ROI, SMART H.264+/H.265+, flexible coding, applicable to various > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, > Intelligent detection: Intrusion, tripwire > Abnormality detection: Motion detection, video tampering, scene > Supports max. 256 GB Micro SD card and built-in Mic > 12V DC/PoE power supply > IP67 protection   | 2 Y | 30  | 50    | 1.500  | ບັນທຶກສຽງ<br>ກາງຄືນເປັນ<br>ພາບສີ<br>Order                   |
| 6  | ASI1212D                   | Water-proof Fingerprint Standalone  > Touch keyboard and LCD display  > Support 30,000 valid cards & 150,000 records  > Support multiple cards(default IC card) ("-D" means ID EM card)  > Support card, password, fingerprint and combination  > TCP/IP to PC, support WAN communication  > Support P2P add device  > Wiegand or RS-485 interface to reader  > Door time out alarm, intrusion alarm, duress alarm and tamper alarm  > Anti-passback, multi-card open  > Software attendance  > Support 128 efficient time and holiday schedules  | 1Y  | 3   | 210   | 630    |   |
| 7  | IC-S50                     | >Mifare card, 13.56MHz;<br>>8K bit EEPROM memory;<br>>86*54*1mm;  | 1Y  | 100 | 1     | 100    |   |
| 8  | DHI-ASF280A                | > Power on-NC;<br>> Single Door;<br>> Relay Input&output<br>> Anti-pull 280kg;<br>> Working Temperature: -30°C~60°C;<br>> DC12V/24V;<br>> 250*47*26mm;  | 1Y  | 3   | 62    | 186    |   |
| 9  | ASF900                     | >ABS plastic;<br>>86*86*25mm;<br>>-30°C~60°C;   | 1Y  | 3   | 3     | 9      |   |
| 10 | NVR616-64-4KS2             | 64 Channel 3U 16HDDs Ultra series Network Video Recorder  > New 4.0 user interface > 16-channel decoding @1080p (30 fps); self-adaptive decoding capability > Access, storage or forwarding at 384 Mbps > Simultaneous video output for VGA and HDMI1; 4K heterogeneous output for the 2 HDMI ports > Multiple data mode such as Raid0, Raid1, Raid5, Raid6, and Raid10 > Remote configuration and management of IPCs, such as setting pa rameters, acquiring information and upgrading IPCs of the same model in batches > AI-by-camera functions such as perimeter protection, face detection and recognition, SMD Plus, video metadata, ANPR and 3D behavior analysis > N+M cluster. When the host fails, the standbydevice will continue to record; once the host recovers, video recorded on the standby device will be transmitted back | 1 Y | 1   | 4.350 | 4.350  | ກ້ອງ 46 ໜ 4 ລ້ານພິກ ເຊວ ບັນທຶກໄດ້ ຫຼາຍກວ່າ > 90 days  Order |
| 11 | ST10000VX0004              | 10TB/7200RPM/256M/ SATA 6Gb/s   | 1 Y | 16  | 440   | 7.040  |   |
| 12 | PFS3206-4P-96              | 4-Port PoE Switch (Unmanaged)  > Two-layer PoE Ethernet switch  > MAC auto study and aging, MAC address list capacity is 1K  > Conform IEEE802.3, IEEE802.3u and IEEE802.3X standards  > Default Mode: The device works as a general switch and all ports support 10/100Mbps auto-negotiation.  > Extend Mode: VLAN isolation is enabled. Ports 1-4 will be isolated respectively (10Mbps auto-negotiation), but they can communicate with the Uplink port. Besides, the transmission distance of power and network data is up to 250m.   | 1 Y | 12  | 48    | 576    | ,   |

| No     | Name/Images          | Specification  | Wty         | Qty   | Price  | Amount | Remark                         |
|--------|----------------------|--|-------------|-------|--------|--------|--------------------------------|
| 13     | PFS3110-8P-96        | 8-Port PoE Switch (Unmanaged) > Layer two commercial switch > Supports PoE power management > Supports wall-mount installation > Supports anti-theft lock hole > MAC auto learning and aging, MAC address capacity is 16K > Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards > RJ45 port supports 10/100 Mbps self-adaptation > Supports 250 meters long distance PoE transmission > Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply                               | 1 Y         | 8     | 90     | 720    |                                |
| 14     | PFS4226-24ET-<br>240 | 24-Port PoE Switch 27 Port LAN  > Layer 2 management PoE switch  > PoE budget: 240W  > Support PoE, PoE+, Hi-PoE  > 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300)  > 250 meters long distance PoE transmission  > PoE management, PoE Setting/Event Statistics/Green PoE  > Search and upgrade via ConfigTool  > Support Web management  > High lightning protection design  > Non-blocking video transmission   | 1 Y         | 8     | 400    | 3.200  |                                |
| 15     | PFS5428-24GT         | L2+ Managed Switch > Hardened L2+ managed aggregation Switch > 24GE+4 x GE/10GE SFP+ > Switching Capacity: 128Gbps > High lightning protection: Common/Differential mode 4KV/2KV > Wide working temperature: -20~55°C > SFP+ fiber uplink > Fanless thermal design > Rack mounting   | 1 Y         | 1     | 840    | 840    | Aggregation<br>Switch<br>Order |
| 16     | DHI-NKB1000          | Keyboard to Control  > Dahua High Speed Dome (all models)  > Dahua Standalone DVR (KBD1000 &NKB1000 only)  > Dahua Network High Speed Dome NKB1000 only)  > Network Video Server NKB1000 only)  Connection  > NKB1000: RS485, RS422, USB, RS232 & Network  Functions  > Three Dimensional Joystick Control of PTZ Functions  > Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Auxiliary Functions  Auxiliary Functions  > On-Screen Menu & User Operation Procedure Tips  > Connect to SmartPSS via USB NKB1000 only) | 1 Y         | 1     | 187    | 187    | Keyboard                       |
| Total: |                      |  | 215         | 7.751 | 24.528 | -      |                                |
| VAT:   |                      |  | <u>10</u> % |       | 2.453  |        |                                |
|        |                      | Grand Total:   |             |       |        | 26.981 |                                |

Order 60 days and conditions must be contracted and reimbursed 50% of the value to deposit in the purchase order.

This bill of quantity is not a contract or a bill. It is our best quess at the total price for the service and goods

described above and can use <= 30 days.

ທ ຈັນທະວິໄລ ບຸນທະລາ

Mr Chanthavilay BOUNTHALA